

FCC PART 15.247
TEST REPORT

For

HONG KONG IPRO TECHNOLOGY CO., LIMITED

ROOM C1D, 6/F, WING HING INDUSTRIAL BUILDING, 14 HING YIP STREET,
KWUN TONG, KOWLOON, HONG KONG

FCC ID: PQ4IPROI3220

Report Type: Original Report	Product Type: GSM Mobile Phone
Test Engineer: Mick Yin	<i>Mick Yin</i>
Report Number: RSZ120829001-00B	
Report Date: 2012-09-07	
Reviewed By: RF Engineer	<i>Sula Huang</i>
Test Laboratory: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★"

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S)	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS.....	7
FCC §15.247 (i) & §2.1093 – RF EXPOSURE	8
APPLICABLE STANDARD	8
FCC §15.203 – ANTENNA REQUIREMENT	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
MEASUREMENT UNCERTAINTY	11
EUT SETUP	11
EMI TEST RECEIVER SETUP	12
TEST EQUIPMENT LIST AND DETAILS	12
TEST PROCEDURE	12
TEST RESULTS SUMMARY	12
TEST DATA	12
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	15
APPLICABLE STANDARD	15
MEASUREMENT UNCERTAINTY	15
EUT SETUP	15
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	16
TEST PROCEDURE	16
CORRECTED AMPLITUDE & MARGIN CALCULATION	16
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST RESULTS SUMMARY	17
TEST DATA	17
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	20
APPLICABLE STANDARD	20
TEST PROCEDURE	20
TEST EQUIPMENT LIST AND DETAILS.....	20
TEST DATA	20
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH TESTING	27
APPLICABLE STANDARD	27

TEST PROCEDURE	27
TEST EQUIPMENT LIST AND DETAILS.....	27
TEST DATA	27
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	33
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST EQUIPMENT LIST AND DETAILS.....	33
TEST DATA	33
FCC §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME).....	36
APPLICABLE STANDARD	36
TEST PROCEDURE	36
TEST EQUIPMENT LIST AND DETAILS.....	36
TEST DATA	36
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT.....	52
APPLICABLE STANDARD	52
TEST PROCEDURE	52
TEST EQUIPMENT LIST AND DETAILS.....	52
TEST DATA	52
FCC §15.247(d) - BAND EDGES TESTING	58
APPLICABLE STANDARD	58
TEST PROCEDURE	58
TEST EQUIPMENT LIST AND DETAILS.....	58
TEST DATA	59

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *HONGKONG IPRO TECHNOLOGY CO., LIMITED*'s product, model number: *i3220 (FCC ID: PQ4IPROI3220)* or the "EUT" in this report was a *GSM Mobile Phone*, which was measured approximately: 11.2 cm (L) x 4.7 cm (W) x 1.2 cm (H), rated input voltage: DC 3.7 V Li-ion battery or DC 5 V charging from adapter.

Adapter information

Model: TC-01

Input: AC 100-240V 50/60 Hz 150mA

SALIDA: DC 5.0V 500 mA

Frequency Range: 2402-2480 MHz (Tx/Rx)

Modulation Mode: GFSK, $\pi/4$ -DQPSK, 8DPSK (Bluetooth)

Transmitter Output Power: 5.03 dBm (Conducted power)

** All measurement and test data in this report was gathered from production sample serial number: IPROI32200000001 (Assigned by applicant). The EUT supplied by the applicant was received on 2012-08-29.*

Objective

This test report is prepared on behalf of *HONGKONG IPRO TECHNOLOGY CO., LIMITED* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 22H/24E PCE and part 15B JBP submissions with FCC ID: PQ4IPROI3220

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a testing mode.

Equipment Modifications

No modification was made to the EUT tested.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
TESCOM	Bluetooth Tester	TC-3000B	3000B650083

External I/O Cable

Cable Description	Length (m)	From Port	To
Unshielded Detachable USB Cable	1.0	EUT	Adapter

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance

FCC §15.247 (i) & §2.1093 – RF EXPOSURE

Applicable Standard

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Table 2 – Summary of SAR Evaluation Requirements for a Cell Phone with Multiple Transmitters

	Individual Transmitter	Simultaneous Transmission
Licensed Transmitters	<u>Routine evaluation required</u>	SAR not required: <u>Unlicensed only</u> - when stand-alone 1-g SAR is not required and antenna is ≥ 5 cm from other antennas Licensed & Unlicensed - when the sum of the 1-g SAR is < 1.6 W/kg for all simultaneous transmitting antennas - when SAR to peak location separation ratio of simultaneous transmitting antenna pair is < 0.3 SAR required: Licensed & Unlicensed antenna pairs with SAR to peak location separation ratio ≥ 0.3 ; test is only required for the configuration that results in the highest SAR in stand-alone configuration for each wireless mode and exposure condition Note: simultaneous transmission exposure conditions for head and body can be different for different style phones; therefore, different test requirements may apply
Unlicensed Transmitters	When there is no simultaneous transmission – - output ≤ 60 f: SAR not required - output > 60 f: stand-alone SAR required When there is simultaneous transmission – <u>Stand-alone SAR not required when</u> - output $\leq 2 \cdot P_{Ref}$ and antenna is ≥ 5.0 cm from other antennas - output $\leq P_{Ref}$ and antenna is ≥ 2.5 cm from other antennas - output $\leq P_{Ref}$ and antenna is < 2.5 cm from other antennas, each with either output power $\leq P_{Ref}$ or 1-g SAR < 1.2 W/kg <u>Otherwise stand-alone SAR is required</u> When stand-alone SAR is required - test SAR on highest output channel for each wireless mode and exposure condition - if SAR for highest output channel is $> 50\%$ of SAR limit, evaluate all channels according to normal procedures	
Jaw, Mouth and Nose	<u>Flat phantom SAR required</u> - when measurement is required in tight regions of SAM and it is not feasible or the results can be questionable due to probe tilt, calibration, positioning and orientation issues - position rectangular and clam-shell phones according to flat phantom procedures and conduct SAR measurements for these specific locations	When simultaneous transmission SAR testing is required, contact the FCC Laboratory for interim guidance.

Routine SAR evaluation refers to that specifically required by §2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

Note:

- 1) GSM voice can transmit simultaneously with Bluetooth.
- 2) The distance between BT and GSM antenna is 5.2 cm > 5 cm. The max output power of Bluetooth antenna is (5.03 dBm) 3.184mW < 2P_{Ref}(24mW). According to KDB648474, stand-alone SAR is not required for BT antenna and simultaneous SAR evaluation is not required for Bluetooth and GSM antennas.
- 3) P_{Ref} is defined as the maximum conducted power available at the antenna according to source-based time-averaging requirements of Section 2.1093(d)(5).

Result: The SAR evaluation of Bluetooth antenna can be exempted.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has an integrated antenna arrangement for bluetooth, which was permanently attached and the gain was 0 dBi, fulfill the requirement of this section. Please refer to the internal photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard


FCC §15.207

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on CISPR 16-4-4, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratory Corp. (Shenzhen) is 2.4 dB (k=2, 95% level of confidence), and the uncertainty will not be taken into consideration for all the test data recorded in the report.

EUT Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

<u>Frequency Range</u>	<u>IF B/W</u>
150 kHz – 30 MHz	9 kHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2011-11-24	2012-11-23
Rohde & Schwarz	L.I.S.N.	ESH2-Z5	892107/021	2011-11-17	2012-11-16
Rohde & Schwarz	Pulse limiter	ESH3Z2	DE25985	2012-07-08	2013-07-07

* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

20.09 dB at 0.515 MHz in the **Line** conducted mode

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa


The testing was performed by Mick Yin on 2012-08-31.

Test Mode: Charging & Transmitting

AC 120 V, 60 Hz, Line:



Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.515	25.91	10.25	46.00	20.09	Ave.
0.175	34.18	10.27	55.29	21.11	Ave.
0.175	42.70	10.27	65.29	22.59	QP
0.345	27.45	10.26	50.43	22.98	Ave.
0.745	22.74	10.21	46.00	23.26	Ave.
0.290	27.98	10.26	52.00	24.02	Ave.
0.230	27.90	10.26	53.71	25.81	Ave.
0.230	36.54	10.26	63.71	27.17	QP
0.515	28.64	10.25	56.00	27.36	QP
0.745	28.53	10.21	56.00	27.47	QP
0.345	30.61	10.26	60.43	29.82	QP
0.290	30.38	10.26	62.00	31.62	QP

AC 120V, 60 Hz, Neutral:

Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.195	42.39	10.24	64.71	22.32	QP
0.195	30.81	10.24	54.71	23.90	Ave.
0.385	23.23	10.25	49.29	26.06	Ave.
0.255	36.36	10.25	63.00	26.64	QP
0.325	32.17	10.25	61.00	28.83	QP
0.325	21.58	10.25	51.00	29.42	Ave.
0.385	29.62	10.25	59.29	29.67	QP
0.635	16.20	10.22	46.00	29.80	Ave.
0.900	15.43	10.18	46.00	30.57	Ave.
0.255	22.16	10.25	53.00	30.84	Ave.
0.635	24.63	10.22	56.00	31.37	QP
0.905	23.10	10.18	56.00	32.90	QP

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard


FCC §15.205; §15.209; §15.247(d)

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-4, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is 4.0 dB. ($k=2$, 95% level of confidence), and the uncertainty will not be taken into consideration for all the test data recorded in the report.

EUT Setup



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209 and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

<i>Frequency Range</i>	<i>RBW</i>	<i>Video B/W</i>	<i>Detector</i>
30 MHz – 1000 MHz	120 kHz	300 kHz	QP
1000 MHz – 25 GHz	1 MHz	3 MHz	PK
1000 MHz – 25 GHz	1 MHz	10 Hz	Ave.

Test Procedure

For radiated emissions, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	8447E	1937A01057	2011-11-24	2012-11-23
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2011-11-17	2012-11-16
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2012-11-27
Mini-Circuits	Amplifier	ZVA-213+	N/A	2011-11-24	2012-11-23
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-01	2012-11-30
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-11-23
Agilent	Spectrum Analyzer	8564E	3943A01781	2012-05-17	2013-05-16
the electro-Mechanics Co.	Horn Antenna	3116	9510-2270	2011-10-14	2012-10-13
Rohde & Schwarz	Auto test Software	EMC32	V6.30	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247, with the worst margin reading of:

6.86 dB at 7323.0 MHz in the Horizontal polarization

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100 kPa

The testing was performed by Mick Yin on 2012-09-05.

Test mode: Transmitting

(Scan with GFSK, $\pi/4$ -DQPSK, 8-DPSK, the worst case is EDR Mode (8DPSK))**30 MHz ~25 GHz:**

Frequency (MHz)	Receiver		Turn Table Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC PART15.247	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2402 MHz)									
2402.0	89.96	PK	35	1.2	H	6.13	96.09	/	/
2402.0	46.42	Ave.	35	1.2	H	6.13	52.55	/	/
2402.0	89.76	PK	122	1.0	V	6.13	95.89	/	/
2402.0	47.18	Ave.	122	1.0	V	6.13	53.31	/	/
7206.0	45.53	PK	131	1.3	V	17.06	62.59	74	11.41
7206.0	25.48	Ave.	131	1.3	V	17.06	42.54	54	11.46
4804.0	29.26	Ave.	38	1.1	V	12.40	41.66	54	12.34
4804.0	46.35	PK	38	1.1	V	12.40	58.75	74	15.25
2389.6	50.76	PK	223	1.1	H	6.13	56.89	74	17.11
9608.0	17.01	Ave.	48	1.2	V	19.28	36.29	54	17.71
2389.6	25.38	Ave.	223	1.1	H	6.13	31.51	54	22.49
9608.0	31.45	PK	48	1.2	V	19.28	50.73	74	23.27
2485.6	41.49	PK	89	1.2	V	6.81	48.30	74	25.70
2485.6	21.35	Ave.	89	1.2	V	6.81	28.16	54	25.84
2313.2	20.38	Ave.	137	1.3	H	5.48	25.86	54	28.14
2313.2	36.53	PK	137	1.3	H	5.48	42.01	74	31.99
Middle Channel (2441 MHz)									
2441.0	86.91	PK	35	1.1	H	7.21	94.12	/	/
2441.0	43.77	Ave.	35	1.1	H	7.21	50.98	/	/
2441.0	90.12	PK	113	1.3	V	6.81	96.93	/	/
2441.0	47.87	Ave.	113	1.3	V	6.81	54.68	/	/
7323.0	30.65	Ave.	168	1.5	H	16.49	47.14	54	6.86
7323.0	50.51	PK	168	1.5	H	16.49	67.00	74	7.00
9764.0	22.32	Ave.	32	1.2	V	19.40	41.72	54	12.28
9764.0	32.75	PK	32	1.2	V	19.40	52.15	74	21.85
2491.2	21.37	Ave.	13	1.1	V	6.81	28.18	54	25.82
2385.5	21.56	Ave.	165	1.2	H	6.13	27.69	54	26.31
2374.9	21.28	Ave.	227	1.0	V	6.13	27.41	54	26.59
2385.5	37.78	PK	165	1.2	H	6.13	43.91	74	30.09
2374.9	37.25	PK	227	1.0	V	6.13	43.38	74	30.62
4882.0	30.74	Ave.	29	1.3	V	12.46	43.20	54	30.74
2491.2	35.42	PK	13	1.1	V	6.81	42.23	74	31.77
4882.0	47.87	PK	29	1.3	V	12.46	60.33	74	47.87

Frequency (MHz)	Receiver		Turn Table Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC PART15.247	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2480 MHz)									
2480.0	88.68	PK	88	1.6	H	7.21	95.89	/	/
2480.0	45.08	Ave.	88	1.6	H	7.21	52.29	/	/
2480.0	89.51	PK	135	1.1	V	6.81	96.32	/	/
2480.0	47.04	Ave.	135	1.1	V	6.81	53.85	/	/
7440.0	26.53	Ave.	269	1.5	V	15.90	42.43	54	11.57
9920.0	22.76	Ave.	31	1.1	H	19.38	42.14	54	11.86
4960.0	29.53	Ave.	87	1.3	V	12.50	42.03	54	11.97
2487.1	52.42	PK	38	1.1	V	6.81	59.23	74	14.77
4960.0	46.32	PK	87	1.3	V	12.50	58.82	74	15.18
2487.1	28.93	Ave.	38	1.1	V	6.81	35.74	54	18.26
2483.6	28.82	Ave.	16	1.2	V	6.81	35.63	54	18.37
7440.0	38.42	PK	269	1.5	V	15.90	54.32	74	19.68
9920.0	32.53	PK	31	1.1	H	19.38	51.91	74	22.09
2353.2	22.57	Ave.	226	1.3	H	5.48	28.05	54	25.95
2353.2	35.53	PK	226	1.3	H	5.48	41.01	74	32.99
2483.6	61.81	PK	16	1.2	V	6.81	68.62	74	5.38

Note: For 30 MHz to 1 GHz, the spurious emissions which 20 dB below the limit or on the system noise floor level are not recorded.

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Set the EUT in transmitting mode, RBW of spectrum was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace
3. Measure the channel separation.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2011-11-17	2012-11-16
TESCOM	Bluetooth Tester	TC-3000B	3000B650083	2011-12-07	2012-12-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100 kPa


* The testing was performed by Mick Yin on 2012-09-04.

Test Mode: Transmitting


Test Result: Compliance. Please refer to following tables and plots

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	≥Limit (MHz)	Result
BDR (GFSK)	Low	2402	1.004	0.672	Pass
	Adjacent	2403			
	Middle	2441	1.004	0.672	Pass
	Adjacent	2442			
	High	2480	1.004	0.672	Pass
	Adjacent	2479			
EDR ($\pi/4$ -DQPSK)	Low	2402	1.004	0.859	Pass
	Adjacent	2403			
	Middle	2441	1.004	0.859	Pass
	Adjacent	2442			
	High	2480	1.004	0.859	Pass
	Adjacent	2479			
EDR (8DPSK)	Low	2402	1.004	0.832	Pass
	Adjacent	2403			
	Middle	2441	1.000	0.832	Pass
	Adjacent	2442			
	High	2480	1.004	0.832	Pass
	Adjacent	2479			

Note: Limit = 20 dB bandwidth *2/3


BDR (GFSK): Low Channel

Date: 4.SEP.2012 19:03:14

BDR (GFSK): Middle Channel


Date: 4.SEP.2012 19:04:19

BDR (GFSK): High Channel




Date: 4.SEP.2012 19:05:03


EDR ($\pi/4$ -DQPSK): Low Channel




Date: 4.SEP.2012 19:37:25

EDR ($\pi/4$ -DQPSK): Middle Channel


Date: 4.SEP.2012 19:38:11

EDR ($\pi/4$ -DQPSK): High Channel

Date: 4.SEP.2012 19:39:05


EDR (8DPSK): Low Channel

Date: 4.SEP.2012 20:20:06

EDR (8DPSK): Middle Channel

Date: 4.SEP.2012 22:54:59

EDR (8DPSK): High Channel



Date: 4.SEP.2012 20:21:04

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2011-11-17	2012-11-16
TESCOM	Bluetooth Tester	TC-3000B	3000B650083	2011-12-07	2012-12-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100 kPa


* The testing was performed by Mick Yin on 2012-09-04.

Test Mode: Transmitting

Test Result: Compliance. Please refer to following tables and plots


Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	1.008
	Middle	2441	1.008
	High	2480	1.008
EDR ($\pi/4$ -DQPSK)	Low	2402	1.288
	Middle	2441	1.288
	High	2480	1.288
EDR (8DPSK)	Low	2402	1.248
	Middle	2441	1.248
	High	2480	1.248

BDR (GFSK): Low Channel




Date: 4.SEP.2012 17:51:03

BDR (GFSK): Middle Channel




Date: 4.SEP.2012 17:53:11


BDR (GFSK): High Channel



Date: 4.SEP.2012 17:54:28


EDR ($\pi/4$ -DQPSK): Low Channel

Date: 4.SEP.2012 19:30:43

EDR ($\pi/4$ -DQPSK): Middle Channel


Date: 4.SEP.2012 19:29:36

EDR ($\pi/4$ -DQPSK): High Channel




Date: 4.SEP.2012 19:31:28

EDR (8DPSK): Low Channel




Date: 4.SEP.2012 20:08:42

EDR (8DPSK): Middle Channel



Date: 4.SEP.2012 20:10:05

EDR (8DPSK): High Channel



Date: 4.SEP.2012 20:11:15

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2011-11-17	2012-11-16
TESCOM	Bluetooth Tester	TC-3000B	3000B650083	2011-12-07	2012-12-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100 kPa


The testing was performed by Mick Yin on 2012-09-04.

Test Mode: Transmitting


Test Result: Compliance. Please refer to following tables and plots

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥ 15
EDR ($\pi/4$ -DQPSK)	2400-2483.5	79	≥ 15
EDR (8DPSK)	2400-2483.5	79	≥ 15


BDR (GFSK): Number of Hopping Channels



Date: 4.SEP.2012 19:22:09

EDR ($\pi/4$ -DQPSK): Number of Hopping Channels

Date: 4.SEP.2012 20:04:50

(8DPSK): Number of Hopping Channels

Date: 4.SEP.2012 20:41:10

FCC §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 X channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell time = Pulse time*hop rate/number of hopping channels*31.6S
Hop rate=1600/S

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2011-11-17	2012-11-16
TESCOM	Bluetooth Tester	TC-3000B	3000B650083	2011-12-07	2012-12-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100 kPa

The testing was performed by Mick Yin on 2012-09-04.


Test Mode: Transmitting

Test Result: Compliance. Please refer to following tables and plots

Mode		Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result
BDR (GFSK)	DH 1	Low	0.422	0.135	0.4	Pass
		Middle	0.422	0.135	0.4	Pass
		High	0.422	0.135	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH 3	Low	1.706	0.273	0.4	Pass
		Middle	1.706	0.273	0.4	Pass
		High	1.706	0.273	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH 5	Low	2.935	0.313	0.4	Pass
		Middle	2.935	0.313	0.4	Pass
		High	2.935	0.313	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR ($\pi/4$ -DQPSK)	DH 1	Low	0.422	0.135	0.4	Pass
		Middle	0.422	0.135	0.4	Pass
		High	0.422	0.135	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH 3	Low	1.694	0.271	0.4	Pass
		Middle	1.694	0.271	0.4	Pass
		High	1.694	0.271	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH 5	Low	2.974	0.317	0.4	Pass
		Middle	2.974	0.317	0.4	Pass
		High	2.974	0.317	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	DH 1	Low	0.422	0.135	0.4	Pass
		Middle	0.422	0.135	0.4	Pass
		High	0.422	0.135	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH 3	Low	1.694	0.271	0.4	Pass
		Middle	1.694	0.271	0.4	Pass
		High	1.694	0.271	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH 5	Low	2.944	0.314	0.4	Pass
		Middle	2.944	0.314	0.4	Pass
		High	2.944	0.314	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				


BDR (GFSK):

Pulse time, Low Channel, DH1




Date: 4.SEP.2012 19:07:43

Pulse time, Middle Channel, DH1




Date: 4.SEP.2012 19:08:00

Pulse time, High Channel, DH1




Date: 4.SEP.2012 19:08:55

Pulse time, Low Channel, DH3




Date: 4.SEP.2012 19:09:39

Pulse time, Middle Channel, DH3



Date: 4.SEP.2012 19:09:55

Pulse time, High Channel, DH3



Date: 4.SEP.2012 19:10:50

RBW 1 MHz
VBW 3 MHz
SWT 5 ms
Delta 1 [T1]
1.63 dB
2.935200 ms

Ref 23.5 dBm
Att 30 dB

Offset 3.5 dB

Marker 1 [T1]
-54.06 dBm
-10.000000 μ s

1 PK
MAXH

TRG 10.1 dBm

3dB
AC

Center 2.402 GHz
500 μ s/

Date: 4.SEP.2012 19:11:39

RBW 1 MHz
 VBW 3 MHz
 SWT 5 ms
 Delta 1 [T1] 1.51 dB
 2.935200 ms

Ref 23.5 dBm
 Att 30 dB


Offset 3.5 dB
 Marker 1 [T1]
 -51.80 dBm
 -10.000000 μs

1 PK MAXH
 TRG LVL
 3DB AC

Center 2.441 GHz
 500 μs/

Date: 4.SEP.2012 19:12:05


Pulse time, High Channel, DH5



Date: 4.SEP.2012 19:15:36


EDR ($\pi/4$ -DQPSK):

Pulse time, Low Channel, DH1




Date: 4.SEP.2012 19:41:38

Pulse time, Middle Channel, DH1




Date: 4.SEP.2012 19:42:13

Pulse time, High Channel, DH1




Date: 4.SEP.2012 19:42:39

Pulse time, Low Channel, DH3




Date: 4.SEP.2012 19:43:22

Pulse time, Middle Channel, DH3




Date: 4.SEP.2012 19:43:48

Pulse time, High Channel, DH3




Date: 4.SEP.2012 19:44:31

Pulse time, Low Channel, DH5




Date: 4.SEP.2012 19:46:04

Pulse time, Middle Channel, DH5



Date: 4.SEP.2012 19:46:29


Pulse time, High Channel, DH5



Date: 4.SEP.2012 19:47:03


EDR (8DPSK):

Pulse time, Low Channel, DH1




Date: 4.SEP.2012 20:21:59

Pulse time, Middle Channel, DH1




Date: 4.SEP.2012 20:22:33

Pulse time, High Channel, DH1




Date: 4.SEP.2012 20:22:55

Pulse time, Low Channel, DH3




Date: 4.SEP.2012 20:23:47

Pulse time, Middle Channel, DH3




Date: 4.SEP.2012 20:24:33

Pulse time, High Channel, DH3




Date: 4.SEP.2012 20:24:50

Pulse time, Low Channel, DH5




Date: 4.SEP.2012 20:26:33

Pulse time, Middle Channel, DH5



Date: 4.SEP.2012 20:26:06

Pulse time, High Channel, DH5



Date: 4.SEP.2012 20:25:37


FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI test receiver.
3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2011-11-17	2012-11-16
TESCOM	Bluetooth Tester	TC-3000B	3000B650083	2011-12-07	2012-12-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100 kPa


The testing was performed by Mick Yin on 2012-09-04.

Test Mode: Transmitting

Test Result: Compliance. Please refer to following tables and plots


Mode	Channel	Frequency (MHz)	Conducted Output Power		Limit (mW)
			(dBm)	(mW)	
BDR (GFSK)	Low	2402	4.84	3.048	1000
	Middle	2441	4.19	2.624	1000
	High	2480	3.68	2.333	1000
EDR ($\pi/4$ -DQPSK)	Low	2402	4.75	2.985	1000
	Middle	2441	4.11	2.576	1000
	High	2480	3.56	2.270	1000
EDR (8DPSK)	Low	2402	5.03	3.184	1000
	Middle	2441	4.39	2.748	1000
	High	2480	3.87	2.438	1000

BDR (GFSK): Low Channel




Date: 4.SEP.2012 19:24:26

BDR (GFSK): Middle Channel




Date: 4.SEP.2012 19:25:09

BDR (GFSK): High Chanel




Date: 4.SEP.2012 19:26:47

EDR($\pi/4$ -DQPSK): Low Channel




Date: 4.SEP.2012 20:05:54

EDR($\pi/4$ -DQPSK): Middle Channel




Date: 4.SEP.2012 20:06:43

EDR($\pi/4$ -DQPSK): High Chanel




Date: 4.SEP.2012 20:07:29

EDR(8DPSK): Low Channel




Date: 4.SEP.2012 20:42:33

EDR(8DPSK): Middle Channel



Date: 4.SEP.2012 20:43:07

EDR(8DPSK): High Channel



Date: 4.SEP.2012 20:43:49

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span including 100 kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1 MHz, VBW=3 MHz.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2011-11-17	2012-11-16
TESCOM	Bluetooth Tester	TC-3000B	3000B650083	2011-12-07	2012-12-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100 kPa


The testing was performed by Mick Yin on 2012-09-04.

Test Mode: Transmitting


Test Result: Compliance. Please refer to following plots

Mode	Frequency (MHz)	Delta Peak to band Emission (dBc)	Delta Limit (dBc)
BDR (GFSK)	2399.930	36.83	20
	2483.588	36.55	20
EDR ($\pi/4$ -DQPSK)	2399.900	36.48	20
	2483.676	39.43	20
EDR (8DPSK)	2399.990	35.09	20
	2483.544	38.78	20


BDR (GFSK): Band Edge-Left Side




Date: 4.SEP.2012 18:00:34

BDR (GFSK): Band Edge-Right Side


Date: 4.SEP.2012 19:02:11

EDR ($\pi/4$ -DQPSK): Band Edge-Left Side

Date: 4.SEP.2012 19:33:58


EDR ($\pi/4$ -DQPSK): Band Edge-Right Side

Date: 4.SEP.2012 19:35:35

EDR (8DPSK): Band Edge-Left Side

Date: 4.SEP.2012 20:13:46

EDR (8DPSK): Band Edge-Right Side



Date: 4.SEP.2012 20:15:28

***** END OF REPORT *****