

Test Data**A. Fundamental**

Operation Mode : TX
 Temperature : 25 °C
 Humidity : 60 %
 Test Date : Aug. 20 2001

Frequency (MHz)	Meter Reading (dBuV)		Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
27.033	45.5	41.3	1.0	46.5	80.0	-33.5	180	1.00

B. Harmonic

Operation Mode : TX
 Temperature : 25 °C
 Humidity : 60 %
 Test Date : Aug. 20 2001

Frequency (MHz)	Meter Reading (dBuV)		Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
54.066	32.4	34.8	-15.0	19.8	40.0	-20.2	270	1.10
81.099	---	---	-14.9	---	40.0	---	---	---
108.132	---	---	-12.1	---	43.5	---	---	---
135.165	32.9	11.1	-11.1	21.8	43.5	-21.7	180	1.30
162.198	---	---	-9.4	---	43.5	---	---	---
189.231	---	---	-8.5	---	43.5	---	---	---
216.264	---	---	-6.1	---	46.0	---	---	---
243.297	---	---	-4.3	---	46.0	---	---	---
270.330	---	---	-3.6	---	46.0	---	---	---

Remark “---” means that the emission level is too low to be measured.

Radiated Measurement Photos

