

TABLE OF CONTENTS

APPLICANT: DYNAMIC TECHNOLOGY INC

FCC ID: PQLSC2000-P

TEST REPORT CONTAINING:

PAGE 1.....	TEST EQUIPMENT LIST
PAGE 2.....	TEST PROCEDURES
PAGE 3-4.....	RADIATION INTERFERENCE TEST DATA
PAGE 5.....	CALCULATION OF DUTY CYCLE
PAGE 6.....	OCCUPIED BANDWIDTH
PAGE 7.....	OCCUPIED BANDWIDTH PLOT

EXHIBIT ATTACHMENTS:

EXHIBIT 1.....	BLOCK DIAGRAM
EXHIBIT 2.....	SCHEMATIC
EXHIBIT 3.....	INSTRUCTION MANUAL
EXHIBIT 4.....	FCC ID LABEL SAMPLE
EXHIBIT 5.....	SKETCH OF FCC ID LABEL LOCATION
EXHIBIT 6.....	FRONT VIEW EXTERNAL PHOTO
EXHIBIT 7.....	REAR VIEW EXTERNAL PHOTO
EXHIBIT 8.....	COMPONENT SIDE INTERNAL PHOTO
EXHIBIT 9.....	COPPER SIDE INTERNAL PHOTO
EXHIBIT 10.....	TEST SET UP PHOTO
EXHIBIT 11.....	CIRCUIT DESCRIPTION

APPLICANT: DYNAMIC TECHNOLOGY INC.

FCC ID: PQLSC2000-P

REPORT #: T:\D\DYN\678Z1\678Z1TestReport.doc

TABLE OF CONTENTS

APPLICANT: DYNAMIC TECHNOLOGY INC
FCC ID: PQLSC2000-P

TEST EQUIPMENT LIST

- 1._X_Spectrum Analyzer: HP 8566B-Opt 462, S/N 3138A07786, w/
preselector HP 85685A, S/N 3221A01400, Quasi-Peak Adapter
HP 85650A, S/N 3303A01690 & Preamplifier HP 8449B-OPT H02,
S/N 3008A00372 Cal. 8/31/01 Due 8/31/02
- 2.___ Biconnical Antenna: Eaton Model 94455-1, S/N 1057,
Cal. 10/1/01 Due 10/1/02
- 3.___ Biconnical Antenna: Electro-Metrics Model BIA-25, S/N 1171
Cal. 4/26/01 Due 4/26/03
- 4._X_Log-Periodic Antenna: Electro-Metrics Model EM-6950, S/N 632
Char. 3/15/00 Due 3/15/01
- 5.___ Log-Periodic Antenna: Electro-Metrics Model LPA-30, S/N 409
Char. 3/15/00 Due 3/15/01
- 6._X_Double-Ridged Horn Antenna: Electro-Metrics Model RGA-180,
1-18 GHz, S/N 2319 Cal. 4/27/99 Due 4/27/00
- 7.___ 18-26.3GHz Systron Donner Standard Gain Horn #DBE-520-20
No Cal Required
- 8.___ Horn 40-60GHz: ATM Part #19-443-6R No Cal Required
- 9.___ Line Impedance Stabilization Network: Electro-Metrics Model
EM-7820, w/NEMA Adapter S/N 2682 Cal. 3/16/01 Due 3/16/02
- 10.___ Temperature Chamber: Tenney Engineering Model TTRC, S/N 11717-7
Char. 1/27/01 Due 1/27/02
- 11.___ Frequency Counter: HP Model 5385A, S/N 3242A07460
Char. 11/20/00 Due 11/20/01
- 12.___ Peak Power Meter: HP Model 8900C, S/N 2131A00545
Char. 1/26/01 Due 1/26/02
- 13._X_Open Area Test Site #1-3meters Cal. 12/22/99
- 14.___ Signal Generator: HP 8640B, S/N 2308A21464
Cal. 11/15/01 Due 11/15/02
- 15.___ Passive Loop Antenna: EMC0 Model 6512, 9KHz to 30MHz, S/N
9706-1211 Char. 6/10/00 Due 6/10/01
- 16.___ Dipole Antenna Kit: Electro-Metrics Model TDA-30/1-4, S/N 153
Char. 11/24/00 Due 11/24/01
- 17.___ AC Voltmeter: HP Model 400FL, S/N 2213A14499
Cal. 10/9/01 Due 10/09/02
- 18._X_Digital Multimeter: Fluke Model 77, S/N 43850817
Cal. 11/16/00 Due 11/16/01
- 19.___ Oscilloscope: Tektronix Model 2230, S/N 300572
Char. 2/1/01 Due 2/1/02

APPLICANT: DYNAMIC TECHNOLOGY INC.

FCC ID: PQLSC2000-P

REPORT #: T:\D\DYN\678Z1\678Z1TestReport.doc

Page 1 of 7

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz. The ambient temperature of the UUT was 85°F with a humidity of 37%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz)	METER READING + ACF = FS
33	20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The UUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The UUT was placed in the center of the table. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to 10th harmonic of the fundamental.

Peak readings were taken in three (3) orthogonal planes and the highest readings were converted to average readings based on the duration of "ON" time.

Measurements were made by TIMCO ENGINEERING INC. at the registered open field test site located at 849 N.W. State Road 45, Newberry, FL 32669.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.231

REQUIREMENTS:

Fundamental Frequency MHz	Field Strength of Fundamental dBuV	Field Strength of Harmonics and Spurious Emissions (dBuV/m @ 3m)
40.66 to 40.70	67.04	47.04
70 to 130	61.94	41.94
130 to 174	61.94 to 71.48	41.94 to 51.48
174 to 260	71.48	51.48
260 to 470	71.48 to 81.94	51.48 to 61.94
470 and above	81.94	61.94

THE LIMIT FOR AVERAGE FIELD STRENGTH dBuV/m FOR THE FUNDAMENTAL FREQUENCY= 81.25 dBuV/m. NO FUNDAMENTAL IS ALLOWED IN THE RESTRICTED BANDS.

THE LIMIT FOR AVERAGE FIELD STRENGTH dBuV/m FOR THE HARMONICS AND SPURIOUS FREQUENCIES = 61.25 dBuV/m. SPURIOUS IN THE RESTRICTED BANDS MUST BE LESS THAN 54dBuV/m OR 15.209.

TEST DATA:

Emission Frequency MHz		Meter Reading dBuV	Ant. Polarity	Coax Loss dB	Correction Factor dB	Duty Cycle Factor dB	Field Strength dBuV/m	Margin dB
447.27		58.5	V	2.94	16.98	0.00	78.42	2.83
497.00		20.3	V	3.09	17.48	0.00	40.87	20.38
596.00		12.9	V	3.39	18.97	0.00	35.26	26.00
745.00		10.9	V	3.84	21.42	0.00	36.16	25.10
795.00		10.8	V	3.99	21.66	0.00	36.45	24.81
845.00		12.1	V	4.09	22.12	0.00	38.31	22.94
895.00		21.9	V	4.19	23.34	0.00	49.43	11.82
944.00		24.9	V	3.21	25.06	0.00	53.17	8.08
994.00	**	17.9	V	2.09	24.40	0.00	44.39	9.62
1,044.00	**	23.3	V	2.00	24.36	0.00	49.66	4.34
1,093.00	**	26.5	V	2.05	25.18	0.00	53.73	0.27
1,143.00	**	19.1	V	2.10	25.19	0.00	46.39	7.61
1,193.00	**	20.0	V	2.15	25.62	0.00	47.77	6.23
1,243.00		21.9	V	2.21	26.04	0.00	50.15	11.11
1,292.00		16.4	V	2.26	26.45	0.00	45.11	16.15
1,342.00	**	13.8	V	2.31	26.87	0.00	42.98	11.02
1,392.00	**	12.5	V	2.36	27.29	0.00	42.15	11.85
1,438.00	**	9.6	V	2.41	27.68	0.00	39.69	14.31
1,491.00	**	12.8	V	2.47	28.12	0.00	43.39	10.61
1,541.00	**	17.1	V	2.52	28.23	0.00	47.85	6.15
1,640.00		22.5	V	2.62	28.30	0.00	53.42	7.83
1,690.00	**	24.0	V	2.67	27.06	0.00	53.73	0.27

APPLICANT: DYNAMIC TECHNOLOGY INC.

FCC ID: PQLSC2000-P

REPORT #: T:\D\DYN\678Z1\678Z1TestReport.doc

FCC ID: PQLSC2000-P

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.231

TEST DATA CONTINUED:

Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity	Coax Loss dB	Correction Factor dB	Duty Cycle Factor dB	Field Strength dBuV/m	Margin dB
1,739.00	22.5	V	2.73	28.37	0.00	53.60	7.66
1,789.00	17.0	V	2.78	28.40	0.00	48.18	13.08
1,839.00	18.4	V	2.83	28.44	0.00	49.67	11.58
1,889.00	25.4	V	2.88	28.47	0.00	56.75	4.50
1,938.00	15.0	V	2.93	28.51	0.00	46.44	14.81
1,988.00	16.9	V	2.99	28.54	0.00	48.43	12.83
2,038.00	17.3	V	3.03	28.58	0.00	48.91	12.34
2,087.00	11.0	V	3.07	28.62	0.00	42.69	18.56
2,137.00	9.8	V	3.11	28.67	0.00	41.58	19.67
2,187.00	17.1	V	3.15	28.71	0.00	48.96	12.29
2,236.00	**	V	3.19	28.75	0.00	38.14	15.86
2,286.00	**	V	3.23	28.80	0.00	41.63	12.37
2,336.00	**	H	3.27	28.84	0.00	41.21	12.79
2,435.00	15.4	V	3.35	28.92	0.00	47.67	13.59
2,485.00	**	V	3.39	28.97	0.00	44.26	9.74
2,584.00	13.8	V	3.47	29.28	0.00	46.55	14.71
2,882.00	**	H	3.71	30.36	0.00	41.07	12.93

SAMPLE CALCULATION OF LIMIT @ 303 MHz:

(470 - 260)Mhz = 210 MHz
 (12500 - 3750)uV/m = 8750 uV/m
 8750uV/m/210MHz = 41.67 uV/m/MHz
 (303-260)MHz = 43 MHz
 43 MHz * 41.67 uV/m/MHz = 1791.81 uV/m
 (1791.81 + 3750)uV/m = 5541.81 uV/m limit @ 303 MHz

The transmitter ceases transmitting when the button is released.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: JOSEPH SCOGLIO

DATE TESTED: JULY 17, 2001

APPLICANT: DYNAMIC TECHNOLOGY INC.

FCC ID: PQLSC2000-P

REPORT #: T:\D\DYN\678Z1\678Z1TestReport.doc

APPLICANT: DYNAMIC TECHNOLOGY INC

FCC ID: PQLSC2000-P

CALCULATION OF DUTY CYCLE:

This device transmits FSK data pulses using an FM transmitter.
The duty cycle in this case is 100%. Therefore, the duty cycle
Correction factor is zero.

APPLICANT: DYNAMIC TECHNOLOGY INC

FCC ID: PQLSC2000-P

NAME OF TEST: Occupied Bandwidth

RULES PART NO.: 15.231(C)

REQUIREMENTS: The bandwidth of the emission shall be no wider than .25% of the center frequency for devices operating between 70 and 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

$$447.27 \text{ MHz} * .0025 = 1.118175 \text{ MHz}$$
$$1.118175 \text{ MHz} / 2 = +/- 559.09$$

THE GRAPH ON THE NEXT REPRESENTS THE EMISSIONS TAKEN FOR THIS DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the plot in exhibit 9 was generated. The vertical scale is set to 10 dB per division: the horizontal scale is set to 100 kHz per division.

TEST RESULTS: The unit meets the FCC requirements.

PERFORMED BY: JOSEPH SCOGLIO

DATE: JULY 17, 2001

DYNAMIC TECHNOLOGY INC.
FCC ID: PQLSC2000-P

