



MET Laboratories, Inc. *Safety Certification - EMI - Telecom Environmental Simulation*

914 WEST PATAPSCO AVENUE ! BALTIMORE, MARYLAND 21230-3432 ! PHONE (410) 354-3300 ! FAX (410) 354-3313
33439 WESTERN AVENUE ! UNION CITY, CALIFORNIA 94587 ! PHONE (510) 489-6300 ! FAX (510) 489-6372
3162 BELICK STREET ! SANTA CLARA, CA 95054 ! PHONE (408) 748-3585 ! FAX (510) 489-6372
13301 MCCALLEN PASS ! AUSTIN, TX 78753 ! PHONE (512) 287-2500 ! FAX (512) 287-2513

March 16, 2018

Caterpillar Inc.
100 NE Adams St.
Peoria, IL 61629

Dear David Mitchell,

Enclosed is the EMC Wireless test report for compliance testing of the Caterpillar Inc., PL671 as tested to the requirements of Title 47 of the CFR, Ch. 1 (10-1-06 ed.) FCC Part 15 Subpart C for Intentional Radiators.

Thank you for using the services of MET Laboratories, Inc. If you have any questions regarding these results or if MET can be of further service to you, please feel free to contact me.

Sincerely yours,
MET LABORATORIES, INC.

Joel Huna
Documentation Department

Reference: (\Caterpillar Inc.\EMC95659B-FCC247 BT Rev. 3)

Certificates and reports shall not be reproduced except in full, without the written permission of MET Laboratories, Inc. While use of the A2LA logo in this report reflects MET accreditation under these programs, the report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the Federal Government. This letter of transmittal is not a part of the attached report.



The Nation's First Licensed Nationally Recognized Testing Laboratory

Electromagnetic Compatibility Criteria Test Report

for the

**Caterpillar Inc.
PL671**

Tested under
the FCC Certification Rules
contained in
Title 47 of the CFR, 15.247 Subpart C
for Intentional Radiators

MET Report: EMC95659B-FCC247 BT Rev. 3

March 16, 2018

Prepared For:

**Caterpillar Inc.
100 NE Adams St.
Peoria, IL 61629**


Prepared By:
MET Laboratories, Inc.
914 West Patapsco Avenue, Baltimore, MD 21230

Electromagnetic Compatibility Criteria Test Report


for the

**Caterpillar Inc.
PL671**

Tested under
the FCC Certification Rules
contained in
Title 47 of the CFR, 15.247 Subpart C
for Intentional Radiators




Surendra Shrestha, Project Engineer
Electromagnetic Compatibility Lab



Joel Huna
Documentation Department

Engineering Statement: The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules and 15.247 under normal use and maintenance.



John Mason,
Director, Electromagnetic Compatibility Lab

Report Status Sheet

Revision	Report Date	Reason for Revision
Ø	January 26, 2018	Initial Issue.
1	March 1, 2018	FCC ID correction.
2	March 15, 2018	TCB Corrections and Customer Name Change.
3	March 16, 2018	TCB Corrections.

Table of Contents

I.	Executive Summary	1
	A. Purpose of Test	2
	B. Executive Summary	2
II.	Equipment Configuration	3
	A. Overview.....	4
	B. References.....	5
	C. Test Site	5
	D. Measurement Uncertainty	5
	E. Description of Test Sample.....	6
	F. Equipment Configuration.....	7
	G. Support Equipment	7
	H. Ports and Cabling Information.....	8
	I. Mode of Operation.....	8
	J. Method of Monitoring EUT Operation	8
	K. Modifications	8
	a) Modifications to EUT.....	8
	b) Modifications to Test Standard.....	8
	L. Disposition of EUT	8
III.	Electromagnetic Compatibility Criteria for Intentional Radiators.....	9
	§ 15.203 Antenna Requirement	10
	§ 15.207(a) Conducted Emissions Limits.....	11
	§ 15.247(a)(1) 20 dB Occupied Bandwidth.....	12
	§15.247(a)(1) Average Time of Occupancy (Dwell Time)	16
	§15.247(a)(1) Number of RF Channels	19
	§15.247(a)(1) RF Channel Separation	21
	§ 15.247(b) Peak Power Output	23
	§ 15.247(d) Radiated Spurious Emissions Requirements and Band Edge	28
	§ 15.247(d) RF Conducted Spurious Emissions Requirements and Band Edge	52
IV.	Test Equipment	61
V.	Certification & User's Manual Information.....	63
	A. Certification Information	64
	B. Label and User's Manual Information	68

List of Tables

Table 1. Executive Summary of EMC Part 15.247 Compliance Testing	2
Table 2. EUT Summary Table.....	4
Table 3. References	5
Table 4. Measurement Uncertainty	5
Table 5. Equipment Configuration.....	7
Table 6. Support Equipment.....	7
Table 7. Ports and Cabling Information	8
Table 8. Antenna List	10
Table 9. Conducted Limits for Intentional Radiators from FCC Part 15 § 15.207(a)	11
Table 10. Average Time of Occupancy	16
Table 11. Peak Power Output, Test Results	24
Table 12. Restricted Bands of Operation.....	28
Table 13. Radiated Emissions Limits Calculated from FCC Part 15, § 15.209 (a)	29
Table 14. Test Equipment List	62

List of Plots

Plot 1. 20 dB Bandwidth, 20 dB BW, 2DH1, high.....	13
Plot 2. 20 dB Bandwidth, 20 dB BW, 2DH1, low.....	13
Plot 3. 20 dB Bandwidth, 20 dB BW, 2DH1, mid.....	13
Plot 4. 20 dB Bandwidth, 20 dB BW, 3DH1, high.....	14
Plot 5. 20 dB Bandwidth, 20 dB BW, 3DH1, low.....	14
Plot 6. 20 dB Bandwidth, 20 dB BW, 3DH1, mid.....	14
Plot 7. 20 dB Bandwidth, 20 dB BW, DM1, high.....	15
Plot 8. 20 dB Bandwidth, 20 dB BW, DM1, low	15
Plot 9. 20 dB Bandwidth, 20 dB BW, DM1, mid	15
Plot 10. Dwell Time, burst 2DH1.....	17
Plot 11. Dwell Time, burst 3DH1.....	17
Plot 12. Dwell Time, burst DM1	17
Plot 13. Dwell Time, Dwell Time 2DH1.....	18
Plot 14. Dwell Time, Dwell Time 3DH1.....	18
Plot 15. Dwell Time, Dwell Time DM1	18
Plot 16. Number of Hopping Channels, 2DH1.1.....	19
Plot 17. Number of Hopping Channels, 2DH1.2.....	19
Plot 18. Number of Hopping Channels, 3DH1.1.....	19
Plot 19. Number of Hopping Channels, 3DH1.2.....	20
Plot 20. Number of Hopping Channels, DM1.1	20
Plot 21. Number of Hopping Channels, DM1.2	20
Plot 22. Channel Separation, 2DH1	21
Plot 23. Channel Separation, 3DH1	22
Plot 24. Channel Separation, DM1	22
Plot 25. Peak Power Output, 2DH1, high.....	25
Plot 26. Peak Power Output, 2DH1, low	25
Plot 27. Peak Power Output, 2DH1, mid.....	25
Plot 28. Peak Power Output, 3DH1, high.....	26
Plot 29. Peak Power Output, 3DH1, low	26
Plot 30. Peak Power Output, 3DH1, mid	26
Plot 31. Peak Power Output, DM1, high	27
Plot 32. Peak Power Output, DM1, low	27
Plot 33. Peak Power Output, DM1, mid	27

Plot 34. Spurious Radiated Emissions, 30 MHz - 1 GHz BT DM1 high	30
Plot 35. Spurious Radiated Emissions, average, radiated spurious, 1G-18G, 2DH1, low.....	30
Plot 36. Spurious Radiated Emissions, average, radiated spurious, 1G-18G, 3DH1, low.....	31
Plot 37. Spurious Radiated Emissions, average, radiated spurious, 1G-18G, DM1, low.....	31
Plot 38. Spurious Radiated Emissions, average, radiated spurious, nonhopping, 1G-18G, 2DH1, mid.....	32
Plot 39. Spurious Radiated Emissions, average, radiated spurious, nonhopping, 1G-18G, 3DH1, high.....	32
Plot 40. Spurious Radiated Emissions, average, radiated spurious, nonhopping, 1G-18G, 3DH1, mid.....	33
Plot 41. Spurious Radiated Emissions, average, radiated spurious, nonhopping, 1G-18G, DM1, high.....	33
Plot 42. Spurious Radiated Emissions, average, radiated spurious, nonhopping, 1G-18G, DM1, mid.....	34
Plot 43. Spurious Radiated Emissions, peak, radiated spurious, 1G-18G, 2DH1, low.....	34
Plot 44. Spurious Radiated Emissions, peak, radiated spurious, 1G-18G, 3DH1, low.....	35
Plot 45. Spurious Radiated Emissions, peak, radiated spurious, 1G-18G, DM1, low.....	35
Plot 46. Spurious Radiated Emissions, peak, radiated spurious, nonhopping, 1G-18G, 2DH1, high	36
Plot 47. Spurious Radiated Emissions, peak, radiated spurious, nonhopping, 1G-18G, 2DH1, mid	36
Plot 48. Spurious Radiated Emissions, peak, radiated spurious, nonhopping, 1G-18G, DM1, mid.....	37
Plot 49. Spurious Radiated Emissions, peak, radiated spurious, nonhopping, 1G-18G, DM1, high.....	37
Plot 50. Spurious Radiated Emissions, peak, radiated spurious, nonhopping, 1G-18G, 3DH1, mid	38
Plot 51. Spurious Radiated Emissions, peak, radiated spurious, nonhopping, 1G-18G, 3DH1, high	38
Plot 52. Spurious Radiated Emissions, average, radiated band edge, hopping, 2DH1, 2390M	39
Plot 53. Spurious Radiated Emissions, average, radiated band edge, hopping, 2DH1, 2483.5M	39
Plot 54. Spurious Radiated Emissions, average, radiated band edge, hopping, 3DH1, 2390M	40
Plot 55. Spurious Radiated Emissions, average, radiated band edge, hopping, 3DH1, 2483.5M	40
Plot 56. Spurious Radiated Emissions, average, radiated band edge, hopping, DM1, 2390M.....	41
Plot 57. Spurious Radiated Emissions, average, radiated band edge, hopping, DM1, 2483.5M.....	41
Plot 58. Spurious Radiated Emissions, average, radiated band edge, nonhopping, 2DH1, 2390M	42
Plot 59. Spurious Radiated Emissions, average, radiated band edge, nonhopping, 2DH1, 2483.5M	42
Plot 60. Spurious Radiated Emissions, average, radiated band edge, nonhopping, 3DH1, 2390M	43
Plot 61. Spurious Radiated Emissions, average, radiated band edge, nonhopping, 3DH1, 2483.5M	43
Plot 62. Spurious Radiated Emissions, average, radiated band edge, nonhopping, DM1, 2390M.....	44
Plot 63. Spurious Radiated Emissions, average, radiated band edge, nonhopping, DM1, 2483.5M.....	44
Plot 64. Spurious Radiated Emissions, peak, radiated band edge, hopping, 2DH1, 2390M	45
Plot 65. Spurious Radiated Emissions, peak, radiated band edge, hopping, 2DH1, 2483.5M	45
Plot 66. Spurious Radiated Emissions, peak, radiated band edge, hopping, 3DH1, 2390M	46
Plot 67. Spurious Radiated Emissions, peak, radiated band edge, hopping, 3DH1, 2483.5M	46
Plot 68. Spurious Radiated Emissions, peak, radiated band edge, hopping, DM1, 2390M.....	47
Plot 69. Spurious Radiated Emissions, peak, radiated band edge, hopping, DM1, 2483.5M.....	47
Plot 70. Spurious Radiated Emissions, peak, radiated band edge, nonhopping, 2DH1, 2390M	48
Plot 71. Spurious Radiated Emissions, peak, radiated band edge, nonhopping, 2DH1, 2483.5M	48
Plot 72. Spurious Radiated Emissions, peak, radiated band edge, nonhopping, 3DH1, 2390M	49
Plot 73. Spurious Radiated Emissions, peak, radiated band edge, nonhopping, 3DH1, 2483.5M	49
Plot 74. Spurious Radiated Emissions, peak, radiated band edge, nonhopping, DM1, 2390M.....	50
Plot 75. Spurious Radiated Emissions, peak, radiated band edge, nonhopping, DM1, 2483.5M.....	50
Plot 76. Spurious RF Conducted Emissions, 50M-26G, 3DH1, low.....	53
Plot 77. Spurious RF Conducted Emissions, 50M-26G, 3DH1, mid	53
Plot 78. Spurious RF Conducted Emissions, 50M-26G, 3DH1, high.....	53
Plot 79. Spurious RF Conducted Emissions, 50M-26G, 2DH1, high.....	54
Plot 80. Spurious RF Conducted Emissions, 50M-26G, 2DH1, mid	54
Plot 81. Spurious RF Conducted Emissions, 50M-26G, 2DH1, low.....	54
Plot 82. Spurious RF Conducted Emissions, 50M-26G, DM1, high.....	55
Plot 83. Spurious RF Conducted Emissions, 50M-26G, DM1, mid.....	55
Plot 84. Spurious RF Conducted Emissions, 50M-26G, DM1, low	55
Plot 85. RF Conducted Band Edge, nonhopping, 3DH1, 2483.5M.....	56
Plot 86. RF Conducted Band Edge, nonhopping, 2DH1, 2483.5M.....	56

Plot 87. RF Conducted Band Edge, nonhopping, DM1, 2483.5M	56
Plot 88. RF Conducted Band Edge, nonhopping, 3DH1, 2390M.....	57
Plot 89. RF Conducted Band Edge, nonhopping, 2DH1, 2390M.....	57
Plot 90. RF Conducted Band Edge, nonhopping, DM1, 2390M	57
Plot 91. RF Conducted Band Edge, hopping, 2DH1, 2390M.....	58
Plot 92. RF Conducted Band Edge, hopping, 2DH1, 2483.5M.....	58
Plot 93. RF Conducted Band Edge, hopping, 3DH1, 2483.5M.....	58
Plot 94. RF Conducted Band Edge, hopping, 3DH1, 2390M.....	59
Plot 95. RF Conducted Band Edge, hopping, DM1, 2483.5M	59
Plot 96. RF Conducted Band Edge, hopping, DM1, 2390	59

List of Figures

Figure 1. Block Diagram of Test Configuration.....	6
Figure 2. Block Diagram, Occupied Bandwidth Test Setup.....	12
Figure 3. Peak Power Output Test Setup.....	23
Figure 4. Block Diagram, Conducted Spurious Emissions Test Setup.....	52

List of Photographs

Photograph 1. Spurious Radiated Emissions, above 1 GHz Test setup.....	51
Photograph 2. Spurious Radiated Emissions, upto 1 GHz Test Setup.....	51

List of Terms and Abbreviations

AC	Alternating Current
ACF	Antenna Correction Factor
Cal	Calibration
D	Measurement Distance
dB	Decibels
dB_μA	Decibels above one microamp
dB_μV	Decibels above one microvolt
dB_μA/m	Decibels above one microamp per meter
dB_μV/m	Decibels above one microvolt per meter
DC	Direct Current
E	Electric Field
DSL	Digital Subscriber Line
ESD	Electrostatic Discharge
EUT	Equipment Under Test
F	Frequency
FCC	Federal Communications Commission
GRP	Ground Reference Plane
H	Magnetic Field
HCP	Horizontal Coupling Plane
Hz	Hertz
IEC	International Electrotechnical Commission
kHz	kilohertz
kPa	kilopascal
kV	kilovolt
LISN	Line Impedance Stabilization Network
MHz	Megahertz
μH	microhenry
μ	microfarad
μs	microseconds
NEBS	Network Equipment-Building System
PRF	Pulse Repetition Frequency
RF	Radio Frequency
RMS	Root-Mean-Square
TWT	Traveling Wave Tube
V/m	Volts per meter
VCP	Vertical Coupling Plane

I. Executive Summary

A. Purpose of Test

An EMC evaluation was performed to determine compliance of the Caterpillar Inc. PL671, with the requirements of Part 15, §15.247. All references are to the most current version of Title 47 of the Code of Federal Regulations in effect. In accordance with §2.1033, the following data is presented in support of the Certification of the PL671. Caterpillar Inc. should retain a copy of this document which should be kept on file for at least two years after the manufacturing of the PL671, has been **permanently** discontinued.

B. Executive Summary

The following tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, §15.247, in accordance with Caterpillar Inc., purchase order number PO9516. All tests were conducted using measurement procedure ANSI C63.10-2013.

FCC Reference 47 CFR Part 15.247	Description	Compliance
Title 47 of the CFR, Part 15 §15.203	Antenna Requirement	Compliant
Title 47 of the CFR, Part 15 §15.207(a)	Conducted Emission Limits	Not Applicable
Title 47 of the CFR, Part 15 §15.247(a)(1)	20 dB Occupied Bandwidth	Compliant
Title 47 of the CFR, Part 15 §15.247(a)(1)	Average Time of Occupancy (Dwell Time)	Compliant
Title 47 of the CFR, Part 15 §15.247(a)(1)	Number of RF Channels	Compliant
Title 47 of the CFR, Part 15 §15.247(a)(1)	RF Channel Separation	Compliant
Title 47 of the CFR, Part 15 §15.247(b)	Peak Power Output	Compliant
Title 47 of the CFR, Part 15 §15.247(d); §15.209; §15.205	Radiated Spurious Emissions	Compliant
Title 47 of the CFR, Part 15 §15.247(d)	Spurious Conducted Emissions	Compliant
Title 47 of the CFR, Part 15 §15.247(i)	Maximum Permissible Exposure (MPE)	Compliant

Table 1. Executive Summary of EMC Part 15.247 Compliance Testing

II. Equipment Configuration

A. Overview

MET Laboratories, Inc. was contracted by Caterpillar Inc. to perform testing on the PL671, under Caterpillar Inc.'s purchase order number PO9516.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the Caterpillar Inc., PL671.

The results obtained relate only to the item(s) tested.

Model(s) Tested:	PL671
Model(s) Covered:	PL671
EUT Specifications:	Primary Power: 9 - 32 VDC
	FCC ID: PQMPL671
	Type of Modulations: $\pi/4$ DQPSK, 8DPSK
	Equipment Code: FHSS
	Peak RF Output Power: 9.442 dBm
	EUT Frequency Ranges: 2402 to 2480 MHz
Analysis:	The results obtained relate only to the item(s) tested.
Environmental Test Conditions:	Temperature: 15-35° C
	Relative Humidity: 30-60%
	Barometric Pressure: 860-1060 mbar
Evaluated by:	Surendra Shrestha
Report Date(s):	March 16, 2018

Table 2. EUT Summary Table

B. References

CFR 47, Part 15, Subpart C	Federal Communication Commission, Code of Federal Regulations, Title 47, Part 15: General Rules and Regulations, Allocation, Assignment, and Use of Radio Frequencies
CFR 47, Part 15, Subpart B	Electromagnetic Compatibility: Criteria for Radio Frequency Devices
ANSI C63.4:2014	Methods and Measurements of Radio-Noise Emissions from Low-Voltage Electrical And Electronic Equipment in the Range of 9 kHz to 40 GHz
ISO/IEC 17025:2005	General Requirements for the Competence of Testing and Calibration Laboratories
ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

Table 3. References

C. Test Site

All testing was performed at MET Laboratories, Inc., 914 West Patapsco Avenue, Baltimore, MD 21230. All equipment used in making physical determinations is accurate and bears recent traceability to the National Institute of Standards and Technology.

Radiated Emissions measurements were performed in a 3 meter semi-anechoic chamber (equivalent to an Open Area Test Site). In accordance with §2.948(a)(3), a complete site description is contained at MET Laboratories.

D. Measurement Uncertainty

Test Method	Typical Expanded Uncertainty	K	Confidence Level
RF Frequencies	± 4.52 Hz	2	95%
RF Power Conducted Emissions	± 2.32 dB	2	95%
RF Power Conducted Spurious Emissions	± 2.25 dB	2	95%
RF Power Radiated Emissions	± 3.01 dB	2	95%

Table 4. Measurement Uncertainty

E. Description of Test Sample

The Caterpillar Inc. PL671, Equipment Under Test (EUT), is a dedicated short range communication (DSRC) device. Units are mounted on heavy machinery on both sides of the vehicle to minimize blind spots. It is intended to provide proximity information vehicle to vehicle. A dedicated radio module in the EUT is used to do provide this link. EUT can also communicate to a stationary device or device on a smaller vehicle by Wi-Fi or BT. A GNSS module inside the EUT provides positioning information to the EUT. The two EUTs communicate with each other and the vehicle using Ethernet. An audio module in the EUT can send audible warnings in case of collision possibilities.




Figure 1. Block Diagram of Test Configuration

Note: EUT modified with antenna terminal only for test purposes. Otherwise, EUT will have permanent antenna.

F. Equipment Configuration

The EUT was set up as outlined in Figure 1. All cards, racks, etc., incorporated as part of the EUT is included in the following list.

Ref. ID	Slot #	Name / Description	Model Number	Part Number	Serial Number	Revision
EUT	N/A	DSRC Radio	PL671			A

Table 5. Equipment Configuration

G. Support Equipment

Support equipment necessary for the operation and testing of the EUT is included in the following list.

Ref. ID	Name / Description	Manufacturer	Model Number	* Customer Supplied Calibration Data
PS	Power Supply	MASTECH	HY1803D	N/A
PC	Computer	Dell	VOSTRO or Equiv.	N/A

The 'Customer Supplied Calibration Data' column will be marked as either not applicable, not available, or will contain the calibration date supplied by the customer.

Table 6. Support Equipment

H. Ports and Cabling Information

Ref. ID	Port Name on EUT	Cable Description	Qty.	Length (m)	Max Length	Shielded (Y/N)	Termination Point
1	Data Cable	RJ45 CAT 5 or 6 on Quake Cable	2	TBD		No	12 PIN Conn.
2	Power Supply Leads	On Quake Conn. Red, Black, and Yellow		TBD		No	9-32V

Table 7. Ports and Cabling Information

I. Mode of Operation

Mode 1: The DSRC module in the EUT is put in a continuous transmit mode using the test script. It will broadcast at full power till turned off.

Mode 2: The Wi-Fi module in the EUT is put into continuous transmit mode using the test script. It will broadcast at full power till turned off.

Mode 3: The GNSS module in the EUT is activated using the test script and sends out NMEA data to the CPU. It will receive and send data till turned off. The EUT must be connected to an active antenna and have a clear sky view

Mode 4: The Ethernet is used to set up the test modes. The Ethernet is set to full duplex and set to communicate with the computer in a continuous mode.

J. Method of Monitoring EUT Operation

Mode 1: The DSRC is activated for the test menu using “d”. It will download load firmware to the DSRC module. A secondary menu will appear. Select “b” (TX with no GPS). Current will increase and a rolling script will appear in the terminal window continuously. Please refer to Quake document 1153-3011 for instructions.

Mode 2: The Wi-Fi is activated by opening another terminal. Use the test script to select “w”. Select TX mode. A continuous script will scroll in the terminal as the module transmits.

Mode 3: Open another terminal and select “g” to activate the GNSS module. The NMEA data stream from the module will scroll continuously.

Mode 4: Open another terminal and set up a ping on the ENET. Continuous acknowledgement will be sent.

K. Modifications

a) Modifications to EUT

No modifications were made to the EUT.

b) Modifications to Test Standard

No modifications were made to the test standard.

L. Disposition of EUT

The test sample including all support equipment submitted to the Electro-Magnetic Compatibility Lab for testing was returned to Caterpillar Inc. upon completion of testing.

III. Electromagnetic Compatibility Criteria for Intentional Radiators

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.203 Antenna Requirement

Test Requirement:

§ 15.203: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The structure and application of the EUT were analyzed to determine compliance with Section 15.203 of the Rules. Section 15.203 states that the subject device must meet at least one of the following criteria:

- a.) Antenna must be permanently attached to the unit.
- b.) Antenna must use a unique type of connector to attach to the EUT.
- c.) Unit must be professionally installed. Installer shall be responsible for verifying that the correct antenna is employed with the unit.

Results: The EUT as tested is compliant the criteria of §15.203. EUT has integral antenna(s).

Test Engineer(s): Surendra Shrestha

Test Date(s): December 12, 2017

Gain	Type	Model	Manufacturer
Peak 3.0 dBi 2.4 GHz (multiplexed with 2.4 GHz WiFi)	Balanced Flex (BT)	146153	Molex

Table 8. Antenna List

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.207(a) Conducted Emissions Limits

Test Requirement(s): **§ 15.207 (a):** For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency range (MHz)	§ 15.207(a), Conducted Limit (dB μ V)	
	Quasi-Peak	Average
* 0.15- 0.45	66 - 56	56 - 46
0.45 - 0.5	56	46
0.5 - 30	60	50

Table 9. Conducted Limits for Intentional Radiators from FCC Part 15 § 15.207(a)

Test Procedure: The EUT was placed on a 0.8 m-high wooden table inside a screen room. The EUT was situated such that the back of the EUT was 0.4 m from one wall of the vertical ground plane, and the remaining sides of the EUT were no closer than 0.8 m from any other conductive surface. The EUT was powered from a 50 Ω /50 μ H Line Impedance Stabilization Network (LISN). The EMC receiver scanned the frequency range from 150 kHz to 30 MHz. Conducted Emissions measurements were made in accordance with *ANSI C63.10-2013 "Methods and Measurements of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40 GHz"*. The measurements were performed over the frequency range of 0.15 MHz to 30 MHz using a 50 Ω /50 μ H LISN as the input transducer to an EMC/field intensity meter. For the purpose of this testing, the transmitter was turned on. Scans were performed with the transmitter on.

Test Results: The EUT was not applicable with this requirement. EUT is DC powered device.

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(a)(1) 20 dB Occupied Bandwidth

Test Requirements: **§ 15.247(a):** Operation under the provisions of this section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

For systems using digital modulation techniques, the EUT may operate in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands. For DTS, the minimum 6 dB bandwidth shall be at least 500 kHz. For frequency hopping systems, the EUT shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Test Procedure: The bandwidth of the fundamental frequency was measured with the spectrum analyzer using a RBW approximately equal to 1% of the total emission bandwidth. The 20 dB bandwidth was measured and recorded.

Test Results The EUT was compliant with § 15.247 (a)(2).

Test Engineer(s): Surendra Shrestha

Test Date(s): December 13, 2017





Figure 2. Block Diagram, Occupied Bandwidth Test Setup


20 dB Occupied Bandwidth Test Results




Plot 1. 20 dB Bandwidth, 20 dB BW, 2DH1, high



Plot 2. 20 dB Bandwidth, 20 dB BW, 2DH1, low



Plot 3. 20 dB Bandwidth, 20 dB BW, 2DH1, mid



Plot 4. 20 dB Bandwidth, 20 dB BW, 3DH1, high




Plot 5. 20 dB Bandwidth, 20 dB BW, 3DH1, low




Plot 6. 20 dB Bandwidth, 20 dB BW, 3DH1, mid



Plot 7. 20 dB Bandwidth, 20 dB BW, DM1, high



Plot 8. 20 dB Bandwidth, 20 dB BW, DM1, low



Plot 9. 20 dB Bandwidth, 20 dB BW, DM1, mid

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(a)(1) Average Time of Occupancy (Dwell Time)

Remarks: The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 31.6 second period.

Total hopping channels is 79. The EUT meets the specifications of Section 15.247(a) (1) (iii) for Number of Hopping Channels.

Data Rate	# of channels	hopping period (s)	# of burst per period	Burst Duration (s)	Dwell Time (s)	limit (s)	Margin
DH1	79	31.6	230	0.00044	0.1012	0.4	-0.2988
2DH1	79	31.6	233	0.00042	0.09786	0.4	-0.30214
3DH1	79	31.6	232	0.00043	0.09976	0.4	-0.30024

Table 10. Average Time of Occupancy

Dwell Time Calculation:


Hopping period = # of channel *0.4

of burst = Burst per hopping period


Burst duration = time of single burst

Dwell time = # of burst * Burst Duration


Dwell Time




Plot 10. Dwell Time, burst 2DH1




Plot 11. Dwell Time, burst 3DH1




Plot 12. Dwell Time, burst DM1



Plot 13. Dwell Time, Dwell Time 2DH1



Plot 14. Dwell Time, Dwell Time 3DH1




Plot 15. Dwell Time, Dwell Time DM1


Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(a)(1)


Number of RF Channels




Plot 16. Number of Hopping Channels, 2DH1.1




Plot 17. Number of Hopping Channels, 2DH1.2




Plot 18. Number of Hopping Channels, 3DH1.1



Plot 19. Number of Hopping Channels, 3DH1.2



Plot 20. Number of Hopping Channels, DM1.1




Plot 21. Number of Hopping Channels, DM1.2

Electromagnetic Compatibility Criteria for Intentional Radiators


§ 15.247(a)(1) RF Channel Separation

Requirement: Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.


Remarks: EUT operates below 125mW (20dBm). Channels are separated by more than two thirds of the -20dB Bandwidth.



Plot 22. Channel Separation, 2DH1



Plot 23. Channel Separation, 3DH1



Plot 24. Channel Separation, DM1

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(b) Peak Power Output

Test Requirements: **§15.247(b)(1):** The maximum peak output power of the intentional radiator shall not exceed 0.125 Watts for frequency hopping systems operating in the 2400-2483.5 MHz band. .

§15.247(c): if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 2400 – 2483.5 MHz band and using a point to point application may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725 – 5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter peak output power.

Fixed, point-to-point operation excludes the use of point-to-multipoint systems, omni-directional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.

Test Procedure: The transmitter was connected to a calibrated spectrum analyzer. The EUT was measured at the low, mid and high channels of each band. The EUT utilizes a 3dBi Omni Antenna, so the maximum power allowed is 30dBm.

Test Results: The EUT was compliant with the Peak Power Output limits of **§15.247(b)**.

Test Engineer(s): Surendra Shrestha

Test Date(s): December 13, 2017





Figure 3. Peak Power Output Test Setup

Peak Power Output Test Results


Mod	Freq	Power (dBm)	Limit (dBm)	Margin	Result
DM1	2402	9.442	30	-20.558	Pass
	2440	9.151	30	-20.849	Pass
	2480	8.832	30	-21.168	Pass
2 DH1	2402	7.226	20.96	-13.734	Pass
	2440	7.125	20.96	-13.835	Pass
	2480	7.054	20.96	-13.906	Pass
3 DH1	2402	7.851	20.96	-13.109	Pass
	2440	7.636	20.96	-13.324	Pass
	2480	7.68	20.96	-13.28	Pass

Table 11. Peak Power Output, Test Results


Peak Power Output Test Results




Plot 25. Peak Power Output, 2DH1, high




Plot 26. Peak Power Output, 2DH1, low




Plot 27. Peak Power Output, 2DH1, mid




Plot 28. Peak Power Output, 3DH1, high




Plot 29. Peak Power Output, 3DH1, low




Plot 30. Peak Power Output, 3DH1, mid



Plot 31. Peak Power Output, DM1, high



Plot 32. Peak Power Output, DM1, low



Plot 33. Peak Power Output, DM1, mid

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(d) Radiated Spurious Emissions Requirements and Band Edge

Test Requirements: §15.247(d); §15.205: Emissions outside the frequency band.

§15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a).

§15.205(a): Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090–0.110-----	16.42–16.423	399.9–410	4.5–5.15
¹ 0.495–0.505-----	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905-----	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128-----	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775-----	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775-----	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218-----	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825-----	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225-----	123–138	2200–2300	14.47–14.5
8.291–8.294-----	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366-----	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675-----	156.7–156.9	2655–2900	22.01–23.12
8.41425–8.41475-----	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293-----	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025-----	240–285	3345.8–3358.36	43–36.5
12.57675–12.57725-----	322–335.4	3600–4400	(²)

Table 12. Restricted Bands of Operation

¹ Until February 1, 1999, this restricted band shall be 0.490 – 0.510 MHz.

² Above 38.6

Test Requirement(s): **§ 15.209 (a):** Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in Table 13.

Frequency (MHz)	§ 15.209(a), Radiated Emission Limits (dB μ V) @ 3m
30 - 88	40.00
88 - 216	43.50
216 - 960	46.00
Above 960	54.00

Table 13. Radiated Emissions Limits Calculated from FCC Part 15, § 15.209 (a)

Test Procedure:

The transmitter was set to the mid channel at the highest output power and placed on a 0.8 m high wooden table inside in a semi-anechoic chamber. Measurements were performed with the EUT rotated 360 degrees and varying the adjustable antenna mast with 1 m to 4 m height to determine worst case orientation for maximum emissions. Measurement were repeated the measurement at the low and highest channels.

For frequencies from 30 MHz to 1 GHz, measurements were made using a quasi-peak detector with a 120 kHz bandwidth.

For intentional radiators with a digital device portion which operates below 10 GHz, the spectrum was investigated as per §15.33(a)(1) and §15.33(a)(4); i.e., the lowest RF signal generated or used in the device up to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

In accordance with §15.35(b) the limit on the radio frequency emissions as measured using instrumentation with a peak detector function shall be 20 dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

EUT Field Strength Final Amplitude = Raw Amplitude – Preamp gain + Antenna Factor + Cable Loss – Distance Correction Factor

Test Results:

The EUT was compliant with the Radiated Spurious Emission limits of **§15.247(d)**.

1. For 30 MHz to 1 GHz, only the worst case is reported. All other modes were investigated, and found below the limit lines.
2. Emissions from 18 GHz to 26 GHz were investigated and only noise floor was measured.


Test Engineer(s):

Surendra Shrestha


Test Date(s):

December 21, 2017


Radiated Spurious Emissions Test Results




Plot 34. Spurious Radiated Emissions, 30 MHz - 1 GHz BT DM1 high




Plot 35. Spurious Radiated Emissions, average, radiated spurious, 1G-18G, 2DH1, low




Plot 36. Spurious Radiated Emissions, average, radiated spurious, 1G-18G, 3DH1, low




Plot 37. Spurious Radiated Emissions, average, radiated spurious, 1G-18G, DM1, low




Plot 38. Spurious Radiated Emissions, average, radiated spurious, nonhopping, 1G-18G, 2DH1, mid




Plot 39. Spurious Radiated Emissions, average, radiated spurious, nonhopping, 1G-18G, 3DH1, high




Plot 40. Spurious Radiated Emissions, average, radiated spurious, nonhopping, 1G-18G, 3DH1, mid




Plot 41. Spurious Radiated Emissions, average, radiated spurious, nonhopping, 1G-18G, DM1, high




Plot 42. Spurious Radiated Emissions, average, radiated spurious, nonhopping, 1G-18G, DM1, mid




Plot 43. Spurious Radiated Emissions, peak, radiated spurious, 1G-18G, 2DH1, low




Plot 44. Spurious Radiated Emissions, peak, radiated spurious, 1G-18G, 3DH1, low




Plot 45. Spurious Radiated Emissions, peak, radiated spurious, 1G-18G, DM1, low




Plot 46. Spurious Radiated Emissions, peak, radiated spurious, nonhopping, 1G-18G, 2DH1, high




Plot 47. Spurious Radiated Emissions, peak, radiated spurious, nonhopping, 1G-18G, 2DH1, mid




Plot 48. Spurious Radiated Emissions, peak, radiated spurious, nonhopping, 1G-18G, DM1, mid



Plot 49. Spurious Radiated Emissions, peak, radiated spurious, nonhopping, 1G-18G, DM1, high



Plot 50. Spurious Radiated Emissions, peak, radiated spurious, nonhopping, 1G-18G, 3DH1, mid




Plot 51. Spurious Radiated Emissions, peak, radiated spurious, nonhopping, 1G-18G, 3DH1, high


Radiated Band Edge Measurements

Test Procedures:


The transmitter was turned. Measurements were performed of the low and high Channels. The EUT was rotated orthogonally through all three axes. Plots shown are corrected for both antenna correction factor and distance.




Plot 52. Spurious Radiated Emissions, average, radiated band edge, hopping, 2DH1, 2390M




Plot 53. Spurious Radiated Emissions, average, radiated band edge, hopping, 2DH1, 2483.5M




Plot 54. Spurious Radiated Emissions, average, radiated band edge, hopping, 3DH1, 2390M




Plot 55. Spurious Radiated Emissions, average, radiated band edge, hopping, 3DH1, 2483.5M




Plot 56. Spurious Radiated Emissions, average, radiated band edge, hopping, DM1, 2390M




Plot 57. Spurious Radiated Emissions, average, radiated band edge, hopping, DM1, 2483.5M




Plot 58. Spurious Radiated Emissions, average, radiated band edge, nonhopping, 2DH1, 2390M




Plot 59. Spurious Radiated Emissions, average, radiated band edge, nonhopping, 2DH1, 2483.5M




Plot 60. Spurious Radiated Emissions, average, radiated band edge, nonhopping, 3DH1, 2390M




Plot 61. Spurious Radiated Emissions, average, radiated band edge, nonhopping, 3DH1, 2483.5M




Plot 62. Spurious Radiated Emissions, average, radiated band edge, nonhopping, DM1, 2390M




Plot 63. Spurious Radiated Emissions, average, radiated band edge, nonhopping, DM1, 2483.5M




Plot 64. Spurious Radiated Emissions, peak, radiated band edge, hopping, 2DH1, 2390M




Plot 65. Spurious Radiated Emissions, peak, radiated band edge, hopping, 2DH1, 2483.5M




Plot 66. Spurious Radiated Emissions, peak, radiated band edge, hopping, 3DH1, 2390M




Plot 67. Spurious Radiated Emissions, peak, radiated band edge, hopping, 3DH1, 2483.5M




Plot 68. Spurious Radiated Emissions, peak, radiated band edge, hopping, DM1, 2390M




Plot 69. Spurious Radiated Emissions, peak, radiated band edge, hopping, DM1, 2483.5M




Plot 70. Spurious Radiated Emissions, peak, radiated band edge, nonhopping, 2DH1, 2390M




Plot 71. Spurious Radiated Emissions, peak, radiated band edge, nonhopping, 2DH1, 2483.5M




Plot 72. Spurious Radiated Emissions, peak, radiated band edge, nonhopping, 3DH1, 2390M



Plot 73. Spurious Radiated Emissions, peak, radiated band edge, nonhopping, 3DH1, 2483.5M




Plot 74. Spurious Radiated Emissions, peak, radiated band edge, nonhopping, DM1, 2390M



Plot 75. Spurious Radiated Emissions, peak, radiated band edge, nonhopping, DM1, 2483.5M

Radiated Spurious Emissions Test Setup



Photograph 1. Spurious Radiated Emissions, above 1 GHz Test setup



Photograph 2. Spurious Radiated Emissions, upto 1 GHz Test Setup

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(d) RF Conducted Spurious Emissions Requirements and Band Edge

Test Requirement: **15.247(d)** In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Test Procedure: For intentional radiators with a digital device portion which operates below 10 GHz, the spectrum was investigated as per §15.33(a)(1) and §15.33(a)(4); i.e., the lowest RF signal generated or used in the device up to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

See following pages for detailed test results with RF Conducted Spurious Emissions.

Test Results: The EUT was compliant with the Conducted Spurious Emission limits of **§15.247(d)**. Emissions from 30 MHz to 50 MHz were investigated, and only noise floor was observed.


Test Engineer(s): Surendra Shrestha

Test Date(s): December 13, 2017




Figure 4. Block Diagram, Conducted Spurious Emissions Test Setup


Conducted Spurious Emissions Test Results




Plot 76. Spurious RF Conducted Emissions, 50M-26G, 3DH1, low




Plot 77. Spurious RF Conducted Emissions, 50M-26G, 3DH1, mid




Plot 78. Spurious RF Conducted Emissions, 50M-26G, 3DH1, high




Plot 79. Spurious RF Conducted Emissions, 50M-26G, 2DH1, high




Plot 80. Spurious RF Conducted Emissions, 50M-26G, 2DH1, mid




Plot 81. Spurious RF Conducted Emissions, 50M-26G, 2DH1, low



Plot 82. Spurious RF Conducted Emissions, 50M-26G, DM1, high




Plot 83. Spurious RF Conducted Emissions, 50M-26G, DM1, mid




Plot 84. Spurious RF Conducted Emissions, 50M-26G, DM1, low


Conducted Band Edge Test Results




Plot 85. RF Conducted Band Edge, nonhopping, 3DH1, 2483.5M




Plot 86. RF Conducted Band Edge, nonhopping, 2DH1, 2483.5M




Plot 87. RF Conducted Band Edge, nonhopping, DM1, 2483.5M




Plot 88. RF Conducted Band Edge, nonhopping, 3DH1, 2390M




Plot 89. RF Conducted Band Edge, nonhopping, 2DH1, 2390M




Plot 90. RF Conducted Band Edge, nonhopping, DM1, 2390M




Plot 91. RF Conducted Band Edge, hopping, 2DH1, 2390M




Plot 92. RF Conducted Band Edge, hopping, 2DH1, 2483.5M




Plot 93. RF Conducted Band Edge, hopping, 3DH1, 2483.5M



Plot 94. RF Conducted Band Edge, hopping, 3DH1, 2390M



Plot 95. RF Conducted Band Edge, hopping, DM1, 2483.5M



Plot 96. RF Conducted Band Edge, hopping, DM1, 2390

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(i) Maximum Permissible Exposure

RF Exposure Requirements: **§1.1307(b)(1) and §1.1307(b)(2):** Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

RF Radiation Exposure Limit: **§1.1310:** As specified in this section, the Maximum Permissible Exposure (MPE) Limit shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Sec. 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Sec. 2.1093 of this chapter.

MPE Limit Calculation: EUT's operating frequencies @ 2400-2483.5 MHz; highest conducted power = 9.442 dBm (peak) therefore, **Limit for Uncontrolled exposure: 1 mW/cm² or 10 W/m²**

EUT maximum antenna gain = 3.0 dBi.

Equation from page 18 of OET 65, Edition 97-01

$$S = PG / 4\pi R^2 \quad \text{or} \quad R = \sqrt{PG / 4\pi S}$$

where,
 S = Power Density (1 mW/cm²)
 P = Power Input to antenna (41.4mW)
 G = Antenna Gain (63.1 numeric)

$$R = (41.4 * 63.1 / 4 * 3.14 * 1.0)^{1/2} = (2612.34 / 12.56)^{1/2} = 14.4\text{cm}$$

FCC									
Frequency (MHz)	Con. Pwr. (dBm)	Con. Pwr. (mW)	Ant. Gain (dBi)	Ant. Gain numeric	Pwr. Density (mW/cm ²)	Limit (mW/cm ²)	Margin	Distance (cm)	Result
2402	9.442	8.794	3	1.995	0.00349	1	0.99651	20	Pass

IV. Test Equipment

Test Equipment

Calibrated test equipment utilized during testing was maintained in a current state of calibration per the requirements of ISO/IEC 17025:2005.

Asset	Equipment	Manufacturer	Model	Calibration Date	Calibration Due Date
1T4612	Spectrum Analyzer	Agilent Technologies	E4407B	3/30/2017	9/30/2018
1T4771	PSA Spectrum Analyzer	Agilent Technologies	E4446A	8/10/2016	2/10/2018
1T4149	High-Frequency Anechoic Chamber	Ray Proof	81	Not Required	
1T4442	Pre-amplifier, Microwave	Miteq	AFS42-01001800-30-10P	Func. Verify	
1T4483	Antenna; Horn	ETS-Lindgren	3117	4/19/2017	10/19/2018
1T4745	Antenna, Horn	ETS-Lindgren	3116	1/21/2017	7/21/2018
1T4752	Pre-Amplifier	Miteq	JS44-18004000-35-8P	Func. Verify	
1T4300A	SEMI-ANECHOIC CHAMBER # 1 (FCC)	EMC TEST SYSTEMS	NONE	1/31/2016	1/31/2019
1T4753	Antenna - Bilog	Sunol Sciences	JB6	10/24/2016	4/24/2018
1T4409	EMI Receiver	Rohde & Schwarz	ESIB7	12/7/2016	12/7/2018
1T4910	Digital Barometer, Hygrometer, Thermometer	Control Company	06-662-4	1/15/2016	1/15/2018

Table 14. Test Equipment List

Note: Functionally tested equipment is verified using calibrated instrumentation at the time of testing.

V. Certification & User's Manual Information

Certification & User's Manual Information

A. Certification Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart I — Marketing of Radio frequency devices:

§ 2.801 Radio-frequency device defined.

As used in this part, a radio-frequency device is any device which in its operation is capable of Emitting radio-frequency energy by radiation, conduction, or other means. Radio- frequency devices include, but are not limited to:

- (a) The various types of radio communication transmitting devices described throughout this chapter.
- (b) *The incidental, unintentional and intentional radiators defined in Part 15 of this chapter.*
- (c) The industrial, scientific, and medical equipment described in Part 18 of this chapter.
- (d) Any part or component thereof which in use emits radio-frequency energy by radiation, conduction, or other means.

§ 2.803 Marketing of radio frequency devices prior to equipment authorization.

- (a) Except as provided elsewhere in this chapter, no person shall sell or lease, or offer for sale or lease (including advertising for sale or lease), or import, ship or distribute for the purpose of selling or leasing or offering for sale or lease, any radio frequency device unless:
 - (1) In the case of a device subject to certification, such device has been authorized by the Commission in accordance with the rules in this chapter and is properly identified and labeled as required by §2.925 and other relevant sections in this chapter; or
 - (2) In the case of a device that is not required to have a grant of equipment authorization issued by the Commission, but which must comply with the specified technical standards prior to use, such device also complies with all applicable administrative (including verification of the equipment or authorization under a Declaration of Conformity, where required), technical, labeling and identification requirements specified in this chapter.
- (d) Notwithstanding the provisions of paragraph (a) of this section, the offer for sale solely to business, commercial, industrial, scientific or medical users (but not an offer for sale to other parties or to end users located in a residential environment) of a radio frequency device that is in the conceptual, developmental, design or pre-production stage is permitted prior to equipment authorization or, for devices not subject to the equipment authorization requirements, prior to a determination of compliance with the applicable technical requirements *provided* that the prospective buyer is advised in writing at the time of the offer for sale that the equipment is subject to the FCC rules and that the equipment will comply with the appropriate rules before delivery to the buyer or to centers of distribution.

(e)(1) Notwithstanding the provisions of paragraph (a) of this section, prior to equipment authorization or determination of compliance with the applicable technical requirements any radio frequency device may be operated, but not marketed, for the following purposes and under the following conditions:

- (i) *Compliance testing;*
- (ii) Demonstrations at a trade show provided the notice contained in paragraph (c) of this section is displayed in a conspicuous location on, or immediately adjacent to, the device;
- (iii) Demonstrations at an exhibition conducted at a business, commercial, industrial, scientific or medical location, but excluding locations in a residential environment, provided the notice contained in paragraphs (c) or (d) of this section, as appropriate, is displayed in a conspicuous location on, or immediately adjacent to, the device;
- (iv) Evaluation of product performance and determination of customer acceptability, provided such operation takes place at the manufacturer's facilities during developmental, design or pre-production stages; or
- (v) Evaluation of product performance and determination of customer acceptability where customer acceptability of a radio frequency device cannot be determined at the manufacturer's facilities because of size or unique capability of the device, provided the device is operated at a business, commercial, industrial, scientific or medical user's site, but not at a residential site, during the development, design or pre-production stages.

(e)(2) For the purpose of paragraphs (e)(1)(iv) and (e)(1)(v) of this section, the term *manufacturer's facilities* includes the facilities of the party responsible for compliance with the regulations and the manufacturer's premises, as well as the facilities of other entities working under the authorization of the responsible party in connection with the development and manufacture, but not the marketing, of the equipment.

(f) For radio frequency devices subject to verification and sold solely to business, commercial, industrial, scientific and medical users (excluding products sold to other parties or for operation in a residential environment), parties responsible for verification of the devices shall have the option of ensuring compliance with the applicable technical specifications of this chapter at each end user's location after installation, provided that the purchase or lease agreement includes a proviso that such a determination of compliance be made and is the responsibility of the party responsible for verification of the equipment.

Certification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart J — Equipment Authorization Procedures:

§ 2.901 Basis and Purpose

- (a) In order to carry out its responsibilities under the Communications Act and the various treaties and international regulations, and in order to promote efficient use of the radio spectrum, the Commission has developed technical standards for radio frequency equipment and parts or components thereof. The technical standards applicable to individual types of equipment are found in that part of the rules governing the service wherein the equipment is to be operated.¹ *In addition to the technical standards provided, the rules governing the service may require that such equipment be verified by the manufacturer or importer,* be authorized under a Declaration of Conformity, or receive an equipment authorization from the Commission by one of the following procedures: certification or registration.
- (b) The following sections describe the verification procedure, the procedure for a Declaration of Conformity, and the procedures to be followed in obtaining certification from the Commission and the conditions attendant to such a grant.

§ 2.907 Certification.

- (a) Certification is an equipment authorization issued by the Commission, based on representation and test data submitted by the applicant.
- (b) Certification attaches to all units subsequently marketed by the grantee which are identical (see Section 2.908) to the sample tested except for permissive changes or other variations authorized by the Commission pursuant to Section 2.1043.

¹ In this case, the equipment is subject to the rules of Part 15. More specifically, the equipment falls under Subpart B (of Part 15), which deals with unintentional radiators.

Certification & User's Manual Information

§ 2.948 Description of measurement facilities.

(a) Each party making measurements of equipment that is subject to an equipment authorization under Part 15 or Part 18 of this chapter, regardless of whether the measurements are filed with the Commission or kept on file by the party responsible for compliance of equipment marketed within the U.S. or its possessions, shall compile a description of the measurement facilities employed.

(1) If the measured equipment is subject to the verification procedure, the description of the measurement facilities shall be retained by the party responsible for verification of the equipment.

(i) *If the equipment is verified through measurements performed by an independent laboratory, it is acceptable for the party responsible for verification of the equipment to rely upon the description of the measurement facilities retained by or placed on file with the Commission by that laboratory. In this situation, the party responsible for the verification of the equipment is not required to retain a duplicate copy of the description of the measurement facilities.*

(ii) If the equipment is verified based on measurements performed at the installation site of the equipment, no specific site calibration data is required. It is acceptable to retain the description of the measurement facilities at the site at which the measurements were performed.

(2) If the equipment is to be authorized by the Commission under the certification procedure, the description of the measurement facilities shall be filed with the Commission's Laboratory in Columbia, Maryland. The data describing the measurement facilities need only be filed once but must be updated as changes are made to the measurement facilities or as otherwise described in this section. At least every three years, the organization responsible for filing the data with the Commission shall certify that the data on file is current.

Certification & User's Manual Information

1. Label and User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart A — General:

§ 15.19 Labeling requirements.

(a) *In addition to the requirements in Part 2 of this chapter, a device subject to certification or verification shall be labeled as follows:*

(1) Receivers associated with the operation of a licensed radio service, e.g., FM broadcast under Part 73 of this chapter, land mobile operation under Part 90, etc., shall bear the following statement in a conspicuous location on the device:

This device complies with Part 15 of the FCC Rules. Operation is subject to the condition that this device does not cause harmful interference.

(2) A stand-alone cable input selector switch, shall bear the following statement in a conspicuous location on the device:

This device is verified to comply with Part 15 of the FCC Rules for use with cable television service.

(3) All other devices shall bear the following statement in a conspicuous location on the device:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

(4) Where a device is constructed in two or more sections connected by wires and marketed together, the statement specified under paragraph (a) of this section is required to be affixed only to the main control unit.

(5) When the device is so small or for such use that it is not practicable to place the statement specified under paragraph (a) of this section on it, the information required by this paragraph shall be placed in a prominent location in the instruction manual or pamphlet supplied to the user or, alternatively, shall be placed on the container in which the device is marketed. However, the FCC identifier or the unique identifier, as appropriate, must be displayed on the device.

§ 15.21 Information to user.

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Verification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart B — Unintentional Radiators:

§ 15.105 Information to the user.

(a) For a Class A digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at own expense.

(b) For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a residential environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

End of Report