



## Test Report

Test Report No.:	KTI01E-F0731		
Registration No.:	99058		
Applicant:	IMI Technology Co., Ltd.		
Applicant Address:	Young Nam Bldg 4F, 677-6, Yeoksam-dong, Kangnam-ku, Seoul, 135-080 Korea		
Product:	1394 Digital Camera		
FCC ID:	PREFIRE-I400	Model No.	Fire-i 400
Receipt No.:	KTI20010628	Date of receipt:	Jun, 28, 2001
Date of Issue:	Jun, 28, 2001		
Testing location	Korea Technology Institute Co., Ltd. 51-19, Sanglim3-Ri, Docheok-Myeun, Gwangju-Shi, Gyeungki-Do, Korea		
Test Standards:	ANSI. C63.4 : 1992		
Rule Parts:	FCC Part 15, Subpart B		
Equipment Class:	Class B		
Test Result:	The above mentioned product has been tested and passed.		

Prepare by: J. H. Lee

Tested by: S. B. Kim/ Engineer

Approved by: G. C. Min/ President

Signature      Date

Signature      Date

Signature      Date

Other Aspects :

Abbreviations : • OK, Pass=passed • Fail=failed • N/A=not applicable

- This test report is not permitted to copy partly without our permission.
- This test result is dependent on only equipment to be used.
- This test result is based on a single evaluation of one sample of the above mentioned.
- This test report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S Government.
- We certify this test report has been based on the measurement standards that is traceable to the national or international standards.



**•• Contents ••**

Contents	2
List of Tables	2
List of Figures	2
List of Photographs	3
1. General	3
2. Test Site	3
2.1 Location	4
2.2 List of Test and Measurement Instruments	4
2.3 Test Data	4
2.4 Test Environment	5
3. Description of the tested samples	5
3.1 Rating and Physical characteristics	5
3.2 Submitted documents	6
4. Measurement conditions	6
4.1 Modes of operation	6
4.2 Additional equipments	6
4.3 Uncertainty	6
4.4 Test Setup	7
5. Emission Test	8
5.1 Conducted Emissions	8
5.2 Radiated Emissions	9
6. Photographs of the Test Set-up	11
Label	13
Annex1	
Annex2	14~16

**• List of Tables**

Table 1	List of test and measurement equipment	4
Table 2	Test Data. Radiated Emissions	10

**• List of Photographs**

Photograph 1	Setup for Conducted Emissions	11
Photograph 2	Setup for Radiated Emissions	12



## 1. General

This equipment has been shown to be capable of compliance with the applicable technical standards and was tested in accordance with the measurement procedures as indicated in this report.

We attest to the accuracy of data. All measurements reported herein were performed by Korea Technology Institute Co., LTD. And were made under Chief Engineer's supervision.

We assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

## 2. Test Site

Korea Technology Institute Co., LTD

### 2.1 Location

51-19, Sanglim3-Ri, Docheok-Myeon, Gwangju-Shi, Gyeungki-Do, Korea

The Test Site is in compliance with ANSI C63.4/1992 for measurement of radio Interference.



**Korea Technology Institute Co., Ltd.**

*Page 4 of 12*

## 2.2 List of Test and Measurement Instruments

**Table 1 : List of Test and Measurement Equipment**

**• Conducted Emissions**

**Kind of Equipment**

Type

S/N

Calibrated until

Spectrum Analyzer  
R3261C  
61720427  
11.2001

Field Strength Meter  
ESPC  
832827/011  
4.2002

LISN  
ESH3-Z5  
8254601019  
5.2002

LISN  
KNW407  
8-1097-7  
11.2001

Pulse limiter  
ESH3Z2  
357.8810.52  
11.2001

Conducted Cable  
N/A  
N/A  
11.2001

**• Radiated Emissions**

**Kind of Equipment**

Type

S/N

Calibrated until

Field Strength Meter  
ESPC  
832827/011  
11.2001

Spectrum Analyzer  
R3261C  
61720427  
11.2001

Pre Amplifier  
8447D  
2944A06874  
11.2001



### **3. Description of the tested samples**

The EUT is 1394 Digital Camera.

#### **3.1 Rating and Physical Characteristics**

Interface: IEEE-1394 (2Ports)

Resolution: 640\*480,320\*240,160\*120

Video Mode: YUV4:1:1,4:2:2,4:4:4,RGB24bit

Frame Rate: 3.75,7.5,15.0,30FPS and Single Shot

Image Device: SONY Wfine 1/4"CCD

White Balance: Automatic or Manual Control

#### **3.2 Submitted Documents**

- User's Guide
- Block Diagram



## 4. Measurement Conditions

Testing Input Voltage: AC 110V.

### 4.1 Modes of Operation

The EUT was in the following operation mode during all testing;

### 4.2 Additional Equipment

#### DEVICE TYPE

#### Manufacturer

M/N

S/N

#### FCC ID

PC

COMPAQ COMPUTER CORPORATION  
Deskpro EXM  
6F13JC8JN619  
DoC

Monitor

Samsung Electronics  
750S  
P223HVAR502035  
DoC

Keyboard

COMPAQ COMPUTER CORPORATION  
KB-9963  
B26960GBUKKOWW  
DoC

Mouse

logitech  
M-S48a  
None  
JNZ201213

Mouse

SEJIN ELECTRON INC.  
SMB-400  
0CIM004047  
GJJS965M3

Printer

Hewlett Packard  
C4569A  
SG78M1H0CF  
DoC

CD-ROM

IOI Technology Corporation  
FWEIDE525  
015A7300000  
DoC

SPEAKER


TaeKwang Co., Ltd.  
TSS-150  
S6601900161

MIC

INKEI Co., Ltd.  
None  
None



#### 4.4 Test setup





## 5. EMISSION Test

### 5.1 Conducted Emissions

**Result :** Pass

The line-conducted facility is located inside a 2.3M x 3.5M x 5.5M shielded closure.

The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 605-05.

A 1m x 1.5m wooden table 80cm. High is placed 80cm away from the vertical wall and 1.5m away from the side wall of the shielded room. R&S Model ESH3-Z5(10kHz-30MHz)

50ohm/50 uH line-Impedance Stabilization Networks(LISN) are bonded to the shielded room.

The EUT is powered from the R&S LISN and the support equipment is powered from the Kyoritsu LISN. Power to the LISN are filtered by a high-current high-insertion loss shield enclosures power line filters(100dB 14kHz-1Ghz).

The purpose of the filter is to attenuate ambient signal interference and this filter is also bonded to the shielded enclosure.

All electrical cables are shielded by braided tinned copper zipper tubing with inner diameter of 1/2".

If the EUT is a DC-Powered device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the Kyoritsu LISN.

All interconnecting cables more than 1 meter were shortened by non-inductive bundling (serpentine fashion) to a 1-meter length.

Sufficient time for the EUT, Support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT.

The spectrum was scanned from 450kHz to 30MHz with 100sec. sweep time.

The frequency producing the maximum level was reexamined using EMI field Intensity meter (ESPC). The detector function was set to CISPR Q.P. mode.

The bandwidth of the receiver was set to 10kHz. The EUT, support equipment, and interconnecting each emission was maximized by: switching power lines; varying the mode of operation or resolution; clock or data exchange speed; if applicable; whichever determined the worst-case emission.

Photographs of the worst-case emission can be seen in photograph of conducted test.

Each EME reported was calibrated using self-calibrating mode.



**Figure 1 : Spectral Diagram, LINE – PE**