

# INTERTEK TESTING SERVICES

---

## RF Exposure

The Equipment under Test (EUT) is a Car unit for Xmods 1/16 Buggy Starter Kit Limited Edition model: 6000938 operating at 2.4GHz band. It is powered by 6 x 1.5V AA size batteries or 1 x 9.6V Rechargeable Lithium Battery. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: 0.0dBm (tolerance: +/- 3dB).

The normal conducted output power is 0.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 94.9dB $\mu$ V/m at 3m in the frequency 2471MHz

The EIRP =  $[(FS^*D)^2 / 30]$  mW = -0.3dBm  
which is within the production variation.

The Minimum peak radiated emission for the EUT is 92.3dB $\mu$ V/m at 3m in the frequency 2403MHz

The EIRP =  $[(FS^*D)^2 / 30]$  mW = -2.9dBm  
which is within the production variation.

The maximum conducted output power specified is 3.0dBm = 2.0mW

The source- based time-averaging conducted output power  
= 2.0 \* Duty factor mW= 0.5 mW

The SAR Exclusion Threshold Level:

= 3.0 \* (min. test separation distance, mm) / sqrt(freq. in GHz)  
= 3.0 \* 5 / sqrt (2.471) mW  
= 9.55 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

Transmitter Duty Cycle Calculation

The duration of one cycle = 0.835ms

Effective period of the cycle = 0.210ms

DC = 0.210ms / 0.835ms = 0.251 or 25.1%

This requirement is according to KDB 865664 D02