

# FCC Test Report

## FCC ID:PT7-X8N

**Product:** Mini All in one PC

**Trade Mark:** PIPO

**Model Number:** X8N

**Family Model:** X8-4020, X8-3735, X8R-3288

**Report No.:** STR220706004006E

**Prepared for**

PIPO TECHNOLOGY CO., LIMITED

Area C, 3F, Bao Yun Da Logistics Centre, Warehouse Xi Xiang Avenue,  
Bao An District, Shenzhen, China

**Prepared by**

Shenzhen NTEK Testing Technology Co., Ltd.  
1/F, Building E, Fenda Science Park, Sanwei Community,  
Xixiang Street Bao'an District, Shenzhen P.R. China  
Tel. 400-800-6106, 0755-2320 0050, 0755-2320 0090  
Website:<http://www.ntek.org.cn>

## TEST RESULT CERTIFICATION

**Applicant's name**.....: PIPO TECHNOLOGY CO., LIMITED

Address.....: Area C, 3F, Bao Yun Da Logistics Centre, Warehouse Xi Xiang Avenue,  
Bao An District, Shenzhen, China

**Manufacturer's Name**.....: JINSON DIGITAL(SHENZHEN)LIMITED

Address.....: Area C,3F, Warehouse Building, BaoYunDa Logistics Center, Xixiang  
Blvd, BaoAn District, Shenzhen, China

**Product description**

Product name.....: Mini All in one PC

Model and/or type reference ..: X8N

Family Model.....: X8-4020, X8-3735, X8R-3288

FCC Part15B

**Standards** .....: ANSI C63.4:2014

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with Part 15 of FCC Rules. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.


**Test Sample Number**.....: STR220706004

**Date of Test** .....

Date (s) of performance of tests .....: Jul 06, 2022 ~Aug 04, 2022

Date of Issue .....: Aug.04, 2022

Test Result.....: **Pass**

Testing Engineer : 

(Mary Hu)

Authorized Signatory : 

(Alex Li)

**Table of Contents****Page**

1 . TEST SUMMARY	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST SETUP	8
2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	9
2.4 MEASUREMENT INSTRUMENTS LIST	10
3 . EMC EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.1.1 POWER LINE CONDUCTED EMISSION	11
3.1.2 TEST PROCEDURE	12
3.1.3 TEST SETUP	12
3.1.4 EUT OPERATING CONDITIONS	12
3.1.5 TEST RESULTS	13
3.2 RADIATED EMISSION MEASUREMENT	15
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	15
3.2.2 TEST PROCEDURE	15
3.2.3 TEST SETUP	16
3.2.4 TEST RESULTS	17
3.2.5 TEST RESULTS(1000~18000MHz)	19

## 1. TEST SUMMARY

Test procedures according to the technical standards:

<b>EMC Emission</b>				
Standard	Test Item	Limit	Judgment	Remark
FCC Part15B ANSI C63.4: 2014	Conducted Emission	Class B	PASS	
	Radiated Emission	Class B	PASS	

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report
- (2) For client's request and manual description, the test will not be executed.

### 1.1 TEST FACILITY

Shenzhen NTEK Testing Technology Co., Ltd

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

IC-Registration The Certificate Registration Number is 9270A.

CAB identifier:CN0074

FCC- Accredited Test Firm Registration Number: 463705.

Designation Number: CN1184

### 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**, providing a level of confidence of approximately **95 %**.

#### A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
NTEKC01	ANSI	150 KHz ~ 30MHz	±2.80dB	

#### B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
NTEKA01	ANSI	30MHz~1000MHz	±2.64dB	
		1GHz~6GHz	±2.40dB	
		6GHz~26.5GHz	±2.52dB	

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Mini All in one PC
Trade Mark	PIPO
Model Name	X8N
Family Model	X8-4020, X8-3735, X8R-3288
Model Difference	All models are the same circuit and RF module, except the Model name and appearance.
Product Description	Connecting I/O port: Micro USB, Earphone
	Operation Frequency: 5.825GHz
Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	
Adapter	Model: SAW30A-120-2400U Input: 100-240V, 50/60Hz, 0.8A Output: 12V --- 2400mA
Battery	N/A
Power supply	DC 12V from adapter
Hardware Version	S101GJSR320
Firmware version	JS-BI-7-S101GJSR310-238-A
Software Version	Windows 10 home 19043.1348

## 2.1.1 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Model 1	Burning Test(USB+TF card+HDMI+LAN)
Model 2	BT Link mode
Model 3	Wi-Fi 2.4G / 5.2G / 5.8G


For Conducted Test	
Final Test Mode	Description
Model 1	Burning Test(USB+TF card+HDMI+LAN)
Model 2	BT Link mode
Model 3	Wi-Fi 2.4G / 5.2G / 5.8G

For Radiated Test	
Final Test Mode	Description
Model 1	Burning Test(USB+TF card+HDMI+LAN)
Model 2	BT Link mode
Model 3	Wi-Fi 2.4G / 5.2G / 5.8G


Note: Final Test Mode: Through Pre-scan, find the model 1 is the worst case.  
Only the worst case mode is recorded in the report.

## 2.2 DESCRIPTION OF TEST SETUP

Mode CE: Burning Test(USB+TF card+HDMI+LAN)



Mode RE: Burning Test(USB+TF card+HDMI+LAN)



## 2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
AE-2	Adapter		SAW30A-120-2400U	N/A	EUT
AE-3	LCD	PHILIPS	241P6V	UHBA1724011720C24	
AE-4	Keyboard		Z4M39PA#AB2	9GCMCB180007747	
AE-5	Mouse	ThinkPad	N/A	N/A	
AE-6	Earphone	N/A	N/A	N/A	
AE-7	U-disk & TF card	N/A	N/A	N/A	

Item	Cable Type	Shielded Type	Ferrite Core	Length	Note
C-1	USB Cable	NO	NO	1.0m	
C-2	USB Cable	NO	NO	1.2m	
C-3	USB Cable	NO	NO	1.2m	
C-4	HDMI Cable	YES	YES	1.0m	
C-5	USB Cable	NO	NO	1.2m	
C-6	Earphone Cable	NO	NO	1.5m	

## Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) "YES" means "shielded" "with core"; "NO" means "unshielded" "without core".

## 2.4 MEASUREMENT INSTRUMENTS LIST

## Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2022.04.01	2023.03.31	1 year
2	Test Receiver	R&S	ESPI	101318	2022.04.06	2023.04.05	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2022.03.30	2023.03.29	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2020.05.11	2023.05.10	3 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2021.11.07	2022.11.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2022.03.31	2023.03.30	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2021.11.07	2022.11.06	1 year
8	Amplifier	EMC	EMC051835SE	980246	2022.06.17	2023.06.16	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2022.06.17	2023.06.16	1 year
10	Power Meter	DARE	RPR3006W	15I00041S NO84	2022.06.16	2023.06.15	1 year
11	Power Sensor	R&S	URV4-Z4	0395.1619.05	2022.06.17	2023.06.16	1 year
12	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2022.06.17	2025.06.16	3 year
13	High Test Cable(1G-40 GHz)	N/A	R-03	N/A	2022.06.17	2025.06.16	3 year
14	High Test Cable(1G-40 GHz)	N/A	R-04	N/A	2022.06.17	2025.06.16	3 year
15	Test Receiver	R&S	ESCI	101160	2022.04.06	2023.04.05	1 year

## AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2022.04.06	2023.04.05	1 year
2	LISN	R&S	ENV216	101313	2022.04.06	2023.04.05	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2022.04.06	2023.04.05	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2020.05.11	2023.05.10	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2020.05.11	2023.05.10	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2020.05.11	2023.05.10	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2020.05.11	2023.05.10	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable which is scheduled for calibration every 3 years.

### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

### 3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 TEST SETUP



**Note: 1. Support units were connected to second LISN.**

**2. Both of LISNs (A and B) are 80 cm from EUT and at least 80 cm from other units and other metal planes**

### 3.1.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


## 3.1.5 TEST RESULTS

EUT:	Mini All in one PC	Model Name. :	X8N
Temperature:	24.5 °C	Relative Humidity:	52%
Pressure:	1010hPa	Test Date:	2022-07-21
Test Mode:	Mode 1	Phase :	L
Test Voltage:	AC 120V/60Hz		

Frequency (MHz)	Reading Level (dB $\mu$ V)	Correct Factor (dB)	Measure-ment (dB $\mu$ V)	Limits (dB $\mu$ V)	Margin (dB)	Remark
0.1650	39.99	9.61	49.60	65.20	-15.60	QP
0.1650	22.43	9.61	32.04	55.20	-23.16	AVG
0.2379	36.77	9.63	46.40	62.17	-15.77	QP
0.2379	26.11	9.63	35.74	52.17	-16.43	AVG
0.5460	36.74	9.66	46.40	56.00	-9.60	QP
0.5460	29.92	9.66	39.58	46.00	-6.42	AVG
0.9455	28.52	9.68	38.20	56.00	-17.80	QP
0.9455	22.65	9.68	32.33	46.00	-13.67	AVG
4.4419	30.29	9.76	40.05	56.00	-15.95	QP
4.4419	22.54	9.76	32.30	46.00	-13.70	AVG
20.2454	28.64	10.17	38.81	60.00	-21.19	QP
20.2454	21.60	10.17	31.77	50.00	-18.23	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Mini All in one PC	Model Name.:	X8N
Temperature:	24.5 °C	Relative Humidity:	52%
Pressure:	1010hPa	Test Date:	2022-07-21
Test Mode:	Mode 1	Phase :	N
Test Voltage:	AC 120V/60Hz		

Frequency (MHz)	Reading Level (dB $\mu$ V)	Correct Factor (dB)	Measure-ment (dB $\mu$ V)	Limits (dB $\mu$ V)	Margin (dB)	Remark
0.1507	40.55	9.65	50.20	65.96	-15.76	QP
0.1507	24.68	9.65	34.33	55.96	-21.63	AVG
0.1819	40.36	9.64	50.00	64.39	-14.39	QP
0.1819	28.78	9.64	38.42	54.39	-15.97	AVG
0.5020	33.34	9.66	43.00	56.00	-13.00	QP
0.5020	26.84	9.66	36.50	46.00	-9.50	AVG
0.9616	28.81	9.69	38.50	56.00	-17.50	QP
0.9616	23.29	9.69	32.98	46.00	-13.02	AVG
1.5180	27.01	9.67	36.68	56.00	-19.32	QP
1.5180	19.72	9.67	29.39	46.00	-16.61	AVG
19.0731	31.27	10.13	41.40	60.00	-18.60	QP
19.0731	25.40	10.13	35.53	50.00	-14.47	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 3m)
	dBuV/m	dBuV/m
30 ~ 88	39.0	40.0
88 ~ 216	43.5	43.5
216 ~ 960	46.5	46.0
Above 960	49.5	54.0

Notes:

- (1) The limit for radiated test was performed according to as following:  
FCC PART 15B /ICES-003.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)= $20\log$  Emission level (uV/m).

#### 3.2.2 TEST PROCEDURE

##### **Test Arrangement for Radiated Emissions up to 1 GHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited test facility. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for quasi-peak detection (QP) at frequency below 1GHz.

##### **Test Arrangement for Radiated Emissions above 1 GHz.**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna can be varied from one meter to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.


Note: For the hand-held device, the EUT should be measured for all 3 axes and only the worst case is recorded in the report

During the radiated emission test, according to ANSI C63.4-2014(4.2), the Spectrum Analyzer was set with the following configurations:


Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
	Avg	1 MHz	10 Hz

### 3.2.3 TEST SETUP

For Radiated Emission 30~1000MHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz



## 3.2.4 TEST RESULTS


## TEST RESULTS (30~1000 MHz)

EUT:	Mini All in one PC	Model Name:	X8N
Temperature:	24.5 °C	Relative Humidity:	55%
Pressure:	1010 hPa	Test Date :	2022-07-21
Test Mode :	Mode 1	Polarization :	Horizontal
Test Power :	AC 120V/60Hz		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	153.2004	20.31	18.19	38.50	43.50	-5.00	QP
H	158.6676	17.81	17.79	35.60	43.50	-7.90	QP
H	308.9125	17.59	20.14	37.73	46.00	-8.27	QP
H	323.3204	16.98	20.42	37.40	46.00	-8.60	QP
H	696.8567	8.34	27.96	36.30	46.00	-9.70	QP
H	796.1829	10.07	29.03	39.10	46.00	-6.90	QP

Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.




EUT:	Mini All in one PC	Model Name :	X8N
Temperature:	24.5 °C	Relative Humidity:	55%
Pressure:	1010 hPa	Test Date :	2022-07-21
Test Mode :	Mode 1	Polarization :	Vertical
Test Power :	AC 120V/60Hz		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	31.2893	5.91	25.48	31.39	40.00	-8.61	QP
V	44.2752	7.20	18.20	25.40	40.00	-14.60	QP
V	148.4410	9.34	18.48	27.82	43.50	-15.68	QP
V	308.9126	11.26	20.14	31.40	46.00	-14.60	QP
V	444.8514	7.01	24.24	31.25	46.00	-14.75	QP
V	742.2587	11.46	28.64	40.10	46.00	-5.90	QP

Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.



## 3.2.5 TEST RESULTS(1000~18000MHz)

EUT:	Mini All in one PC	Model Name :	X8N
Temperature:	24.5 °C	Relative Humidity:	55%
Pressure:	1010 hPa	Test Date :	2022-07-21
Test Mode :	Mode 1		
Test Power :	AC 120V/60Hz		

All the modulation modes have been tested, and the worst result was report as below:

Polar (H/V)	Frequency	Reading	Correct	Result	Limit	Over Limit	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
V	4230.000	37.77	17.46	55.23	74.00	-18.77	peak
V	4230.000	24.64	17.46	42.10	54.00	-11.90	AVG
V	4995.000	39.40	18.95	58.35	74.00	-15.65	peak
V	4995.000	24.39	18.95	43.34	54.00	-10.66	AVG
V	7672.500	35.63	22.94	58.57	74.00	-15.43	peak
V	7672.500	24.36	22.94	47.30	54.00	-6.70	AVG
V	8820.000	35.97	23.64	59.61	74.00	-14.39	peak
V	8820.000	22.54	23.64	46.18	54.00	-7.82	AVG
V	14005.000	33.01	28.97	61.98	74.00	-12.02	peak
V	14005.000	19.23	28.97	48.20	54.00	-5.80	AVG
V	15535.000	34.73	27.78	62.51	74.00	-11.49	peak
V	15535.000	20.28	27.78	48.06	54.00	-5.94	AVG
H	4995.000	42.92	18.95	61.87	74.00	-12.13	peak
H	4995.000	25.39	18.95	44.34	54.00	-9.66	AVG
H	7077.500	35.37	22.26	57.63	74.00	-16.37	peak
H	7077.500	20.94	22.26	43.20	54.00	-10.80	AVG
H	8310.000	34.84	24.14	58.98	74.00	-15.02	peak
H	8310.000	21.16	24.14	45.30	54.00	-8.70	AVG
H	10477.500	34.83	25.26	60.09	74.00	-13.91	peak
H	10477.500	21.03	25.26	46.29	54.00	-7.71	AVG
H	14430.000	33.35	29.45	62.80	74.00	-11.20	peak
H	14430.000	19.22	29.45	48.67	54.00	-5.33	AVG
H	15620.000	35.02	27.19	62.21	74.00	-11.79	peak
H	15620.000	21.51	27.19	48.70	54.00	-5.30	AVG

## Remark:

Result = Reading + Correct, Over Limit= Result - Limit

Note: Only the worst results data points are reported in the report.

Other emissions are attenuated 20dB below the limit that does not recorded in the report.

END OF REPORT