



**Test Report:** 4W07862

**Applicant:** Gecko Electronics Inc  
450 Des Canetons  
Quebec, G2E 5W6

**Equipment Under Test:** (EUT) IRFMR-1, RF TRANSMITTER

**In Accordance With:** FCC PART 15, SUBPART C, 15.249

**Tested By:** Nemko Canada Inc.  
303 River Road, R.R. 5  
Ottawa, Ontario K1V 1H2

**Authorized By:**

Kevin Carr, EMC/EMI/Wireless Specialist

**Date:** 18 August 2004

**Total Number of Pages:** 21

---

## Table of Contents

<b>Section 1.</b>	<b>Summary of Test Results .....</b>	<b>3</b>
<b>Section 2.</b>	<b>Equipment Under Test .....</b>	<b>5</b>
<b>Section 3.</b>	<b>Transmission Requirements .....</b>	<b>7</b>
<b>Section 4.</b>	<b>Radiated Emissions.....</b>	<b>10</b>
<b>Section 5.</b>	<b>Frequency Stability.....</b>	<b>13</b>
<b>Section 6.</b>	<b>Power line Conducted Emissions.....</b>	<b>14</b>
<b>Section 7.</b>	<b>Occupied Bandwidth .....</b>	<b>18</b>
<b>Section 8.</b>	<b>Block Diagram.....</b>	<b>20</b>
<b>Section 9.</b>	<b>Test Equipment List .....</b>	<b>21</b>

**Section 1. Summary of Test Results****General****All measurements are traceable to national standards.**

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, Subpart C. All tests were conducted using measurement procedure ANSI C63.4-2001. Radiated emissions are made on an open area test site. A description of the test facility is on file with the FCC.

THIS TEST REPORT RELATES ONLY TO THE ITEM(S) TESTED.

THE FOLLOWING DEVIATIONS FROM, ADDITIONS TO, OR EXCLUSIONS FROM THE TEST SPECIFICATIONS HAVE BEEN MADE.

See "Summary of Test Data".



TESTED BY: \_\_\_\_\_  
Daxesh Thakker, Wireless Test Engineer

DATE: 18 August 2004

Nemko Canada Inc. authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

This report applies only to the items tested.

This report shall not be reproduced except in full without the written approval of the testing laboratory.



Nemko Canada Inc., a testing laboratory, is accredited by the Standards Council of Canada.  
The tests included in this report are within the scope of this accreditation.

## Nemko Canada Inc.

## FCC Part 15, Subpart C, 15.249

PROJECT NO.: 4W07862

### *EQUIPMENT: IRFMR-1, RF TRANSMITTER*

## Summary Of Test Data

Name of Test	Para. Number	Results
Transmission Requirements	15.249 (a)	Complied
Radiated Emissions	15.249 (d)	Complied
Occupied Bandwidth	2.202	Complied
Frequency Tolerance	15.249(b) (2)	Complied
Power line Conducted Emissions	15.207	Complied

## Test Conditions:


**Indoor**      Temperature: 22° C  
                    Humidity: 30 %

**Outdoor**      Temperature: 18° C  
                    Humidity: 39 %

**Section 2. Equipment Under Test****General Equipment Information**

<b>Manufacturer:</b>	Gecko Electronics Inc
<b>Model No.:</b>	IRFMR-1 RF TRANSMITTER
<b>Serial No.:</b>	None
<b>Date Received In Laboratory:</b>	May 26 2004
<b>Nemko Identification No.:</b>	Item no. 1 & 2
<b>Tested To Standard No.:</b>	FCC part 15, Subpart C, 15.249
<b>Test Voltage</b>	<b>Tx.</b> 120 V, 60 Hz
<b>Frequency Range (or <i>fixed frequency</i>):</b>	Tx. 915.85 MHz & 916.59 MHz
<b>Field Strength (<i>distance</i>):</b>	86.2 dBuVolts/m @ 3m.
<b>Occupied Bandwidth (99% BW):</b>	176.7 KHz
<b>Type of Modulation:</b>	FSK
<b>Emission Designator (TRC-43):</b>	176K7F1D
<b>Transmitter Spurious (<i>worst case</i>):</b>	53.5 dBuV/m @3m @ 1831.7 MHz

Test Set-up



**Section 3.        Transmission Requirements****Para. No.: 15.249 (a)**

<b>Test Performed By: Daxesh Thakker</b>	<b>Date of Test: May 26, 2004</b>
--	-----------------------------------



**Minimum Standard:** The non-momentarily operated devices in the frequency bands of 902-928 MHz, 2.4 – 2.4835 GHz & 5.725-5.875 GHz shall not exceed 50 millivolts/m (94 dBuVolts/m) field strength of the fundamental, at a distance of 3 meters.

**Test Results:** Complied

**Test Data:** Compliance was determined by verification of technical specifications and a functional test on the equipment.

**Rationale for Compliance with Transmission Requirements**

<b>15.249 (a)</b>	The EUT is transmitting one 61 mSec pulse at every 5 seconds interval. The EUT is non-momentarily operated device.
<b>15.249 (a)</b>	The EUT transmits in the frequency band of 902-928 MHz.

**EQUIPMENT: IRFMR-1, RF TRANSMITTER**

**Section 4. Radiated Emissions****Para. No.: 15.249 (a) - Transmitter**

<b>Test Performed By: Daxesh Thakker</b>	<b>Date of Test: July 21, 2004</b>
--	------------------------------------

**Minimum Standard:**

<b>Fundamental Frequency (MHz)</b>	<b>Field Strength of Fundamental (millivolts/m @ 3m)</b>	<b>Field Strength of harmonics (millivolts/m @ 3m)</b>
902-928	50	0.5
2400-2483.5	50	0.5
5725-5875	50	0.5


**Test Results:** Complied**Test Data:** As per attached tabulated data.

**Transmitter Radiated Emissions' data.**


Test Date: July 21, 2004											
Engineer's Name: Daxesh Thakker											
Temperature (C°): 22						Humidity : 39 %					
Tested as per Table Top											
Test Distance (meters): 3						Range: A					
Freq. (MHz)	Ant.	Pol. V/H	RCVD Signal (dB $\mu$ V)	Ant. Factor (dB)	Amp. Gain (dB)	Cable Loss (dB)	Field Strength (dB $\mu$ V/ m)	Limit (dB $\mu$ V/ m)	Margin (dB)	Detector	Amp.
915.8500	ED4	V	53.7	28.5	N/A	4.0	86.2	94.0	7.8	Q-Peak	-
915.8500	ED4	H	49.5	28.5	N/A	4.0	82.0	94.0	12.0	Q-Peak	-
1831.7000	Horn2	V	67.7	28.2	46.6	3.9	53.5	54.0	0.5	Peak	1-2GHz
1831.7000	Horn2	H	65.1	28.1	46.6	3.9	51.3	54.0	2.7	Peak	1-2GHz
2747.5500	Horn2	V	71.6	30.3	56.6	5.7	50.8	54.0	3.2	Peak	2-4GHz
2747.5500	Horn2	H	74.5	30.3	56.6	5.7	53.5	54.0	0.5	Peak	2-4GHz
3663.5400	Horn2	V	64.7	32.7	54.9	7.0	49.4	54.0	4.6	Peak	2-4GHz
3663.5400	Horn2	H	64.4	32.7	54.9	7.0	49.2	54.0	4.8	Peak	2-4GHz
4579.8910	Horn2	V	61.1	34.3	53.3	7.7	49.6	54.0	4.4	Peak	4-8GHz
4579.8910	Horn2	H	62.2	34.1	53.3	7.7	50.9	54.0	3.1	Peak	4-8GHz
5495.1000	Horn2	V	58.7	34.4	51.2	8.7	50.7	54.0	3.3	Peak	4-8GHz
5495.1000	Horn2	H	59.5	34.6	51.2	8.7	51.7	54.0	2.3	Peak	4-8GHz
Note 1: Antenna Legend: BC = Biconical, BL = Bilog, LP = Log-Periodic, Horn = Horn, ED = EMCO Dipole											
Note 2: Detector Legend: Q-Peak = 120 kHz RBW, Peak = 1.0 MHz RBW											
Note 3: The EUT was searched up to 10th harmonics of the fundamental.											
Notes:		Measurement Receiver = H.P.8565E, RBW/VBW = 1/3MHz, using a peak detector Measurement Receiver = ESVS30, 120kHz RBW using a Q-Peak detector									

**Radiated Emission Setup photo-**

**Front View:**



**Rear View**



**Section 5. Frequency Stability****Para. No.: 15.249 (b) (2)**

<b>Test Performed By: Daxesh Thakker</b>	<b>Date of Test: June 22, 2004</b>
--	------------------------------------

**Limit:** +/-0.001%, +/- 10ppm**Test Results:** Complied.**Test Data:** See the table.

STV = 120 volts, 60 Hz.

**Voltage Stability**

	Ref. Freq.	Measured	Variance	
Voltage	(MHz)	(MHz)	(Hz)	ppm
85% X STV	915.847715	915.847528	187	0.2
115% X STV	915.847715	915.847580	135	0.1

**Temperature Stability @ STV**

	Ref. Freq.	Measured	Variance	
Deg. Cel.	(MHz)	(MHz)	(Hz)	ppm
-20	915.847715	915.852799	-5084	-5.6
50	915.847715	915.841715	6000	6.6

Ref. Freq. (20Deg. C): 915.847715 MHz

1 ppm = 0.000915848 MHz

1 ppm = 915.847715 Hz

**Section 6. Power line Conducted Emissions****Para. No.: 15.207**

<b>Test Performed By: Daxesh Thakker</b>	<b>Date of Test: June 17, 2004</b>
--	------------------------------------

**Limit:**

<b>Limits For Conducted Disturbance At The Mains Ports: Paragraph No. 15.207 for Class A</b>			
Frequency Range MHz	Limits dB( $\mu$ V)		Result (Pass/Fail)
	Quasi-Peak	Average	
0.15 to 0.50	79	66	
0.50 to 30	73	60	N/A
<b>Limits For Conducted Disturbance At The Mains Ports: Paragraph No. 15.207 for Class B</b>			
Frequency Range MHz	Limits dB( $\mu$ V)		Result (Pass/Fail)
	Quasi-Peak	Average	
0.15 to 0.50	66 to 56	56 to 46	
0.5 to 5	56	46	
5 to 30	60	50	PASS

**Notes**



1. The lower limit shall apply at the transition frequency.  
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50MHz.

**Test Results:** Complied**Test Data:** See attached graphs and table.



**EQUIPMENT: IRFMR-1, RF TRANSMITTER****AC Power line Conducted Emissions:**

Test Date: June 17, 2004										
Engineer's Name: Daxesh Thakker										
Temperature (C°): 21	Humidity %: 15									
Tested as per (Table Top/Floor Standing): Table Top										
Spectrum plots for each frequency band can be found at the back of this section. Any Emissions that were above or within 5 dB of the average limits were remeasured with a receiver and recorded. . *All plots were generated with a peak detector.										
Port under test: AC Input	Test Voltage: 120VAC, 60Hz									
Receiver Results (if applicable) :										
Conductor	Frequency (MHz)	Detector	Level dB(µV)	Limit dB(µV)	Margin dB					
Phase	0.15	Quasi-Peak	51.7	66.0	14.3					
Phase	0.15	Average	1.5	56.0	54.5					
Phase	0.325	Quasi-Peak	47.9	59.6	11.7					
Phase	0.325	Average	1	49.6	48.6					
Phase	0.5	Quasi-Peak	39.4	56.0	16.6					
Phase	0.5	Average	-0.3	46.0	46.3					
Neutral	0.15	Quasi-Peak	51.9	66.0	14.1					
Neutral	0.15	Average	1.3	56.0	54.7					
Neutral	0.325	Quasi-Peak	48.1	59.6	11.5					
Neutral	0.325	Average	0.6	49.6	49.0					
Neutral	0.5	Quasi-Peak	40	56.0	16.0					
Neutral	0.5	Average	-0.2	46.0	46.2					
Notes:										

## AC Power line Conducted Emissions Plots





*EQUIPMENT: IRFMR-1, RF TRANSMITTER*




**Section 7.        Occupied Bandwidth****Para. No.: 2.202**

<b>Test Performed By:</b> Daxesh Thakker	<b>Date of Test:</b> June 17, 2004
--	------------------------------------

**Test Results:** Complied.**Test Data:** See attached graphs.

**EQUIPMENT: IRFMR-1, RF TRANSMITTER**

**Section 8. Block Diagram****Outdoor Test Site For Radiated Emissions**

The spectrum was searched up to the 10th harmonic of the fundamental frequency of operation.

## Section 9. Test Equipment List

Conducted Disturbance at Mains Test Equipment Used:

CAL Cycle	Equipment	Manufacturer	Model No.	Asset/Serial No.	Last Cal.	Next Cal.
1 Year	LISN	EMCO	4825/2	FA001545	Oct. 30/03	Oct. 30/04
Extended	Spectrum Analyzer	Hewlett-Packard	8566B	FA001309	May 26/04	May. 26/05
Extended	Spectrum Analyzer Display	Hewlett-Packard	85662A	FA001309	May 26/04	May. 26/05
1 Year	Transient Limiter	Hewlett-Packard	1194 7A	FA000975	June. 18/04	June. 18/05

Note: N/A = Not Applicable, NCR = No Cal Required, COU = CAL On Use, OUT = Out For CAL/Repair

### Equipment List - Radiated Emissions

CAL Cycle	Equipment	Manufacturer	Model No.	Asset/Serial No.	Last Cal.	Next Cal.
1 Year	Spectrum Analyzer	Hewlett-Packard	8565E	FA000981	May 31/04	May 31/05
1 Year	Dipole Antenna Set	EMCO #1	3121C	FA000814	May. 09/04	May. 09/05
1 Year	Receiver	Rohde & Schwarz	ESVS-30	FA001437	July. 24/03	July. 24/04
1 Year	Horn Antenna #1	EMCO	3115	FA000649	Dec. 18/03	Dec. 18/04
1 Year	1.0 – 2.0 GHz Amplifier	JCA	12-400	FA001498	June. 18/04	June. 18/05
1 Year	2.0 – 4.0 GHz Amplifier	JCA	24-600	FA001496	June. 18/04	June. 18/05
1 Year	4.0 – 8.0 GHz Amplifier	JCA	48-600	FA001497	June. 18/04	June. 18/05

Note: N/A = Not Applicable, NCR = No Cal Required, COU = CAL On Use, OUT = Out For CAL/Repair

## Section 10. Test Equipment List, 4w07862

Conducted Disturbance at Mains Test Equipment Used:

CAL Cycle	Equipment	Manufacturer	Model No.	Asset/Serial No.	Last Cal.	Next Cal.
1 Year	LISN	EMCO	4825/2	FA001545	Oct. 30/03	Oct. 30/04
Extended	Spectrum Analyzer	Hewlett-Packard	8566B	FA001309	May 26/04	May. 26/05
Extended	Spectrum Analyzer Display	Hewlett-Packard	85662A	FA001309	May 26/04	May. 26/05
1 Year	Transient Limiter	Hewlett-Packard	1194 7A	FA000975	June. 18/03	June. 18/04

Note: N/A = Not Applicable, NCR = No Cal Required, COU = CAL On Use, OUT = Out For CAL/Repair

### Equipment List - Radiated Emissions

CAL Cycle	Equipment	Manufacturer	Model No.	Asset/Serial No.	Last Cal.	Next Cal.
1 Year	Spectrum Analyzer	Hewlett-Packard	8565E	FA000981	May 31/04	May 31/05
1 Year	Dipole Antenna Set	EMCO #1	3121C	FA000814	May. 09/04	May. 09/05
1 Year	Receiver	Rohde & Schwarz	ESVS-30	FA001437	July. 24/03	July. 24/04
1 Year	Horn Antenna #1	EMCO	3115	FA000649	Dec. 18/03	Dec. 18/04
1 Year	1.0 – 2.0 GHz Amplifier	JCA	12-400	FA001498	June. 18/04	June. 18/05
1 Year	2.0 – 4.0 GHz Amplifier	JCA	24-600	FA001496	June. 18/04	June. 18/05
1 Year	4.0 – 8.0 GHz Amplifier	JCA	48-600	FA001497	June. 18/04	June. 18/05
1 Year	Receiver	Rohde & Schwarz	ESH3	FA000872	Jan. 14/04	Jan. 14/05
COU	5.0 – 18.0 GHz Amplifier	NARDA	DWT-186N23U40	FA001409	COU	COU
1 Year	Active Loop Antenna	Rohde & Schwarz	HFH2-Z2	FA000631	17 May 2004	17 May 2005
1 Year	Frequency Counter	Hewlett Packard	HP5350A	2444A00135	Feb. 19/04	Feb. 19/05
1 Year	Climate Chamber	Thermotron	SM-16C	15649-S	COU	COU
1 Year	Temp. Measurement System	fluke	55	FA001247 FA001248	Feb. 17/04	Feb. 17/05

Note: N/A = Not Applicable, NCR = No Cal Required, COU = CAL On Use, OUT = Out For CAL/Repair