

Section 8. Host PC labeling

<E-label screen>

To access the E-label screen, do one of the following:

- Restart the computer. When the logo screen is displayed, press F9. The E-label screen is displayed.
- Restart the computer. When the logo screen is displayed, press Enter or tap the prompt to enter the Startup Interrupt menu. Then press F9 or tap the Regulatory Information option. The E-label screen is displayed.



Regulatory Information



CAN ICES-3(B)/NMB-3(B)


ご使用のコンピュータにIEEE802.11a準拠の無線機が搭載されている場合は、電波法の規定により5.15-5.35GHz周波数帯での使用は屋内に限られます。

This product contains a lithium-ion battery and a lithium battery; dispose of according to local, state, or federal laws.

Copyrighted code and parts contained herein.
© Copyright Lenovo 2005, 2018.

M/N: TP00107A
FCC ID: PU5-TP00107A, IC: 4182A-TP00107A
Contains FCC ID: PD9AX200D2L, IC: 1000M-AX200D2L
Contains FCC ID: MCLT77H747, IC: 2878D-T77H747

R-R-LVK-TP00107A
MSIP-CRM-FOB-L850-GL
MSIP-CRM-INT-9560D2W
MSIP-CRM-FOX-T77H747



MIC/KS 総務省指定
第AC-1607号

Press **Enter** to exit and restart your computer

v0.91