



REPORT No.: SZ24100159W01

TEST REPORT

APPLICANT : Savant Technologies LLc, dba Ge
lighting, a Savant Company

**PRODUCT
NAME** : LED LAMP

MODEL NAME : CLEDA199CD1, CLEDA199CDRV

BRAND NAME : GE

FCC ID : PUU-A19-DMFCIX

STANDARD(S) : 47 CFR Part 15 Subpart C

**RECEIPT
DATE** : 2024-10-18

TEST DATE : 2024-10-29 to 2024-11-21

ISSUE DATE : 2024-12-16



Edited by:

Su Xiaoxian

Su Xiaoxian (Rapporteur)

Approved by:

Shen Junsheng

Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Result	4
1.1. Testing Applied Standards	5
1.2. Test Equipment List	6
1.3. Measurement Uncertainty	8
1.4. Testing Laboratory	8
2. General Description	9
2.1. Information of Applicant and Manufacturer	9
2.2. Information of EUT	9
2.3. Channel List of EUT	10
2.4. Test Configuration of EUT	11
2.5. Test Conditions	11
2.6. Test Setup Layout Diagram	11
3. Test Results	14
3.1. Antenna Requirement	14
3.2. Duty Cycle of Test Signal	15
3.3. Maximum Peak Conducted Output Power	16
3.4. Maximum Average Conducted Output Power	17
3.5. 6 dB Bandwidth	18
3.6. Conducted Spurious Emissions and Band Edge	19
3.7. Power Spectral Density	20
3.8. Conducted Emission	21
3.9. Restricted Frequency Bands	22
3.10. Radiated Emission	23
Annex A Test Data and Result	25



REPORT No.: SZ24100159W01

Change History		
Version	Date	Reason for change
1.0	2024-12-16	First edition



1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	N/A	Duty Cycle of Test Signal	Oct. 31, 2024	Lin Haoyang	PASS	No deviation
3	15.247(b)	Maximum Peak Conducted Output Power	Oct. 31, 2024	Lin Haoyang	PASS	No deviation
4	15.247(b)	Maximum Average Conducted Output Power	Oct. 31, 2024	Lin Haoyang	PASS	No deviation
5	15.247(a)	Bandwidth	Oct. 31, 2024	Lin Haoyang	PASS	No deviation
6	15.247(d)	Conducted Spurious Emission and Band Edge	Oct. 31, 2024	Lin Haoyang	PASS	No deviation
7	15.247(e)	Power Spectral Density	Oct. 31, 2024	Lin Haoyang	PASS	No deviation
8	15.207	Conducted Emission	Oct. 29, 2024	Fan Shengquan	PASS	No deviation
9	15.247(d)	Restricted Frequency Bands	Nov. 08, 2024	Yang Lian	PASS	No deviation
10	15.209, 15.247(d)	Radiated Emission	Nov. 06, 2024	Wang Deyong	PASS	No deviation

Note 1: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2013 and KDB 558074 D01 v05r02.

Note 2: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 3: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.



1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



1.2. Test Equipment List

1.2.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY5347083 6	N9010A	Agilent	2024.02.19	2025.02.18
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial Cable	CB02	RF02	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.2.2 Conducted Emission Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY5640009 3	N9038A	KEYSIGHT	2024.01.25	2025.01.24
LISN	8127449	NSLK 8127	Schwarzbeck	2024.02.02	2025.02.01
Pulse Limiter (10dB)	VTSD 9561 F-B #206	VTSD 9561-F	Schwarzbeck	2024.05.30	2025.05.29
RF Coaxial Cable (DC-100MHz)	BNC	MRE04	Qualwave	2024.07.02	2025.07.01

1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
Morlab EMCR	Morlab	V1.2
TS+ -[JS32-CE]	Tonscend	V2.5.0.0

**1.2.4 Radiated Test Equipments**

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Signal Analyzer	MY56060145	N9020A	Agilent	2024.05.30	2025.05.29
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2024.06.03	2025.06.02
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2024.06.22	2025.06.21
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2024.05.30	2025.05.29
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2024.05.30	2025.05.29
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	2024.07.03	2025.07.02
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KKF-2	Qualwave	2024.07.03	2025.07.02
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-NN-5	Qualwave	2024.07.03	2025.07.02
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.05.10	2025.05.09



1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Peak Output Power	$\pm 2.22\text{dB}$	Confidence levels of 95%
Power Spectral Density	$\pm 2.22\text{dB}$	Confidence levels of 95%
Bandwidth	$\pm 5\%$	Confidence levels of 95%
Conducted Spurious Emission	$\pm 2.77\text{dB}$	Confidence levels of 95%
Restricted Frequency Bands	$\pm 5\%$	Confidence levels of 95%
Radiated Emission	$\pm 2.95\text{dB}$	Confidence levels of 95%
Conducted Emission	$\pm 2.44\text{dB}$	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone	+86 755 36698555
Facsimile	+86 755 36698525
FCC Designation Number	CN1192
FCC Test Firm Registration Number	226174



2. General Description

2.1. Information of Applicant and Manufacturer

Applicant	Savant Technologies LLc, dba Ge lighting, a Savant Company
Applicant Address	1975 Noble Road Cleveland Ohio United States 44112
Manufacturer	Xiamen Topstar lighting Co.,Ltd.
Manufacturer Address	676 Meixi Avenue,Tong'an District,Xiamen,China

2.2. Information of EUT

Product Name:	LED LAMP
Sample No.:	2#,3#, 4#
Hardware Version:	5
Software Version:	1.1.084.AB (for CLEDA199CD1), 1.1.084.6B (for CLEDA199CDRV)
Equipment Type:	Bluetooth LE
Bluetooth Version:	N/A
Modulation Type:	GFSK
Data Rate:	1Mbps, 2Mbps, 512kbps
Operating Frequency Range:	2402MHz-2480MHz
Antenna Type:	On-board antenna
Antenna Gain:	-1.2dBi

Note 1: According to the certificate holder, they declared that the product name: LED LAMP, with model name: CLEDA199CD1, CLEDA199CDRV have the same hardware and software. They have differences in model name and software versions of the product. The specifications of the product's LED beads also vary. The main test model name is CLEDA199CD1, only the result for CLEDA199CD1 was recorded in this report.

Note 2: We use the dedicated software to control the EUT continuous transmission.

Note 3: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2.3.Channel List of EUT

Channel I	Frequency y (MHz)	Channel I	Frequency y (MHz)	Channel I	Frequency y (MHz)	Channel I	Frequency y (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Note 1: The black bold channels were selected for test.

2.4. Test Configuration of EUT


Test mode is used to control the EUT under the maximum power level during test.

2.5. Test Conditions

Temperature (°C)	15-35
Relative Humidity (%)	30-60
Atmospheric Pressure (kPa)	86-106

2.6. Test Setup Layout Diagram

2.6.1. Conducted Measurement




2.6.2. Conducted Emission Measurement




2.6.3.Radiation Measurement


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz





3. Test Results

3.1. Antenna Requirement

3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.2. Test Result

Antenna location	Antenna Type	Coupling Method
☒ Internal ☐ External	☐ FPC Antenna ☐ Spring Antenna ☐ Ceramic Antenna ☐ Integrated Antenna ☐ Dipole Antenna ☐ PCB Antenna ☐ PIFA Antenna ☒ On-board antenna	☐ I-PEX Connector ☐ SMA Connector ☐ RP-SMA Connector ☐ Metal Shrapnel ☒ Layout



3.2. Duty Cycle of Test Signal

3.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be non constant.

3.2.2. Test Result

Refer to Annex A.1 in this report.



3.3. Maximum Peak Conducted Output Power

3.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

3.3.2. Test Procedures

KDB 558074 Section 8.3.1 was used in order to prove compliance.

3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.3.4. Test Result

Refer to Annex A.2 in this report.



3.4. Maximum Average Conducted Output Power

3.4.1. Requirement

According to FCC section 15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum average conducted output power of the intentional radiator shall not exceed 1 Watt.

3.4.2. Test Procedures

KDB 558074 Section 8.3.2 was used in order to prove compliance.

3.4.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.4.4. Test Result

Refer to Annex A.3 in this report.



3.5.6 dB Bandwidth

3.5.1.Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

3.5.1.Test Procedures

The steps for the first option are as follows:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 100kHz
- c) Set VBW to 300kHz
- d) Detector = peak.
- e) Trace mode = max hold
- f) Sweep time = auto couple
- g) Allow the trace to fully stabilize
- h) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., $RBW = 100\text{ kHz}$, $VBW \geq 3 \times RBW$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be $\geq 6\text{ dB}$.

3.5.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.5.3.Test Result

Refer to Annex A.4 in this report.



3.6. Conducted Spurious Emissions and Band Edge

3.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.6.2. Test Procedures

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.

3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.6.4. Test Result

Refer to Annex A.5 and A.6 in this report.



3.7. Power Spectral Density

3.7.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.7.2. Test Procedures

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 3kHz
- d) Set VBW to 10kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level within the RBW

3.7.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.7.4. Test Result

Refer to Annex A.7 in this report.

3.8. Conducted Emission

3.8.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.8.2. Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.

3.8.3. Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.8.4. Test Result

Refer to Annex A.8 in this report.

3.9. Restricted Frequency Bands

3.9.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

3.9.2. Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

3.9.3. Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.9.4. Test Result

Refer to Annex A.9 in this report.

3.10. Radiated Emission

3.10.1.Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2:For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



3.10.2.Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.10.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.10.4.Test Result

Refer to Annex A.10 in this report.




Annex A Test Data and Result

A.1. Duty Cycle of Test Signal


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE_512K	2402	Ant1	57.45	2.41	0.93
NVNT	BLE_512K	2440	Ant1	57.22	2.42	0.93
NVNT	BLE_512K	2480	Ant1	57.45	2.41	0.93
NVNT	BLE 1M	2402	Ant1	63.49	1.97	2.5
NVNT	BLE 1M	2440	Ant1	63.49	1.97	2.5
NVNT	BLE 1M	2480	Ant1	62.9	2.01	2.56
NVNT	BLE 2M	2402	Ant1	33.87	4.7	4.76
NVNT	BLE 2M	2440	Ant1	33.87	4.7	4.76
NVNT	BLE 2M	2480	Ant1	33.87	4.7	4.76

Test Graphs


Duty Cycle NVNT BLE_512K 2402MHz Ant1




Duty Cycle NVNT BLE_512K 2440MHz Ant1



Duty Cycle NVNT BLE_512K 2480MHz Ant1




Duty Cycle NVNT BLE 1M 2402MHz Ant1






Duty Cycle NVNT BLE 1M 2440MHz Ant1




Duty Cycle NVNT BLE 1M 2480MHz Ant1






Duty Cycle NVNT BLE 2M 2402MHz Ant1




Duty Cycle NVNT BLE 2M 2440MHz Ant1





Duty Cycle NVNT BLE 2M 2480MHz Ant1




**A.2. Maximum Peak Conducted Output Power**


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	BLE_512K	2402	Ant1	6.79	0	6.79	0.00478	30	Pass
NVNT	BLE_512K	2440	Ant1	8.09	0	8.09	0.00644	30	Pass
NVNT	BLE_512K	2480	Ant1	7.3	0	7.3	0.00537	30	Pass
NVNT	BLE 1M	2402	Ant1	11.01	0	11.01	0.01262	30	Pass
NVNT	BLE 1M	2440	Ant1	12.16	0	12.16	0.01644	30	Pass
NVNT	BLE 1M	2480	Ant1	11.27	0	11.27	0.0134	30	Pass
NVNT	BLE 2M	2402	Ant1	11.16	0	11.16	0.01306	30	Pass
NVNT	BLE 2M	2440	Ant1	12.36	0	12.36	0.01722	30	Pass
NVNT	BLE 2M	2480	Ant1	11.43	0	11.43	0.0139	30	Pass

Test Graphs


Peak Power NVNT BLE_512K 2402MHz Ant1



Peak Power NVNT BLE_512K 2440MHz Ant1




Peak Power NVNT BLE_512K 2480MHz Ant1



Peak Power NVNT BLE 1M 2402MHz Ant1




Peak Power NVNT BLE 1M 2440MHz Ant1



Peak Power NVNT BLE 1M 2480MHz Ant1



Peak Power NVNT BLE 2M 2402MHz Ant1




Peak Power NVNT BLE 2M 2440MHz Ant1





Peak Power NVNT BLE 2M 2480MHz Ant1




**A.3. Maximum Average Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	BLE_512K	2402	Ant1	2.68	2.41	5.09	0.00323	30	Pass
NVNT	BLE_512K	2440	Ant1	4.17	2.42	6.59	0.00456	30	Pass
NVNT	BLE_512K	2480	Ant1	3.22	2.41	5.63	0.00366	30	Pass
NVNT	BLE 1M	2402	Ant1	7.72	1.97	9.69	0.00931	30	Pass
NVNT	BLE 1M	2440	Ant1	8.7	1.97	10.67	0.01167	30	Pass
NVNT	BLE 1M	2480	Ant1	8.02	2.01	10.03	0.01007	30	Pass
NVNT	BLE 2M	2402	Ant1	5.43	4.7	10.13	0.0103	30	Pass
NVNT	BLE 2M	2440	Ant1	6.62	4.7	11.32	0.01355	30	Pass
NVNT	BLE 2M	2480	Ant1	5.56	4.7	10.26	0.01062	30	Pass



Test Graphs

Average Power NVNT BLE_512K 2402MHz Ant1




Average Power NVNT BLE_512K 2440MHz Ant1





Average Power NVNT BLE_512K 2480MHz Ant1




Average Power NVNT BLE 1M 2402MHz Ant1





Average Power NVNT BLE 1M 2440MHz Ant1



Average Power NVNT BLE 1M 2480MHz Ant1





Average Power NVNT BLE 2M 2402MHz Ant1




Average Power NVNT BLE 2M 2440MHz Ant1





Average Power NVNT BLE 2M 2480MHz Ant1




**A.4. 6 dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE_512K	2402	Ant1	0.637	0.5	Pass
NVNT	BLE_512K	2440	Ant1	0.623	0.5	Pass
NVNT	BLE_512K	2480	Ant1	0.616	0.5	Pass
NVNT	BLE 1M	2402	Ant1	0.632	0.5	Pass
NVNT	BLE 1M	2440	Ant1	0.623	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.625	0.5	Pass
NVNT	BLE 2M	2402	Ant1	1.002	0.5	Pass
NVNT	BLE 2M	2440	Ant1	1.05	0.5	Pass
NVNT	BLE 2M	2480	Ant1	1.088	0.5	Pass



Test Graphs

-6dB Bandwidth NVNT BLE_512K 2402MHz Ant1




-6dB Bandwidth NVNT BLE_512K 2440MHz Ant1




-6dB Bandwidth NVNT BLE_512K 2480MHz Ant1




-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2440MHz Ant1




-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1




-6dB Bandwidth NVNT BLE 2M 2402MHz Ant1



-6dB Bandwidth NVNT BLE 2M 2440MHz Ant1



-6dB Bandwidth NVNT BLE 2M 2480MHz Ant1



**A.5. Conducted Spurious Emissions**


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE_512K	2402	Ant1	-45.61	-20	Pass
NVNT	BLE_512K	2440	Ant1	-45.77	-20	Pass
NVNT	BLE_512K	2480	Ant1	-45.35	-20	Pass
NVNT	BLE 1M	2402	Ant1	-49.87	-20	Pass
NVNT	BLE 1M	2440	Ant1	-51.27	-20	Pass
NVNT	BLE 1M	2480	Ant1	-49.16	-20	Pass
NVNT	BLE 2M	2402	Ant1	-49.5	-20	Pass
NVNT	BLE 2M	2440	Ant1	-51.52	-20	Pass
NVNT	BLE 2M	2480	Ant1	-49.78	-20	Pass

Test Graphs

Tx. Spurious NVNT BLE_512K 2402MHz Ant1 Ref




Tx. Spurious NVNT BLE_512K 2402MHz Ant1 Emission



Tx. Spurious NVNT BLE_512K 2440MHz Ant1 Ref




Tx. Spurious NVNT BLE_512K 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE_512K 2480MHz Ant1 Ref




Tx. Spurious NVNT BLE_512K 2480MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2402MHz Ant1 Ref




Tx. Spurious NVNT BLE 2M 2402MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Ref




Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 2M 2480MHz Ant1 Emission




**A.6. Band Edge**


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE_512K	2402	Ant1	-55.51	-20	Pass
NVNT	BLE_512K	2480	Ant1	-57.71	-20	Pass
NVNT	BLE 1M	2402	Ant1	-55.72	-20	Pass
NVNT	BLE 1M	2480	Ant1	-59.22	-20	Pass
NVNT	BLE 2M	2402	Ant1	-53.05	-20	Pass
NVNT	BLE 2M	2480	Ant1	-61.01	-20	Pass

Test Graphs


Band Edge NVNT BLE_512K 2402MHz Ant1 Ref




Band Edge NVNT BLE_512K 2402MHz Ant1 Emission




Band Edge NVNT BLE_512K 2480MHz Ant1 Ref




Band Edge NVNT BLE_512K 2480MHz Ant1 Emission




Band Edge NVNT BLE 1M 2402MHz Ant1 Ref




Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



Band Edge NVNT BLE 1M 2480MHz Ant1 Ref




Band Edge NVNT BLE 1M 2480MHz Ant1 Emission



Band Edge NVNT BLE 2M 2402MHz Ant1 Ref




Band Edge NVNT BLE 2M 2402MHz Ant1 Emission



Band Edge NVNT BLE 2M 2480MHz Ant1 Ref



Band Edge NVNT BLE 2M 2480MHz Ant1 Emission




**A.7. Power Spectral Density**

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE_512K	2402	Ant1	-1.35	0	-1.35	8	Pass
NVNT	BLE_512K	2440	Ant1	-0.02	0	-0.02	8	Pass
NVNT	BLE_512K	2480	Ant1	-0.84	0	-0.84	8	Pass
NVNT	BLE 1M	2402	Ant1	-4.73	0	-4.73	8	Pass
NVNT	BLE 1M	2440	Ant1	-3.68	0	-3.68	8	Pass
NVNT	BLE 1M	2480	Ant1	-4.65	0	-4.65	8	Pass
NVNT	BLE 2M	2402	Ant1	-6.6	0	-6.6	8	Pass
NVNT	BLE 2M	2440	Ant1	-5.18	0	-5.18	8	Pass
NVNT	BLE 2M	2480	Ant1	-5.94	0	-5.94	8	Pass

Test Graphs


PSD NVNT BLE_512K 2402MHz Ant1



PSD NVNT BLE_512K 2440MHz Ant1



PSD NVNT BLE_512K 2480MHz Ant1




PSD NVNT BLE 1M 2402MHz Ant1





PSD NVNT BLE 1M 2440MHz Ant1




PSD NVNT BLE 1M 2480MHz Ant1



PSD NVNT BLE 2M 2402MHz Ant1




PSD NVNT BLE 2M 2440MHz Ant1





PSD NVNT BLE 2M 2480MHz Ant1





A.8. Conducted Emission

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT+Lampholder+BT TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.2042	48.50	32.59	63.44	53.44	Line	PASS
2	0.4011	41.43	25.98	57.83	47.83		PASS
3	0.7832	36.95	23.96	56.00	46.00		PASS
4	2.3433	27.43	16.88	56.00	46.00		PASS
5	5.7140	25.58	12.74	60.00	50.00		PASS
6	27.6756	21.82	15.49	60.00	50.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1913	51.09	32.44	63.98	53.98	Neutral	PASS
2	0.2990	44.36	28.28	60.27	50.27		PASS
3	0.5123	40.46	26.06	56.00	46.00		PASS
4	2.4895	27.37	15.72	56.00	46.00		PASS
5	5.6046	25.89	13.05	60.00	50.00		PASS
6	28.3517	24.54	17.91	60.00	50.00		PASS



A.9. Restricted Frequency Bands

The lowest and highest channels are tested to verify the Restricted Frequency Bands.

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading


G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

1Mbps


Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
0	2344.33	PK	21.72	5.78	27.50	55.00	74	PASS
0	2390.00	AV	-0.23	5.78	27.50	33.05	54	PASS
39	2483.50	PK	26.08	5.78	27.50	59.36	74	PASS
39	2483.50	AV	4.11	5.78	27.50	37.39	54	PASS



(PEAK, Channel 0)



(AVERAGE, Channel 0)




(PEAK, Channel 39)




(AVERAGE, Channel 39)

**2Mbps**

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
0	2386.11	PK	21.78	5.78	27.50	55.06	74	PASS
0	2387.67	AV	0.21	5.78	27.50	33.49	54	PASS
39	2484.84	PK	22.53	5.78	27.50	55.81	74	PASS
39	2483.63	AV	1.73	5.78	27.50	35.01	54	PASS



(PEAK, Channel 0)



(AVERAGE, Channel 0)




(PEAK, Channel 39)




(AVERAGE, Channel 39)

**512kbps**

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
0	2385.07	PK	22.07	5.78	27.50	55.35	74	PASS
0	2390.00	AV	0.13	5.78	27.50	33.41	54	PASS
39	2483.74	PK	24.70	5.78	27.50	57.98	74	PASS
39	2483.50	AV	0.60	5.78	27.50	33.88	54	PASS



(PEAK, Channel 0)



(AVERAGE, Channel 0)



(PEAK, Channel 39)





A.10. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain


A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.


Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note3: For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

**1Mbps****Plot for Channel 0**


Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
33.8839	31.09	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
88.2583	24.72	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
102.8228	31.12	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
159.1391	22.47	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
262.0621	28.57	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
360.1301	24.57	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1038.0076	43.24	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2373.2747	42.28	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4803.7608	52.74	N/A	44.75	74.00	N/A	54.00	Horizontal	PASS
8758.1516	43.97	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
14036.8074	49.14	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
17431.0862	48.25	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
32.9129	27.86	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
85.3453	30.44	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
168.8488	21.15	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
250.4104	27.94	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
360.1301	25.07	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
760.1702	24.02	N/A	N/A	N/A	46.00	N/A	Vertical	PASS


(Antenna Vertical, 30MHz to 1GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1031.0062	44.17	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
1599.1198	39.55	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4803.7608	51.72	N/A	35.15	74.00	N/A	54.00	Vertical	PASS
7193.0386	41.63	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
11163.4327	47.26	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
14305.6611	49.45	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 1GHz to 18GHz)

Plot for Channel 19




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
33.8839	32.36	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
102.8228	27.73	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
158.1682	27.34	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
188.2683	22.94	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
347.5075	26.11	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
760.1702	25.44	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1037.0074	43.64	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
1628.1256	40.08	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3821.5643	44.22	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4879.7760	52.56	N/A	41.99	74.00	N/A	54.00	Horizontal	PASS
10580.1160	45.48	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
15126.6253	48.13	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
34.8549	28.42	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
80.4905	22.29	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
130.0100	25.30	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
275.6557	25.27	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
360.1301	26.08	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
760.1702	24.59	N/A	N/A	N/A	46.00	N/A	Vertical	PASS


(Antenna Vertical, 30MHz to 1GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1016.0032	44.30	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
1797.1594	39.97	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4879.7760	52.92	N/A	40.40	74.00	N/A	54.00	Vertical	PASS
10630.5261	46.33	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13050.2100	48.10	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
16946.1892	48.89	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 1GHz to 18GHz)

Plot for Channel 39




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
34.8549	30.36	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
86.3163	31.89	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
133.8939	33.26	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
192.1522	25.60	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
360.1301	25.18	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
760.1702	25.02	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1098.0196	43.69	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
1726.1452	41.10	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2505.3011	46.75	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4959.7920	52.76	N/A	44.08	74.00	N/A	54.00	Horizontal	PASS
11360.2721	46.99	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
14646.5293	49.20	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
33.8839	28.44	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
87.2873	30.96	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
107.6777	24.93	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
133.8939	25.89	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
251.3814	26.75	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
521.3113	29.28	N/A	N/A	N/A	46.00	N/A	Vertical	PASS

(Antenna Vertical, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1102.0204	41.60	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
1761.1522	39.60	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2502.3005	44.93	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4959.7920	54.50	N/A	40.92	74.00	N/A	54.00	Vertical	PASS
11165.8332	46.97	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
14641.7283	48.93	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 1GHz to 18GHz)


**512kbps**

Plot for Channel 0




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.5936	18.69	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
102.8228	24.84	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
128.0681	20.02	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
189.2392	24.84	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
360.1301	28.90	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
836.8769	32.36	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1099.0198	42.26	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
1799.1598	41.11	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4803.7608	53.28	N/A	40.06	74.00	N/A	54.00	Horizontal	PASS
7205.0410	42.51	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
11235.4471	46.52	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
13755.9512	49.21	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.5936	21.62	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
83.4034	24.15	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
133.8939	24.49	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
255.2653	29.80	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
360.1301	31.18	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
835.9059	27.17	N/A	N/A	N/A	46.00	N/A	Vertical	PASS

(Antenna Vertical, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1063.0126	44.21	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2195.2390	41.58	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4803.7608	52.26	N/A	39.08	74.00	N/A	54.00	Vertical	PASS
6753.7508	40.20	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
10628.1256	46.05	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
14039.2078	49.01	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 1GHz to 18GHz)




Plot for Channel 19




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
87.2873	25.73	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
103.7938	28.06	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
129.0390	26.59	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
196.0360	22.54	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
360.1301	28.73	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
835.9059	32.11	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1113.0226	42.63	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
1585.1170	39.30	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4879.7760	53.12	N/A	40.94	74.00	N/A	54.00	Horizontal	PASS
7250.6501	42.00	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10666.5333	46.45	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
14639.3279	49.23	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.5936	22.28	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
86.3163	29.29	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
106.7067	33.53	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
261.0911	27.12	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
360.1301	30.80	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
836.8769	28.02	N/A	N/A	N/A	46.00	N/A	Vertical	PASS


(Antenna Vertical, 30MHz to 1GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1190.0380	42.83	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
1713.1426	41.74	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4880.7762	53.08	N/A	42.01	74.00	N/A	54.00	Vertical	PASS
6400.8802	39.17	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
10630.5261	45.80	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
14665.7331	49.11	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 1GHz to 18GHz)

Plot for Channel 39




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
44.5646	19.40	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
87.2873	26.67	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
105.7357	29.46	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
158.1682	26.61	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
360.1301	28.84	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
835.9059	32.07	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1142.0284	44.32	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2499.2999	44.80	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4959.7920	53.59	N/A	42.83	74.00	N/A	54.00	Horizontal	PASS
9507.1014	43.88	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12243.6487	47.57	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
14653.7307	49.72	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.5936	22.11	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
56.2162	24.98	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
104.7648	28.18	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
250.4104	23.85	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
360.1301	30.99	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
836.8769	26.81	N/A	N/A	N/A	46.00	N/A	Vertical	PASS

(Antenna Vertical, 30MHz to 1GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1044.0088	44.49	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
1997.1994	42.66	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4960.7922	55.41	N/A	39.08	74.00	N/A	54.00	Vertical	PASS
8899.7800	43.55	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13621.5243	48.27	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
16432.4865	47.89	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 1GHz to 18GHz)

END OF REPORT