





# Test Report

**Report No.** : MTi250224040-0105E2  
**Date of Issue** : 2025-03-17  
**Applicant** : Foryou Multimedia Electronics Co., Ltd.  
**Product** : Wireless Accessory Charger Module  
**Model(s)** : W1BCFV4  
**FCC ID** : PUZ-W1BCFV4

**Shenzhen Microtest Co., Ltd.**

**Table of contents**

<b>1 General Description .....</b>	<b>4</b>
1.1 Description of the EUT .....	4
1.2 Description of test modes .....	5
1.3 Description of support units .....	6
<b>2 Measurement uncertainty .....</b>	<b>6</b>
<b>3 Test facilities and accreditations.....</b>	<b>7</b>
3.1 Test laboratory .....	7
<b>4 List of test equipment .....</b>	<b>8</b>
<b>5 Test result .....</b>	<b>9</b>
5.2 Test setup .....	10
5.3 Test Procedures.....	10
5.4 Information of test equipment.....	11
5.5 Test results.....	12
<b>Photographs of the Test Setup.....</b>	<b>14</b>
<b>Photographs of the EUT .....</b>	<b>14</b>

<b>Test Result Certification</b>		
Applicant	Foryou Multimedia Electronics Co., Ltd.	
Applicant Address	No.1, North Shangxia Road, Dongjiang Hi-tech Industry Park, Huizhou, Guangdong, P.R. China	
Manufacturer	Foryou Multimedia Electronics Co., Ltd.	
Manufacturer Address	No.1, North Shangxia Road, Dongjiang Hi-tech Industry Park, Huizhou, Guangdong, P.R. China	
<b>Product description</b>		
Product name	Wireless Accessory Charger Module	
Trademark	ADAYO	
Model name	W1BCFV4	
Series Model(s)	N/A	
Standards	47 CFR PART 1, § 1.1310 part2.1091	
Test method	KDB 680106 D01 Wireless Power Transfer v04	
<b>Testing Information</b>		
Date of test	2025-03-01 to 2025-03-03	
Test Result	Pass	
Prepared by	James Qin	
Reviewed by	David Lee	
Approved by	Lewis Lian	

## 1 General Description

### 1.1 Description of the EUT

Product name:	Wireless Accessory Charger Module
Model name:	W1BCFV4
Series Model:	N/A
Model difference:	N/A
Electrical rating:	Input: DC 9-16V, 3A Max Wireless Output: 15W Max
Accessories:	N/A
Hardware version:	R2TT-14G588-AA
Software version:	R2TT-14G583-AC
Test sample(s) number:	MTi250224040-01-R001
<b>RF specification:</b>	
Operation frequency:	115-205kHz
Modulation type:	ASK
Antenna type:	Coil

**1.2 Description of test modes**

All the test modes were carried out with the EUT in normal operation, the final test mode of the EUT was the worst test mode for emission test, which was shown in this report and defined as:

No.	Emission test modes
Mode1	Wireless Output 5W(Upper coil)
Mode2	Wireless Output 7.5W(Upper coil)
Mode3	Wireless Output 10W(Upper coil)
Mode4	Wireless Output 15W(Upper coil)
Mode5	Wireless Output 5W(Central coil)
Mode6	Wireless Output 7.5W(Central coil)
Mode7	Wireless Output 10W(Central coil)
Mode8	Wireless Output 15W(Central coil)
Mode9	Wireless Output 5W(Lower coil)
Mode10	Wireless Output 7.5W(Lower coil)
Mode11	Wireless Output 10W(Lower coil)
Mode12	Wireless Output 15W(Lower coil)
Mode13	standby

**1.3 Description of support units**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

<b>Support equipment list</b>			
Description	Model	Serial No.	Manufacturer
Accumulator	55D23LX	/	CAMEL
Mobile phone	iPhone 15	KXPWNQFK90	Apple
<b>Support cable list</b>			
Description	Length (m)	From	To
/	/	/	/

**2 Measurement uncertainty**

Parameter	Expanded Uncertainty
Magnetic field measurements(3kHz~10MHz)	±14.8%
Electric field measurements(3kHz~10MHz)	±17.5%

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

### 3 Test facilities and accreditations

#### 3.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573

**4 List of test equipment**

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
MTI-E143	Near-field Electric and Magnetic Field Sensor System	SPEAG	MAGPy-8H3 D+ED3	3101	2024/3/12	2027/3/11

No.	Equipment	Manufacturer	Model	Software version:	Cal. date	Cal. Due
MTI-E016S	MPE test software	SPEAG	MAGPY 2.6	2.6	/	/

## 5 Test result

### 5.1.1 Requirement

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter.

**Table 1 to §1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(i) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30-300	61.4	0.163	1.0	<6
300-1500			f/300	<6
1500-100000			5	<6
<b>(ii) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30-300	27.5	0.073	0.2	<30
300-1500			f/1500	<30
1500-100000			1.0	<30


f = frequency in MHz

\* = Plane-wave equivalent power density

**Note 1:** Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure.

**Note 2:** General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

## 5.2 Test setup



## 5.3 Test Procedures

- The RF exposure test was performed in anechoic chamber.
- E and H-field measurements should be made with these devices considered to meet the § 2.1091-Mobile conditions ("generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the RF source's radiating structure(s) and [the nearest person]").
- The highest emission level was recorded and compared with limit.
- The EUT was measured according to the dictates of KDB 680106 D01 Wireless Power Transfer v04.

**5.4 Information of test equipment**

Test equipment: MAGPy-8H3D+ED3	
Diameter	60mm
8 isotropic H-field sensors	Concentric loops of 1cm <sup>2</sup> arranged at the corner of a cube of 22mm side length
1 isotropic E-field sensor	Orthogonal dipole/monopole (arm length: 50mm)
Measurement center	18.5mm from the probe tip
Dimensions	110*635*35mm (MAGPy-8H3D+E3D V2 & MAGPy-DAS V2)
	
Test probe, without the casing	

### 5.5 Test results

#### Test condition 1: Mode 8 operating mode with client device (1 % battery status of client device)

Probe Position	E-field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Z axis	1.56	614	0.25%	0.09	1.63	5.52%
Left	1.31			0.03		
Right	1.02			0.04		
Front	1.15			0.04		
Rear	0.98			0.01		
Bottom	0.86			0.02		

#### Test condition 2: Mode 8 operating mode with client device (50 % battery status of client device)

Probe Position	E-field (V/m)			H-field (A/m)		
	Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
Z axis	1.57	614	0.26%	0.10	1.63	5.90%
Left	1.32			0.03		
Right	1.04			0.03		
Front	1.16			0.05		
Rear	0.98			0.01		
Bottom	0.86			0.01		

**Test condition 3: Mode 8 operating mode with client device (99 % battery status of client device)**

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Z axis	1.56	614	0.25%	0.08	1.63	4.91%
Left	1.30			0.03		
Right	1.00			0.03		
Front	1.15			0.04		
Rear	0.97			0.02		
Bottom	0.85			0.02		



# TEST REPORT

Report No.: MTI250224040-0105E2

## Photographs of the Test Setup

See the Appendix - Test Setup Photos.



## Photographs of the EUT

See the Appendix - EUT Photos.



## Statement

1. This report is invalid without the seal and signature of the laboratory.
2. The test results of this report are only responsible for the samples submitted. Client shall be responsible for representativeness of the sample and authenticity of the material.
3. The report shall not be partially reproduced without the written consent of the Laboratory.
4. This report is invalid if transferred, altered or tampered with in any form without authorization.
5. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
6. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

\*\*\*\*\* END OF REPORT \*\*\*\*\*