

EXHIBIT 5

User's Manual

User's Manual

Cautions and Instructions

1. Handling

Never drop or strike lamp.

The lamp should not be disassembled or modified.

To prevent burns, do not touch the bulb during operation or immediately after switching off.

2. Fixture

Never use with a dimming circuit or an emergency light fixture.

Never use with a close fixture.

This device is not intended for use with emergency exit fixture or emergency exit lights.

3. Electric Source

Use only at the rated voltage indicated on the lamp, 120 volt, 60 hertz. If the source voltage rises by 6% the lamp life may be shortened. If the source voltage drops by 10% the lamp may not light up. The light output will be lower even after it can light up.

Never use with a direct current. Otherwise the lamp will stop working

4. Ambience

Never use where water may drop on the lamp. Never use in a humid atmosphere. This is extremely dangerous because it may cause an electric leak.

Never use in front or over a room heater. Do not switch on and off frequently. Switching on and off may shorten the lamp service life.

Make sure that the lamp is firmly screwed in the socket. Otherwise, the lamp may drop or result in an electric disconnection.

5. Notes

It takes the lamp about 1 second before it begins to light up. Output rapidly increases and the light fully lights within 30 seconds. The color of the light stabilizes in about 20 minutes.

In a cold room below 0°C, it may not light up or take even more time to light up. The light output will also be lower even after the lamp performance stabilizes.

When the lamp is switched on first darkening and specks of mercury may be observed around the tubeend (the base-side and top ends). But this is only a normal phenomenon of the lamp and does not indicate a malfunction.

6. Important

A short circuit fuse is built into this lamp. This prevents serious accidents from occurring if the lamp is used incorrectly.

No internal parts are available from the lamp manufacture for repair. If damaged do not attempt to disassemble or repair the lamp. Serious accidents may occur if a repaired lamp is installed.

7. This product could produce interference when used near a TV, radio, wireless remote control or maritime safety communications equipment or other critical navigation or communication equipment operating between 0.45-30MHZ. If interference should occur, move the lamp away from the appliance a distance of three feet or more. Or, plug the lamp or the appliance into a different outlet.

Not for use with dimmers, electronic timer or photocell devices or occupancy sensor.