

FCC Part 15B Measurement and Test Report

For

Motic China Group Co.,Ltd

Motic BLDG, TORCH HI-TECH INDUSTRIAL DEV ZONE XIAMEN

FUJIAN, CHINA, 361006

FCC ID: PVEMOTICAMBTW8

Test Rule(s): FCC Part 15 Subpart B

Product Description: Tablet PC

Tested Model: MoticamBTW8

Report No.: STR15118132I-1

Tested Date: 2015-11-10 to 2015-11-15

Issued Date: 2015-11-15

Tested By: Irving Liu / Engineer

Irving Liu

Reviewed By: Silin Chen / EMC Manager

Silin Chen

Approved & Authorized By: Jandy so / PSQ Manager

Jandy so

Prepared By:

Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY	4
1.4 TEST FACILITY	4
1.5 EUT SETUP AND OPERATION MODE	5
1.6 TEST EQUIPMENT LIST AND DETAILS	5
2. SUMMARY OF TEST RESULTS	6
3. CONDUCTED EMISSIONS	7
3.1 MEASUREMENT UNCERTAINTY	7
3.2 TEST PROCEDURE.....	7
3.3 BASIC TEST SETUP BLOCK DIAGRAM.....	7
3.4 ENVIRONMENTAL CONDITIONS	8
3.5 SUMMARY OF TEST RESULTS/PLOTS	8
3.6 CONDUCTED EMISSIONS TEST DATA.....	8
4. RADIATED EMISSIONS	15
4.1 MEASUREMENT UNCERTAINTY	15
4.2 TEST PROCEDURE.....	15
4.3 TEST RECEIVER SETUP	16
4.4 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	16
4.5 ENVIRONMENTAL CONDITIONS	16
4.6 SUMMARY OF TEST RESULTS/PLOTS	16

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Motic China Group Co.,Ltd
Address of applicant: Motic BLDG, TORCH HI-TECH INDUSTRIAL DEV
ZONE, XIAMEN FUJIAN, CHINA, 361006

Manufacturer: Nanjing Wanlida Technology Co., Ltd.
Address of manufacturer: Wanlida Industry Zone, Nanjing, Fujian, China.
363601

General Description of EUT	
Product Name:	Tablet PC
Brand Name:	Motic
Model No.:	MoticamBTW8
Adapter Model:	KSA29B0500200D5
	INPUT:100-240V,50/60Hz; OUTPUT:5V,2A
Adding Adapter Model:	Model:ICP12-050-2000B
	INPUT:100-240V,50/60Hz; OUTPUT:5V,2A
Hardware version:	8872C
Software version:	e8005_user_20150302
Note: The test data is gathered from a production sample provided by the manufacturer.	

Technical Characteristics of EUT	
Rated Voltage:	DC 3.7V battery
Battery capacity:	4000mAh
Rated Power:	/
Lowest Internal Frequency:	32.768KHz
Highest Internal Frequency:	1.33GHz
Classification of ITE:	Class B

1.2 Test Standards

The following report is prepared on behalf of the Motic China Group Co.,Ltd in accordance with Part 2, Subpart J, and Part 15, Subparts A and B of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart B, and section 15.205, 15.107, and 15.109 rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

FCC – Registration No.: 934118

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

CNAS Registration No.: L4062

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101).

1.5 EUT Setup and Operation Mode

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted according to the operation manual for use, more detailed description as follows:

Test Mode List:

Test Mode	Description	Remark
TM1	Charging & Playing	Connect to Adapter (master adapter)
TM2	Charging & Playing	Connect to Adapter(adding adapter)
TM3	Downloading	Connected to PC

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Notebook Computer	Lenovo	E10	LR-63C8R

Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

1.6 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal Date	Due Date
Spectrum Analyzer	Agilent	E4407B	MY41440400	2015-06-17	2016-06-16
Spectrum Analyzer	Rohde & Schwarz	FSP	836079/035	2015-06-17	2016-06-16
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2015-06-17	2016-06-16
Amplifier	Agilent	8447F	3113A06717	2015-06-17	2016-06-16
Amplifier	C&D	PAP-1G18	2002	2015-06-17	2016-06-16
Broadband Antenna	Schwarz beck	VULB9163	9163-333	2015-06-17	2016-06-16
Horn Antenna	ETS	3117	00086197	2015-06-17	2016-06-16
Loop Antenna	Schwarz beck	FMZB 1516	9773	2015-06-17	2016-06-16
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2015-06-17	2016-06-16
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2015-06-17	2016-06-16
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2015-06-17	2016-06-16

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 15.107 (a)	Conducted Emissions	Compliant
§ 15.109 (a)	Radiated Emissions	Compliant

N/A: not applicable

3. Conducted Emissions


3.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is ± 2.88 dB.

3.2 Test Procedure

Test is conducting under the description of ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

3.3 Basic Test Setup Block Diagram



3.4 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	52%
ATM Pressure:	1011 mbar

3.5 Summary of Test Results/Plots

According to the data in section 3.6, the EUT complied with the FCC Part 15.107(a) Conducted margin for a Class B device, with the *worst* margin reading of:


-4.76 dB at 0.4740 MHz in the **Line** mode, **TM1, Peak** detector, **0.15-30MHz**

3.6 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


EUT: Tablet PC
 Tested Model: MoticomBTW8
 Operating Condition: TM1
 Comment: AC 120V/60Hz, Adapter DC 5V

Test Specification: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.4740	40.17	9.50	49.67	56.44	-6.77	peak
2	0.4780	31.99	9.50	41.49	46.37	-4.88	AVG
3	0.9060	35.75	9.91	45.66	56.00	-10.34	peak
4	0.9580	25.03	9.96	34.99	46.00	-11.01	AVG
5	2.1660	33.87	10.00	43.87	56.00	-12.13	peak
6	2.3700	20.76	10.00	30.76	46.00	-15.24	AVG

Test Specification: Line




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1740	39.20	9.50	48.70	64.77	-16.07	peak
2	0.1740	27.76	9.50	37.26	54.77	-17.51	AVG
3	0.4740	42.18	9.50	51.68	56.44	-4.76	peak
4	0.4780	31.56	9.50	41.06	46.37	-5.31	AVG
5	2.2780	19.30	10.00	29.30	46.00	-16.70	AVG
6	2.5660	35.44	10.00	45.44	56.00	-10.56	peak

Plot of Conducted Emissions Test Data


EUT: Tablet PC
Tested Model: MoticomBTW8
Operating Condition: TM2
Comment: AC 120V/60Hz, Adapter DC 5V

Test Specification: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1540	41.81	12.50	54.31	65.78	-11.47	peak
2	0.1620	21.70	12.50	34.20	55.36	-21.16	AVG
3	1.4300	24.63	13.00	37.63	56.00	-18.37	peak
4	1.4300	14.84	13.00	27.84	46.00	-18.16	AVG
5	3.5780	17.05	13.00	30.05	46.00	-15.95	AVG
6	3.6780	26.59	13.00	39.59	56.00	-16.41	peak

Test Specification: Line




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1500	44.27	12.50	56.77	66.00	-9.23	peak
2	0.1500	23.72	12.50	36.22	56.00	-19.78	AVG
3	0.2380	38.53	12.50	51.03	62.17	-11.14	peak
4	0.2380	18.92	12.50	31.42	52.17	-20.75	AVG
5	4.2980	25.87	13.00	38.87	56.00	-17.13	peak
6	4.2980	16.19	13.00	29.19	46.00	-16.81	AVG

Plot of Conducted Emissions Test Data


EUT: Tablet PC
 Tested Model: MoticomBTW8
 Operating Condition: TM3
 Comment: AC 120V/60Hz; USB DC 5V

Test Specification: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2100	28.71	9.50	38.21	63.21	-25.00	peak
2	0.2100	19.46	9.50	28.96	53.21	-24.25	AVG
3	0.7780	13.07	9.78	22.85	46.00	-23.15	AVG
4	0.7820	21.38	9.78	31.16	56.00	-24.84	peak
5	1.6460	19.94	10.00	29.94	56.00	-26.06	peak
6	2.1020	10.38	10.00	20.38	46.00	-25.62	AVG

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2100	28.06	9.50	37.56	63.21	-25.65	peak
2	0.2100	20.63	9.50	30.13	53.21	-23.08	AVG
3	0.4580	23.00	9.50	32.50	56.73	-24.23	peak
4	0.7780	13.06	9.78	22.84	46.00	-23.16	AVG
5	0.9460	20.28	9.95	30.23	56.00	-25.77	peak
6	2.1380	11.81	10.00	21.81	46.00	-24.19	AVG

4. Radiated Emissions

4.1 Measurement Uncertainty


Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any radiation emissions measurement is ± 5.10 dB.

4.2 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.109 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



4.3 Test Receiver Setup

Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

4.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} - \text{Corr. Factor}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for a Class B device. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15.109(a) Limit}$$

4.5 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	55 %
ATM Pressure:	1011 mbar

4.6 Summary of Test Results/Plots


According to the data, the EUT complied with the FCC Part 15.109(a) rule, and had the worst margin of:

-3.45 dB at 210.0482 MHz in the Horizontal polarization, TM1, 9 kHz to 7 GHz, 3Meters

Plot of Radiated Emissions Test Data


EUT: Tablet PC
Tested Model: MoticamBTW8
Operating Condition: TM1
Comment: AC 120V/60Hz, Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	76.2442	27.63	1.45	29.08	40.00	-10.92	158	100	peak
2	169.5990	37.33	2.68	40.01	43.50	-3.49	326	100	peak
3	210.0482	35.66	4.39	40.05	43.50	-3.45	219	100	peak
4	231.7179	35.57	5.82	41.39	46.00	-4.61	178	100	peak
5	385.2805	27.38	9.44	36.82	46.00	-9.18	209	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	39.4372	22.34	9.16	31.50	40.00	-8.50	151	100	peak
2	73.6170	30.31	1.76	32.07	40.00	-7.93	308	100	peak
3	150.0108	33.92	2.50	36.42	43.50	-7.08	120	100	peak
4	171.9946	35.35	2.70	38.05	43.50	-5.45	178	100	peak
5	202.1005	33.16	3.83	36.99	43.50	-6.51	359	100	peak

Plot of Radiated Emissions Test Data


EUT: Tablet PC
Tested Model: MoticamBTW8
Operating Condition: TM2
Comment: AC 120V/60Hz, Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	37.2855	19.00	9.25	28.25	40.00	-11.75	180	150	peak
2	53.6932	23.86	6.28	30.14	40.00	-9.86	180	150	peak
3	80.0806	26.39	1.69	28.08	40.00	-11.92	180	150	peak
4	203.5228	22.24	4.87	27.11	43.50	-16.39	180	150	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	Factor(dB)	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	199.2855	30.15	4.61	34.76	43.50	-8.74	0	100	peak
2	216.7828	29.27	5.72	34.99	46.00	-11.01	0	100	peak
3	281.0075	25.76	9.29	35.05	46.00	-10.95	0	100	peak

Plot of Radiated Emissions Test Data


EUT: Tablet PC
 Tested Model: MoticamBTW8
 Operating Condition: TM3
 Comment: AC 120V/60Hz, USB DC 5V

Test Specification: Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	Factor(dB)	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	166.6514	35.60	2.66	38.26	43.50	-5.24	158	100	QP
2	204.9551	34.90	4.03	38.93	43.50	-4.57	226	100	QP
3	224.5193	35.52	5.39	40.91	46.00	-5.09	295	100	peak
4	239.9874	36.20	6.33	42.53	46.00	-3.47	178	100	QP
5	605.6592	23.45	12.92	36.37	46.00	-9.63	214	100	peak

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	45.3755	21.61	7.65	29.26	40.00	-10.74	145	100	peak
2	54.6429	22.14	5.85	27.99	40.00	-12.01	102	100	peak
3	167.2368	34.14	2.66	36.80	43.50	-6.70	174	100	peak
4	183.8440	34.14	2.93	37.07	43.50	-6.43	178	100	peak
5	208.5803	31.54	4.29	35.83	43.50	-7.67	186	100	peak

Note: Testing is carried out with frequency rang 9kHz to the 10GHz, which above 1GHz is close to the noise base even antenna close up to 1meter distance according the measurement of ANSI C63.4.

The measurements greater than 20dB below the limit from 9kHz to 30MHz and test data are not provided.

***** END OF REPORT *****