

FCCID: PVTRAD-TF

FCC RADIATED EMISSIONS DATA

CLIENT: IKUSI
EUT: RAD-TF TRANSMITTER
ANTENNA: INTERNAL
FREQ.: 902.25 MHZ
POWER: N/A

3 METER TEST PEAK DETECT DATE: 02/03/2003

FREQUENCY MHz	POLARITY		SPEC A	AF/C	AMP Gain dB	Average Factor dB	Peak E-Field dbuV/m	QP Limit dBuV/m	MARGIN dB	CONDITION
	H	V	dBuV	dB/m						
902.25	H		64.00	24.00	0.00	0.00	88.00	94.00	6.00	PASS
1,804.50	H		40.00	30.60	25.00	0.00	45.60	54.00	8.40	PASS
2,706.75	H		31.00	34.30	25.00	0.00	40.30	54.00	13.70	PASS
3,609.00		V	32.00	36.70	25.00	0.00	43.70	54.00	10.30	PASS
4,511.25		V	30.00	38.80	25.00	0.00	43.80	54.00	10.20	PASS
5,413.50	H		28.00	32.00	25.00	0.00	35.00	54.00	19.00	PASS
6,315.75		V	29.00	32.00	25.00	0.00	36.00	54.00	18.00	PASS
7,218.00	H		25.00	33.50	25.00	0.00	33.50	54.00	20.50	PASS

FCC RADIATED EMISSIONS DATA

CLIENT: IKUSI
EUT: RAD-TF TRANSMITTER
ANTENNA: INTERNAL
FREQ.: 927.75 MHZ
POWER: N/A

3 METER TEST PEAK DETECT DATE: 02/03/2003

FREQUENCY MHz	POLARITY		SPEC A	AF/C	AMP Gain dB	Average Factor dB	Peak E-Field dbuV/m	QP Limit dBuV/m	MARGIN dB	CONDITION
	H	V	dBuV	dB/m						
927.75	H		65.00	24.00	0.00	0.00	89.00	94.00	5.00	PASS
1,855.50	H		41.00	30.60	25.00	0.00	46.60	54.00	7.40	PASS
2,783.25	H		32.00	34.30	25.00	0.00	41.30	54.00	12.70	PASS
3,711.00		V	31.00	36.70	25.00	0.00	42.70	54.00	11.30	PASS
4,638.75		V	29.00	38.80	25.00	0.00	42.80	54.00	11.20	PASS
5,566.50	H		29.00	32.00	25.00	0.00	36.00	54.00	18.00	PASS
6,494.25		V	30.00	32.00	25.00	0.00	37.00	54.00	17.00	PASS
7,422.00	H		26.00	33.50	25.00	0.00	34.50	54.00	19.50	PASS