

Underwriters Laboratories Inc.  
1285 Walt Whitman Road  
Melville, New York 11747-3081  
(631) 271-6200

**Report of Measurements  
of Electromagnetic Compatibility Testing**

Test Report File No. : **NC4085** Date of issue: 10/22/2002  
Applicant : Hafele  
Model / Serial No. : Central Locking Wall Terminal /  
Product Type : Access Controller  
Power Supply : 120Vac, 60Hz to 12VDC converter  
Manufacturer : Same As Applicant  
  
License holder : Same As Applicant  
Address : 3901 Cheyenne Drive  
Archdale, NC 27263  
Test Type :  **Compliance Investigation  
Manufacturer's Specification**  
Test Project Number : 00ME10760  
References(s) : FCC ID: PW3104

Underwriters Laboratories Inc. authorizes the above-named company to reproduce this Report provided it is reproduced in its entirety.

*Underwriters Laboratories Inc. reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. Underwriters Laboratories Inc. shall have no liability for any deductions, inferences or generalizations drawn by the client or others from Underwriters Laboratories Inc. issued reports.*

*This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval. This report shall not be used by the client to claim product endorsement by NVLAP or any agency of the US government.*

## Report Directory

<b>1.0</b>	<b><i>G E N E R A L - Product Description</i></b>	<b>3</b>
1.1	Device Configuration During Test .....	3
1.2	Deviations from ANSI C63.4 .....	3
1.3	Device Modifications Necessary for Compliance .....	3
<b>2.0</b>	<b><i>EMISSIONS TEST REGULATIONS</i></b>	<b>4</b>
2.1	EUT OPERATION MODE - EMISSIONS TESTS .....	4
2.1.1	Conducted Emissions Tests.....	5
2.1.2	Radiated Emissions Test (10 Meter Semi-Anechoic Chamber).....	9
<b>3.0</b>	<b><i>Sample Calculations</i></b>	<b>18</b>
<b>4.0</b>	<b><i>SUMMARY:</i></b>	<b>19</b>

## 1.0 G E N E R A L - Product Description

The EUT (equipment under test) is a wall terminal that can open and close doors and motor locks. The device operates by using an intentional radio frequency (RF) to a pre-programmed transponder key. The transponder keys are passive devices that take the energy from the magnetic field of the EUT then sends the information stored within it to the EUT.

The device operates continuously at an intention radiation frequency of 134Khz.  
The transmitting antenna is not removable.

The device does not need to undergo RF-exposure measurements/calculations.  
Per FCC Part 2.1093(c) this device is not required to undergo test

### 1.1 Device Configuration During Test

The device under test was configured to operate continuously by transmitting the authorization frequency of 134Khz.

The device was tested in its normal orientation. All other orientations were examined. The data contained in this report represents the worst-case axis.

The device was powered with a Switching mode power supply. The manufacturer is Mean Well, Model number PSU30A-3. Input voltage is 120VAC, 60Hz and the output voltage is 12VDC.

"The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report"

### 1.2 Deviations from ANSI C63.4

Not Applicable

### 1.3 Device Modifications Necessary for Compliance

N/A

#### Environmental conditions in the lab:

	<u>Range</u>
Temperature:	20-25°C
Relative Humidity	30 - 60 %
Atmospheric pressure	680 - 1060 mbar

File Number: NC4085  
Project Number: 00ME10760  
Model Number: Central Locking Wall Terminal

Issued: 10/22/2002

FCC ID: PW3104

## 2.0 EMISSIONS TEST REGULATIONS

**FCC Part 15, Subpart C, 15.109 and 15.209**

**FCC Part 15, Subpart B, Class B**

### 2.1 EUT OPERATION MODE - EMISSIONS TESTS

- Standby
- Test program (H-Pattern)
- Test program (color bar)
- Test program (customer specific)
- Practice operation
- Normal operation Mode:
- As per manufacturer's instructions: Continuous operation

File Number: NC4085  
Project Number: 00ME10760  
Model Number: Central Locking Wall Terminal

Issued: 10/22/2002

FCC ID: PW3104

## 2.1.1 Conducted Emissions Tests

Test Applicable     Test Not Applicable

Temperature: 22.5 °C  
Humidity: 40 %RH  
Pressure: 1036 mbar  
Date test performed: October 22 2002

Frequency range on each side of line.	Measurement Point
<input checked="" type="checkbox"/> 150kHz to 30MHz	<input checked="" type="checkbox"/> Voltage
	<input checked="" type="checkbox"/> Mains


### Test equipment used for conducted emissions:

<input checked="" type="checkbox"/> ES126	Rhode & Schwartz	EMI Receiver	Equipment No.: ME5B-081
		Resolution BW: 100kHz	
		Video BW: 100kHz	
		QP BW: 10kHz	

Range: .150 – 30MHz    Last Calibration Date: August 20 2002    Calibration Due Date: August 20 2003

### Test Accessories for Conducted Emissions:

<input checked="" type="checkbox"/> 11947A	Hewlett Packard	Transient Limiter	Equipment No.: ME5A-443
Last Calibration Date: January 16 2002	Calibration Due Date: January 16 2003		
<input checked="" type="checkbox"/> 9252-50-R-24-BNC	Solar Electronics	LISN	Equipment No.: ME5A-637
Last Calibration Date: April 4 2002	Calibration Due Date: April 4 2003		
<input checked="" type="checkbox"/> Temp/Pressure	Oakton	Barometer	Equipment No.: ME4-263
Last Calibration Date: April 3 2002	Calibration Due Date: April 3 2003		
<input checked="" type="checkbox"/> 453320	Ex-Tech	Hydro-Thermometer	Equipment No.: ME4-264
Last Calibration Date: April 3 2002	Calibration Due Date: April 3 2003		



Note: Cyan data displays Average detection

Hafele America Co. Central Locking Wall Terminal 910.51.071 Line 1 Proj:02ME10760 File:NC4085 Tested By: GB Blue=Pk Green=QP							
No.	Test	Meter	Gain/Loss	Transducer	Level	Limit:1	2
	No.	Frequency	Reading	Factor	Factor	[dB(uVolts)]	
		[MHz]	[dB(uV)]	[dB]	[dB]		
=====							
		Range: 1	.15 - 1MHz				
1	1	.18942	62.24	avlg	-30.6	0	31.64
						Margin [dB]	-32.46
2	2	.22438	61.54	avlg	-30.6	0	30.94
						Margin [dB]	-31.76
3	3	.29491	58.22	avlg	-30.6	0	27.62
						Margin [dB]	-32.78
=====							
		Range: 2	1 - 30MHz				
4	4	24.83419	74.44	avlg	-30.6	0	43.84
						Margin [dB]	-16.16
5	5	25.49609	77.34	avlg	-30.6	0	46.74
						Margin [dB]	-13.26
6	6	25.889	76.05	avlg	-30.6	0	45.45
						Margin [dB]	-14.55

LIMIT 1: FCC Pt15 Subpart B Class B QP

LIMIT 2: FCC Pt15 Subpart B Class B Avg


avlg - denotes average log detection

File Number: NC4085  
Project Number: 00ME10760

Issued: 10/22/2002

Model Number: Central Locking Wall Terminal

FCC ID: PW3104



Note: Cyan data displays Average detection

Hafele America Co.  
Central Locking Wall Terminal  
910.51.071 Line 2  
Proj:02ME10760 File:NC4085  
Tested By: GB Blue=Pk Green=QP

Test	Meter	Gain/Loss	Transducer	Level	Limit:1	2
No.	Frequency	Reading	Factor	Factor	[dB(uVolts)]	
	[MHz]	[dB(uV)]	[dB]	[dB]		
Range: 1 .15 - 1MHz -----						
1	.19127	68.68	avlg	-30.6	0 38.08 64	54
					Margin [dB]	-25.92 -15.92
2	.23783	66.78	avlg	-30.6	0 36.18 62.2	52.2
					Margin [dB]	-26.02 -16.02
3	.29867	64.9	avlg	-30.6	0 34.3 60.3	50.3
					Margin [dB]	-26 -16
Range: 2 1 - 30MHz -----						
4	24.83562	73.74	avlg	-30.6	0 43.14 60	50
					Margin [dB]	-16.86 -6.86
5	25.48852	76.94	avlg	-30.6	0 46.34 60	50
					Margin [dB]	-13.66 -3.66
6	25.88751	75.48	avlg	-30.6	0 44.88 60	50
					Margin [dB]	-15.12 -5.12

LIMIT 1: FCC Pt15 SubpartB Class B QP

LIMIT 2: FCC Pt15 Subpart B Class B Avg

avlg - denotes average log detection

File Number: NC4085  
Project Number: 00ME10760  
Model Number: Central Locking Wall Terminal

Issued: 10/22/2002

FCC ID: PW3104



Conducted Emissions Test .150 – 30 MHz

## 2.1.2 Radiated Emissions Test (10 Meter Semi-Anechoic Chamber)

### Test Applicable

Date test performed: 6-5-2000

120kHz – 30MHz using Magnetic loop Antenna  
The measurement antenna distance  1  10 meters from the EUT.

Measurement obtained at 1 meter due to low operating frequency emissions. The operating frequency was not measurable at 3 meters therefore the antenna was moved into 1 meter from the EUT.

The measurement at 1 meter was compared to the 3-meter limit. Since the measurement at 1 meter is lower than the 3-meter limit, data was not extrapolated and is found to be well within the limits.

30MHz – 1000MHz  
The measurement antenna distance  3  10 meters from the EUT.

Tests were performed on the transmitter in accordance with the limitation set forth by CFR47 FCC Part 15 Subpart B, Class B, Paragraphs 15.209 and tested in accordance with the test procedures and methodologies in ANSI C63.4:1992.

The EUT was checked throughout the frequency band 120kHz to 1000MHz. The transmitter operated at 134kHz. The allowable field strength limits in accordance with 15.209 were applied to the fundamental frequency. All other emissions were tested in accordance with the general limitations 15.209.

From 120kHz to 30MHz, measurements were made at a distance of 1 meter. The limit was adjusted using the 40dB/decade limit extrapolation method to a distance of 3 meters and all 1 meter measurements were compared to the 3 meter limit.

### Test equipment used for final radiated emissions tests:

<input checked="" type="checkbox"/> <b>HP 8574A</b>	<b>Hewlett-Packard</b>	<b>EMI Receiver,</b>	<b>Equipment No.: ME5A-461</b>
Range: 0.1 – 1000MHz	Last Calibration Date: January 27 2000	Calibration Due Date: January 27 2001	
<b>Consisting of:</b>			
	<b>HP - 8566B</b>	<b>Hewlett-Packard</b>	<b>Spectrum Analyzer,</b>
	Resolution BW:	100kHz	9kHz to 30 MHz
		1MHz	30MHz to 1000 MHz
	<b>Video BW:</b>	100kHz	9kHz to 30 MHz
		1MHz	30MHz TO 1000MHz
	<b>Average BW:</b>	1Hz	10kHz to 30MHz
<b>HP - 85662A</b>	<b>Hewlett-Packard</b>		<b>Analyzer Display</b>
<b>HP - 85650A</b>	<b>Hewlett-Packard</b>		<b>Quasi-Peak Adapter,</b>
	Quasi Peak BW:	200Hz	9kHz to 150kHz
		9kHz	150kHz to 30MHz
		120kHz	30 to 1000 MHz
<b>HP - 85685A</b>	<b>Hewlett-Packard</b>		<b>Preselector</b>

### Test Accessories for Radiated Emissions:

<input checked="" type="checkbox"/> <b>94455-1</b>	<b>Ailtech</b>	<b>Biconnical Antenna</b>	<b>Equipment No.: ME5-439</b>
Last Calibration Date: October 5 1999	Calibration Due Date: October 5 2000		
<input checked="" type="checkbox"/> <b>3146</b>	<b>EMCO</b>	<b>Log Periodic Antenna</b>	<b>Equipment No.: ME5-451</b>
Last Calibration Date: September 28 1999	Calibration Due Date: September 28 2000		
<input checked="" type="checkbox"/> <b>6507</b>	<b>EMCO</b>	<b>Active Loop Antenna</b>	<b>Equipment No.: ME5A-288</b>
Last Calibration Date: January 14 2000	Calibration Due Date: January 14 2001		

File Number: NC4085  
Project Number: 00ME10760


Issued: 10/22/2002

Model Number: Central Locking Wall Terminal

FCC ID: PW3104

5 Jun 2000 15:04:52

UL - EMC TEST SYSTEM



Radiated Emissions 30 – 1000 MHz

File Number: NC4085  
Project Number: 00ME10760

Issued: 10/22/2002

Model Number: Central Locking Wall Terminal  
Hafele America Corp.  
Wall Terms incl. Central lock  
Proj.: 00ME10760 File: NC4085  
Tested By: GB Blue=H Green=V

FCC ID: PW3104

Test Frequency	Meter Reading	Gain/Loss Factor	Transducer Factor	Level dB[uVolts/meter]	Limit:1	2	3	4
[MHz]	[dB(uV)]	[dB]	[dB]					
188.1089	19.6	pk	1.1	13.8	34.5	43.5	N/A	N/A
51.5314	19.7	pk	.5	11.2	31.4	40	N/A	N/A
160.4197	17.6	pk	1	16.5	35.1	43.5	N/A	N/A
213.7219	20.8	pk	1.1	11.9	33.8	43.5	N/A	N/A
960.5662	6.7	pk	2.9	24.5	34.1	54	N/A	N/A
470.5745	8.7	pk	1.9	17.6	28.2	46	N/A	N/A
816.4197	7.8	pk	2.6	22.7	33.1	46	N/A	N/A

LIMIT 1: FCC Part 15 Subpart B Class B

pk - Peak detector  
qp - Quasi-Peak detector  
av - Average detector  
tm - Trace Math Result

MARKER NO.	TEST FREQUENCY	LEVEL dB[uVolts/meter]	LIMIT:1	2	3	4	TABLE	TOWER
1	188.1089	34.5	43.5	N/A	N/A	N/A	141	98 H
2	51.5314	31.4	40	N/A	N/A	N/A	99	99 V
3	160.4197	35.1	43.5	N/A	N/A	N/A	271	99 V
4	213.7219	33.8	43.5	N/A	N/A	N/A	8	98 H
5	960.5662	34.1	54	N/A	N/A	N/A	141	98 H
6	470.5745	28.2	46	N/A	N/A	N/A	143	201 V
7	816.4197	33.1	46	N/A	N/A	N/A	74	301 V

File Number: NC4085  
Project Number: 00ME10760  
Model Number: Central Locking Wall Terminal

Issued: 10/22/2002

FCC ID: PW3104

Hafele America Corp.  
Wall Terms incl. Central lock  
Proj.:00ME10760 File: NC4085  
Tested By: GB Blue=H Green=V

Test Frequency	Meter Reading	Gain/Loss Factor	Transducer Factor	Level	Limit:1	2	3	4
[MHz]	[dB(uV)]	[dB]	[dB]			dB[uVolts/meter]		
32.5076	17.31	qp	.3	14	31.61	40	N/A	N/A
Azimuth: 101	Height:100	Vert		Margin	[dB]	-8.39	N/A	N/A
33.1859	16.75	qp	.3	14	31.05	40	N/A	N/A
Azimuth: 160	Height:100	Vert		Margin	[dB]	-8.95	N/A	N/A
34.3244	22.71	qp	.3	14	37.01	40	N/A	N/A
Azimuth: 137	Height:100	Vert		Margin	[dB]	-2.99	N/A	N/A

LIMIT 1: FCC Part 15 Subpart B Class B

pk - Peak detector  
qp - Quasi-Peak detector  
av - Average detector


File Number: NC4085  
Project Number: 00ME10760

Issued: 10/22/2002

Model Number: Central Locking Wall Terminal  
UL - EMC TEST SYSTEM

FCC ID: PW3104

6 Jun 2000 15:03:36



#### Radiated Emissions .1 – 30 MHz

Measurement obtained at 1 meter due to low operating frequency emissions. The operating frequency was not measurable at 3 meters therefore the antenna was moved into 1 meter from the EUT. The measurement at 1 meter was compared to the 3-meter limit. Since the measurement at 1 meter is lower than the 3-meter limit, data was not extrapolated and is found to be well within the limits.

File Number: NC4085  
Project Number: 00ME10760  
Model Number: Central Locking Wall Terminal  
Hafele America Co.  
Wall terminals w/cntrl lock  
Proj:00ME10760, File:NC4085  
Tested By:DL

Issued: 10/22/2002

FCC ID: PW3104

Test Frequency	Meter Reading	Gain/Loss Factor	Transducer Factor	Level dB[uVolts/meter]	Limit:1	2	3	4	
[MHz]	[dB(uV)]	[dB]	[dB]						
.13434	79.3	pk	.3	14.7	94.3	105.05	N/A	N/A	N/A
.15497	63.4	pk	.3	14.6	78.3	105.05	N/A	N/A	N/A
.39852	66.6	pk	.3	14.8	81.7	105.05	N/A	N/A	N/A
.66941	54.2	pk	.3	14.7	69.2	105.05	N/A	N/A	N/A
.93782	48.8	pk	.3	15	64.1	105.05	N/A	N/A	N/A
1.20622	44.7	pk	.3	15.3	60.3	105.05	N/A	N/A	N/A
1.47462	41.1	pk	.3	15.3	56.7	105.05	N/A	N/A	N/A
1.74303	38.9	pk	.3	15.4	54.6	105.05	N/A	N/A	N/A

LIMIT 1: FCC PT.15 SUB C (3M)

LIMIT 2: NONE

LIMIT 3: NONE

LIMIT 4: NONE

pk - Peak detector  
qp - Quasi-Peak detector  
av - Average detector  
tm - Trace Math Result

File Number: NC4085  
Project Number: 00ME10760  
Model Number: Central Locking Wall Terminal  
Hafele America Co.  
Wall terminals w/cntrl lock  
Proj:00ME10760, File:NC4085  
Tested By:DL

Issued: 10/22/2002

FCC ID: PW3104

Test	Meter	Gain/Loss	Transducer	Level	Limit:1	2	3	4
Frequency	Reading	Factor	Factor	dB[uVolts/meter]				
[MHz]	[dB(uV)]	[dB]	[dB]					
.13434	76.43	av	.3	14.7	91.43	105.05	N/A	N/A
Azimuth 0 Height: 100								

LIMIT 1: FCC PT.15 SUB C (3M)


Spectrum Analyzer Settings:

Frequency Span = 0Hz, Resolution Bandwidth = 100kHz, Video Bandwidth = 10Hz

File Number: NC4085  
Project Number: 00ME10760  
Model Number: Central Locking Wall Terminal

Issued: 10/22/2002

FCC ID: PW3104




Radiated Emissions Test 30 – 1000 MHz

File Number: NC4085  
Project Number: 00ME10760  
Model Number: Central Locking Wall Terminal

Issued: 10/22/2002

FCC ID: PW3104



Radiated Emissions Test .1 – 30 MHz

File Number: NC4085  
Project Number: 00ME10760  
Model Number: Central Locking Wall Terminal

Issued: 10/22/2002

FCC ID: PW3104

### 3.0 Sample Calculations

Radiated Emissions Limit conversion from  $\mu\text{V/m}$  to  $\text{dB}\mu\text{V/m}$   
(limits in accordance with paragraph 15.109)

Radiated Emissions Limit (dB $\mu$ V/m) = 20\*log ( $\mu$ V/m)

Radiated Emissions Limit (dB $\mu$ V/m) = 20 \* log (90)

Radiated Emissions Limit (dB $\mu$ V/m) = 39.1

Radiated Emissions test data obtained during measurements.

Field Strength (dB $\mu$ V/m) = Measured field strength (dB $\mu$ V/m) + Antenna Factor(dB) + Cable Factor(dB)

Field Strength (dB $\mu$ V/m) = 19.7dB $\mu$ V/m + 12.5dB + 0.3dB

Field Strength (dB $\mu$ V/m) = 32.5

Radiated Emissions Limit conversion from  $\mu\text{V/m}$  to  $\text{dB}\mu\text{V/m}$  and 40dB/decade (limits in accordance with paragraph 15.209)

## Radiated Emission Limits; General Requirements

134kHz 2400/(134) at 300 meters

Radiated emissions at 134 kHz at 300 meters = 17.9  $\mu$ V/meter

$$\text{dB}\mu\text{V/m} = 20 * \log(17.9\mu\text{V/m})$$

dB $\mu$ V/m=25.05 at 300meters

40dB/decade

300 meters to 3 meters = 80 dB

Radiated Emissions Limit = db $\mu$ V/m + dB

25.05 + 80

105.05 dB $\mu$ V/m

File Number: NC4085  
Project Number: 00ME10760  
Model Number: Central Locking Wall Terminal

Issued: 10/22/2002

FCC ID: PW3104

#### 4.0 SUMMARY:

The equipment under test has


met the technical requirements as defined under section(s)  2.0 and  3.0  
 not met the technical requirements as defined under section(s)  2.0 and  3.0

Test Start Date: 5-19-2000

Test Completion Date: 10-22-2002

#### - UNDERWRITERS LABORATORIES, INC. -

Project Engineer



Donald Lerner (Ext.22765)  
Project Engineer  
International EMC Services  
Conformity Assessment Services-3014AMEL

Reviewer



Robert DeLisi (Ext.22452)  
Staff Engineer  
International EMC Services  
Conformity Assessment Services -3014AMEL