



3301 East Deseret Drive
St. George, Utah 84790
www.wilsonelectronics.com
info@wilsonelectronics.com

Phone 800.204.4104 • Fax 435.656.2432

August 8, 2012

To: Whom it May Concern

Subject: Final Amplification Stage Voltage and Current

Please note that the maximum voltages and currents for the ten final amplification stages of the Model 273470 Signal Booster are:

Uplink Amplifier (698-716 MHz): 4.0 V, 0.5 A

Downlink Amplifier (728-746 MHz): 4.0 V, 0.5 A

Uplink Amplifier (776--787 MHz): 4.0 V, 0.5 A

Downlink Amplifier (746-757 MHz): 4.0 V, 0.5 A

Uplink Amplifier (1710-1755 MHz): 4.0 V, 0.5 A

Downlink Amplifier (2110-2155 MHz): 4.0 V, 0.5 A

Uplink Amplifier (824-849 MHz): 4.0 V, 0.5 A

Downlink Amplifier (869-894 MHz): 4.0 V, 0.5 A

Uplink Amplifier (1850-1910 MHz): 4.0 V, 0.5 A

Downlink Amplifier (1930-1990 MHz): 4.0 V, 0.5 A

Sincerely,

A handwritten signature in black ink, appearing to read 'Patrick L. Cook', written over a light blue horizontal line.

Patrick L. Cook
Senior Research and Development Engineer