

# Minimum Safe Distance to Antennas

## Based upon FCC OET Bulletin 65 and other FCC Sources

### INPUT DATA

Frequency MHz	896
Pout Watts	1.0000
Duty Cycle Percent	33.3%
Ant. Gain dBi	15.00
Coax Loss dB	0.00

### RESULTS

Min. Distance Inches	14.75
Min. Distance Centimeters	37.45
ERP (Watts)	6.4210
EIRP (Watts)	10.5304

### REFERENCE DATA

Antenna Gain (non-log)	31.62
Coax loss (non-log)	1.00
Calculated limit (mw/cm <sup>2</sup> )	0.60
FCC Limit (mw/cm <sup>2</sup> )	f/1500

#### Notes:

(1) Valid only between 300 MHz - 100,000 MHz

(2) Calculations are sufficient for determining antenna safe distance for mobile devices provided that calculated ERP < 1.5 watts for frequencies equal to or below 1.5GHz, and ERP < 3 watts for frequencies above 1.5 GHz.

(3) Mobile antenna distances shall be no less than 8 inches.

(4) No predefined distance limitations for fixed outside (building) equipment (see #5).

(5) Indoor building antenna criteria is same as for mobile antennas.

### SUMMARY

For Amplifier Model Number:	2B4310
Mobile or Building?	Building
Outside/Inside Antenna?	Outside
Antenna Type:	Yagi 900 MHz
Safe Distance (inches):	15
Signature:	
Date:	1/3/2008