

Electromagnetic Emission

FCC MEASUREMENT REPORT

VERIFICATION OF COMPLIANCE

FCC Part 15 Certification Measurement

This ADSL Modem, Model Wel+8010D has been tested in accordance with the measurement procedures specified in ANSI C63.4-1992 at the ETL/EMC Test Laboratory and has been shown to be compliant with the electromagnetic radiated emission limits specified in FCC Rule Part 15 Computing Peripheral Devices.

I attest to the accuracy of data. All measurement herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

The results of testing in this report apply to the product / system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

yo han, Park

Name : Yo Han, Park

Title : Chief Engineer & Lab. Manager

E-RAE Testing Laboratory Inc.

371-51, Gasan-Dong, Geumcheon-Gu,
Seoul, 153-023, Korea

Table of Contents

ATTACHMENT A: COVER LETTER(S)

FCC Measurement Report

- 1. Introduction**
- 2. Product Information**
- 3. Description of Tests**
- 4. Test Condition**
- 5. Test Results**
 - 5.1 Summary of Test Results**
 - 5.2 Conducted Emissions Measurement**
 - 5.3 Radiated Emissions Measurement**
- 6. Sample Calculations**
- 7. List of test Equipment used for Measurement**

Appendix A. FCC ID Label and Location

Appendix B. Test Setup Photographs

Appendix C. External Photographs

Appendix D. Internal Photographs

Appendix E. Block Diagram

Appendix F. User Manual

Appendix G. Circuit Diagram

FCC MEASUREMENT REPORT

Scope – *Measurement and determination of electromagnetic emission (EME) of radio frequency devices including intentional radiators and/or unintentional radiators for compliance with the technical rules and regulations of the U.S Federal Communications Commission (FCC)*

General Information

Applicant Name : Wellink Corporation

Address : Koosantower, 10F, 3250 Bangbae2-Dong,
Seocho-Ku, Seoul, Korea 137-062

Attention : Techyou Hahm / Manager, Business Development Div.

- **EUT Type** : ADSL Modem
- **Model Number** : Wel+8010S
- **FCC Identifier** : PWV-WEL8010D
- **S/N** : N/A
- **Modulation** : DMT
- **FCC Rule Part(s)** : FCC Part 15 Subpart B
- **Test Procedure** : ANSI C63.4-1992
- **FCC Classification** : Computer peripheral Devices
- **Dates of Tests** : January 07~08, 2002
- **Place of Tests** : ETL Inc
EMC Testing Lab (FCC Registration Number : 95422)
584, Sangwhal-Ri, Kanam-Myun, Yoju-Kun,
Kyounggi-Do, Korea
Tel : (031) 885-0072 Fax : (031) 885-0074
- **Test Report No.** : E02.0118.FCC.038N

1. INTRODUCTION

The measurement test for radiated and conducted emission test were conducted at the open area test site of E-RAE Testing Laboratory Inc. facility located at 584, Sangwhal-ri, Ganam-myun, Youju-kun, Kyoungki-do, Korea. The site is constructed in conformance with the requirements of the ANSI C63.4-1992 and CISPR Publication 22. The ETL has site descriptions on file with the FCC for 3 and 10 meters site configurations. Detailed description of test facility was found to be in compliance with the requirements of Section 2.948 FCC Rules according to the ANSI C63.4-1992 and registered to the Federal Communications Commission (Registration Number : 95422).

The measurement procedure described in American National Standard for Method of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C.63.4-1992) was used in determining radiated and conducted emissions from the Wellink Corporation Model : Wel+8010D.

2. PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test(EUT) is the Wellink Corporation

Please refer to Users manual

2.2 General Specification

● Chassis Type	: Plastic
● List of Each OSC. Or X-Tal. Freq. (>=1MHz)	: X-TAL – 20MHz, OSC – 35.328MHz
● Chipset Brand & Part No.	: WTC29841-Virata : V3141AT - ST : HY57V66120B – HYUNDAI : V317ABQ - ST
● Number of Layers	: Main board – 4Layers
● H/W Interface	: IEEE 802.3 10BaseT/USB-B
● H/W Rate(DN/UP)	: max 8Mbps/1Mbps
● H/W Standard	: ANSI T1.413 issue2 / ITU-T G.992.1(G.dmt) G.992.2(G.lite),G.994.1(G.hs)
● H/W Splitter	: Internal
● H/W LED	: LAN(LINK,ACK)/ADSL(Sync,Rx,Tx), Power & ALARM
● S/W Modulation	: DMT
● S/W Error Detect	: Reed-Soloman
● S/W Signaling	: PVC
● Board specification	: size(171mmX131mmX40mm)
● Interface	: ADSL Line - RJ11, POTS-RJ1, Ethernet-RJ45
● Operation Power	: input power :110/220Vac to 5Vdc frequency : 50/60Hz
● Operation O.S	Win95/98(first,second)/2K/NT/ME/Linux/Unix/Machintosh

3. DESCRIPTION OF TESTS

3.1 Conducted Emission Measurement

Conducted emissions measurements were made in accordance with § 12.2 in ANSI C63.4-1992 "Measurement of Information Technology Equipment ". The measurement were performed over the frequency range of 0.15MHz to 30MHz using a 50 /50uH LISN as the input transducer to a Spectrum Analyzer or a Field Intensity Meter. The measurements were made with the detector set for "Peak" amplitude within a bandwidth of 10KHz or for "quasi-peak" within a bandwidth of 9KHz.

- Procedure of Test

The line-conducted facility is located inside a shielded room 1m X 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 1.5m away from the side wall of the shielded room. Two EMCO 3825/2 LISN are bonded to the shielded room. The EUT is powered from the EMCO LISN and the support equipment is powered from another EMCO LISN. Power to the LISN is filtered by a noise cut power line filters. All electrical cables are shielded by braided tinned steel tubing with inner ϕ 1.2cm. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and these supply lines will be connected to the EMCO LISN. Non-inductive bundling to a 1m length shortened all interconnecting cables more than 1m. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the R3261A Spectrum Analyzer to determine the frequency producing the max. emission from the EUT. The frequency producing the max. level was reexamined using to set Quasi-Peak mode by manual, after scanned by automatic Peak mode from 0.15 to 30MHz. The bandwidth of the Spectrum Analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission.

3. DESCRIPTION OF TESTS

3.2 Radiated Emission Measurement

Radiated emission measurements were in accordance with ANSI C63.4-1992. The measurements were performed over the frequency range of 30MHz to 1GHz using antenna as the input transducer to a Spectrum analyzer or a Field Intensity Meter. The measurements were made with the detector set for "Quasi-peak" within a bandwidth of 120KHz.

- Procedure of Test

Preliminary measurements were made at 3 meter using broadband antennas, and spectrum analyzer to determined the frequency producing the max. emission in shielded room. Appropriate precaution was taken to ensure that all emission from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth and height with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30 to 1000MHz using SchwarzBeck Log-Bicon antenna. Above 1GHz, linearly polarized double ridge horn antennas were used. Final measurements were made open site at 3 meters. The test equipment was placed on a wooden turn-table. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined by manual. The detector function was set to CISPR Quasi-peak mode and the bandwidth of the receiver was set to 120kHz or 1MHz depending on the frequency of type of signal. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the max. emission for the frequency and were placed on top of a 0.8-meter high nonmetallic 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the max. emission. Each emission was maximized by: varying the mode of operation to the EUT and/or support equipment and changing the polarity of the antenna, whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in Test Setup photos.

4. TEST CONDITION

4.1 Test Configuration

The device was configured for testing in a typical fashion (as a customer would normally use it). During the tests, the following conditions and configurations were used.

4.2 EUT operation

Operating Mode	The worst operating condition
Stand-by Mode	
Ping Test Mode	O

O : Worst case investigated during the Test

4.3 Support Equipment Used

Following peripheral devices and interface cables were connected during the measurement:

EUT – ADSL Modem

FCC ID	: PWV-WEL8010D
Model Name	: Wel+8010D
Serial No.	: N/A
Manufacturer	: Wellink Corporation.
Power Supply Type	: DC 5V/12V From Adaptor
Power Cord	: Non-shielded, Detachable: 1.2m
Data Cable	: Non-Shielded RJ-45, RJ-11, Shielded USB Cable

Support Unit 1-Personal computer(DELL)

FCC ID	: N/A(DoC)
Model Name	: MMP
Serial No.	: 2LL11S
Manufacturer	: DELL
Power Supply Type	: Switching
Power Cord	: Non-shielded, Detachable: 1.2m
Data Cable	: Shielded, Detachable:1.5m

Support Unit 2-Keyboard (DELL)

FCC ID	: N/A(DoC)
Model Name	: SK-8000
Serial No.	: 2965
Manufacturer	: DELL
Power Supply Type	: N/A
Power Cord	: N/A
Data Cable	: Shielded, 1.5m



FCC ID : PWV-WEL8010D
Report No: E02.0118.FCC.038N
Date of Test : January 07~08, 2002

Support Unit 3-Mouse(LOGITECH)

FCC ID	: DZL211029
Model Name	: M-S34
Serial No.	: LZC01002314
Manufacturer	: LOGITECH
Power Supply Type	: N/A
Power Cord	: N/A
Data Cable	: Shielded, 1.2m

Support Unit 4- Monitor(E-RAE)

FCC ID	: OIOELM-150
Model Name	: ELM-150A
Serial No.	: N/A
Manufacturer	: E-RAE Electronics Industry Co., Ltd.
Power Supply Type	: DC12V From Adaptor
Power Cord	: Non-shielded, Detachable: 1.2m
Data Cable	: Shielded 15pin D-sub, 1.5m

Support Unit 5- Telephone(CHINO-E)

FCC ID	: N/A
Model Name	: HA6138
Serial No.	: N/A
Manufacturer	: SHENZHEM CHINO ELECTRONICS CO., LTD.
Power Supply Type	: N/A
Power Cord	: N/A
Data Cable	: Non-Shielded RJ-11, 1.2m

5. TEST RESULTS

5.1 Summary of Test Results

The measurement results were obtained with the EUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum emission of the EUT are reported.

Test Rule Parts	Measurement Required	Result
PART 15	Conducted Emissions Measurement	Passed by -3.73dB
PART 15	Radiated Emissions Measurement	Passed by -4.70dB

The data collected shows that the Willink Corporation ADSL Modem, Wel+8010D complies with technical requirements of the FCC PART 15 Computing Peripheral Device

The equipment is not modified anything, mechanical or circuits to improve EMI status during a measurement. No EMI suppression device(s) was added and/or modified during testing.

5. TEST RESULTS

5.2 Conducted Emissions Measurement

EUT	ADSL Modem / Wel+8010D (SN:N/A)
Limit apply to	FCC PART 15 Subpart B
Test Date	January 07, 2002
Operating Condition	Test Program Execute play(ping test)
Environment Condition	Humidity Level : 35 %RH, Temperature : 20
Result	Passed by -3.73dB

Conducted Emission Test Data


The following table shows the highest levels of conducted emissions on both polarization of live and neutral line.

Detector mode : CISPR Quasi-Peak mode (6dB Bandwidth : 9 KHz)

Frequency [MHz]	Reading [dB μ V]		Phase (*H/**N)	Limit [dB μ V]		Margin [dB]	
	Quasi-peak	Average		Quasi-peak	Average	Q.Peak	Average
0.506	38.86	-	N	48.0	-	9.14	-
0.708	38.15	-				9.85	-
0.809	37.65	-				10.35	-
2.431	44.27	-				3.73	-
2.965	38.32	-				9.68	-
9.758	37.35	-				10.65	-
12.78	40.22	-				7.78	-
20.06	39.90	-				8.10	-
24.02	36.95	-				11.05	-
26.73	39.62	-				8.38	-

NOTES :



1. * H : HOT Line , **N : Neutral Line
2. Margin value = Limit – Reading
3. Measurement were performed at the DC Power Supply Inlet in the frequency band of 0.450MHz ~ 30MHz according to the FCC PART 15 Sub Part B



Test Engineer : H. J. Kim



5. TEST RESULTS

Line: HOT Line



5. TEST RESULTS

Line: Neutral Line



5. TEST RESULTS

5.3 Radiated Emissions Measurement

EUT	ADSL Modem/Wel+8010D (SN:N/A)
Limit apply to	FCC PART 15 Subpart B
Test Date	January 08, 2002
Operating Condition	Test Program Execute (ping test)
Environment Condition	Humidity Level : 32 %RH, Temperature : 19
Result	Passed by -4.70dB

Radiated Emission Test Data

The following table shows the highest levels of radiated emissions on both polarization of horizontal and vertical.


Detector mode : CISPR Quasi-Peak mode (6dB Bandwidth : 120 kHz)

Measurement Distance : 3 meters

Frequency [MHz]	Reading [dB μ V]	Polarization (*H/**V)	Ant. Factor [dB]	Cable Loss [dB]	Emission Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
141.35	22.35	H	12.50	3.00	37.85	43.5	5.65
169.55	15.92	H	12.64	3.30	31.86	43.5	11.64
201.77	16.96	H	8.82	3.90	29.68	43.5	13.82
216.00	17.30	H	9.37	4.00	30.67	43.5	12.83
239.98	17.31	H	10.27	4.00	31.58	46.0	14.42
247.29	26.56	H	10.64	4.10	41.30	46.0	4.70
311.97	18.50	H	12.68	4.60	35.78	46.0	10.22
317.95	19.70	H	12.68	4.60	36.98	46.0	9.02
388.60	17.76	H	14.32	5.30	37.38	46.0	8.62
459.25	14.54	H	16.88	5.70	37.12	46.0	8.88
565.23	12.19	H	17.78	6.40	36.37	46.0	9.63

NOTE :

1. * H : Horizontal polarization , ** V : Vertical polarization
2. Emission Level = Reading + Antenna factor + Cable loss
3. Margin value = Limit - Emission Level
4. The measurement was performed for the frequency range 30MHz ~1000MHz according to the FCC PART 15 Sub Part B



Test Engineer : H. J. Kim

6. SAMPLE CALCULATION

Sample Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor.
The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

$$dB(\mu V/m) = 20 \log_{10} (\mu V /m) : \text{Equation 1}$$

$$dB\mu V = dBm + 107 : \text{Equation 2}$$

Example 1 : @ 2.431 MHz

Class B Limit	=	250 μ V	=	48.00 dB μ V
Reading	=	44.27dB μ V		
Convert to μ V	=	163.49 μ V		
Margin	=	44.27	-	48.00 = -3.73
			=	-3.73dB below Limit

Example 2 : @247.29MHz

Class B Limit	=	200 μ V	=	46.0 dB μ V /m
Reading	=	26.56dB μ V		
Antenna Factor + Cable Loss	=	15.74 dB μ V		
Total	=	41.30 dB μ V /m		
Margin	=	41.30	-	46.0 = -4.70
			=	-4.70 dB below Limit

7. TEST EQUIPMENT LIST

List of Test Equipments Used for Measurements

Test Equipment		Model	Mfg.	Serial No.	Cal. Date
<input checked="" type="checkbox"/>	Spectrum Analyzer	R3261A	Advantest	21720033	01-10-25
<input type="checkbox"/>	Spectrum Analyzer	ESA-L1500A	H.P	US37360920	01-03-12
<input checked="" type="checkbox"/>	Receiver	ESVS 10	R & S	835165/001	01-03-30
<input checked="" type="checkbox"/>	LISN	3825/2	EMCO	9208-1995	01-12-27
<input checked="" type="checkbox"/>	LISN	3825/2	EMCO	9006-1669	01-12-27
<input checked="" type="checkbox"/>	Preamplifier	HP8447D	HP	2944A07626	02-01-10
<input type="checkbox"/>	Preamplifier	HP 8347A	HP	2834A00544	01-05-23
<input checked="" type="checkbox"/>	TriLog Antenna	VULB9160	Schwarz Beck	3082	01-06-19
<input type="checkbox"/>	LogBicon	VULB9165	Schwarz Beck	2023	01-06-01
<input checked="" type="checkbox"/>	Dipole Antenna	VHAP	Schwarz Beck	964	01-05-04
<input checked="" type="checkbox"/>	Dipole Antenna	VHAP	Schwarz Beck	965	01-05-04
<input checked="" type="checkbox"/>	Dipole Antenna	UHAP	Schwarz Beck	949	01-05-04
<input checked="" type="checkbox"/>	Dipole Antenna	UHAP	Schwarz Beck	950	01-05-04
<input type="checkbox"/>	Double Ridged Horn	3115	EMCO	9809-2334	01-09-20
<input checked="" type="checkbox"/>	Turn-Table	DETT-03	Daeil EMC	-	N/A
<input checked="" type="checkbox"/>	Antenna Master	DEAM-03	Daeil EMC	-	N/A
<input checked="" type="checkbox"/>	Plotter	7440A	H.P	2725A 75722	N/A
<input checked="" type="checkbox"/>	Chamber	DTEC01	DAETONG	-	N/A
<input type="checkbox"/>	Impedance Matching Pad	6001.01.A	SUNNER	3252	01-09-22
<input checked="" type="checkbox"/>	Thermo Hygrograph	3-3122	ISUZU	3312201	02-01-10
<input checked="" type="checkbox"/>	BaroMeter	-	Regulus	-	-