
Appendix for the Report

Dosimetric Assessment of the Siemens C66 (FCC ID: PWX-C66) According to the FCC Requirements

SAR Distribution Plots

July 28, 2004
IMST GmbH
Carl-Friedrich-Gauß-Str. 2
D-47475 Kamp-Lintfort

Customer
Siemens Information & Communication Mobile LLC
16475 West Bernado Drive, Suite 400
San Diego CA 92127

The test results only relate to the items tested.
This report shall not be reproduced except in full without the written
approval of the testing laboratory.

Table of Contents

1	SAR DISTRIBUTION PLOTS, GSM 850 HEAD WITHOUT FLASH	3
2	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD WITHOUT FLASH.....	15
3	SAR DISTRIBUTION PLOTS, GSM 850 HEAD WITH FLASH.....	27
4	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD WITH FLASH	39
5	SAR DISTRIBUTION PLOTS, PCS 850 BODY WITH HEADSET.....	51
6	SAR DISTRIBUTION PLOTS, PCS 850 BODY WITH DATA CABLE.....	54
7	SAR DISTRIBUTION PLOTS,PCS 1900 BODY WITH HEADSET.....	57
8	SAR DISTRIBUTION PLOTS, PCS 1900 BODY WITH DATA CABLE.....	60
9	SAR Z-AXIS SCANS (VALIDATION)	63
10	SAR Z-AXIS SCANS (MEASUREMENTS).....	71

1 SAR Distribution Plots, GSM 850 Head without Flash

Test Laboratory: IMST GmbH; File Name: [butglm_1.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Cheek Left

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.91$; mho/m, $\epsilon_r = 40.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.67, 6.67, 6.67); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 23.7 V/m; Power Drift = -0.048 dB

Maximum value of SAR (measured) = 0.703 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23.7 V/m; Power Drift = -0.048 dB

Maximum value of SAR (measured) = 0.707 mW/g

Peak SAR (extrapolated) = 0.941 W/kg

SAR(1 g) = 0.672 mW/g; SAR(10 g) = 0.469 mW/g




Fig. 1: SAR distribution for GSM 850, channel 190, cheek position, left side of head, Butterfly. (16.06.2004; Ambient Temperature: 21.6° C; Liquid Temperature: 20.3° C).

Test Laboratory: IMST GmbH; File Name: [butglm_2.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Tilted Left

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.91$; mho/m, $\epsilon_r = 40.6$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.67, 6.67, 6.67); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 21.5 V/m; Power Drift = -0.038 dB

Maximum value of SAR (measured) = 0.458 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.5 V/m; Power Drift = -0.038 dB

Maximum value of SAR (measured) = 0.462 mW/g

Peak SAR (extrapolated) = 0.657 W/kg

SAR(1 g) = 0.431 mW/g; SAR(10 g) = 0.290 mW/g




Fig. 2: SAR distribution for GSM 850, channel 190, tilted position, left side of head, Butterfly. (16.06.2004; Ambient Temperature: 21.6° C; Liquid Temperature : 20.3° C).

Test Laboratory: IMST GmbH; File Name: [butgerm_1.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Cheek Right

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.91$; mho/m, $\epsilon_r = 40.6$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.67, 6.67, 6.67); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 23.7 V/m; Power Drift = 0.050 dB

Maximum value of SAR (measured) = 0.689 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23.7 V/m; Power Drift = 0.050 dB

Maximum value of SAR (measured) = 0.695 mW/g

Peak SAR (extrapolated) = 0.836 W/kg

SAR(1 g) = 0.651 mW/g; SAR(10 g) = 0.467 mW/g




Fig. 3: SAR distribution for GSM 850, channel 190, cheek position, right side of head, Butterfly. (16.06.2004; Ambient Temperature: 21.7° C; Liquid Temperature : 20.3° C).

Test Laboratory: IMST GmbH; File Name: [butgerm_2.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Tilted Right

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.91$; mho/m, $\epsilon_r = 40.6$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.67, 6.67, 6.67); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 21.9 V/m; Power Drift = 0.043 dB

Maximum value of SAR (measured) = 0.406 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.9 V/m; Power Drift = 0.043 dB

Maximum value of SAR (measured) = 0.432 mW/g

Peak SAR (extrapolated) = 0.556 W/kg

SAR(1 g) = 0.405 mW/g; SAR(10 g) = 0.283 mW/g




Fig. 4: SAR distribution for GSM 850, channel 190, tilted position, right side of head, Butterfly. (16.06.2004; Ambient Temperature: 21.7° C; Liquid Temperature : 20.3° C).

Test Laboratory: IMST GmbH; File Name: [arclm_1.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Cheek Left

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.91$; mho/m, $\epsilon_r = 40.6$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.67, 6.67, 6.67); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 23.9 V/m; Power Drift = -0.052 dB

Maximum value of SAR (measured) = 0.713 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23.9 V/m; Power Drift = -0.052 dB

Maximum value of SAR (measured) = 0.720 mW/g

Peak SAR (extrapolated) = 0.946 W/kg

SAR(1 g) = 0.688 mW/g; SAR(10 g) = 0.482 mW/g




Fig. 5: SAR distribution for GSM 850, channel 190, cheek position, left side of head, ARC. (16.06.2004; Ambient Temperature: 20.9° C; Liquid Temperature: 20.0° C).

Test Laboratory: IMST GmbH; File Name: [arcglm_2.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Tilted Left

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.91$; mho/m, $\epsilon_r = 40.6$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.67, 6.67, 6.67); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 21.5 V/m; Power Drift = -0.042 dB

Maximum value of SAR (measured) = 0.448 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.5 V/m; Power Drift = -0.042 dB

Maximum value of SAR (measured) = 0.452 mW/g

Peak SAR (extrapolated) = 0.652 W/kg

SAR(1 g) = 0.425 mW/g; SAR(10 g) = 0.290 mW/g




Fig. 6: SAR distribution for GSM 850, channel 190, channel 661, tilted position, left side of head, ARC. (16.06.2004; Ambient Temperature: 20.9° C; Liquid Temperature : 20.1° C).

Test Laboratory: IMST GmbH; File Name: [arcgrm_1.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Cheek Right

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.91$; mho/m, $\epsilon_r = 40.6$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.67, 6.67, 6.67); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 23.6 V/m; Power Drift = -0.010 dB

Maximum value of SAR (measured) = 0.695 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23.6 V/m; Power Drift = -0.010 dB

Maximum value of SAR (measured) = 0.699 mW/g

Peak SAR (extrapolated) = 0.845 W/kg

SAR(1 g) = 0.653 mW/g; SAR(10 g) = 0.467 mW/g




Fig. 7: SAR distribution for GSM 850, channel 190, cheek position, right side of head, ARC. (16.06.2004; Ambient Temperature: 20.9° C; Liquid Temperature : 20.1° C).

Test Laboratory: IMST GmbH; File Name: [arcgrm_2.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Tilted Right

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.91$; mho/m, $\epsilon_r = 40.6$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.67, 6.67, 6.67); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 21.7 V/m; Power Drift = 0.054 dB

Maximum value of SAR (measured) = 0.406 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.7 V/m; Power Drift = 0.054 dB

Maximum value of SAR (measured) = 0.432 mW/g

Peak SAR (extrapolated) = 0.549 W/kg

SAR(1 g) = 0.405 mW/g; SAR(10 g) = 0.282 mW/g




Fig. 8: SAR distribution for GSM 850, channel 190, tilted position, right side of head, ARC. (16.06.2004; Ambient Temperature: 20.9° C; Liquid Temperature : 20.1° C).

Test Laboratory: IMST GmbH; File Name: [stdglm_1.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Cheek Left

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.94$; mho/m, $\epsilon_r = 42.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(6.57, 6.57, 6.57); Calibrated: 21.05.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 22.3 V/m; Power Drift = -0.042 dB

Maximum value of SAR (measured) = 0.541 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.3 V/m; Power Drift = -0.042 dB

Maximum value of SAR (measured) = 0.551 mW/g

Peak SAR (extrapolated) = 0.745 W/kg

SAR(1 g) = 0.522 mW/g; SAR(10 g) = 0.360 mW/g




Fig. 9: SAR distribution for GSM 850, channel 190, cheek position, left side of head, Standard. (27.07.2004; Ambient Temperature: 21.0° C; Liquid Temperature: 20.4° C).

Test Laboratory: IMST GmbH; File Name: [stdglm_2.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Tilted Left

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.94$; mho/m, $\epsilon_r = 42.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(6.57, 6.57, 6.57); Calibrated: 21.05.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 20.8 V/m; Power Drift = 0.057 dB

Maximum value of SAR (measured) = 0.423 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.8 V/m; Power Drift = 0.057 dB

Maximum value of SAR (measured) = 0.428 mW/g

Peak SAR (extrapolated) = 0.603 W/kg

SAR(1 g) = 0.393 mW/g; SAR(10 g) = 0.263 mW/g




Fig. 10: SAR distribution for GSM 850, channel 190, channel 661, tilted position, left side of head, Standard. (27.07.2004; Ambient Temperature: 21.0° C; Liquid Temperature : 20.4° C).

Test Laboratory: IMST GmbH; File Name: [stdgrm_1.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Tilted Left

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.94$; mho/m, $\epsilon_r = 42.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(6.57, 6.57, 6.57); Calibrated: 21.05.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 23.2 V/m; Power Drift = -0.020 dB

Maximum value of SAR (measured) = 0.455 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23.2 V/m; Power Drift = -0.020 dB

Maximum value of SAR (measured) = 0.516 mW/g

Peak SAR (extrapolated) = 0.623 W/kg

SAR(1 g) = 0.476 mW/g; SAR(10 g) = 0.339 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23.2 V/m; Power Drift = -0.020 dB

Maximum value of SAR (measured) = 0.542 mW/g

Peak SAR (extrapolated) = 0.641 W/kg

SAR(1 g) = 0.448 mW/g; SAR(10 g) = 0.290 mW/g




Fig. 11: SAR distribution for GSM 850, channel 190, cheek position, right side of head, Standard. (27.07.2004; Ambient Temperature: 21.0° C; Liquid Temperature : 20.4° C).

Test Laboratory: IMST GmbH; File Name: [stdgrm_2.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Tilted Right

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.94$; mho/m, $\epsilon_r = 42.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(6.57, 6.57, 6.57); Calibrated: 21.05.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 21.7 V/m; Power Drift = -0.042 dB

Maximum value of SAR (measured) = 0.397 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.7 V/m; Power Drift = -0.042 dB

Maximum value of SAR (measured) = 0.420 mW/g

Peak SAR (extrapolated) = 0.558 W/kg

SAR(1 g) = 0.392 mW/g; SAR(10 g) = 0.277 mW/g




Fig. 12: SAR distribution for GSM 850, channel 190, tilted position, right side of head, Standard. (27.07.2004; Ambient Temperature: 21.0° C; Liquid Temperature : 20.4° C).

2 SAR Distribution Plots, PCS 1900 Head without Flash

Test Laboratory: IMST GmbH; File Name: [butplm_1.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 16.6 V/m; Power Drift = -0.016 dB

Maximum value of SAR (measured) = 0.540 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.6 V/m; Power Drift = -0.016 dB

Maximum value of SAR (measured) = 0.663 mW/g

Peak SAR (extrapolated) = 0.992 W/kg

SAR(1 g) = 0.592 mW/g; SAR(10 g) = 0.326 mW/g




Fig. 13: SAR distribution for PCS 1900, channel 661, cheek position, left side of head, Butterfly. (18.06.2004; Ambient Temperature: 20.8° C; Liquid Temperature: 20.1° C).

Test Laboratory: IMST GmbH; File Name: [butplm_2.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19 V/m; Power Drift = 0.043 dB

Maximum value of SAR (measured) = 0.607 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19 V/m; Power Drift = 0.043 dB

Maximum value of SAR (measured) = 0.656 mW/g

Peak SAR (extrapolated) = 0.986 W/kg

SAR(1 g) = 0.592 mW/g; SAR(10 g) = 0.331 mW/g




Fig. 14: SAR distribution for PCS 1900, channel 661, tilted position, left side of head, Butterfly. (18.06.2004; Ambient Temperature: 20.9° C; Liquid Temperature : 20.2° C).

Test Laboratory: IMST GmbH; File Name: [butprm_1.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18.9 V/m; Power Drift = 0.077 dB

Maximum value of SAR (measured) = 0.452 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.9 V/m; Power Drift = 0.077 dB

Maximum value of SAR (measured) = 0.470 mW/g

Peak SAR (extrapolated) = 0.656 W/kg

SAR(1 g) = 0.430 mW/g; SAR(10 g) = 0.250 mW/g




Fig. 15: SAR distribution for PCS 1900, channel 661, cheek position, right side of head, Butterfly. (18.06.2004; Ambient Temperature: 20.9° C; Liquid Temperature : 20.2° C).

Test Laboratory: IMST GmbH; File Name: [butprm_2.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 20 V/m; Power Drift = 0.030 dB

Maximum value of SAR (measured) = 0.490 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20 V/m; Power Drift = 0.030dB

Maximum value of SAR (measured) = 0.529 mW/g

Peak SAR (extrapolated) = 0.759 W/kg

SAR(1 g) = 0.481 mW/g; SAR(10 g) = 0.274 mW/g




Fig. 16: SAR distribution for PCS 1900, channel 661, tilted position, right side of head, Butterfly. (18.06.2004; Ambient Temperature: 21.0° C; Liquid Temperature : 20.2° C).

Test Laboratory: IMST GmbH; File Name: [arcplm_1.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 17.3 V/m; Power Drift = 0.050 dB

Maximum value of SAR (measured) = 0.548 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.3 V/m; Power Drift = 0.050 dB

Maximum value of SAR (measured) = 0.630 mW/g

Peak SAR (extrapolated) = 0.920 W/kg

SAR(1 g) = 0.566 mW/g; SAR(10 g) = 0.315 mW/g




Fig. 17: SAR distribution for PCS 1900, channel 661, cheek position, left side of head, ARC. (18.06.2004; Ambient Temperature: 21.4° C; Liquid Temperature: 20.3° C).

Test Laboratory: IMST GmbH; File Name: [arcplm_2.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19.2 V/m; Power Drift = 0.053 dB

Maximum value of SAR (measured) = 0.606 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.2 V/m; Power Drift = 0.053 dB

Maximum value of SAR (measured) = 0.626 mW/g

Peak SAR (extrapolated) = 0.911 W/kg

SAR(1 g) = 0.563 mW/g; SAR(10 g) = 0.317 mW/g




Fig. 18: SAR distribution for PCS 1900, channel 661, tilted position, left side of head, ARC. (18.062004; Ambient Temperature: 21.4° C; Liquid Temperature : 20.3° C).

Test Laboratory: IMST GmbH; File Name: [arcprm_1.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18.4 V/m; Power Drift = 0.2 dB

Maximum value of SAR (measured) = 0.441 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.4 V/m; Power Drift = 0.2 dB

Maximum value of SAR (measured) = 0.469 mW/g

Peak SAR (extrapolated) = 0.666 W/kg

SAR(1 g) = 0.430 mW/g; SAR(10 g) = 0.250 mW/g




Fig. 19: SAR distribution for PCS 1900, channel 661, cheek position, right side of head, ARC. (18.06.2004; Ambient Temperature: 21.4° C; Liquid Temperature : 20.3° C).

Test Laboratory: IMST GmbH; File Name: [arcprm_2.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19.4 V/m; Power Drift = 0.124 dB

Maximum value of SAR (measured) = 0.454 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.4 V/m; Power Drift = 0.124 dB

Maximum value of SAR (measured) = 0.483 mW/g

Peak SAR (extrapolated) = 0.680 W/kg

SAR(1 g) = 0.440 mW/g; SAR(10 g) = 0.254 mW/g




Fig. 20: SAR distribution for PCS 1900, channel 661, tilted position, right side of head, ARC. (18.06.2004; Ambient Temperature: 21.4° C; Liquid Temperature : 20.3° C).

Test Laboratory: IMST GmbH; File Name: [stdplm_1.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(4.93, 4.93, 4.93); Calibrated: 21.05.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn489; Calibrated: 19.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 16 V/m; Power Drift = 0.038 dB

Maximum value of SAR (measured) = 0.577 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16 V/m; Power Drift = 0.038 dB

Maximum value of SAR (measured) = 0.662 mW/g

Peak SAR (extrapolated) = 0.961 W/kg

SAR(1 g) = 0.595 mW/g; SAR(10 g) = 0.336 mW/g




Fig. 21: SAR distribution for PCS 1900, channel 661, cheek position, left side of head, Standard. (23.07.2004; Ambient Temperature: 21.1° C; Liquid Temperature: 20.1° C).

Test Laboratory: IMST GmbH; File Name: [stdplm_2.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(4.93, 4.93, 4.93); Calibrated: 21.05.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn489; Calibrated: 19.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18.8 V/m; Power Drift = 0.063 dB

Maximum value of SAR (measured) = 0.615 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.8 V/m; Power Drift = 0.063 dB

Maximum value of SAR (measured) = 0.692 mW/g

Peak SAR (extrapolated) = 1.01 W/kg

SAR(1 g) = 0.632 mW/g; SAR(10 g) = 0.357 mW/g




Fig. 22: SAR distribution for PCS 1900, channel 661, tilted position, left side of head, Standard. (23.072004; Ambient Temperature: 21.1° C; Liquid Temperature : 20.1° C).

Test Laboratory: IMST GmbH; File Name: [stdprm_1.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(4.93, 4.93, 4.93); Calibrated: 21.05.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn489; Calibrated: 19.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18.7 V/m; Power Drift = 0.091 dB

Maximum value of SAR (measured) = 0.436 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.7 V/m; Power Drift = 0.091 dB

Maximum value of SAR (measured) = 0.464 mW/g

Peak SAR (extrapolated) = 0.638 W/kg

SAR(1 g) = 0.423 mW/g; SAR(10 g) = 0.251 mW/g




Fig. 23: SAR distribution for PCS 1900, channel 661, cheek position, right side of head, Standard. (23.07.2004; Ambient Temperature: 21.2° C; Liquid Temperature : 20.2° C).

Test Laboratory: IMST GmbH; File Name: [stdprm_2.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(4.93, 4.93, 4.93); Calibrated: 21.05.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn489; Calibrated: 19.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 20 V/m; Power Drift = 0.063 dB

Maximum value of SAR (measured) = 0.466 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20 V/m; Power Drift = 0.063 dB

Maximum value of SAR (measured) = 0.519 mW/g

Peak SAR (extrapolated) = 0.712 W/kg

SAR(1 g) = 0.469 mW/g; SAR(10 g) = 0.271 mW/g




Fig. 24: SAR distribution for PCS 1900, channel 661, tilted position, right side of head, Standard. (23.07.2004; Ambient Temperature: 21.2° C; Liquid Temperature : 20.2° C).

3 SAR Distribution Plots, GSM 850 Head with Flash

Test Laboratory: IMST GmbH; File Name: [butglm_1_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Cheek Left

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.91$; mho/m, $\epsilon_r = 40.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.67, 6.67, 6.67); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 23 V/m; Power Drift = -0.058 dB

Maximum value of SAR (measured) = 0.767 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23 V/m; Power Drift = -0.058 dB

Maximum value of SAR (measured) = 0.784 mW/g

Peak SAR (extrapolated) = 1.04 W/kg

SAR(1 g) = 0.745 mW/g; SAR(10 g) = 0.524 mW/g




Fig. 25: SAR distribution for GSM 850, channel 190, cheek position, left side of head Butterfly. (16.06.2004; Ambient Temperature: 21.8° C; Liquid Temperature : 20.3° C).

Test Laboratory: IMST GmbH; File Name: [butglm_2_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Tilted Left

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.91$; mho/m, $\epsilon_r = 40.6$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.67, 6.67, 6.67); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19.4 V/m; Power Drift = 0.040 dB

Maximum value of SAR (measured) = 0.365 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.4 V/m; Power Drift = 0.040 dB

Maximum value of SAR (measured) = 0.395 mW/g

Peak SAR (extrapolated) = 0.668 W/kg

SAR(1 g) = 0.362 mW/g; SAR(10 g) = 0.218 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.4 V/m; Power Drift = 0.040 dB

Maximum value of SAR (measured) = 0.310 mW/g

Peak SAR (extrapolated) = 0.380 W/kg

SAR(1 g) = 0.296 mW/g; SAR(10 g) = 0.215 mW/g




Fig. 26: SAR distribution for GSM 850, channel 190, cheek position, left side of head Butterfly. (16.06.2004; Ambient Temperature: 21.9° C; Liquid Temperature : 20.3° C).

Test Laboratory: IMST GmbH; File Name: [butgerm_1_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Cheek Right

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.91$; mho/m, $\epsilon_r = 40.6$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.67, 6.67, 6.67); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 22.8 V/m; Power Drift = 0.035 dB

Maximum value of SAR (measured) = 0.731 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.8 V/m; Power Drift = 0.035 dB

Maximum value of SAR (measured) = 0.763 mW/g

Peak SAR (extrapolated) = 0.908 W/kg

SAR(1 g) = 0.713 mW/g; SAR(10 g) = 0.508 mW/g




Fig. 27: SAR distribution for GSM 850, channel 190, cheek position, right side of head Butterfly. (16.06.2004; Ambient Temperature: 21.9° C; Liquid Temperature : 20.3° C).

Test Laboratory: IMST GmbH; File Name: [butgrm_2_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Tilted Right

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.91$; mho/m, $\epsilon_r = 40.6$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.67, 6.67, 6.67); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 20.4 V/m; Power Drift = -0.104 dB

Maximum value of SAR (measured) = 0.349 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.4 V/m; Power Drift = -0.104 dB

Maximum value of SAR (measured) = 0.349 mW/g

Peak SAR (extrapolated) = 0.571 W/kg

SAR(1 g) = 0.322 mW/g; SAR(10 g) = 0.201 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.4 V/m; Power Drift = -0.104 dB

Maximum value of SAR (measured) = 0.296 mW/g

Peak SAR (extrapolated) = 0.361 W/kg

SAR(1 g) = 0.280 mW/g; SAR(10 g) = 0.204 mW/g




Fig. 28: SAR distribution for GSM 850, channel 190, cheek position, right side of head Butterfly. (16.06.2004; Ambient Temperature: 21.7° C; Liquid Temperature : 20.3° C).

Test Laboratory: IMST GmbH; File Name: [arcglm_1_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Cheek Left

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.91$; mho/m, $\epsilon_r = 40.6$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.67, 6.67, 6.67); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 22.7 V/m; Power Drift = 0.003 dB

Maximum value of SAR (measured) = 0.752 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.7 V/m; Power Drift = 0.003 dB

Maximum value of SAR (measured) = 0.764 mW/g

Peak SAR (extrapolated) = 0.984 W/kg

SAR(1 g) = 0.722 mW/g; SAR(10 g) = 0.512 mW/g




Fig. 29: SAR distribution for GSM 850, channel 190, cheek position, left side of head ARC. (16.06.2004; Ambient Temperature: 20.9° C; Liquid Temperature : 20.1° C).

Test Laboratory: IMST GmbH; File Name: [arclm_2_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Tilted Left

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.91$; mho/m, $\epsilon_r = 40.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.67, 6.67, 6.67); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 20.4 V/m; Power Drift = 0.052 dB

Maximum value of SAR (measured) = 0.420 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.4 V/m; Power Drift = 0.052 dB

Maximum value of SAR (measured) = 0.426 mW/g

Peak SAR (extrapolated) = 0.521 W/kg

SAR(1 g) = 0.404 mW/g; SAR(10 g) = 0.289 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.4 V/m; Power Drift = 0.052 dB

Maximum value of SAR (measured) = 0.412 mW/g

Peak SAR (extrapolated) = 0.666 W/kg

SAR(1 g) = 0.386 mW/g; SAR(10 g) = 0.262 mW/g




Fig. 30: SAR distribution for GSM 850, channel 190, cheek position, left side of head ARC. (16.06.2004; Ambient Temperature: 20.9° C; Liquid Temperature : 20.1° C).

Test Laboratory: IMST GmbH; File Name: [arcgrm_1_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Cheek Right

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.91$; mho/m, $\epsilon_r = 40.6$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.67, 6.67, 6.67); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 23 V/m; Power Drift = 0.085 dB

Maximum value of SAR (measured) = 0.697 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23 V/m; Power Drift = 0.085 dB

Maximum value of SAR (measured) = 0.737 mW/g

Peak SAR (extrapolated) = 0.886 W/kg

SAR(1 g) = 0.691 mW/g; SAR(10 g) = 0.493 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23 V/m; Power Drift = 0.085 dB

Maximum value of SAR (measured) = 0.625 mW/g

Peak SAR (extrapolated) = 0.775 W/kg

SAR(1 g) = 0.551 mW/g; SAR(10 g) = 0.367 mW/g




Fig. 31: SAR distribution for GSM 850, channel 190, cheek position, right side of head ARC. (16.06.2004; Ambient Temperature: 20.9° C; Liquid Temperature : 20.1° C).

Test Laboratory: IMST GmbH; File Name: [arcgrm_2_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Tilted Right

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.91$; mho/m ; $\epsilon_r = 40.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.67, 6.67, 6.67); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x12x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Reference Value = 20.1 V/m; Power Drift = 0.038 dB

Maximum value of SAR (measured) = 0.351 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.1 V/m; Power Drift = 0.038 dB

Maximum value of SAR (measured) = 0.355 mW/g

Peak SAR (extrapolated) = 0.580 W/kg

SAR(1 g) = 0.324 mW/g; SAR(10 g) = 0.204 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.1 V/m; Power Drift = 0.038 dB

Maximum value of SAR (measured) = 0.313 mW/g

Peak SAR (extrapolated) = 0.386 W/kg

SAR(1 g) = 0.295 mW/g; SAR(10 g) = 0.214 mW/g




Fig. 32: SAR distribution for GSM 850, channel 190, cheek position, right side of head ARC. (16.06.2004; Ambient Temperature: 20.9° C; Liquid Temperature : 20.1° C).

Test Laboratory: IMST GmbH; File Name: [stdglm_1_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Cheek Left

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.94$; mho/m, $\epsilon_r = 42.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(6.57, 6.57, 6.57); Calibrated: 21.05.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 22.1 V/m; Power Drift = -0.01 dB

Maximum value of SAR (measured) = 0.610 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.1 V/m; Power Drift = -0.01 dB

Maximum value of SAR (measured) = 0.615 mW/g

Peak SAR (extrapolated) = 0.806 W/kg

SAR(1 g) = 0.583 mW/g; SAR(10 g) = 0.411 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.1 V/m; Power Drift = -0.01 dB

Maximum value of SAR (measured) = 0.574 mW/g

Peak SAR (extrapolated) = 0.741 W/kg

SAR(1 g) = 0.510 mW/g; SAR(10 g) = 0.334 mW/g




Fig. 33: SAR distribution for GSM 850, channel 190, cheek position, left side of head Standard. (27.07.2004; Ambient Temperature: 21.4° C; Liquid Temperature : 20.6° C).

Test Laboratory: IMST GmbH; File Name: [stdglm_2_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870
Program Name: Tilted Left

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3
 Medium parameters used: $\sigma = 0.94$; mho/m, $\epsilon_r = 42.7$; $\rho = 1000$ kg/m³
 Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(6.57, 6.57, 6.57); Calibrated: 21.05.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19.2 V/m; Power Drift = 0.015 dB

Maximum value of SAR (measured) = 0.357 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.2 V/m; Power Drift = 0.015 dB

Maximum value of SAR (measured) = 0.416 mW/g

Peak SAR (extrapolated) = 0.788 W/kg

SAR(1 g) = 0.393 mW/g; SAR(10 g) = 0.221 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.2 V/m; Power Drift = 0.015 dB

Maximum value of SAR (measured) = 0.289 mW/g

Peak SAR (extrapolated) = 0.360 W/kg

SAR(1 g) = 0.275 mW/g; SAR(10 g) = 0.200 mW/g




Fig. 34: SAR distribution for GSM 850, channel 190, cheek position, left side of head Standard. (27.07.2004; Ambient Temperature: 21.4° C; Liquid Temperature : 20.6° C).

Test Laboratory: IMST GmbH; File Name: [stdgrm_1_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870
Program Name: Tilted Left

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3
 Medium parameters used: $\sigma = 0.94$; mho/m, $\epsilon_r = 42.7$; $\rho = 1000$ kg/m³
 Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(6.57, 6.57, 6.57); Calibrated: 21.05.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 23.1 V/m; Power Drift = 0.060 dB

Maximum value of SAR (measured) = 0.601 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23.1 V/m; Power Drift = 0.060 dB

Maximum value of SAR (measured) = 0.613 mW/g

Peak SAR (extrapolated) = 0.809 W/kg

SAR(1 g) = 0.581 mW/g; SAR(10 g) = 0.420 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23.1 V/m; Power Drift = 0.060 dB

Maximum value of SAR (measured) = 0.581 mW/g

Peak SAR (extrapolated) = 0.778 W/kg

SAR(1 g) = 0.525 mW/g; SAR(10 g) = 0.362 mW/g




Fig. 35: SAR distribution for GSM 850, channel 190, cheek position, right side of head Standard. (27.07.2004; Ambient Temperature: 21.4° C; Liquid Temperature : 20.6° C).

Test Laboratory: IMST GmbH; File Name: [stdgrm_2_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Tilted Right

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.94$; mho/m, $\epsilon_r = 42.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(6.57, 6.57, 6.57); Calibrated: 21.05.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 20.4 V/m; Power Drift = 0.021 dB

Maximum value of SAR (measured) = 0.377 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.4 V/m; Power Drift = 0.021 dB

Maximum value of SAR (measured) = 0.405 mW/g

Peak SAR (extrapolated) = 0.669 W/kg

SAR(1 g) = 0.367 mW/g; SAR(10 g) = 0.226 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.4 V/m; Power Drift = 0.021 dB

Maximum value of SAR (measured) = 0.314 mW/g

Peak SAR (extrapolated) = 0.384 W/kg

SAR(1 g) = 0.298 mW/g; SAR(10 g) = 0.219 mW/g




Fig. 36: SAR distribution for GSM 850, channel 190, cheek position, right side of head Standard. (27.07.2004; Ambient Temperature: 21.4° C; Liquid Temperature : 20.6° C).

4 SAR Distribution Plots, PCS 1900 Head with Flash

Test Laboratory: IMST GmbH; File Name: [butplm_1_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek left/Area Scan (6x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Reference Value = 16.9 V/m; Power Drift = 0.106 dB

Maximum value of SAR (measured) = 0.523 mW/g

Cheek left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 16.9 V/m; Power Drift = 0.106 dB

Maximum value of SAR (measured) = 0.628 mW/g

Peak SAR (extrapolated) = 0.971 W/kg

SAR(1 g) = 0.574 mW/g; SAR(10 g) = 0.319 mW/g




Fig. 37: SAR distribution for PCS 1900, channel 661, cheek position, left side of head Butterfly. (18.06.2004; Ambient Temperature: 21.3° C; Liquid Temperature : 20.3° C).

Test Laboratory: IMST GmbH; File Name: [butplm_2_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x13x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18.5 V/m; Power Drift = 0.098 dB

Maximum value of SAR (measured) = 0.532 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.5 V/m; Power Drift = 0.098 dB

Maximum value of SAR (measured) = 0.658 mW/g

Peak SAR (extrapolated) = 0.945 W/kg

SAR(1 g) = 0.591 mW/g; SAR(10 g) = 0.334 mW/g




Fig. 38: SAR distribution for PCS 1900, channel 661, cheek position, left side of head Butterfly. (18.06.2004; Ambient Temperature: 21.2° C; Liquid Temperature : 20.3° C).

Test Laboratory: IMST GmbH; File Name: [butprm_1_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18.6 V/m; Power Drift = 0.079 dB

Maximum value of SAR (measured) = 0.429 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.6 V/m; Power Drift = 0.079 dB

Maximum value of SAR (measured) = 0.456 mW/g

Peak SAR (extrapolated) = 0.641 W/kg

SAR(1 g) = 0.411 mW/g; SAR(10 g) = 0.241 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.6 V/m; Power Drift = 0.079 dB

Maximum value of SAR (measured) = 0.431 mW/g

Peak SAR (extrapolated) = 0.607 W/kg

SAR(1 g) = 0.358 mW/g; SAR(10 g) = 0.184 mW/g




Fig. 39: SAR distribution for PCS 1900, channel 661, cheek position, right side of head Butterfly. (18.06.2004; Ambient Temperature: 21.2° C; Liquid Temperature : 20.3° C).

Test Laboratory: IMST GmbH; File Name: [butprm_2_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x13x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18.7 V/m; Power Drift = 0.045 dB

Maximum value of SAR (measured) = 0.455 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.7 V/m; Power Drift = 0.045dB

Maximum value of SAR (measured) = 0.471 mW/g

Peak SAR (extrapolated) = 0.669 W/kg

SAR(1 g) = 0.430 mW/g; SAR(10 g) = 0.250 mW/g




Fig. 40: SAR distribution for PCS 1900, channel 810, cheek position, right side of head Butterfly. (18.06.2004; Ambient Temperature: 21.2° C; Liquid Temperature : 20.3° C).

Test Laboratory: IMST GmbH; File Name: [arcplm_1_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x13x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18.3 V/m; Power Drift = 0.0664 dB

Maximum value of SAR (measured) = 0.563 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.3 V/m; Power Drift = 0.0664 dB

Maximum value of SAR (measured) = 0.594 mW/g

Peak SAR (extrapolated) = 0.862 W/kg

SAR(1 g) = 0.536 mW/g; SAR(10 g) = 0.306 mW/g




Fig. 41: SAR distribution for PCS 1900, channel 661, cheek position, left side of head ARC. (18.06.2004; Ambient Temperature: 21.0° C; Liquid Temperature : 20.2° C).

Test Laboratory: IMST GmbH; File Name: [arcplm_2_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x13x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 17.6 V/m; Power Drift = -0.0246 dB

Maximum value of SAR (measured) = 0.450 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.6 V/m; Power Drift = -0.0246 dB

Maximum value of SAR (measured) = 0.578 mW/g

Peak SAR (extrapolated) = 0.825 W/kg

SAR(1 g) = 0.515 mW/g; SAR(10 g) = 0.293 mW/g




Fig. 42: SAR distribution for PCS 1900, channel 810, cheek position, left side of head ARC. (18.06.2004; Ambient Temperature: 21.1° C; Liquid Temperature : 20.4° C).

Test Laboratory: IMST GmbH; File Name: [arcprm_1_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x13x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18 V/m; Power Drift = 0.0452 dB

Maximum value of SAR (measured) = 0.430 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18 V/m; Power Drift = 0.0452 dB

Maximum value of SAR (measured) = 0.445 mW/g

Peak SAR (extrapolated) = 0.615 W/kg

SAR(1 g) = 0.404 mW/g; SAR(10 g) = 0.239 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18 V/m; Power Drift = 0.0452 dB

Maximum value of SAR (measured) = 0.389 mW/g

Peak SAR (extrapolated) = 0.523 W/kg

SAR(1 g) = 0.283 mW/g; SAR(10 g) = 0.159 mW/g




Fig. 43: SAR distribution for PCS 1900, channel 661, cheek position, right side of head ARC. (18.06.2004; Ambient Temperature: 21.1° C; Liquid Temperature : 20.4° C).

Test Laboratory: IMST GmbH; File Name: [arcprm_2_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x13x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18 V/m; Power Drift = 0.0488 dB

Maximum value of SAR (measured) = 0.384 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18 V/m; Power Drift = 0.0488dB

Maximum value of SAR (measured) = 0.456 mW/g

Peak SAR (extrapolated) = 0.644 W/kg

SAR(1 g) = 0.412 mW/g; SAR(10 g) = 0.241 mW/g




Fig. 44: SAR distribution for PCS 1900, channel 810, cheek position, right side of head ARC. (18.06.2004; Ambient Temperature: 21.0° C; Liquid Temperature : 20.3° C).

Test Laboratory: IMST GmbH; File Name: [stdplm_1_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(4.93, 4.93, 4.93); Calibrated: 21.05.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn489; Calibrated: 19.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Reference Value = 15.7 V/m; Power Drift = 0.082 dB

Maximum value of SAR (measured) = 0.529 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 15.7 V/m; Power Drift = 0.082 dB

Maximum value of SAR (measured) = 0.640 mW/g

Peak SAR (extrapolated) = 0.932 W/kg

SAR(1 g) = 0.577 mW/g; SAR(10 g) = 0.330 mW/g




Fig. 45: SAR distribution for PCS 1900, channel 661, cheek position, left side of head Standard. (23.07.2004; Ambient Temperature: 21.4° C; Liquid Temperature : 20.7° C).

Test Laboratory: IMST GmbH; File Name: [stdplm_2_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(4.93, 4.93, 4.93); Calibrated: 21.05.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn489; Calibrated: 19.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x13x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 17.8 V/m; Power Drift = 0.101 dB

Maximum value of SAR (measured) = 0.536 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.8 V/m; Power Drift = 0.101 dB

Maximum value of SAR (measured) = 0.655 mW/g

Peak SAR (extrapolated) = 0.943 W/kg

SAR(1 g) = 0.586 mW/g; SAR(10 g) = 0.333 mW/g




Fig. 46: SAR distribution for PCS 1900, channel 810, cheek position, left side of head Standard. (23.07.2004; Ambient Temperature: 21.4° C; Liquid Temperature : 20.7° C).

Test Laboratory: IMST GmbH; File Name: [stdprm_1_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(4.93, 4.93, 4.93); Calibrated: 21.05.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn489; Calibrated: 19.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18.4 V/m; Power Drift = -0.052 dB

Maximum value of SAR (measured) = 0.387 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.4 V/m; Power Drift = -0.052 dB

Maximum value of SAR (measured) = 0.431 mW/g

Peak SAR (extrapolated) = 0.573 W/kg

SAR(1 g) = 0.390 mW/g; SAR(10 g) = 0.237 mW/g




Fig. 47: SAR distribution for PCS 1900, channel 661, cheek position, right side of head Standard. (23.07.2004; Ambient Temperature: 21.4° C; Liquid Temperature : 20.7° C).

Test Laboratory: IMST GmbH; File Name: [stdprm_2_flash.da4](#)

DUT: Siemens + Flash; Type: C66; Serial: 004400005236870

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(4.93, 4.93, 4.93); Calibrated: 21.05.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn489; Calibrated: 19.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x13x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18.3 V/m; Power Drift = -0.153 dB

Maximum value of SAR (measured) = 0.405 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.3 V/m; Power Drift = -0.153 dB

Maximum value of SAR (measured) = 0.435 mW/g

Peak SAR (extrapolated) = 0.612 W/kg

SAR(1 g) = 0.402 mW/g; SAR(10 g) = 0.238 mW/g




Fig. 48: SAR distribution for PCS 1900, channel 810, cheek position, right side of head Standard. (23.07.2004; Ambient Temperature: 21.4° C; Liquid Temperature : 20.7° C).

5 SAR Distribution Plots, PCS 850 Body with headset

Test Laboratory: IMST GmbH; File Name: [butghm_2.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Body Worn

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.99$; mho/m, $\epsilon_r = 54.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.32, 6.32, 6.32); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 16 V/m; Power Drift = 0.0 107dB

Maximum value of SAR (measured) = 0.256 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16 V/m; Power Drift = 0.0 107dB

Maximum value of SAR (measured) = 0.268 mW/g

Peak SAR (extrapolated) = 0.339 W/kg

SAR(1 g) = 0.252 mW/g; SAR(10 g) = 0.178 mW/g




Fig. 49: SAR distribution for GSM 850, channel 190, body worn configuration, antenna towards the phantom, Butterfly cover with headset (22.06.2004; Ambient Temperature: 21.4° C; Liquid Temperature : 20.5° C).

Test Laboratory: IMST GmbH; File Name: [arcghm_2.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Body Worn

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0.99$; mho/m, $\epsilon_r = 54.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.32, 6.32, 6.32); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 17 V/m; Power Drift = 0.01 dB

Maximum value of SAR (measured) = 0.292 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17 V/m; Power Drift = 0.01 dB

Maximum value of SAR (measured) = 0.310 mW/g

Peak SAR (extrapolated) = 0.385 W/kg

SAR(1 g) = 0.289 mW/g; SAR(10 g) = 0.205 mW/g




Fig. 50: SAR distribution for GSM 850, channel 190, body worn configuration, antenna towards the phantom, ARC cover with headset (22.06.2004; Ambient Temperature: 21.3° C; Liquid Temperature : 20.5° C).

Test Laboratory: IMST GmbH; File Name: [stdghm_2.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Body Worn

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 1.01$; mho/m, $\epsilon_r = 53.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.32, 6.32, 6.32); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18 V/m; Power Drift = 0.052 dB

Maximum value of SAR (measured) = 0.340 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18 V/m; Power Drift = 0.052 dB

Maximum value of SAR (measured) = 0.344 mW/g

Peak SAR (extrapolated) = 0.439 W/kg

SAR(1 g) = 0.324 mW/g; SAR(10 g) = 0.228 mW/g




Fig. 51: SAR distribution for GSM 850, channel 190, body worn configuration, antenna towards the phantom, Standard cover with headset (29.07.2004; Ambient Temperature: 21.2° C; Liquid Temperature : 20.3° C).

6 SAR Distribution Plots, PCS 850 Body with data cable

Test Laboratory: IMST GmbH; File Name: [butghm_1.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Body Worn

Communication System: GPRS 850; Frequency: 836.6 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 0.99$; mho/m, $\epsilon_r = 54.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.32, 6.32, 6.32); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 21.4 V/m; Power Drift = 0.029 dB

Maximum value of SAR (measured) = 0.455 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.4 V/m; Power Drift = 0.029 dB

Maximum value of SAR (measured) = 0.478 mW/g

Peak SAR (extrapolated) = 0.600 W/kg

SAR(1 g) = 0.446 mW/g; SAR(10 g) = 0.314 mW/g




Fig. 52: SAR distribution for GSM 850, channel 190, body worn configuration, antenna towards the phantom, Butterfly cover with data cable, 2TX (22.06.2004; Ambient Temperature: 21.5° C; Liquid Temperature : 20.5° C).

Test Laboratory: IMST GmbH; File Name: [arcghm_1.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Body Worn

Communication System: GPRS 850; Frequency: 836.6 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 0.99$; mho/m, $\epsilon_r = 54.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.32, 6.32, 6.32); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 21.1 V/m; Power Drift = -0.059 dB

Maximum value of SAR (measured) = 0.432 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.1 V/m; Power Drift = -0.059 dB

Maximum value of SAR (measured) = 0.443 mW/g

Peak SAR (extrapolated) = 0.546 W/kg

SAR(1 g) = 0.418 mW/g; SAR(10 g) = 0.296 mW/g




Fig. 53: SAR distribution for GSM 850, channel 190, body worn configuration, antenna towards the phantom, ARC cover with data cable, 2 TX (22.06.2004; Ambient Temperature: 21.5° C; Liquid Temperature : 20.5° C).

Test Laboratory: IMST GmbH; File Name: [stdghm_1.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Body Worn

Communication System: GPRS 850; Frequency: 836.6 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 1.01$; mho/m, $\epsilon_r = 53.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(6.32, 6.32, 6.32); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Sugar; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 20.9 V/m; Power Drift = -0.114 dB

Maximum value of SAR (measured) = 0.443 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.9 V/m; Power Drift = -0.114 dB

Maximum value of SAR (measured) = 0.453 mW/g

Peak SAR (extrapolated) = 0.567 W/kg

SAR(1 g) = 0.427 mW/g; SAR(10 g) = 0.301 mW/g




Fig. 54: SAR distribution for GSM 850, channel 190, body worn configuration, antenna towards the phantom, Standard cover with data cable, 2 TX (29.07.2004; Ambient Temperature: 21.2° C; Liquid Temperature : 20.3° C).

7 SAR Distribution Plots, PCS 1900 Body with headset

Test Laboratory: IMST GmbH; File Name: [Butphm_2.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 1.52$; mho/m, $\epsilon_r = 52.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.54, 4.54, 4.54); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 7.55 V/m; Power Drift = 0.116 dB

Maximum value of SAR (measured) = 0.343 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.55 V/m; Power Drift = 0.116 dB

Maximum value of SAR (measured) = 0.376 mW/g

Peak SAR (extrapolated) = 0.550 W/kg

SAR(1 g) = 0.343 mW/g; SAR(10 g) = 0.205 mW/g




Fig. 55: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, Butterfly cover with headset (21.06.2004; Ambient Temperature: 21.7° C; Liquid Temperature : 20.7° C).

Test Laboratory: IMST GmbH; File Name: [ARCphm_2.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 1.52$; mho/m, $\epsilon_r = 52.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.54, 4.54, 4.54); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 7.19 V/m; Power Drift = -0.045 dB

Maximum value of SAR (measured) = 0.288 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.19 V/m; Power Drift = -0.045 dB

Maximum value of SAR (measured) = 0.312 mW/g

Peak SAR (extrapolated) = 0.471 W/kg

SAR(1 g) = 0.288 mW/g; SAR(10 g) = 0.175 mW/g




Fig. 56: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, ARC cover with headset (21.06.2004; Ambient Temperature: 21.7°C; Liquid Temperature : 20.7°C).

Test Laboratory: IMST GmbH; File Name: [stdphm_2.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 1.54$; mho/m, $\epsilon_r = 52.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(4.45, 4.45, 4.45); Calibrated: 21.05.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 7.52 V/m; Power Drift = 0.069 dB

Maximum value of SAR (measured) = 0.281 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.52 V/m; Power Drift = 0.069 dB

Maximum value of SAR (measured) = 0.326 mW/g

Peak SAR (extrapolated) = 0.478 W/kg

SAR(1 g) = 0.302 mW/g; SAR(10 g) = 0.182 mW/g




Fig. 57: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, Standard cover with headset (27.07.2004; Ambient Temperature: 21.8°C; Liquid Temperature : 20.7°C).

8 SAR Distribution Plots, PCS 1900 Body with data cable

Test Laboratory: IMST GmbH; File Name: [Butphm_1.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 1.52$; mho/m, $\epsilon_r = 52.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.54, 4.54, 4.54); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 11.8 V/m; Power Drift = 0.016 dB

Maximum value of SAR (measured) = 0.620 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.8 V/m; Power Drift = 0.016 dB

Maximum value of SAR (measured) = 0.688 mW/g

Peak SAR (extrapolated) = 1.01 W/kg

SAR(1 g) = 0.629 mW/g; SAR(10 g) = 0.377 mW/g




Fig. 58: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, Butterfly cover with data cable, 2 TX (21.06.2004; Ambient Temperature: 21.7°C; Liquid Temperature : 20.7° C).

Test Laboratory: IMST GmbH; File Name: [arcphm_1.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 1.52$; mho/m, $\epsilon_r = 52.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.54, 4.54, 4.54); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 29.04.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 11.7 V/m; Power Drift = -0.005 dB

Maximum value of SAR (measured) = 0.617 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.7 V/m; Power Drift = -0.005 dB

Maximum value of SAR (measured) = 0.709 mW/g

Peak SAR (extrapolated) = 1.04 W/kg

SAR(1 g) = 0.652 mW/g; SAR(10 g) = 0.390 mW/g




Fig. 59: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, ARC cover with data cable, 2 TX (21.06.2004; Ambient Temperature: 21.7° C; Liquid Temperature : 20.7° C).

Test Laboratory: IMST GmbH; File Name: [stdphm_1.da4](#)

DUT: Siemens; Type: C66; Serial: 004400005236870

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 1.54$; mho/m, $\epsilon_r = 52.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(4.45, 4.45, 4.45); Calibrated: 21.05.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 11.6 V/m; Power Drift = 0.049 dB

Maximum value of SAR (measured) = 0.618 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.6 V/m; Power Drift = 0.049 dB

Maximum value of SAR (measured) = 0.711 mW/g

Peak SAR (extrapolated) = 1.05 W/kg

SAR(1 g) = 0.651 mW/g; SAR(10 g) = 0.388 mW/g




Fig. 60: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, Standard cover with data cable, 2 TX (27.07.2004; Ambient Temperature: 21.8° C; Liquid Temperature : 20.7° C).

9 SAR z-axis scans (Validation)




Fig. 61: SAR versus liquid depth, 835 MHz, head ARC, Butterfly (16.06.2004; Ambient Temperature: 22.0° C; Liquid Temperature : 21.0° C).




Fig. 62: SAR versus liquid depth, 835 MHz, body ARC, Butterfly (22.06.2004; Ambient Temperature: 21.5° C; Liquid Temperature : 20.5° C).




Fig. 63: SAR versus liquid depth, 1900 MHz, head ARC Butterfly (18.06.2004; Ambient Temperature: 21.5° C; Liquid Temperature : 20.4° C).




Fig. 64: SAR versus liquid depth, 1900 MHz, body, ARC, Butterfly(21.06.2004; Ambient Temperature: 21.4° C; Liquid Temperature : 20.7° C).




Fig. 65: SAR versus liquid depth, 835 MHz, head, Standard (27.07.2004; Ambient Temperature: 21.0° C; Liquid Temperature : 20.4° C).




Fig. 66: SAR versus liquid depth, 835 MHz, body, Standard (29.07.2004; Ambient Temperature: 22.2° C; Liquid Temperature : 21.0° C).




Fig. 67: SAR versus liquid depth, 1900 MHz, head, Standard (23.07.2004; Ambient Temperature: 21.0° C; Liquid Temperature : 20.5° C).




Fig. 68: SAR versus liquid depth, 1900 MHz, body, Standard (27.07.2004; Ambient Temperature: 21.7° C; Liquid Temperature : 20.7° C).

10 SAR z-axis scans (Measurements)

The following pictures show the plots of SAR versus liquid depth for the worst case values.




Fig. 69: SAR versus liquid depth, head: with flash, GSM 850, channel 190, cheek position, left side of head with Butterfly cover. (16.06.2004, Ambient Temperature: 21.8° C; Liquid Temperature : 20.3° C).




Fig. 70: SAR versus liquid depth, head: without flash, PCS 1900, channel 661, tilted position, left side of head with Standard cover. (23.07.2004, Ambient Temperature: 21.1° C; Liquid Temperature : 20.1° C).




Fig. 71: SAR versus liquid depth: GSM 850 body, channel 190, body worn configuration, antenna towards the phantom, data cable, 2 TX with Butterfly cover (22.06.2004, Ambient Temperature: 21.5° C; Liquid Temperature : 20.5° C).




Fig. 72: SAR versus liquid depth: PCS 1900 body, channel 661, body worn configuration, antenna towards the phantom, data cable, 2 TX with ARC cover (21.06.2004, Ambient Temperature: 21.7° C; Liquid Temperature : 20.7° C).