
Appendix for the Report

Dosimetric Assessment of the Siemens CX70 (FCC ID: PWX-CX70) According to the FCC Requirements

SAR Distribution Plots

August 16, 2004
IMST GmbH
Carl-Friedrich-Gauß-Str. 2
D-47475 Kamp-Lintfort

Customer
Siemens Information & Communication Mobile LLC
16475 West Bernado Drive, Suite 400
San Diego CA 92127

The test results only relate to the items tested.
This report shall not be reproduced except in full without the written
approval of the testing laboratory.

Table of Contents

1	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD WITHOUT FLASH.....	3
2	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD WITH FLASH	19
3	SAR DISTRIBUTION PLOTS, PCS 1900 BODY WITH HEADSET (GAP = 22 MM).....	35
4	SAR DISTRIBUTION PLOTS, PCS 1900 BODY WITH DATA CABLE (GAP = 22 MM).....	39
5	SAR DISTRIBUTION PLOTS, PCS 1900 BODY PTT MODE (GAP = 25 MM).....	43
6	SAR Z-AXIS SCANS (VALIDATION)	47
7	SAR Z-AXIS SCANS (MEASUREMENTS)	50

1 SAR Distribution Plots, PCS 1900 Head without Flash

Test Laboratory: IMST GmbH; File Name: [stdplm_1.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18.8 V/m; Power Drift = -0.117 dB

Maximum value of SAR (measured) = 0.595 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.8 V/m; Power Drift = -0.117 dB

Maximum value of SAR (measured) = 0.631 mW/g

Peak SAR (extrapolated) = 0.943 W/kg

SAR(1 g) = 0.586 mW/g; SAR(10 g) = 0.340 mW/g




Fig. 1: SAR distribution for PCS 1900, channel 661, cheek position, left side of head, Standard. (11.08.2004; Ambient Temperature: 22.7° C; Liquid Temperature: 21.4° C).

Test Laboratory: IMST GmbH; File Name: [stdplm_2.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Reference Value = 21.5 V/m; Power Drift = 0.007 dB

Maximum value of SAR (measured) = 0.630 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 21.5 V/m; Power Drift = 0.007 dB

Maximum value of SAR (measured) = 0.703 mW/g

Peak SAR (extrapolated) = 1.02 W/kg

SAR(1 g) = 0.627 mW/g; SAR(10 g) = 0.357 mW/g




Fig. 2: SAR distribution for PCS 1900, channel 661, tilted position, left side of head, Standard. (11.08.2004; Ambient Temperature: 22.7° C; Liquid Temperature : 21.4° C).

Test Laboratory: IMST GmbH; File Name: [stdprm_1.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 20.2 V/m; Power Drift = -0.032 dB

Maximum value of SAR (measured) = 0.492 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.2 V/m; Power Drift = -0.032 dB

Maximum value of SAR (measured) = 0.525 mW/g

Peak SAR (extrapolated) = 0.700 W/kg

SAR(1 g) = 0.481 mW/g; SAR(10 g) = 0.294 mW/g




Fig. 3: SAR distribution for PCS 1900, channel 661, cheek position, right side of head, Standard. (11.08.2004; Ambient Temperature: 22.7° C; Liquid Temperature : 21.5° C).

Test Laboratory: IMST GmbH; File Name: [stdprm_2.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 21.9 V/m; Power Drift = 0.014 dB

Maximum value of SAR (measured) = 0.475 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.9 V/m; Power Drift = 0.014 dB

Maximum value of SAR (measured) = 0.622 mW/g

Peak SAR (extrapolated) = 0.877 W/kg

SAR(1 g) = 0.561 mW/g; SAR(10 g) = 0.325 mW/g




Fig. 4: SAR distribution for PCS 1900, channel 661, tilted position, right side of head, Standard. (11.08.2004; Ambient Temperature: 22.7° C; Liquid Temperature : 21.5° C).

Test Laboratory: IMST GmbH; File Name: [bfplm_1.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18.6 V/m; Power Drift = -0.091 dB

Maximum value of SAR (measured) = 0.587 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.6 V/m; Power Drift = -0.091 dB

Maximum value of SAR (measured) = 0.650 mW/g

Peak SAR (extrapolated) = 0.959 W/kg

SAR(1 g) = 0.587 mW/g; SAR(10 g) = 0.335 mW/g




Fig. 5: SAR distribution for PCS 1900, channel 661, cheek position, left side of head, BF. (11.08.2004; Ambient Temperature: 22.4° C; Liquid Temperature: 21.2° C).

Test Laboratory: IMST GmbH; File Name: [bfplm_2.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 21.6 V/m; Power Drift = -0.051 dB

Maximum value of SAR (measured) = 0.632 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.6 V/m; Power Drift = -0.051 dB

Maximum value of SAR (measured) = 0.722 mW/g

Peak SAR (extrapolated) = 1.06 W/kg

SAR(1 g) = 0.649 mW/g; SAR(10 g) = 0.366 mW/g




Fig. 6: SAR distribution for PCS 1900, channel 661, tilted position, left side of head, BF. (11.08.2004; Ambient Temperature: 22.4° C; Liquid Temperature : 21.2° C).

Test Laboratory: IMST GmbH; File Name: [bfprm_1.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 20.1 V/m; Power Drift = 0.042 dB

Maximum value of SAR (measured) = 0.469 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.1 V/m; Power Drift = 0.042 dB

Maximum value of SAR (measured) = 0.516 mW/g

Peak SAR (extrapolated) = 0.729 W/kg

SAR(1 g) = 0.476 mW/g; SAR(10 g) = 0.285 mW/g




Fig. 7: SAR distribution for PCS 1900, channel 661, cheek position, right side of head, BF. (11.08.2004; Ambient Temperature: 22.4° C; Liquid Temperature : 21.2° C).

Test Laboratory: IMST GmbH; File Name: [bfprm_2.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 23.6 V/m; Power Drift = -0.020 dB

Maximum value of SAR (measured) = 0.475 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23.6 V/m; Power Drift = -0.020 dB

Maximum value of SAR (measured) = 0.610 mW/g

Peak SAR (extrapolated) = 0.857 W/kg

SAR(1 g) = 0.547 mW/g; SAR(10 g) = 0.313 mW/g




Fig. 8: SAR distribution for PCS 1900, channel 661, tilted position, right side of head, BF. (11.08.2004; Ambient Temperature: 22.4° C; Liquid Temperature : 21.2° C).

Test Laboratory: IMST GmbH; File Name: [butplm_1.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Reference Value = 16.8 V/m; Power Drift = -0.063 dB

Maximum value of SAR (measured) = 0.644 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 16.8 V/m; Power Drift = -0.063 dB

Maximum value of SAR (measured) = 0.721 mW/g

Peak SAR (extrapolated) = 1.1 W/kg

SAR(1 g) = 0.653 mW/g; SAR(10 g) = 0.369 mW/g




Fig. 9: SAR distribution for PCS 1900, channel 661, cheek position, left side of head, Butterfly. (11.08.2004; Ambient Temperature: 22.6° C; Liquid Temperature: 21.3° C).

Test Laboratory: IMST GmbH; File Name: [butplm_2.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19.8 V/m; Power Drift = -0.009 dB

Maximum value of SAR (measured) = 0.609 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.8 V/m; Power Drift = -0.009 dB

Maximum value of SAR (measured) = 0.722 mW/g

Peak SAR (extrapolated) = 1.05 W/kg

SAR(1 g) = 0.650 mW/g; SAR(10 g) = 0.366 mW/g




Fig. 10: SAR distribution for PCS 1900, channel 661, tilted position, left side of head, Butterfly. (11.08.2004; Ambient Temperature: 22.6° C; Liquid Temperature : 21.3° C)

. Test Laboratory: IMST GmbH; File Name: [butprm_1.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19.4 V/m; Power Drift = 0.053 dB

Maximum value of SAR (measured) = 0.461 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.4 V/m; Power Drift = 0.053 dB

Maximum value of SAR (measured) = 0.487 mW/g

Peak SAR (extrapolated) = 0.691 W/kg

SAR(1 g) = 0.450 mW/g; SAR(10 g) = 0.269 mW/g




Fig. 11: SAR distribution for PCS 1900, channel 661, cheek position, right side of head, Butterfly. (11.08.2004; Ambient Temperature: 22.6° C; Liquid Temperature : 21.3° C).

Test Laboratory: IMST GmbH; File Name: [butprm_2.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 20.7 V/m; Power Drift = -0.024 dB

Maximum value of SAR (measured) = 0.487 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.7 V/m; Power Drift = -0.024 dB

Maximum value of SAR (measured) = 0.577 mW/g

Peak SAR (extrapolated) = 0.807 W/kg

SAR(1 g) = 0.522 mW/g; SAR(10 g) = 0.302 mW/g




Fig. 12: SAR distribution for PCS 1900, channel 661, tilted position, right side of head, Butterfly. (11.08.2004; Ambient Temperature: 22.6° C; Liquid Temperature : 21.3° C).

Test Laboratory: IMST GmbH; File Name: [arcplm_1.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Reference Value = 18.8 V/m; Power Drift = 0.002 dB

Maximum value of SAR (measured) = 0.619 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 18.8 V/m; Power Drift = 0.002 dB

Maximum value of SAR (measured) = 0.666 mW/g

Peak SAR (extrapolated) = 1.02 W/kg

SAR(1 g) = 0.616 mW/g; SAR(10 g) = 0.352 mW/g




Fig. 13: SAR distribution for PCS 1900, channel 661, cheek position, left side of head, ARC. (11.08.2004; Ambient Temperature: 22.4° C; Liquid Temperature: 21.1° C).

Test Laboratory: IMST GmbH; File Name: [arcplm_2.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.45 \text{ mho/m}$; $\epsilon_r = 39.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Reference Value = 21.8 V/m ; Power Drift = -0.132 dB

Maximum value of SAR (measured) = 0.637 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.8 V/m ; Power Drift = -0.132 dB

Maximum value of SAR (measured) = 0.709 mW/g

Peak SAR (extrapolated) = 1.02 W/kg

SAR(1 g) = 0.635 mW/g ; SAR(10 g) = 0.362 mW/g




Fig. 14: SAR distribution for PCS 1900, channel 661, tilted position, left side of head, ARC. (11.08.2004; Ambient Temperature: 22.4° C ; Liquid Temperature: 21.1° C).

Test Laboratory: IMST GmbH; File Name: [arcprm_1.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 20.5 V/m; Power Drift = -0.0002 dB

Maximum value of SAR (measured) = 0.484 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.5 V/m; Power Drift = -0.0002 dB

Maximum value of SAR (measured) = 0.533 mW/g

Peak SAR (extrapolated) = 0.751 W/kg

SAR(1 g) = 0.494 mW/g; SAR(10 g) = 0.299 mW/g




Fig. 15: SAR distribution for PCS 1900, channel 661, cheek position, right side of head, ARC. (11.08.2004; Ambient Temperature: 22.4° C; Liquid Temperature: 21.1° C).

Test Laboratory: IMST GmbH; File Name: [arcprm_2.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 21.9 V/m; Power Drift = 0.0005 dB

Maximum value of SAR (measured) = 0.484 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.9 V/m; Power Drift = 0.0005 dB

Maximum value of SAR (measured) = 0.622 mW/g

Peak SAR (extrapolated) = 0.867 W/kg

SAR(1 g) = 0.561 mW/g; SAR(10 g) = 0.324 mW/g




Fig. 16: SAR distribution for PCS 1900, channel 661, tilted position, right side of head, ARC. (11.08.2004; Ambient Temperature: 22.4° C; Liquid Temperature: 21.1° C).

2 SAR Distribution Plots, PCS 1900 Head with Flash

Test Laboratory: IMST GmbH; File Name: [stdplm_1_flash.da4](#)

DUT: Siemens; Type: CX 70 + Flash; Serial: 004999003279147

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18.4 V/m; Power Drift = -0.149 dB

Maximum value of SAR (measured) = 0.541 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.4 V/m; Power Drift = -0.149 dB

Maximum value of SAR (measured) = 0.557 mW/g

Peak SAR (extrapolated) = 0.799 W/kg

SAR(1 g) = 0.508 mW/g; SAR(10 g) = 0.299 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.4 V/m; Power Drift = -0.149 dB

Maximum value of SAR (measured) = 0.386 mW/g

Peak SAR (extrapolated) = 0.516 W/kg

SAR(1 g) = 0.357 mW/g; SAR(10 g) = 0.231 mW/g




Fig. 17: SAR distribution for PCS 1900, channel 661, cheek position, left side of head, Standard. (12.08.2004; Ambient Temperature: 22.6° C; Liquid Temperature : 21.3° C).

Test Laboratory: IMST GmbH; File Name: [stdplm_2_flash.da4](#)

DUT: Siemens; Type: CX 70 + Flash; Serial: 004999003279147

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19 V/m; Power Drift = -0.024 dB

Maximum value of SAR (measured) = 0.555 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19 V/m; Power Drift = -0.024 dB

Maximum value of SAR (measured) = 0.581 mW/g

Peak SAR (extrapolated) = 0.851 W/kg

SAR(1 g) = 0.522 mW/g; SAR(10 g) = 0.299 mW/g




Fig. 18: SAR distribution for PCS 1900, channel 661, tilted position, left side of head, Standard. (12.08.2004; Ambient Temperature: 22.6° C; Liquid Temperature : 21.3° C).

Test Laboratory: IMST GmbH; File Name: [stdprm_1_flash.da4](#)

DUT: Siemens; Type: CX 70 + Flash; Serial: 004999003279147

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 20.2 V/m; Power Drift = 0.032 dB

Maximum value of SAR (measured) = 0.477 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.2 V/m; Power Drift = 0.032 dB

Maximum value of SAR (measured) = 0.512 mW/g

Peak SAR (extrapolated) = 0.708 W/kg

SAR(1 g) = 0.469 mW/g; SAR(10 g) = 0.289 mW/g




Fig. 19: SAR distribution for PCS 1900, channel 661, cheek position, right side of head, Standard. (12.08.2004; Ambient Temperature: 22.6° C; Liquid Temperature : 21.3° C).

Test Laboratory: IMST GmbH; File Name: [stdprm_2_flash.da4](#)

DUT: Siemens; Type: CX 70 + Flash; Serial: 004999003279147

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 20.2 V/m; Power Drift = -0.087 dB

Maximum value of SAR (measured) = 0.480 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.2 V/m; Power Drift = -0.087 dB

Maximum value of SAR (measured) = 0.533 mW/g

Peak SAR (extrapolated) = 0.757 W/kg

SAR(1 g) = 0.485 mW/g; SAR(10 g) = 0.281 mW/g




Fig. 20: SAR distribution for PCS 1900, channel 661, tilted position, right side of head, Standard. (12.08.2004; Ambient Temperature: 22.6 °C; Liquid Temperature : 21.3° C).

Test Laboratory: IMST GmbH; File Name: [bfplm_1_flash.da4](#)

DUT: Siemens; Type: CX 70 + Flash; Serial: 004999003279147

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 15.5 V/m; Power Drift = -0.044 dB

Maximum value of SAR (measured) = 0.474 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 15.5 V/m; Power Drift = -0.044 dB

Maximum value of SAR (measured) = 0.532 mW/g

Peak SAR (extrapolated) = 0.804 W/kg

SAR(1 g) = 0.491 mW/g; SAR(10 g) = 0.283 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 15.5 V/m; Power Drift = -0.044 dB

Maximum value of SAR (measured) = 0.399 mW/g

Peak SAR (extrapolated) = 0.500 W/kg

SAR(1 g) = 0.374 mW/g; SAR(10 g) = 0.239 mW/g




Fig. 21: SAR distribution for PCS 1900, channel 661, cheek position, left side of head, BF. (12.08.2004; Ambient Temperature: 22.9° C; Liquid Temperature : 21.5° C).

Test Laboratory: IMST GmbH; File Name: [bfplm_2_flash.da4](#)

DUT: Siemens; Type: CX 70 + Flash; Serial: 004999003279147

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 17.8 V/m; Power Drift = -0.011 dB

Maximum value of SAR (measured) = 0.547 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.8 V/m; Power Drift = -0.011 dB

Maximum value of SAR (measured) = 0.611 mW/g

Peak SAR (extrapolated) = 0.913 W/kg

SAR(1 g) = 0.558 mW/g; SAR(10 g) = 0.317 mW/g




Fig. 22: SAR distribution for PCS 1900, channel 661, tilted position, left side of head BF. (12.08.2004; Ambient Temperature: 22.9° C; Liquid Temperature : 21.5° C).

Test Laboratory: IMST GmbH; File Name: [bfprm_1_flash.da4](#)

DUT: Siemens; Type: CX 70 + Flash; Serial: 004999003279147

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18.8 V/m; Power Drift = -0.013 dB

Maximum value of SAR (measured) = 0.440 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.8 V/m; Power Drift = -0.013 dB

Maximum value of SAR (measured) = 0.474 mW/g

Peak SAR (extrapolated) = 0.654 W/kg

SAR(1 g) = 0.435 mW/g; SAR(10 g) = 0.269 mW/g




Fig. 23: SAR distribution for PCS 1900, channel 661, cheek position, right side of head BF. (12.08.2004; Ambient Temperature: 22.9° C; Liquid Temperature : 21.5° C).

Test Laboratory: IMST GmbH; File Name: [bfprm_2_flash.da4](#)

DUT: Siemens; Type: CX 70 + Flash; Serial: 004999003279147

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19.9 V/m; Power Drift = 0.020 dB

Maximum value of SAR (measured) = 0.493 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.9 V/m; Power Drift = 0.020 dB

Maximum value of SAR (measured) = 0.505 mW/g

Peak SAR (extrapolated) = 0.726 W/kg

SAR(1 g) = 0.462 mW/g; SAR(10 g) = 0.270 mW/g




Fig. 24: SAR distribution for PCS 1900, channel 661, tilted position, right side of head BF. (11.08.2004; Ambient Temperature: 22.9° C; Liquid Temperature : 21.5° C).

Test Laboratory: IMST GmbH; File Name: [butplm_1_flash.da4](#)

DUT: Siemens; Type: CX 70 + Flash; Serial: 004999003279147

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 16 V/m; Power Drift = -0.049 dB

Maximum value of SAR (measured) = 0.509 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16 V/m; Power Drift = -0.049 dB

Maximum value of SAR (measured) = 0.593 mW/g

Peak SAR (extrapolated) = 0.892 W/kg

SAR(1 g) = 0.535 mW/g; SAR(10 g) = 0.306 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16 V/m; Power Drift = -0.049 dB

Maximum value of SAR (measured) = 0.388 mW/g

Peak SAR (extrapolated) = 0.475 W/kg

SAR(1 g) = 0.361 mW/g; SAR(10 g) = 0.233 mW/g




Fig. 25: SAR distribution for PCS 1900, channel 661, cheek position, left side of head Butterfly. (12.08.2004; Ambient Temperature: 23.0° C; Liquid Temperature : 21.5° C).

Test Laboratory: IMST GmbH; File Name: [butplm_2_flash.da4](#)

DUT: Siemens; Type: CX 70 + Flash; Serial: 004999003279147

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 17.7 V/m; Power Drift = 0.0058 dB

Maximum value of SAR (measured) = 0.538 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.7 V/m; Power Drift = 0.0058 dB

Maximum value of SAR (measured) = 0.596 mW/g

Peak SAR (extrapolated) = 0.869 W/kg

SAR(1 g) = 0.544 mW/g; SAR(10 g) = 0.312 mW/g




Fig. 26: SAR distribution for PCS 1900, channel 661, tilted position, left side of head Butterfly. (12.08.2004; Ambient Temperature: 23.0° C; Liquid Temperature : 21.5° C).

Test Laboratory: IMST GmbH; File Name: [butprm_1_flash.da4](#)

DUT: Siemens; Type: CX 70 + Flash; Serial: 004999003279147

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19.1 V/m; Power Drift = -0.1 dB

Maximum value of SAR (measured) = 0.451 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.1 V/m; Power Drift = -0.1 dB

Maximum value of SAR (measured) = 0.489 mW/g

Peak SAR (extrapolated) = 0.680 W/kg

SAR(1 g) = 0.449 mW/g; SAR(10 g) = 0.273 mW/g




Fig. 27: SAR distribution for PCS 1900, channel 661, cheek position, right side of head Butterfly. (12.08.2004; Ambient Temperature: 23.0° C; Liquid Temperature : 21.5° C).

Test Laboratory: IMST GmbH; File Name: [butprm_2_flash.da4](#)

DUT: Siemens; Type: CX 70 + Flash; Serial: 004999003279147

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19.2 V/m; Power Drift = -0.0338 dB

Maximum value of SAR (measured) = 0.449 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.2 V/m; Power Drift = -0.0338 dB

Maximum value of SAR (measured) = 0.466 mW/g

Peak SAR (extrapolated) = 0.663 W/kg

SAR(1 g) = 0.426 mW/g; SAR(10 g) = 0.251 mW/g




Fig. 28: SAR distribution for PCS 1900, channel 661, tilted position, right side of head Butterfly. (12.08.2004; Ambient Temperature: 23.0° C; Liquid Temperature :21.5° C).

Test Laboratory: IMST GmbH; File Name: [ARCplm_1_flash.da4](#)

DUT: Siemens; Type: CX 70 + Flash; Serial: 004999003279147

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 17.5 V/m; Power Drift = 0.0427 dB

Maximum value of SAR (measured) = 0.508 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.5 V/m; Power Drift = 0.0427 dB

Maximum value of SAR (measured) = 0.567 mW/g

Peak SAR (extrapolated) = 0.835 W/kg

SAR(1 g) = 0.514 mW/g; SAR(10 g) = 0.298 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.5 V/m; Power Drift = 0.0427 dB

Maximum value of SAR (measured) = 0.433 mW/g

Peak SAR (extrapolated) = 0.552 W/kg

SAR(1 g) = 0.404 mW/g; SAR(10 g) = 0.260 mW/g




Fig. 29: SAR distribution for PCS 1900, channel 661, cheek position, left side of head ARC. (12.08.2004; Ambient Temperature: 23.0° C; Liquid Temperature : 21.6° C).

Test Laboratory: IMST GmbH; File Name: [ARCP1m_2_flash.da4](#)

DUT: Siemens; Type: CX 70 + Flash; Serial: 004999003279147

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19.4 V/m; Power Drift = 0.0236 dB

Maximum value of SAR (measured) = 0.582 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.4 V/m; Power Drift = 0.0236 dB

Maximum value of SAR (measured) = 0.593 mW/g

Peak SAR (extrapolated) = 0.891 W/kg

SAR(1 g) = 0.543 mW/g; SAR(10 g) = 0.311 mW/g




Fig. 30: SAR distribution for PCS 1900, channel 661, tilted position, left side of head ARC. (12.08.2004; Ambient Temperature: 23.0° C; Liquid Temperature : 21.6° C).

Test Laboratory: IMST GmbH; File Name: [ARCprm_1_flash.da4](#)

DUT: Siemens; Type: CX 70 + Flash; Serial: 004999003279147

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19.7 V/m; Power Drift = -0.0542 dB

Maximum value of SAR (measured) = 0.484 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.7 V/m; Power Drift = -0.0542 dB

Maximum value of SAR (measured) = 0.499 mW/g

Peak SAR (extrapolated) = 0.706 W/kg

SAR(1 g) = 0.460 mW/g; SAR(10 g) = 0.282 mW/g




Fig. 31: SAR distribution for PCS 1900, channel 661, cheek position, right side of head ARC. (12.08.2004; Ambient Temperature: 23.0° C; Liquid Temperature : 21.6° C).

Test Laboratory: IMST GmbH; File Name: [ARCprm_2_flash.da4](#)

DUT: Siemens; Type: CX 70 + Flash; Serial: 004999003279147

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.19, 5.19, 5.19); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19.5 V/m; Power Drift = -0.0361 dB

Maximum value of SAR (measured) = 0.476 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.5 V/m; Power Drift = -0.0361 dB

Maximum value of SAR (measured) = 0.494 mW/g

Peak SAR (extrapolated) = 0.695 W/kg

SAR(1 g) = 0.450 mW/g; SAR(10 g) = 0.263 mW/g




Fig. 32: SAR distribution for PCS 1900, channel 661, tilted position, right side of head ARC. (12.08.2004; Ambient Temperature: 23.0° C; Liquid Temperature : 21.6° C).

3 SAR Distribution Plots, PCS 1900 Body with headset (gap = 22 mm)

Test Laboratory: IMST GmbH; File Name: [stdphm_2.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 1.56$; mho/m, $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.54, 4.54, 4.54); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 6.18 V/m; Power Drift = 0.070 dB

Maximum value of SAR (measured) = 0.316 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.18 V/m; Power Drift = 0.070 dB

Maximum value of SAR (measured) = 0.372 mW/g

Peak SAR (extrapolated) = 0.532 W/kg

SAR(1 g) = 0.340 mW/g; SAR(10 g) = 0.204 mW/g




Fig. 33: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, Standard cover with headset (06.08.2004; Ambient Temperature: 22.9° C; Liquid Temperature : 21.5° C).

Test Laboratory: IMST GmbH; File Name: [bfphm_2.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 1.56$; mho/m, $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.54, 4.54, 4.54); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 6.26 V/m; Power Drift = 0.138 dB

Maximum value of SAR (measured) = 0.358 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.26 V/m; Power Drift = 0.138 dB

Maximum value of SAR (measured) = 0.374 mW/g

Peak SAR (extrapolated) = 0.529 W/kg

SAR(1 g) = 0.341 mW/g; SAR(10 g) = 0.204 mW/g




Fig. 34: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, BF cover with headset (06.08.2004; Ambient Temperature: 22.6° C; Liquid Temperature : 21.1° C).

Test Laboratory: IMST GmbH; File Name: [butphm_2.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 1.56$; mho/m, $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.54, 4.54, 4.54); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 7.18 V/m; Power Drift = 0.083 dB

Maximum value of SAR (measured) = 0.396 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.18 V/m; Power Drift = 0.083 dB

Maximum value of SAR (measured) = 0.423 mW/g

Peak SAR (extrapolated) = 0.610 W/kg

SAR(1 g) = 0.387 mW/g; SAR(10 g) = 0.230 mW/g




Fig. 35: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, Butterfly cover with headset (06.08.2004; Ambient Temperature: 22.8° C; Liquid Temperature : 21.3° C).

Test Laboratory: IMST GmbH; File Name: [arcphm_2.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 1.56$; mho/m, $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.54, 4.54, 4.54); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 6.52 V/m; Power Drift = 0.064 dB

Maximum value of SAR (measured) = 0.380 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.52 V/m; Power Drift = 0.064 dB

Maximum value of SAR (measured) = 0.391 mW/g

Peak SAR (extrapolated) = 0.555 W/kg

SAR(1 g) = 0.358 mW/g; SAR(10 g) = 0.213 mW/g




Fig. 36: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, ARC cover with headset (06.08.2004; Ambient Temperature: 22.9° C; Liquid Temperature : 21.7° C).

4 SAR Distribution Plots, PCS 1900 Body with data cable (gap = 22 mm)

Test Laboratory: IMST GmbH; File Name: [stdphm_1.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 1.56$; mho/m, $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.54, 4.54, 4.54); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 9.82 V/m; Power Drift = -0.032 dB

Maximum value of SAR (measured) = 0.554 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.82 V/m; Power Drift = -0.032 dB

Maximum value of SAR (measured) = 0.662 mW/g

Peak SAR (extrapolated) = 0.953 W/kg

SAR(1 g) = 0.606 mW/g; SAR(10 g) = 0.361 mW/g




Fig. 37: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, Standard cover with data cable, 2 TX (06.08.2004; Ambient Temperature: 22.9° C; Liquid Temperature : 21.5° C).

Test Laboratory: IMST GmbH; File Name: [bfphm_1.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 1.56$; mho/m, $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.54, 4.54, 4.54); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 9.34 V/m; Power Drift = -0.005 dB

Maximum value of SAR (measured) = 0.743 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.34 V/m; Power Drift = -0.005 dB

Maximum value of SAR (measured) = 0.768 mW/g

Peak SAR (extrapolated) = 1.08 W/kg

SAR(1 g) = 0.695 mW/g; SAR(10 g) = 0.413 mW/g




Fig. 38: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, BF cover with data cable, 2 TX (06.08.2004; Ambient Temperature: 22.6° C; Liquid Temperature : 21.1 C).

Test Laboratory: IMST GmbH; File Name: [butphm_1.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 1.56$; mho/m, $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.54, 4.54, 4.54); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 9.55 V/m; Power Drift = 0.010 dB

Maximum value of SAR (measured) = 0.780 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.55 V/m; Power Drift = 0.010 dB

Maximum value of SAR (measured) = 0.793 mW/g

Peak SAR (extrapolated) = 1.13 W/kg

SAR(1 g) = 0.726 mW/g; SAR(10 g) = 0.431 mW/g




Fig. 39: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, Butterfly cover with data cable, 2 TX (06.08.2004; Ambient Temperature: 22.8° C; Liquid Temperature : 21.3° C).

Test Laboratory: IMST GmbH; File Name: [arcphm_1.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 1.56$; mho/m, $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.54, 4.54, 4.54); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 10.1 V/m; Power Drift = -0.069 dB

Maximum value of SAR (measured) = 0.773 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.1 V/m; Power Drift = -0.069 dB

Maximum value of SAR (measured) = 0.797 mW/g

Peak SAR (extrapolated) = 1.13 W/kg

SAR(1 g) = 0.725 mW/g; SAR(10 g) = 0.430 mW/g




Fig. 40: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, ARC cover with data cable, 2 TX (06.08.2004; Ambient Temperature: 22.9° C; Liquid Temperature : 21.7° C).

5 SAR Distribution Plots, PCS 1900 Body PTT mode (gap = 25 mm)

Test Laboratory: IMST GmbH; File Name: [stdphm_3.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 1.56$; mho/m, $\epsilon_r = 52.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.54, 4.54, 4.54); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 7.25 V/m; Power Drift = -0.1 dB

Maximum value of SAR (measured) = 0.150 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.25 V/m; Power Drift = -0.1 dB

Maximum value of SAR (measured) = 0.155 mW/g

Peak SAR (extrapolated) = 0.211 W/kg

SAR(1 g) = 0.145 mW/g; SAR(10 g) = 0.095 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.25 V/m; Power Drift = -0.1 dB

Maximum value of SAR (measured) = 0.111 mW/g

Peak SAR (extrapolated) = 0.148 W/kg

SAR(1 g) = 0.104 mW/g; SAR(10 g) = 0.069 mW/g




Fig. 41: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the ground, Standard cover in PTT mode, 2 TX (06.08.2004; Ambient Temperature: 22.9° C; Liquid Temperature : 21.5° C).

Test Laboratory: IMST GmbH; File Name: [bfphm_3.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 1.56$; mho/m, $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.54, 4.54, 4.54); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 7.51 V/m; Power Drift = 0.003 dB

Maximum value of SAR (measured) = 0.154 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.51 V/m; Power Drift = 0.003 dB

Maximum value of SAR (measured) = 0.161 mW/g

Peak SAR (extrapolated) = 0.230 W/kg

SAR(1 g) = 0.149 mW/g; SAR(10 g) = 0.098 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.51 V/m; Power Drift = 0.003 dB

Maximum value of SAR (measured) = 0.107 mW/g

Peak SAR (extrapolated) = 0.139 W/kg

SAR(1 g) = 0.099 mW/g; SAR(10 g) = 0.067 mW/g




Fig. 42: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, BF cover in PTT mode, 2 TX (06.08.2004; Ambient Temperature: 22.6° C; Liquid Temperature : 21.1 C).

Test Laboratory: IMST GmbH; File Name: [butphm_3.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 1.56$; mho/m, $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.54, 4.54, 4.54); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 7.83 V/m; Power Drift = -0.175 dB

Maximum value of SAR (measured) = 0.165 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.83 V/m; Power Drift = -0.175 dB

Maximum value of SAR (measured) = 0.168 mW/g

Peak SAR (extrapolated) = 0.225 W/kg

SAR(1 g) = 0.156 mW/g; SAR(10 g) = 0.103 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.83 V/m; Power Drift = -0.175 dB

Maximum value of SAR (measured) = 0.106 mW/g

Peak SAR (extrapolated) = 0.145 W/kg

SAR(1 g) = 0.099 mW/g; SAR(10 g) = 0.067 mW/g




Fig. 43: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the ground, Butterfly cover in PTT mode, 2 TX (06.08.2004; Ambient Temperature: 22.8° C; Liquid Temperature : 21.3° C).

Test Laboratory: IMST GmbH; File Name: [arcphm_3.da4](#)

DUT: Siemens; Type: CX 70; Serial: 004999003279147

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 1.56$; mho/m, $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.54, 4.54, 4.54); Calibrated: 18.03.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn906; Calibrated: 22.07.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 7.68 V/m; Power Drift = 0.053 dB

Maximum value of SAR (measured) = 0.166 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.68 V/m; Power Drift = 0.053 dB

Maximum value of SAR (measured) = 0.178 mW/g

Peak SAR (extrapolated) = 0.249 W/kg

SAR(1 g) = 0.165 mW/g; SAR(10 g) = 0.108 mW/g




Fig. 44: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the ground, ARC cover in PTT mode, 2 TX (06.08.2004; Ambient Temperature: 22.9° C; Liquid Temperature : 21.7° C).

6 SAR z-axis scans (Validation)




Fig. 45: SAR versus liquid depth, 1900 MHz, head (11.08.2004; Ambient Temperature: 22.2° C; Liquid Temperature : 21.0° C).




Fig. 46: SAR versus liquid depth, 1900 MHz, head (12.08.2004; Ambient Temperature: 22.0° C; Liquid Temperature : 21.0° C).




Fig. 47: SAR versus liquid depth, 1900 MHz, body (06.08.2004; Ambient Temperature: 22.8° C; Liquid Temperature : 21.4° C).

7 SAR z-axis scans (Measurements)

The following pictures show the plots of SAR versus liquid depth for the worst case values.




Fig. 48: SAR versus liquid depth, head: without flash, PCS 1900, channel 661, tilted position, left side of head with Butterfly cover. (11.08.2004, Ambient Temperature: 22.6° C; Liquid Temperature : 21.3° C).




Fig. 49: SAR versus liquid depth: PCS 1900 body, channel 661, body worn configuration, antenna towards the phantom, data cable, 2 TX with Butterfly cover (06.08.2004, Ambient Temperature: 22.8° C; Liquid Temperature : 21.3° C).