

FCC PART 15 SUBPART C MEASUREMENT AND TEST REPORT

For

ECORE TECHNOLOGY COMPANY LIMITED

North of Bingang East Road, Huahu Development Zone, Ezhou City, Hubei Province, China

E.U.T.: Party Block

Model Name: HL2536

Brand Name: 
bēm
WIRELESS

FCC ID: PXK-HL2536

Report Number: NTC1406755F-2

Test Date(s): May 30, 2014 to July 19, 2014

Report Date(s): July 19, 2014

Prepared by


Dongguan Nore Testing Center Co., Ltd.

Building D, Gaosheng Science & Technology Park, Zhouxi Longxi Road, Nancheng District, Dongguan, Guangdong, China.

Tel: +86-769-22022444

Fax: +86-769-22022799

Prepared By


Rose Hu / Engineer

Approved & Authorized Signer



Sunn Lv / Q.A. Director

Note: This test report is for the customer shown above and their specific product only. It may not be duplicated or used in part without prior written consent from Dongguan Nore Testing Center Co., Ltd. The test results referenced from this report are relevant only to the sample tested.

Table of Contents

1. GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST	3
1.2 RELATED SUBMITTAL(S) / GRANT (S)	6
1.3 TEST METHODOLOGY	6
1.4 EQUIPMENT MODIFICATIONS	6
1.5 SUPPORT DEVICE	6
1.6 TEST FACILITY AND LOCATION	6
1.7 SUMMARY OF TEST RESULTS	7
2. SYSTEM TEST CONFIGURATION	8
2.1 EUT CONFIGURATION	8
2.2 SPECIAL ACCESSORIES	8
2.3 DESCRIPTION OF TEST MODES	8
2.4 EUT EXERCISE	8
3. CONDUCTED EMISSIONS TEST	9
3.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	9
3.2 TEST CONDITION	9
3.3 MEASUREMENT RESULTS	9
4. RADIATED EMISSION TEST	12
4.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	12
4.2 MEASUREMENT PROCEDURE	13
4.3 LIMIT	14
4.4 MEASUREMENT RESULTS	15
5. 20DB BANDWIDTH	19
5.1 MEASUREMENT PROCEDURE	19
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	19
5.3 MEASUREMENT RESULTS	19
6. BAND EDGE	22
6.1 MEASUREMENT PROCEDURE	22
6.2 LIMIT	22
6.3 MEASUREMENT RESULTS	23
7. ANTENNA APPLICATION	24
7.1 ANTENNA REQUIREMENT	24
7.2 MEASUREMENT RESULTS	24
8. TEST EQUIPMENT LIST	25

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test

This device is a multi-function BT speaker with wireless audio transmission, AUX IN, charging and BT functions. It's powered by DC 5V/12V come from adapter or DC 3.7V/7.4V Li-ion Battery. For more details features, please refer to User's Manual.

Manufacturer : ECORE TECHNOLOGY COMPANY LIMITED

Address : North of Bingang East Road, Huahu Development Zone, Ezhou City, Hubei Province, China

Power Supply : **For host:**
DC 5V Come from Adapter
Adapter M/N: BI20-050240-AdU
Input: AC 100-240V 50/60Hz 0.5A
Output: DC 5V 2.4A
DC 3.7V 2000mAh;

For Speaker:
DC 12V Come from Adapter
Adapter M/N: BI30-120200-AdU
Input: AC 100-240V 50/60Hz 1.2A
Output: DC 12V 2.0A
DC 7.4V 4000mAh *2

Model name : HL2536

Note: : N/A

Technical Specification

For BT function

BT Version	: BLE and backward compatible 3.0HS, 2.1+EDR version. We prepare version BLE and 2.1+EDR for RF test.
Frequency:	: 2402-2480MHz
Modulation	: For V2.1+EDR: GFSK, $\pi/4$ -DQPSK, 8DPSK For V4.0: GFSK
Number of Channel	: For V2.1+EDR: 79; For V4.0: 40
Channel space	: For V2.1+EDR: 1MHz; For V4.0: 2MHz
Antenna Type	: PCB
Antenna Gain	: -0.61dBi (declaration by manufacturer)
Note	: N/A

For wireless audio transmission function

Frequency range	: 5730~5805MHz
Modulation Type	: GFSK
Number of channel	: 10
Antenna Type	: Integral
Antenna Gain	: 1.5dBi (declaration by manufacturer)
Note	: Speaker only for RX function.

For wireless audio transmission Channel list:

No.	Frequency (GHz)
1	5.730
2	5.735
3	5.745
4	5.761
5	5.763
6	5.765
7	5.775
8	5.801
9	5.803
10	5.805

1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: PXK-HL2536 filing to comply with Section 15.249 of the FCC Part 15 (2013), Subpart C Rule.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009). Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters.

1.4 Equipment Modifications

Not available for this EUT intended for grant.

1.5 Support Device

None

1.6 Test Facility and Location

Listed by FCC, August 02, 2011
The Certificate Registration Number is 665078.

Listed by Industry Canada, July 01, 2011
The Certificate Registration Number is 46405-9743.

Dongguan Nore Testing Center Co., Ltd.
Building D, Gaosheng Science & Technology Park,
Zhouxi Longxi Road, Nancheng District, Dongguan,
Guangdong, China.

1.7 Summary of Test Results

FCC Rules	Description Of Test	Result
§15.249(c)	20dB Bandwidth	Compliant
§15.249(d)	Band edge test	Compliant
§15.207 (a)	AC Power Conducted Emission	Compliant
§15.249(a)(d), §15.209, §15.205	Radiated Emission	Compliant
§15.203	Antenna Requirement	Compliant

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 Special Accessories

Not available for this EUT intended for grant.

2.3 Description of test modes


The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and normal mode is programmed. The Lowest, middle and highest channel were chosen for testing.

2.4 EUT Exercise

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

3. Conducted Emissions Test

3.1 Test SET-UP (Block Diagram of Configuration)



3.2 Test Condition

Test Requirement: FCC Part 15.207

Frequency Range: 150KHz ~ 30MHz

Detector: RBW 9KHz, VBW 30KHz

Operation Mode: TX Mode

3.3 Measurement Results


Please refer to following plots.



Dongguan NTC Co., Ltd.
 Tel: +86-769-22022444 Fax: +86-769-22022799
 Web: [Http://www.ntc-c.com](http://www.ntc-c.com)

Site: Conduction

Test Time: 2014-6-20 10:44:57




No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.4761	10.80	34.80	45.60	56.41	-10.81	QP	P	
2	0.4761	10.80	28.80	39.60	46.41	-6.81	AVG	P	
3	0.5433	10.80	33.30	44.10	56.00	-11.90	QP	P	
4	0.5433	10.80	15.10	25.90	46.00	-20.10	AVG	P	
5	0.8618	10.80	31.10	41.90	56.00	-14.10	QP	P	
6	0.8618	10.80	13.70	24.50	46.00	-21.50	AVG	P	
7	0.9735	10.80	29.40	40.20	56.00	-15.80	QP	P	
8	0.9735	10.80	13.30	24.10	46.00	-21.90	AVG	P	
9	1.4874	10.80	29.00	39.80	56.00	-16.20	QP	P	
10	1.4874	10.80	13.60	24.40	46.00	-21.60	AVG	P	
11	2.1325	10.80	28.70	39.50	56.00	-16.50	QP	P	
12	2.1325	10.80	14.80	25.60	46.00	-20.40	AVG	P	

Note: Level=Reading+Factor.

Margin=Limit-Level.



Test Time: 2014-6-20 10:50:06



No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.3653	10.80	28.70	39.50	58.61	-19.11	QP	P	
2	0.3653	10.80	12.90	23.70	48.61	-24.91	AVG	P	
3	0.4736	10.80	30.40	41.20	56.45	-15.25	QP	P	
4	0.4736	10.80	14.90	25.70	46.45	-20.75	AVG	P	
5	0.5378	10.80	29.40	40.20	56.00	-15.80	QP	P	
6	0.5378	10.80	11.30	22.10	46.00	-23.90	AVG	P	
7	0.7389	10.80	26.70	37.50	56.00	-18.50	QP	P	
8	0.7389	10.80	11.90	22.70	46.00	-23.30	AVG	P	
9	0.8944	10.80	26.80	37.60	56.00	-18.40	QP	P	
10	0.8944	10.80	11.30	22.10	46.00	-23.90	AVG	P	
11	1.3958	10.80	28.70	39.50	56.00	-16.50	QP	P	
12	1.3958	10.80	11.90	22.70	46.00	-23.30	AVG	P	


Note: Level=Reading+Factor.

Margin=Limit-Level.


4. Radiated Emission Test

4.1 Test SET-UP (Block Diagram of Configuration)

4.1.1 Radiated Emission Test Set-Up, Frequency Below 30MHz



4.1.2 Radiated Emission Test Set-Up, Frequency above 1GHz



4.2 Measurement Procedure

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- e. A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.
 1. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300KHz for Quasi-peak detection at frequency below 1GHz.
 2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
 3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for average detection(AV) at frequency above 1GHz.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution Bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
	Average	1 MHz	10 Hz

4.3 Limit

Frequency range MHz	Distance Meters	Field Strengths Limit (15.209)	
		μV/m	
0.009 ~ 0.490	300	2400/F(kHz)	
0.490 ~ 1.705	30	24000/F(kHz)	
1.705 ~ 30	30	30	
30 ~ 88	3	100	
88 ~ 216	3	150	
216 ~ 960	3	200	
Above 960	3	500	
Frequency range MHz	Distance Meters	Field Strengths Limit (15.249)	
		μV/m (Field strength of fundamental)	μV/m (Field strength of Harmonics)
902 ~ 928	3	50	500
2400 ~ 2483.5	3	50	500
5725 ~ 5875	3	50	500
24000 ~ 2425000	3	250	2500

Remark : (1) Emission level (dB) μ V = 20 log Emission level μ V/m
 (2) The smaller limit shall apply at the cross point between two frequency bands.
 (3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
 (4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

4.4 Measurement Results

Operation Mode: TX
Frequency Range: 9KHz~1GHz
Test Result: PASS
Measured Distance: 3m
Test Date : June 20, 2014
Temperature : 22 °C
Humidity : 55 %
Test By: Sance

Freq. (MHz)	Ant.Pol.	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Margin (dB)	Note
34.8500	V	33.10	40.00	-6.90	QP
94.0199	V	38.20	43.50	-5.30	QP
115.3599	V	32.20	43.50	-11.30	QP

94.0199	H	32.70	43.50	-10.80	QP
233.7000	H	39.80	46.00	-6.20	QP
272.7800	H	40.20	46.00	-5.80	QP

Other emissions are lower than 10dB below the allowable limit.

Note:

- (1) Emission Level= Reading Level + Factor
- (2) Factor= Antenna Gain + Cable Loss – Amplifier Gain
- (3) Measurement uncertainty : $\pm 3.4\text{dB}$
- (4) Loop antenna used for the emission below 30MHz.
- (5) Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 10dB below the permissible limits.

Modulation: Low Frequency: 5730MHz)
Operation Mode: TX Mode (Low) Test Date : June 20, 2014
Frequency Range: 1-40GHz Temperature : 22 °C
Test Result: PASS Humidity : 55 %
Measured Distance: 3m Test By: Sance

Freq. (MHz)	Ant. Pol.	Emission Level (dBuV)		Limit 3m (dBuV/m)		Margin (dB)	
		Peak	AV	Peak	AV	Peak	AV
5730	V	109.36	91.04	114.00	94.00	-4.64	-2.96
11460	V	60.54	48.58	74.00	54.00	-13.46	-5.42

5730	H	108.12	90.86	114.00	94.00	-5.88	-3.14
11460	H	60.64	52.00	74.00	54.00	-13.36	-2.00

Note:

- (1) All Readings are Peak Value and AV.
- (2) Emission Level = Reading Level + Factor
- (3) Factor = Antenna Gain + Cable Loss – Amplifier Gain
- (4) Data of measurement within this frequency range shown “ --- ” in the table above means there is no emission can be found.
- (5) Measurement uncertainty : $\pm 3.7\text{dB}$.
- (6) Horn antenna used for the emission over 1000MHz.

Modulation: Mid Frequency: 5765MHz
Operation Mode: TX Mode (Mid) Test Date : June 20, 2014
Frequency Range: 1-40GHz Temperature : 22 °C
Test Result: PASS Humidity : 55 %
Measured Distance: 3m Test By: Sance

Freq. (MHz)	Ant. Pol.	Emission Level (dBuV)		Limit 3m (dBuV/m)		Margin (dB)	
		Peak	AV	Peak	AV	Peak	AV
5765	V	108.30	89.51	114.00	94.00	-5.70	-4.49
11530	V	58.27	51.11	74.00	54.00	-15.73	-2.89

5765	H	108.38	88.72	114.00	94.00	-5.62	-5.28
11530	H	59.80	50.42	74.00	54.00	-14.20	-3.58

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level + Factor
(3) Factor= Antenna Gain + Cable Loss – Amplifier Gain
(4) Data of measurement within this frequency range shown “ --- ” in the table above means there is no emission can be found.
(5) Measurement uncertainty : ± 3.7 dB.
(6) Horn antenna used for the emission over 1000MHz.

Modulation: High Frequency: 5805MHz
Operation Mode: TX Mode (High) Test Date : June 20, 2014
Frequency Range: 1-40GHz Temperature : 22 °C
Test Result: PASS Humidity : 55 %
Measured Distance: 3m Test By: Sance

Freq. (MHz)	Ant. Pol.	Emission Level (dBuV)		Limit 3m (dBuV/m)		Margin (dB)	
		Peak	AV	Peak	AV	Peak	AV
5805	V	108.50	88.32	114.00	94.00	-5.50	-5.68
11610	V	62.04	50.50	74.00	54.00	-11.96	-3.50

5805	H	109.41	89.22	114.00	94.00	-4.59	-4.78
11610	H	60.85	50.37	74.00	54.00	-13.15	-3.63

Note:

- (1) All Readings are Peak Value and AV.
- (2) Emission Level= Reading Level + Factor
- (3) Factor= Antenna Gain + Cable Loss – Amplifier Gain
- (4) Data of measurement within this frequency range shown “ --- ” in the table above means there is no emission can be found.
- (5) Measurement uncertainty : $\pm 3.7\text{dB}$.
- (6) Horn antenna used for the emission over 1000MHz.

5. 20dB Bandwidth

5.1 Measurement Procedure

Maximum 20dB RF Bandwidth, FCC Rule 15.249:

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. Use the spectrum 20dB down delta function to measure the bandwidth.

5.2 Test SET-UP (Block Diagram of Configuration)




5.3 Measurement Results

Refer to attached data chart.

RBW:	100KHz	VBW:	300KHz
Packet:	DH5	Spectrum Detector:	PK
Test By:	Sance	Test Date :	Jul. 04, 2014
Temperature :	22 °C	Humidity :	50 %
Test Result:	PASS		


Channel frequency (MHz)	20dB Down BW(kHz)
5730	2560
5765	2540
5805	2560

Lowest Channel




Date: 4.JUL.2014 22:52:49

Middle Channel



Date: 4.JUL.2014 22:53:29

Highest Channel



Date: 4.JUL.2014 22:54:05

6. Band Edge

6.1 Measurement Procedure

Out of Band Conducted Emissions, FCC Rule 15.249:

The transmitter output is connected to spectrum analyzer. The resolution bandwidth is set to 100KHz, and the video bandwidth set to 300KHz.

A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

1. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300KHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for average detection(AV) at below at frequency above 1GHz.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution Bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
	Average	1 MHz	10 Hz

6.2 Limit

15.249 In any 100KHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

6.3 Measurement Results

Please see below test table.
For Radiated Emission

Freq. (MHz)	Ant. Pol.	Emission Level (dBuV)		Limit 3m (dBuV/m)		Margin (dB)	
		Peak	AV	Peak	AV	Peak	AV
5724.002	H	60.36	42.55	74.00	54.00	-13.64	-11.45
5724.899	V	61.71	43.40	74.00	54.00	-12.29	-10.60
5875.120	H	42.48	25.34	74.00	54.00	-31.52	-28.66
5875.025	V	42.28	27.95	74.00	54.00	-31.72	-26.05

Note: (1) Emission Level= Reading Level + Factor
(2) Factor= Antenna Gain + Cable Loss – Amplifier Gain
(3) Horn antenna used for the emission over 1000MHz.

7. Antenna Application

7.1 Antenna requirement

According to of FCC part 15C section 15.203 and 15.240:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Systems operating in the 5725-5875MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

7.2 Measurement Results

The antenna is integrated on the main PCB and no consideration of replacement, and the best case gain of the antenna is 1.5dBi. So, the antenna is consider meet the requirement.

8. Test Equipment List

Description	Manufacturer	Model Number	Serial Number	Characteristics	Calibration Date	Calibration Due Date
Test Receiver	Rohde & Schwarz	ESCI7	100837	9KHz~7GHz	Nov. 25, 2013	Nov. 24, 2014
Antenna	Schwarzbeck	VULB9162	9162-010	30MHz~7GHz	Nov. 28, 2013	Nov. 27, 2014
Positioning Controller	UC	UC 3000	N/A	0~360°, 1-4m	N/A	N/A
Color Monitor	SUNSPO	SP-140A	N/A	N/A	N/A	N/A
Single Phase Power Line Filter	SAEMC	PF201A-32	110210	32A	N/A	N/A
3 Phase Power Line Filter	SAEMC	PF401A-200	110318	200A	N/A	N/A
DC Power Filter	SAEMC	PF301A-200	110245	200A	N/A	N/A
Cable	Huber+Suhner	CBL2-NN-1M	22390001	9KHz~7GHz	Nov. 09, 2013	Nov. 08, 2014
Cable	Huber+Suhner	CIL02	N/A	9KHz~7GHz	Nov. 09, 2013	Nov. 08, 2014
Power Amplifier	HP	HP 8447D	1145A00203	100KHz~1.3GHz	Nov. 09, 2013	Nov. 08, 2014
Horn Antenna	Schwarzbeck	BBHA9170	9170-372	15GHz~26.5GHz	Oct.24, 2013	Oct.23, 2014
Horn Antenna	Com-Power	AH-118	071078	1GHz~18GHz	Nov. 07, 2013	Nov. 06, 2014
Loop antenna	Daze	ZA30900A	0708	9KHz~30MHz	Oct.11, 2013	Oct.10, 2014
Spectrum Analyzer	Agilent	E4408B	MY414407D	9KHz~26.5GHz	Nov. 05, 2013	Nov. 04, 2014
Pre-Amplifier	Agilent	8449B	3008A02964	1GHz~26.5GHz	Nov. 05, 2013	Nov. 04, 2014
L.I.S.N.	Rohde & Schwarz	ENV 216	101317	9KHz~30MHz	Nov. 09, 2013	Nov. 08, 2014

---End of report---