

Certification of Compliance

CFR 47 Part 15 Subpart B

Test Report File No. : 04-IST-0314 **Date of Issue :** November 2, 2004

Model(s) : OP-42TN

Kind of Product : 42" Plasma Display Panel

Applicant : Orcom CO., LTD

Address : 1113-1 Dalan-Dong, Dongan-Gu, Anyang-Si, Kyonggi-Do, Korea

Manufacturer : Orcom CO., LTD

Address : 1113-1 Dalan-Dong, Dongan-Gu, Anyang-Si, Kyonggi-Do, Korea

Test Result

Positive

Negative

Reviewed By



J. H. Lee / EMC Group Manager

Approved By



G. Chung / Chief

Comment(s)

- Investigations requested : Measurement to the relevant clauses of FCC rules and regulations Part 15 Subpart B - Unintentional Radiators, Class B.
- The test report with appendix consists of 15 pages.
- The test result only responds to the tested sample.
- It is not allowed to copy this report even partly without the allowance of IST EMC Laboratory.
- This equipment as for has been shown to be capable of continued compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4 2001.



TABLE OF CONTENTS

Table of contents	2
Information of test laboratory, Environmental conditions, Power used, Product information	3
Descriptions of test	
Conducted Emission	4
Radiated Emission	5
Equipment Under Test	6
Summary	7

■ Test Conditions and Data - Emissions

◆ Conducted Emissions	0.15MHz - 30MHz	Applicable
Test Conditions / Data and Plots		8-10
◆ Radiated Emissions	30MHz - 1GHz	Applicable
Test Conditions / Data and Plots		11-12

Appendix	A. The Photos of Test Setup	13-14
	B. The Photos of Equipment Under Test	15

Note:

INFORMATIONS OF TEST LABORATORY

EMC LABORATORY of IST Co., Ltd. (**FCC Filing Lab.**)
San 21-8, Goan-Ri, Baekam-Myun, Yongin-City
Kyonggi-Do, 449-860, Korea
TEL : +82 31 333 4093 FAX : +82 31 333 4094

ENVIRONMENTAL CONDITIONS

Temperature 20.0 °C
Humidity 49 %
Atmospheric pressure 1008 mbar

POWER SUPPLY SYSTEM USED

Power supply system AC 120Vac, 60Hz
(Refer to the product information)

PRODUCT INFORMATION

Power Source	AC 100-240 V, 50/60Hz
Power Consumption	300W
Screen Size	42"
Number of Pixels	852 (H) x 480 (V)
Pixel Pitch	1.080mm (H) x 1.080mm (V)
Input Terminal	DVI, RGB, Audio L/R, S-Video, Component, Antenna
Output Terminal	Speaker
Dimension	1028mm x 625mm x 89.8mm (without stand) 1028mm x 692.5mm x 270mm (with stand)
Weight	35Kg (without stand) 40.5Kg (with stand)

- EMC suppression device is not used during the test.
- Please refer to user's manual.


DESCRIPTIONS OF TEST

Conducted Emissions:


The measurement were performed over the frequency range of 0.15MHz to 30MHz using a $50\Omega/50\mu\text{H}$ LISN as the input transducer to a Spectrum Analyzer or a Field Intensity Meter. The measurements were made with the detector set for "Peak" amplitude within a bandwidth of 10KHz or for "quasi-peak" & "Average" within a bandwidth of 9KHz.

-Procedure of Test

The line-conducted facility is located inside a shielded room No.1. A 1m X 1.5m wooden table 80cm height is placed 40cm away from the vertical wall and 1.5m away from the other wall of the shielded room. The R/S ESH3-Z5 and EMCO 3825/2 LISN are bonded to bottom of the shielded room. The EUT is located on the wooden table with distance more than 80cm from the LISN and powered from the EMCO LISN .The peripheral equipment is powered from the other LISN. Power to the LISNs are filtered by a noise cut power line filters. All electrical cables are shielded by braided tinned steel tubing with inner ϕ 1.2cm. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the EMCO LISN. All interconnecting cables more than 1m were shortened by non-inductive bundling to a 1m length. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating conditions. The RF output of the LISN was connected to the R/S receiver to determine the frequency producing the maximum emission from the EUT. The frequency producing the maximum level was reexamined using Quasi-Peak mode by manual measurement, after scanned by automatic Peak mode for frequency range from 0.15 to 30MHz. The bandwidth of the receiver was set to 10kHz. The EUT, peripheral equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission.



< Side View >



< Concept Drawing >


DESCRIPTION OF TEST

Radiated Emissions:

The measurement was performed over the frequency range of 30MHz to 1GHz using antenna as the input transducer to a Spectrum analyzer or a Field Intensity Meter. The measurement was made with the detector set for "quasi-peak" within a bandwidth of 120KHz.

-Procedure of Test

Preliminary measurements were made at 3 meter using bi-conical and log-periodic antennas, and spectrum analyzer to determine the frequency producing the max. emission in anechoic chamber. Appropriate precaution was taken to ensure that all emission from the EUT were maximized and investigated. The system configuration, mode of operation, turn-table azimuth and height with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30MHz to 300MHz using S/B bi-conical antenna and 300 to 1000MHz using S/B log-periodic antenna. Above 1GHz, linearly polarized double ridge horn antennas were used. Final measurements were made at open site with 3-meters test distance using S/B bi-log antenna or horn antenna. The OATS have been verified in regular for its normalized site attenuation. The test equipment was placed on a wooden table. Sufficient time for the EUT, peripheral equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined by manual. The detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 120kHz or 1MHz depending on the frequency of type of signal. The EUT, peripheral equipment and interconnecting cables were re-configured to the set-up producing the max. emission for the frequency and were placed on top of a 0.8-meter high nonmetallic 1 x 1.5 meter table. The EUT, peripheral equipment, and interconnecting cables were re-arranged and manipulated to maximize each emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation to the EUT and/or peripheral equipment and changing the polarity of the antenna, whichever determined the worst-case emission.



Equipment Under Test

EUT Type :

- Table-Top.
- Floor-Standing.
- Table-Top and Floor-Standing(Combination).

Operation - mode of the E.U.T. :

The equipment under test was operated during the measurement under following conditions :

- Standby Mode
- Operational Condition :
 - 640x480, 60Hz
 - 800x600, 60Hz
 - 1024x768, 60Hz

The test results of followings are the representative of worst case emissions for the available resolution can be adjusted.

It is investigated the emission characteristic for DVI and RGB mode.

Configuration of the equipment under test :

Following peripheral devices and interface cables were connected during the measurement :

Equipment	Type	Brand	Serial No.	FCC	Compliance Info.
PC	Vectra VL420 MT	HP	SG21208253	DoC	
Keyboard	SK-2502C	HP	M020321534	DoC	
PS/2 Mouse	M-S48a	HP	LZC20660272	JNZ201213	
Printer	A0302380	Northern Telecom	2516S60951	BS46XU225C-L	
Serial Mouse	M-M28	Logitech	LCA53305547	DZL210365	

Connecting Interface Cables :

- Unshielded AC power cable : 1.8 m
- Shielded monitor's signal cable (with two ferrite core) : 1.5 m
- Shielded Printer's signal cable (with two ferrite core) : 1.8 m

Note :

TEST CONDITIONS AND DATA

Conducted Emissions

[Applicable]

◆ Test Equipment Used

Model Name	Description	Manufacture	Calibration Date	Serial Number
ESH 3	Test Receiver	Rohde & Schwarz	Jul. 15, 2004	892108/018
ESH 3-Z5	Artificial mains network	Rohde & Schwarz	Jul. 15, 2004	862770/025
ESH 3-Z2	Transient limiter	Rohde & Schwarz	Jul. 15, 2004	357.8810.52

◆ Test Accessories Used

Type	Manufacturer
Aneroid Barometer	Sato
Hygrometer	Sato


◆ Test Program Scrolling "H" patterns on the Windows

◆ Test Date October 27, 2004

◆ Test Area Shielded room No.1

Note : *The equipment used is calibrated in regular for every year.*


Conducted Emissions



Freq. [MHz]	Measurement [dB μ V]		Limit [dB μ V]		Insertion Loss [dB]	Cable Loss [dB μ V]	Result [dB μ V]		Margin [dB]	
	Q-peak	Average	Q-peak	Average			Q-peak	Average	Q-peak	Average
0.158	48.3	43.1	65.6	55.6	0.1	0.5	48.9	43.7	16.7	11.9
3.479	37.5	12.8	56.0	46.0	0.0	0.5	38.0	13.3	18.0	32.7
15.929	47.5	18.1	60.0	50.0	0.1	0.7	48.3	18.9	11.7	31.1

Note :

Conducted Emissions



Freq. [MHz]	Measurement [dB μ V]		Limit [dB μ V]		Insertion Loss [dB]	Cable Loss [dB μ V]	Result [dB μ V]		Margin [dB]	
	Q-peak	Average	Q-peak	Average			Q-peak	Average	Q-peak	Average
0.156	46.9	41.4	65.7	55.7	0.1	0.5	47.5	42.0	18.2	13.7
0.869	32.1	10.4	56.0	46.0	0.0	0.4	32.5	10.8	23.5	35.2
17.018	41.0	16.4	60.0	50.0	0.1	0.7	41.8	17.2	18.2	32.8

Note :

TEST CONDITIONS AND DATA

Radiated Emission

[Applicable]

◆ Test Equipment Used

Name	Type	Manufacturer	Calibration. Date	Serial Number
ESVP	Test Receiver	Rohde & Schwarz	Jul. 15, 2004	861744/004
VULB 9160	Antenna	Schwarzbeck	Jul. 19, 2004	3048

◆ Test Accessories Used

Type	Manufacturer
Aneroid Barometer	Sato
Hygrometer	Sato

◆ Test Program Scrolling "H" patterns on the Windows

◆ Test Date October 28, 2004

◆ Test Area Open site No.2

Note : The equipment used is calibrated in regular for every year.

Radiated Emissions

Mode	Freq. [MHz]	Reading [dBuV]	Antenna Factor [dB/m]	Cable Loss [dB]	Polar. [H/V]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]
640x480, 60Hz	31.4	23.5	V	11.2	1.2	35.9	40.0	4.1
	77.3	18.7	H	8.5	1.9	29.1	40.0	10.9
	84.1	12.4	V	8.0	2.0	22.4	40.0	17.6
	262.8	13.0	H	11.4	3.9	28.3	46.0	17.7
	364.5	14.4	V	14.0	4.9	33.3	46.0	12.7
	546.7	16.8	H	15.9	6.2	38.9	46.0	7.1
<hr/>								
800x600, 60Hz	31.4	21.4	H	11.2	1.2	33.8	40.0	6.2
	77.5	10.8	H	8.5	1.9	21.2	40.0	18.8
	84.1	15.8	V	8.0	2.0	25.8	40.0	14.2
	262.8	14.1	H	11.4	3.9	29.4	46.0	16.6
	364.5	14.3	H	14.0	4.9	33.2	46.0	12.8
	546.7	14.8	H	15.9	6.2	36.9	46.0	9.1
<hr/>								
1024x768, 60Hz	31.5	22.2	V	11.2	1.2	34.6	40.0	5.4
	77.6	21.5	H	8.3	1.9	31.7	40.0	8.3
	84.1	26.8	V	8.0	2.0	36.8	40.0	3.2
	262.8	15.3	H	11.4	3.9	30.6	46.0	15.4
	364.5	14.6	H	14.0	4.9	33.5	46.0	12.5
	546.7	15.1	H	15.9	6.2	37.2	46.0	8.8

Note:

Appendix A. The Photos of Test Setup



Conducted Emissions - Front View



Conducted Emissions - Rear View

Appendix A. The Photos of Test Setup



Radiated Emissions - Front View



Radiated Emissions - Rear View

Appendix A. The Photos of EUT



Front View



Rear View