

FCC RADIO TEST REPORT

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : N300 Wireless Router
Model No. : WNR2200
Brand Name : NETGEAR
Filing Type : New Application
Applicant : NETGEAR, INC.
350 East Plumeria Drive San Jose, CA 95134
FCC ID : PY310200131
Manufacturer : NETGEAR, INC.
350 East Plumeria Drive San Jose, CA 95134
Received Date : May 23, 2010
Final Test Date : Jul. 20, 2010

Statement

Test result included is only for the 802.11b/g part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



SPORTON International Inc.

No. 52 Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

Table of Contents

1 SUMMARY OF THE TEST RESULT 2

2 GENERAL INFORMATION..... 3

2.1 Product Details 3

2.2 Accessories 3

2.3 Table for Filed Antenna 3

2.4 Table for Carrier Frequencies 4

2.5 Table for Test Modes 4

2.6 Test Manner 4

2.7 Table for Testing Locations 4

2.8 Table for Supporting Units..... 5

2.9 Table for Parameters of Test Software Setting 5

2.10 EUT Operation during Test 6

2.11 Test Configuration 7

3 TEST RESULT 9

3.1 AC Power Line Conducted Emissions Measurement..... 9

3.2 Maximum Conducted Output Power Measurement 19

3.3 Power Spectral Density Measurement 22

3.4 6dB Spectrum Bandwidth Measurement..... 28

3.5 Radiated Emissions Measurement..... 34

3.6 Band Edge and Fundamental Emissions Measurement 54

3.7 Antenna Requirements..... 59

4 LIST OF MEASURING EQUIPMENTS 60

5 TEST LOCATION..... 62

6 TAF CERTIFICATE OF ACCREDITATION 63

APPENDIX A. MAXIMUM PERMISSIBLE EXPOSURE..... A1 ~ A3

APPENDIX B. TEST PHOTOS B1 ~ B12

APPENDIX C. PHOTOGRAPHS OF EUT C1 ~ C11

CERTIFICATE OF COMPLIANCE

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : N300 Wireless Router

Model No. : WNR2200

Brand Name : NETGEAR

Applicant : NETGEAR, INC.

350 East Plumeria Drive San Jose, CA 95134

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on May 23, 2010 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Wayne Hsu / Vice Manager

SPORTON International Inc.

No. 52 Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

1 SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
3.1	15.207	AC Power Line Conducted Emissions	Complies	16.18 dB
3.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	2.14 dB
3.3	15.247(e)	Power Spectral Density	Complies	8.12 dB
3.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
3.5	15.247(d)	Radiated Emissions	Complies	3.07 dB
3.6	15.247(d)	Band Edge Emissions	Complies	0.97 dB
3.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Peak Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

2 GENERAL INFORMATION

2.1 Product Details

Only the radio detail of IEEE 802.11b/g is shown in the table below. For more detailed features description, please refer to the manufacturer’s specifications or user’s manual.

Items	Description
Power Type	12V from adapter
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (DBPSK / DQPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11b/g: 11
Channel Band Width (99%)	11b: 13.76 MHz ; 11g: 16.56 MHz
Conducted Output Power	11b: 22.33 dBm ; 11g: 27.86 dBm

2.2 Accessories

Power	Brand	Model	Rating
AC-DC Adapter	NETGEAR	AD661F	INPUT : 100-120V~50/60Hz 680mA OUTPUT : 12V 1.5A
I.T.E. Power supply	NETGEAR	MT18-9120150-A1	INPUT : 120V~60Hz 0.5A OUTPUT : 12V 1.5A

2.3 Table for Filed Antenna

Antenna & Bandwidth

Antenna	Two (TX)	
	20 MHz	40 MHz
802.11b	V	X
802.11g	V	X
802.11n (2.4GHz)	V	V

Ant.	Antenna Type	Connector	Gain (dBi)	Remark
A	Printed Antenna	Fixed on Board	4.27	TX / RX
B	Printed Antenna	Fixed on Board	4.27	TX / RX

Antenna: There are two antennas configuration used in this EUT. Both antennas are for signal transceiving.

2.4 Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

2.5 Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on the entire possible configuration for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	See the test manner	Auto	-	-
Maximum Conducted Output Power	11b/CCK	11 Mbps	1/6/11	A/B; A+B
	11g/BPSK	6 Mbps	1/6/11	A/B; A+B
Power Spectral Density 6dB Spectrum Bandwidth Radiated Emissions Above 1GHz	11b/CCK	11 Mbps	1/6/11	A+B
	11g/BPSK	6 Mbps	1/6/11	A+B
Radiated Emissions Below 1GHz	See the test manner	Auto	-	-
Band Edge Emissions	11b/CCK	11 Mbps	1/11	A+B
	11g/BPSK	6 Mbps	1/11	A+B

2.6 Test Manner

- a. The following test modes were for conducted final test:
 - Mode 1. EUT with adapter : AD661F stand mode
 - Mode 2. EUT with adapter : AD661F lie mode
 - Mode 3. EUT with adapter : MT18-9120150-A1stand mode
 - Mode 4. EUT with adapter : MT18-9120150-A1 lie mode
- b. The following test modes were for radiated emissions (30MHz~1GHz) final test:
 - Mode 1. EUT with adapter : AD661F stand mode
 - Mode 2. EUT with adapter : MT18-9120150-A1stand mode

2.7 Table for Testing Locations

Test Site No.	Site Category	Location
CO01-NH	Conduction	Nei Hu
TH01-HY	OVEN Room	Hwa Ya
03CH03-HY	SAC	Hwa Ya

Semi Anechoic Chamber (SAC).

2.8 Table for Supporting Units

Support Unit	Brand	Model	FCC ID	Remark
LCD Monitor	DELL	E198WFPF	DoC	Conducted
Printer	HP	C2642X	DoC	
Modem	ACEEX	DM-1414	IFAXDM1414	
Personal Computer	DELL	DCTA	N/A	
USB Keyboard	DELL	SK-8175	N/A	
USB Mouse	DELL	MOC5UO	N/A	
Flash	SONY	1G	N/A	
Personal Computer (Remote Workstation)	HP Compaq	D330uT	DoC	
LCD Monitor (Remote Workstation)	DELL	E198WFPF	DoC	
PS/2 Keyboard (Remote Workstation)	HP	KB-0133	DoC	
PS/2 Mouse (Remote Workstation)	HP	M-S69	NZ211443	
Notebook (Remote Workstation)	HP	541	N/A	
Notebook	DELL	PP25L	N/A	Radiated

2.9 Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

For Two Chain:

Power Parameters of IEEE 802.11b/g

Test Software Version	ART		
	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	20	20	20
IEEE 802.11g	16	20	15

2.10 EUT Operation during Test

< Conducted >

An executive program, "EMCTEST.EXE" under WIN XP, which generate a complete line of continuously repeating "H" pattern was used as the test software.

The program was executed as follows:

- a. Turn on the power of all equipment.
- b. The EUT reads the "WINTHRAX.EXE" test program from the hard disk drive and runs it.
- c. The EUT sends "H" messages to the LCD monitor and displays "H" patterns on the screen.
- d. The EUT sends "H" messages to the printer, and then the printer prints them on the paper.
- e. The EUT sends "H" messages to the internal Hard Disk, and the Hard Disk reads and writes the message.
- f. Repeat the steps from c to e.

At the same time, the following programs were executed:

-Executed "ping.exe" to link with the remote workstation to receive and transmit data by LAN and WLAN.

< Radiated >

An executive program, "EMCTEST.EXE" under WIN XP, which generate a complete line of continuously repeating "H" pattern was used as the test software.


At the same time, the following programs were executed:

-Executed "ART" to keep transmitting signals at fixed frequency.


2.11 Test Configuration

2.11.1 Radiation Emissions Test Configuration

For radiated emissions 9kHz~1GHz



For radiated emissions above 1GHz



3 TEST RESULT

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Class B

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

3.1.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

3.1.3 Test Procedures

1. The EUT warm up about 15 minutes then start test.
2. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
5. The frequency range from 150 KHz to 30 MHz was searched.
6. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
7. The measurement has to be done between each power line and ground at the power terminal.

3.1.4 Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω. LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

3.1.5 Test Deviation

There is no deviation with the original standard.


3.1.6 EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.

3.1.7 Results of AC Power Line Conducted Emissions Measurement


Final Test Date	Jul. 20, 2010	Test Site No.	CO01-NH
Temperature	28	Humidity	52%
Test Engineer	Eddie	Configuration	Mode 1

Line



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.152	48.68	-17.19	65.87	37.89	10.69	0.10	QP
2	0.152	35.05	-20.82	55.87	24.26	10.69	0.10	AVERAGE
3	0.193	26.41	-27.48	53.89	15.63	10.68	0.10	AVERAGE
4	0.193	40.95	-22.94	63.89	30.17	10.68	0.10	QP
5	0.235	40.66	-21.60	62.26	29.89	10.67	0.10	QP
6	0.235	26.12	-26.14	52.26	15.35	10.67	0.10	AVERAGE
7	1.269	20.84	-25.16	46.00	10.07	10.63	0.13	AVERAGE
8	1.269	31.41	-24.59	56.00	20.64	10.63	0.13	QP
9	2.435	26.39	-29.61	56.00	15.54	10.65	0.20	QP
10	2.435	17.92	-28.08	46.00	7.07	10.65	0.20	AVERAGE
11	8.964	18.40	-31.60	50.00	7.47	10.73	0.20	AVERAGE
12	8.964	26.06	-33.94	60.00	15.13	10.73	0.20	QP

Neutral




	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	dB	dBuV	dBuV	dB	Loss	Remark
1	0.154	45.76	-20.02	65.78	35.43	10.23	0.10	QP
2	0.154	33.10	-22.68	55.78	22.77	10.23	0.10	AVERAGE
3	0.166	27.20	-27.97	55.16	16.87	10.23	0.10	AVERAGE
4	0.166	42.29	-22.88	65.16	31.96	10.23	0.10	QP
5	0.201	39.95	-23.63	63.58	29.62	10.23	0.10	QP
6	0.201	23.68	-29.90	53.58	13.35	10.23	0.10	AVERAGE
7	0.428	19.56	-27.73	47.29	9.24	10.22	0.10	AVERAGE
8	0.428	28.38	-28.91	57.29	18.06	10.22	0.10	QP
9	2.474	27.45	-28.55	56.00	17.00	10.25	0.20	QP
10	2.474	17.93	-28.07	46.00	7.48	10.25	0.20	AVERAGE
11	10.342	16.73	-33.27	50.00	6.18	10.35	0.20	AVERAGE
12	10.342	22.30	-37.70	60.00	11.75	10.35	0.20	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.


Final Test Date	Jul. 20, 2010	Test Site No.	CO01-NH
Temperature	28	Humidity	52%
Test Engineer	Eddie	Configuration	Mode 2

Line



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.152	48.11	-17.81	65.91	37.31	10.69	0.10	QP
2	0.152	34.83	-21.09	55.91	24.03	10.69	0.10	AVERAGE
3	0.197	26.86	-26.90	53.76	16.07	10.68	0.10	AVERAGE
4	0.197	41.79	-21.97	63.76	31.00	10.68	0.10	QP
5	0.235	40.05	-22.21	62.26	29.28	10.67	0.10	QP
6	0.235	25.69	-26.57	52.26	14.92	10.67	0.10	AVERAGE
7	0.953	20.80	-25.20	46.00	10.06	10.63	0.10	AVERAGE
8	0.953	30.76	-25.24	56.00	20.02	10.63	0.10	QP
9	2.622	25.73	-30.27	56.00	14.88	10.65	0.20	QP
10	2.622	17.45	-28.55	46.00	6.60	10.65	0.20	AVERAGE
11	9.757	17.71	-32.29	50.00	6.77	10.74	0.20	AVERAGE
12	9.757	23.81	-36.19	60.00	12.87	10.74	0.20	QP

Neutral




	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.152	46.56	-19.35	65.91	36.23	10.23	0.10	QP
2	0.152	34.87	-21.04	55.91	24.54	10.23	0.10	AVERAGE
3	0.189	26.39	-27.67	54.06	16.06	10.23	0.10	AVERAGE
4	0.189	39.09	-24.97	64.06	28.76	10.23	0.10	QP
5	0.232	38.50	-23.90	62.39	28.17	10.23	0.10	QP
6	0.232	25.97	-26.43	52.39	15.64	10.23	0.10	AVERAGE
7	0.315	20.82	-29.02	49.84	10.50	10.22	0.10	AVERAGE
8	0.315	31.91	-27.93	59.84	21.59	10.22	0.10	QP
9	1.276	25.22	-30.78	56.00	14.85	10.24	0.13	QP
10	1.276	16.43	-29.57	46.00	6.06	10.24	0.13	AVERAGE
11	13.408	16.21	-33.79	50.00	5.60	10.41	0.20	AVERAGE
12	13.408	21.04	-38.96	60.00	10.43	10.41	0.20	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.


Final Test Date	Jul. 20, 2010	Test Site No.	CO01-NH
Temperature	28	Humidity	52%
Test Engineer	Eddie	Configuration	Mode 3

Line



	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.158	45.74	-19.82	65.56	34.95	10.69	0.10	QP
2	0.158	34.15	-21.41	55.56	23.36	10.69	0.10	AVERAGE
3	0.183	18.45	-35.87	54.33	7.67	10.68	0.10	AVERAGE
4	0.183	36.92	-27.40	64.33	26.14	10.68	0.10	QP
5	0.230	33.74	-28.69	62.44	22.97	10.67	0.10	QP
6	0.230	17.70	-34.73	52.44	6.93	10.67	0.10	AVERAGE
7	0.502	21.55	-24.45	46.00	10.81	10.64	0.10	AVERAGE
8	0.502	27.86	-28.14	56.00	17.12	10.64	0.10	QP
9	4.622	31.20	-24.80	56.00	20.33	10.67	0.20	QP
10	4.622	25.62	-20.38	46.00	14.75	10.67	0.20	AVERAGE
11	16.573	27.25	-22.75	50.00	16.19	10.82	0.24	AVERAGE
12	16.573	32.63	-27.37	60.00	21.57	10.82	0.24	QP

Neutral




	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.166	41.71	-23.46	65.16	31.38	10.23	0.10	QP
2	0.166	31.02	-24.15	55.16	20.69	10.23	0.10	AVERAGE
3	0.191	24.34	-29.64	53.98	14.01	10.23	0.10	AVERAGE
4	0.191	39.63	-24.35	63.98	29.30	10.23	0.10	QP
5	0.489	36.03	-20.15	56.19	25.71	10.22	0.10	QP
6	0.489	30.00	-16.18	46.19	19.68	10.22	0.10	AVERAGE
7	3.364	22.73	-23.27	46.00	12.28	10.26	0.20	AVERAGE
8	3.364	28.46	-27.54	56.00	18.01	10.26	0.20	QP
9	6.523	28.61	-31.39	60.00	18.10	10.30	0.20	QP
10	6.523	22.46	-27.54	50.00	11.95	10.30	0.20	AVERAGE
11	17.849	28.55	-21.45	50.00	17.82	10.47	0.26	AVERAGE
12	17.849	33.59	-26.41	60.00	22.86	10.47	0.26	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.


Final Test Date	Jul. 20, 2010	Test Site No.	CO01-NH
Temperature	28	Humidity	52%
Test Engineer	Eddie	Configuration	Mode 4

Line



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.154	43.31	-22.47	65.78	32.52	10.69	0.10	QP
2	0.154	28.59	-27.19	55.78	17.80	10.69	0.10	AVERAGE
3	0.189	21.55	-32.51	54.06	10.77	10.68	0.10	AVERAGE
4	0.189	36.97	-27.09	64.06	26.19	10.68	0.10	QP
5	0.237	34.61	-27.60	62.22	23.84	10.67	0.10	QP
6	0.237	20.15	-32.06	52.22	9.38	10.67	0.10	AVERAGE
7	0.494	18.99	-27.11	46.10	8.25	10.64	0.10	AVERAGE
8	0.494	29.46	-26.64	56.10	18.72	10.64	0.10	QP
9	3.364	27.91	-28.09	56.00	17.06	10.65	0.20	QP
10	3.364	22.18	-23.82	46.00	11.33	10.65	0.20	AVERAGE
11	16.928	28.21	-21.79	50.00	17.14	10.82	0.24	AVERAGE
12	16.928	33.30	-26.70	60.00	22.23	10.82	0.24	QP

Neutral



	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.156	44.91	-20.73	65.65	34.58	10.23	0.10	QP
2	0.156	34.37	-21.27	55.65	24.04	10.23	0.10	AVERAGE
3	0.199	31.29	-22.38	53.67	20.96	10.23	0.10	AVERAGE
4	0.199	39.99	-23.68	63.67	29.66	10.23	0.10	QP
5	0.277	33.77	-27.12	60.90	23.45	10.23	0.10	QP
6	0.277	27.97	-22.92	50.90	17.65	10.23	0.10	AVERAGE
7	0.486	29.55	-16.68	46.23	19.23	10.22	0.10	AVERAGE
8	0.486	37.41	-18.82	56.23	27.09	10.22	0.10	QP
9	3.025	28.13	-27.87	56.00	17.67	10.26	0.20	QP
10	3.025	22.95	-23.05	46.00	12.49	10.26	0.20	AVERAGE
11	17.475	28.56	-21.44	50.00	17.84	10.47	0.25	AVERAGE
12	17.475	33.72	-26.28	60.00	23.00	10.47	0.25	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Filter No.	Auto
Measurement time	0.135 s ~ 26 s
Used Peak Sensor	NRV-Z32 (model 04)

3.2.3 Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the peak power value.
3. Repeat above procedures on all channels needed to be tested.
4. When measuring maximum conducted output power within multiple antenna systems, add every result of the values by mathematic formula.

3.2.4 Test Setup Layout



3.2.5 Test Deviation

There is no deviation with the original standard.

3.2.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.2.7 Test Result of Maximum Conducted Output Power

Final Test Date	May 23, 2010	Test Site No.	TH01-HY
Temperature	26	Humidity	52%
Test Engineer	Ian	Configuration	802.11b/g

Configuration of IEEE 802.11b Ant. A (20MHz)

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	18.41	30.00	Complies
6	2437 MHz	19.26	30.00	Complies
11	2462 MHz	19.56	30.00	Complies

Configuration of IEEE 802.11b Ant. B (20MHz)

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	17.11	30.00	Complies
6	2437 MHz	18.14	30.00	Complies
11	2462 MHz	19.06	30.00	Complies

Configuration of IEEE 802.11b Ant. A +Ant. B (20MHz)

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	20.82	30.00	Complies
6	2437 MHz	21.75	30.00	Complies
11	2462 MHz	22.33	30.00	Complies

Configuration of IEEE 802.11g Ant. A (20MHz)

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	22.15	30.00	Complies
6	2437 MHz	25.25	30.00	Complies
11	2462 MHz	21.64	30.00	Complies

Configuration of IEEE 802.11g Ant. B (20MHz)

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	21.37	30.00	Complies
6	2437 MHz	24.41	30.00	Complies
11	2462 MHz	20.61	30.00	Complies

Configuration of IEEE 802.11g Ant. A +Ant. B (20MHz)

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	24.79	30.00	Complies
6	2437 MHz	27.86	30.00	Complies
11	2462 MHz	24.17	30.00	Complies

3.3 Power Spectral Density Measurement

3.3.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

3.3.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

3.3.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set RBW of spectrum analyzer to 3 kHz and VBW to 30 kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.
5. While measuring multiple antennas, the connectors are required to link with Power Meter through a combiner.

3.3.4 Test Setup Layout



3.3.5 Test Deviation

There is no deviation with the original standard.

3.3.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.3.7 Test Result of Power Spectral Density

Final Test Date	May 23, 2010	Test Site No.	TH01-HY
Temperature	26	Humidity	52%
Test Engineer	Ian	Configuration	802.11b/g


Configuration IEEE 802.11b

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-3.50	8.00	Complies
6	2437 MHz	-0.12	8.00	Complies
11	2462 MHz	-1.28	8.00	Complies

Configuration IEEE 802.11g


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-6.75	8.00	Complies
6	2437 MHz	-0.75	8.00	Complies
11	2462 MHz	-8.55	8.00	Complies

Power Density Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 23.MAY.2010 19:05:55

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 23.MAY.2010 18:51:48

Power Density Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 23.MAY.2010 19:00:17

Power Density Plot on Configuration IEEE 802.11g / 2412 MHz




Date: 23.MAY.2010 19:16:05

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 23.MAY.2010 19:21:55

Power Density Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 23.MAY.2010 19:26:04

3.4 6dB Spectrum Bandwidth Measurement

3.4.1 Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

3.4.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

3.4.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.
4. While measuring multiple antennas, the connectors are required to link with Power Meter through a combiner.

3.4.4 Test Setup Layout



3.4.5 Test Deviation

There is no deviation with the original standard.

3.4.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.4.7 Test Result of 6dB Spectrum Bandwidth

Final Test Date	May 23, 2010	Test Site No.	TH01-HY
Temperature	26	Humidity	52%
Test Engineer	Ian	Configuration	802.11b/g


Configuration IEEE 802.11b

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	8.44	13.68	500	Complies
6	2437 MHz	8.40	13.72	500	Complies
11	2462 MHz	8.44	13.76	500	Complies

Configuration IEEE 802.11g


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.44	16.52	500	Complies
6	2437 MHz	16.40	16.56	500	Complies
11	2462 MHz	16.44	16.56	500	Complies

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 23.MAY.2010 19:04:47

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 23.MAY.2010 18:49:22

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 23.MAY.2010 18:59:08

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2412 MHz




Date: 23.MAY.2010 19:14:49

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 23.MAY.2010 19:20:51

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 23.MAY.2010 19:24:53

3.5 Radiated Emissions Measurement

3.5.1 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.5.3 Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

3.5.4 Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

3.5.5 Test Deviation

There is no deviation with the original standard.

3.5.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.5.7 Results of Radiated Emissions (9kHz~30MHz)

Final Test Date	Jun. 24, 2010	Test Site No.	03CH03-HY
Temperature	25.8	Humidity	51%
Test Engineer	Eddie		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

3.5.8 Results of Radiated Emissions (30MHz~1GHz)


Final Test Date	Jun. 24, 2010	Test Site No.	03CH03-HY
Temperature	25.8	Humidity	51%
Test Engineer	Eddie	Configuration	Mode 1

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	32.380	31.54	-8.46	40.00	42.38	16.71	0.76	28.31	---	---	Peak
2	186.540	40.17	-3.33	43.50	56.86	9.15	2.25	28.10	---	---	Peak
3	250.250	41.54	-4.46	46.00	53.86	12.68	2.75	27.76	---	---	Peak
4	524.680	40.30	-5.70	46.00	46.87	18.69	4.01	29.27	---	---	Peak
5	625.840	40.80	-5.20	46.00	46.28	19.47	4.60	29.55	---	---	Peak
6	822.870	41.32	-4.68	46.00	44.64	20.79	5.19	29.30	---	---	Peak

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	48.520	29.46	-10.54	40.00	47.25	8.86	1.08	27.73	---	---	Peak
2	178.960	39.11	-4.39	43.50	55.85	9.10	2.19	28.03	---	---	Peak
3	255.120	42.93	-3.07	46.00	54.81	13.18	2.78	27.84	---	---	Peak
4	516.280	38.65	-7.35	46.00	45.39	18.50	3.98	29.22	---	---	Peak
5	652.240	39.61	-6.39	46.00	44.56	19.64	4.61	29.20	---	---	Peak
6	860.860	36.22	-9.78	46.00	39.12	20.88	5.37	29.15	---	---	Peak

Note:


The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


Final Test Date	Jun. 24, 2010	Test Site No.	03CH03-HY
Temperature	25.8	Humidity	51%
Test Engineer	Eddie	Configuration	Mode 2

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	35.680	28.94	-11.06	40.00	41.32	14.94	0.83	28.15	---	---	Peak
2	153.640	40.42	-3.08	43.50	55.84	10.31	2.11	27.83	---	---	Peak
3	255.240	42.81	-3.19	46.00	54.69	13.18	2.78	27.84	---	---	Peak
4	525.680	40.89	-5.11	46.00	47.42	18.74	4.02	29.28	---	---	Peak
5	622.520	40.29	-5.71	46.00	45.84	19.45	4.60	29.60	---	---	Peak
6	824.320	42.14	-3.86	46.00	45.43	20.79	5.20	29.29	---	---	Peak

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	52.430	26.23	-13.77	40.00	45.38	7.69	1.13	27.97	---	---	Peak
2	186.840	40.28	-3.22	43.50	56.97	9.15	2.25	28.10	---	---	Peak
3	255.120	42.93	-3.07	46.00	54.81	13.18	2.78	27.84	---	---	Peak
4	514.590	36.79	-9.21	46.00	43.57	18.45	3.98	29.21	---	---	Peak
5	653.840	40.48	-5.52	46.00	45.42	19.66	4.61	29.21	---	---	Peak
6	862.430	36.95	-9.05	46.00	39.85	20.89	5.37	29.16	---	---	Peak

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.5.9 Results for Radiated Emissions (1GHz~10th Harmonic)

Final Test Date	Jun. 24, 2010	Test Site No.	03CH03-HY
Temperature	25.8	Humidity	51%
Test Engineer	Eddie	Configuration	802.11b Ch. 1


Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg	
1	4824.000	47.06	-6.94	54.00	43.59	33.06	2.70	32.28	---	PK
2	7236.000	49.54			42.06	35.53	4.55	32.61	---	Peak
3	9648.000	52.79			41.34	38.41	5.32	32.28	---	Peak

Note: The item 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	4823.900	56.50	-17.50	74.00	53.03	33.06	2.70	32.28	---	---	Peak
2	4823.900	44.60	-9.40	54.00	41.13	33.06	2.70	32.28	---	---	Average
3	7236.000	48.19			40.71	35.53	4.55	32.61	---	---	Peak
4	9648.000	53.40			41.95	38.41	5.32	32.28	---	---	Peak

Note: The item 3 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Final Test Date	Jun. 24, 2010	Test Site No.	03CH03-HY
Temperature	25.8	Humidity	51%
Test Engineer	Eddie	Configuration	802.11b Ch. 6


Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	4874.000	47.14	-6.86	54.00	43.71	33.16	2.60	32.33	---	---	PK
2	7311.000	50.52	-3.48	54.00	42.67	35.68	4.65	32.48	---	---	PK
3	9748.000	53.27			41.57	38.62	5.42	32.33	---	---	Peak

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	4874.000	52.61	-21.39	74.00	49.18	33.16	2.60	32.33	---	---	Peak
2	4874.000	44.16	-9.84	54.00	40.73	33.16	2.60	32.33	---	---	Average
3	7311.000	48.77	-5.23	54.00	40.92	35.68	4.65	32.48	---	---	PK
4	9748.000	52.65			40.95	38.62	5.42	32.33	---	---	Peak

Note: The item 4 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Final Test Date	Jun. 24, 2010	Test Site No.	03CH03-HY
Temperature	25.8	Humidity	51%
Test Engineer	Eddie	Configuration	802.11b Ch. 11


Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna	Cable	Preamp	Ant	Table		
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	4924.000	44.86	-9.14	54.00	41.42	33.26	2.56	32.38	---	---	PK
2	7386.000	50.79	-3.21	54.00	42.47	35.87	4.75	32.30	---	---	PK
3	9848.000	54.76			42.87	38.79	5.49	32.38	---	---	Peak

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	4924.000	51.46	-22.54	74.00	48.02	33.26	2.56	32.38	---	---	Peak
2	4924.000	43.36	-10.64	54.00	39.92	33.26	2.56	32.38	---	---	Average
3	7386.000	50.32	-3.68	54.00	42.00	35.87	4.75	32.30	---	---	PK
4	9848.000	53.92			42.03	38.79	5.49	32.38	---	---	Peak

Note: The item 4 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Final Test Date	Jun. 24, 2010	Test Site No.	03CH03-HY
Temperature	25.8	Humidity	51%
Test Engineer	Eddie	Configuration	802.11g Ch. 1


Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	4824.000	44.44	-9.56	54.00	40.97	33.06	2.70	32.28	---	---	PK
2	7236.000	48.24			40.76	35.53	4.55	32.61	---	---	Peak
3	9648.000	52.84			41.39	38.41	5.32	32.28	---	---	Peak

Note: The item 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	4824.000	46.47	-7.53	54.00	43.00	33.06	2.70	32.28	---	---	PK
2	7236.000	48.67			41.19	35.53	4.55	32.61	---	---	Peak
3	9648.000	52.84			41.39	38.41	5.32	32.28	---	---	Peak

Note: The item 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Final Test Date	Jun. 24, 2010	Test Site No.	03CH03-HY
Temperature	25.8	Humidity	51%
Test Engineer	Eddie	Configuration	802.11g Ch. 6


Horizontal



	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	4874.000	46.39	-7.61	54.00	42.96	33.16	2.60	32.33	---	---	PK
2	7311.000	55.58	-18.42	74.00	47.73	35.68	4.65	32.48	---	---	Peak
3	7311.000	43.00	-11.00	54.00	35.15	35.68	4.65	32.48	---	---	Average
4	9748.000	53.37			41.67	38.62	5.42	32.33	---	---	Peak

Note: The item 4 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	4874.000	53.24	-20.76	74.00	49.81	33.16	2.60	32.33	---	---	Peak
2	4874.000	41.06	-12.94	54.00	37.63	33.16	2.60	32.33	---	---	Average
3	7311.000	53.25	-20.75	74.00	45.40	35.68	4.65	32.48	---	---	Peak
4	7311.000	41.14	-12.86	54.00	33.29	35.68	4.65	32.48	---	---	Average
5	9748.000	53.44			41.74	38.62	5.42	32.33	---	---	Peak

Note: The item 5 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Final Test Date	Jun. 24, 2010	Test Site No.	03CH03-HY
Temperature	25.8	Humidity	51%
Test Engineer	Eddie	Configuration	802.11g Ch. 11


Horizontal



	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg	Remark
1	4924.000	45.03	-8.97	54.00	41.59	33.26	2.56	32.38	---	PK
2	7386.000	49.17	-4.83	54.00	40.85	35.87	4.75	32.30	---	PK
3	9848.000	53.45			41.56	38.79	5.49	32.38	---	Peak

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Rnt Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	4924.000	46.52	-7.48	54.00	43.08	33.26	2.56	32.38	---	---	PK
2	7386.000	49.31	-4.69	54.00	40.99	35.87	4.75	32.30	---	---	PK
3	9848.000	53.06			41.17	38.79	5.49	32.38	---	---	Peak

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.6 Band Edge and Fundamental Emissions Measurement

3.6.1 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.6.2 Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak

3.6.3 Test Procedures

1. The test procedure is the same as section 3.5.3; only the frequency range investigated is limited to 100MHz around band edges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

3.6.4 Test Setup Layout

This test setup layout is the same as that shown in section 3.5.4.

3.6.5 Test Deviation

There is no deviation with the original standard.

3.6.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.6.7 Test Result of Band Edge and Fundamental Emissions

Final Test Date	Jun. 24, 2010	Test Site No.	03CH03-HY
Temperature	25.8	Humidity	51%
Test Engineer	Eddie	Configuration	802.11b Ch. 1, 6, 11

Channel 1

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	2390.000	61.80	-12.20	74.00	31.08	28.13	2.58	0.00	---	---	Peak
2 @	2410.700	119.78			89.03	28.16	2.58	0.00	---	---	Peak
1 @	2331.850	50.36	-3.64	54.00	19.79	28.02	2.54	0.00	---	---	Average
2 @	2411.460	111.65			80.90	28.16	2.58	0.00	---	---	Average

The item 2 is Fundamental Emissions.

Channel 6

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 @	2438.250	117.79			86.97	28.22	2.61	0.00	---	---	Peak
1 @	2438.820	109.33			78.51	28.22	2.61	0.00	---	---	Average

The item 1 is Fundamental Emissions.

Channel 11

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 @	2462.570	118.76			87.89	28.24	2.63	0.00	---	---	Peak
2	2483.500	59.66	-14.34	74.00	28.76	28.27	2.63	0.00	---	---	Peak
1 @	2462.380	110.73			79.86	28.24	2.63	0.00	---	---	Average
2 @	2483.500	47.89	-6.11	54.00	16.99	28.27	2.63	0.00	---	---	Average

The item 1 is Fundamental Emissions.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Final Test Date	Jun. 24, 2010	Test Site No.	03CH03-HY
Temperature	25.8	Humidity	51%
Test Engineer	Eddie	Configuration	802.11g Ch. 1, 6, 11

Channel 1

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 ☒	2390.000	70.39	-3.61	74.00	39.67	28.13	2.58	0.00	---	---	Peak
2 ☒	2415.260	109.14			78.37	28.16	2.61	0.00	---	---	Peak
1 ☒	2390.000	50.12	-3.88	54.00	19.40	28.13	2.58	0.00	---	---	Average
2 ☒	2414.690	98.48			67.71	28.16	2.61	0.00	---	---	Average

The item 2 is Fundamental Emissions.

Channel 6

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 ☒	2433.500	118.53			87.73	28.19	2.61	0.00	---	---	Peak
1 ☒	2433.690	107.92			77.12	28.19	2.61	0.00	---	---	Average

The item 1 is Fundamental Emissions.

Channel 11

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 ☒	2464.850	112.10			81.23	28.24	2.63	0.00	---	---	Peak
2 ☒	2483.660	72.68	-1.32	74.00	41.78	28.27	2.63	0.00	---	---	Peak
1 ☒	2467.700	101.09			70.22	28.24	2.63	0.00	---	---	Average
2 ☒	2483.500	53.03	-0.97	54.00	22.13	28.27	2.63	0.00	---	---	Average

The item 1 is Fundamental Emissions.

Note:


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Emission not in Restricted Band


Final Test Date	May 23, 2010	Test Site No.	TH01-HY
Temperature	26	Humidity	52%
Test Engineer	Ian	Configuration	802.11b/g

Low Band Edge Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 23.MAY.2010 19:03:21

High Band Edge Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 23.MAY.2010 18:56:59

Low Band Edge Plot on Configuration IEEE 802.11g / 2412 MHz



Date: 23.MAY.2010 19:13:38

High Band Edge Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 23.MAY.2010 19:23:46

3.7 Antenna Requirements

3.7.1 Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

3.7.2 Antenna Connector Construction

Please refer to section 2.3 in this test report; antenna connector complied with the requirements.

4 LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Receiver	R&S	ESCS 30	100357	9 kHz - 2.75 GHz	Nov. 10, 2009	Conduction (CO01-NH)
LISN	SCHAFFNER	NNB 41	04/10153	9kHz – 30MHz	Nov. 26, 2009	Conduction (CO01-NH)
Power Filter	CORCOM	MR12030	N/A	30A*2	N/A	Conduction (CO01-NH)
RF Cable-CON	Suhner Switzerland	RG223/U	CB004	9kHz – 30MHz	Dec. 15, 2009	Conduction (CO01-NH)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 18, 2010	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 24, 2010	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	Jul. 21, 2009	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100004	9 kHz - 40 GHz	Oct. 03, 2009	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Sep. 26, 2009	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	May 20, 2010	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan.11, 2010	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Jan. 05, 2010	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Jan. 05, 2010	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	Jul. 28, 2008*	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is two year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSU26.5	100015	20Hz ~ 26.5GHz	Oct. 29, 2009	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jul. 31, 2009	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Apr. 16, 2010	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20-S	MAB0103-001	N/A	Aug. 06, 2009	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 02, 2009	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 02, 2009	Conducted (TH01-HY)
Power Sensor	Anritsu	MA2411B	0917017	300MHz~40GHz	Dec. 03, 2009	Conducted (TH01-HY)
Power Meter	Anritsu	ML2495A	0949003	300MHz~40GHz	Dec. 03, 2009	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	Jul. 12, 2009*	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is two year.

5 TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

6 TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-100529

財團法人全國認證基金會
Taiwan Accreditation Foundation


Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2010 to January 09, 2013
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities



Jay-San Chen
President, Taiwan Accreditation Foundation
Date : May 29, 2010

PI, total 23 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix