



# SPORTON International Inc.

No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.  
Ph: 886-3-656-9065 / FAX: 886-3-656-9085 / www.sporton.com.tw

## FCC RADIO TEST REPORT

Applicant's company	NETGEAR, Inc.
Applicant Address	350 East Plumeria Drive, San Jose, California 95134-1911
FCC ID	PY312300208

Product Name	Universal Dual Band Wi-Fi Extender
Brand Name	NETGEAR
Model No.	WN3500RP
Test Rule Part(s)	47 CFR FCC Part 15 Subpart E § 15.407
Test Freq. Range	5250 ~ 5350MHz / 5470 ~ 5725MHz
Received Date	Jul. 30, 2012
Final Test Date	Jul. 08, 2013
Submission Type	Class II Change
Operating Mode	Master / Client (without radar detection function)

### Statement

Test result included is for the IEEE 802.11n and IEEE 802.11a (5250 ~ 5350MHz / 5470 ~ 5725MHz) of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in ANSI C63.10-2009, 47 CFR FCC Part 15 Subpart E, KDB 789033 D01 v01r03 and KDB 662911 D01 v02.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



## Table of Contents

<b>1. CERTIFICATE OF COMPLIANCE .....</b>	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT .....</b>	<b>2</b>
<b>3. GENERAL INFORMATION .....</b>	<b>3</b>
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies .....	6
3.5. Table for Product Information .....	6
3.6. Table for Test Modes .....	7
3.7. Table for Testing Locations.....	8
3.8. Class II Change .....	9
3.9. Table for Supporting Units .....	9
3.10. Table for Parameters of Test Software Setting .....	10
3.11. EUT Operation during Test .....	10
3.12. Duty Cycle .....	11
3.13. Test Configurations .....	13
<b>4. TEST RESULT .....</b>	<b>15</b>
4.1. AC Power Line Conducted Emissions Measurement.....	15
4.2. 26dB Bandwidth & 99% Occupied Bandwidth Measurement.....	19
4.3. Maximum Conducted Output Power Measurement.....	32
4.4. Power Spectral Density Measurement .....	36
4.5. Peak Excursion Measurement .....	43
4.6. Radiated Emissions Measurement .....	49
4.7. Band Edge Emissions Measurement .....	72
4.8. Frequency Stability Measurement .....	80
4.9. Antenna Requirements .....	82
<b>5. LIST OF MEASURING EQUIPMENTS .....</b>	<b>83</b>
<b>6. TEST LOCATION.....</b>	<b>85</b>
<b>7. MEASUREMENT UNCERTAINTY.....</b>	<b>86</b>
<b>APPENDIX A. TEST PHOTOS .....</b>	<b>A1 ~ A5</b>
<b>APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE .....</b>	<b>B1 ~ B3</b>
<b>APPENDIX C. CO-LOCATION.....</b>	<b>C1 ~ C3</b>
<b>APPENDIX D. 20DB BANDWIDTH REPORT .....</b>	<b>D1 ~ D4</b>




## History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR282215-02	Rev. 01	Initial issue of report	Aug. 09, 2013

## 1. CERTIFICATE OF COMPLIANCE

Product Name : Universal Dual Band WI-FI Extender  
Brand Name : NETGEAR  
Model No. : WN3500RP  
Applicant : NETGEAR, Inc.  
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart E § 15.407

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jul. 30, 2012 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart E				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	0.86 dB
4.2	15.407(a)	26dB Spectrum Bandwidth & 99% Occupied Bandwidth	Complies	-
4.3	15.407(a)	Maximum Conducted Output Power	Complies	0.02dB
4.4	15.407(a)	Power Spectral Density	Complies	4.46 dB
4.5	15.407(a)	Peak Excursion	Complies	2.88 dB
4.6	15.407(b)	Radiated Emissions	Complies	0.22 dB
4.7	15.407(b)	Band Edge Emissions	Complies	0.20 dB
4.8	15.407(g)	Frequency Stability	Complies	-
4.9	15.203	Antenna Requirements	Complies	-

### 3. GENERAL INFORMATION

#### 3.1. Product Details

##### IEEE 802.11n

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Internal DC Power
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	5250 ~ 5350MHz / 5470 ~ 5725MHz
Channel Number	12 for 20MHz bandwidth ; 5 for 40MHz bandwidth
Channel Band Width (99%)	MCS0 (20MHz): 38.88 MHz ; MCS0 (40MHz): 45.76 MHz
Conducted Output Power	Band 2: MCS0 (20MHz): 23.86 dBm ; MCS0 (40MHz): 23.98 dBm Band 3: MCS0 (20MHz): 22.51 dBm ; MCS0 (40MHz): 23.20 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

##### IEEE 802.11a

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Internal DC Power
Modulation	OFDM for IEEE 802.11a
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	OFDM (6/9/12/18/24/36/48/54)
Frequency Range	5250 ~ 5350MHz / 5470 ~ 5725MHz
Channel Number	12
Channel Band Width (99%)	11a: 22.88 MHz
Conducted Output Power	Band 2: 23.88 dBm ; Band 3: 22.14 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

**Antenna & Band width**

Antenna	Two (TX)	
Band width Mode	20 MHz	40 MHz
IEEE 802.11a	V	X
IEEE 802.11n	V	V

**IEEE 11n Spec.**

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	2	M0-15
802.11n (HT40)	2	M0-15

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20 and HT40.

Note 2: Modulation modes consist of below configuration:  
HT20/HT40: IEEE 802.11n

**3.2. Accessories**

Internal DC Power	Brand	Model	P/N	Rating
Power 1	LEI	SU18-9120150-I3	114-002-001	INPUT: 100-240V~50/60Hz 0.6A OUTPUT: 12V 1.5A
Power 2	AM	T99B109.00	114-0023-001	Input: 100-240V~50-60Hz, 0.5A OUTPUT:12V 1.65A
<b>Others</b>				
Cradle*1				
FCC Plug*1				
FCC Power Cable*1, Non-shielded, 1.4 m				

### 3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	
					2.4GHz	5GHz
1	Foxconn	-	PCB Antenna	I-PEX	1.52 dBi	-
2	Foxconn	-	PCB Antenna	I-PEX	-0.92 dBi	-
3	Foxconn	-	PCB Antenna	I-PEX	1.45 dBi	2.93 dBi
4	Foxconn	-	PCB Antenna	I-PEX	0.86 dBi	2.94 dBi

Note: The EUT has two RF Chips.

One is 2.4GHz Band Only. (eth1)

The other is 2.4GHz+5GHz Band. (eth2)

The EUT has four antennas.


< For 5GHz Band: >

**For IEEE 802.11n mode (2TX/2RX):**

Chain 3 and Chain 4 could transmit/receive simultaneously.

**For IEEE 802.11a mode (2TX/2RX):**

Chain 3 and Chain 4 could transmit/receive simultaneously.



### 3.4. Table for Carrier Frequencies

The EUT has two bandwidth system.

For 20MHz bandwidth systems, use Channel 52, 56, 60, 64, 100, 104, 108, 112, 116, 132, 136, 140.

For 40MHz bandwidth systems, use Channel 54, 62, 102, 110, 134.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5250~5350 MHz Band 2	52	5260 MHz	60	5300 MHz
	54	5270 MHz	62	5310 MHz
	56	5280 MHz	64	5320 MHz
5470~5725 MHz Band 3	100	5500 MHz	116	5580 MHz
	102	5510MHz	132	5660 MHz
	104	5520 MHz	134	5670 MHz
	108	5540 MHz	136	5680 MHz
	110	5550 MHz	140	5700 MHz
	112	5560 MHz	-	-

### 3.5. Table for Product Information

Items	Description			
Communication Mode	<input checked="" type="checkbox"/>	IP Based (Load Based)	<input type="checkbox"/>	Frame Based
TPC Function	<input checked="" type="checkbox"/>	With TPC	<input type="checkbox"/>	Without TPC
Weather Band (5600~5650MHz)	<input type="checkbox"/>	With 5600~5650MHz	<input checked="" type="checkbox"/>	Without 5600~5650MHz
Beamforming Function	<input type="checkbox"/>	With beamforming	<input checked="" type="checkbox"/>	Without beamforming

### 3.6. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode		Data Rate	Channel	Chain
AC Power Conducted Emission	Normal Link		-	-	-
Max. Conducted Output Power	11n 20MHz	Band 2	MCS0	52/60/64	3+4
		Band 3	MCS0	100/116/140	3+4
	11n 40MHz	Band 2	MCS0	54/62	3+4
		Band 3	MCS0	102/110/134	3+4
	11a/BPSK	Band 2	6Mbps	52/60/64	3+4
		Band 3	6Mbps	100/116/140	3+4
Power Spectral Density	11n 20MHz	Band 2	MCS0	52/60/64	3+4
		Band 3	MCS0	100/116/140	3+4
	11n 40MHz	Band 2	MCS0	54/62	3+4
		Band 3	MCS0	102/110/134	3+4
	11a/BPSK	Band 2	6Mbps	52/60/64	3+4
		Band 3	6Mbps	100/116/140	3+4
26dB Spectrum Bandwidth 99% Occupied Bandwidth Measurement	11n 20MHz	Band 2	MCS0	52/60/64	3+4
		Band 3	MCS0	100/116/140	3+4
	11n 40MHz	Band 2	MCS0	54/62	3+4
		Band 3	MCS0	102/110/134	3+4
	11a/BPSK	Band 2	6Mbps	52/60/64	3+4
		Band 3	6Mbps	100/116/140	3+4
Peak Excursion	11n 20MHz	Band 2	MCS0	52/60/64	3+4
		Band 3	MCS0	100/116/140	3+4
	11n 40MHz	Band 2	MCS0	54/62	3+4
		Band 3	MCS0	102/110/134	3+4
	11a/BPSK	Band 2	6Mbps	52/60/64	3+4
		Band 3	6Mbps	100/116/140	3+4
Radiated Emission Below 1GHz	Normal Link		-	-	-

Radiated Emission Above 1GHz	11n 20MHz	Band 2	MCS0	52/60/64	3+4
		Band 3	MCS0	100/116/140	3+4
	11n 40MHz	Band 2	MCS0	46/54/62	3+4
		Band 3	MCS0	102/110/134	3+4
	11a/BPSK	Band 2	6Mbps	52/60/64	3+4
		Band 3	6Mbps	100/116/140	3+4
Band Edge Emission	11n 20MHz	Band 2	MCS0	52/60/64	3+4
		Band 3	MCS0	100/116/140	3+4
	11n 40MHz	Band 2	MCS0	54/62	3+4
		Band 3	MCS0	102/110/134	3+4
	11a/BPSK	Band 2	6Mbps	52/60/64	3+4
		Band 3	6Mbps	100/116/140	3+4
Frequency Stability	Un-modulation		-	60	N/A

The following test modes were performed for all tests:

**For Conducted Emission test:**

Mode 1. Power 1 + Power Cable

Mode 2. Power 2 + Power Cable

Due to Mode 1 generated the worst test result, so it was recorded in this report.

**For Radiated Emission Below 1GHz test:**

Mode 1. Power 1 + Power Cable

Mode 2. Power 2 + Power Cable

Due to Mode 1 generated the worst test result, so it was recorded in this report.

**For Radiated Emission Above 1GHz test:**

Mode 1: CTX

**<For MPE and Co-location Test>:**

The EUT could be applied with 2.4GHz WLAN function and 5GHz WLAN function; therefore Maximum Permissible Exposure (Please refer to Appendix B) and Co-location (please refer to Appendix C) tests are added for simultaneously transmit between 2.4GHz WLAN function and 5GHz WLAN function.

### 3.7. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D	-
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D	-
TH01-CB	OVEN Room	Hsin Chu	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Please refer section 6 for Test Site Address.

### 3.8. Class II Change

This product is an extension of original one reported under Sporton project number: FR282215.

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
Add Band 2 and Band 3 (5250~5350 MHz, 5470~5725 MHz) for this device.	1. AC Power Line Conducted Emissions 2. 26dB Spectrum Bandwidth 3. Maximum Conducted Output Power 4. Power Spectral Density 5. Peak Excursion 6. Radiated Emissions Below 30MHz~1GHz Above 1GHz 7. Band Edge Emissions 8. Frequency Stability

### 3.9. Table for Supporting Units

< AC Power Line Conduction Emissions and Radiation Emissions (30MHz~1GHz) >

Support Unit	Brand	Model	FCC ID
Printer	EPSON	LQ-300+	N/A
Wireless AP	BELKIN	GW-AP54SGX	N/A
Notebook	DELL	D505	E2KWM3945ABG
Notebook	DELL	D505	E2KWM3945ABG
Notebook	DELL	D505	E2KWM3945ABG
Earphone	SHYARO CHI	MIC-04	DoC

< Radiation Emissions (above 1G) >

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D505	E2KWM3945ABG

< TH-01 >

Support Unit	Brand	Model	FCC ID
Notebook	DELL	M1330	E2K24GBRL

### 3.10. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

#### Power Parameters of IEEE 802.11n MCS0 20MHz

Test Software Version	Manual Tool Version: 1.0.0.10					
Frequency	5260 MHz	5300 MHz	5320 MHz	5500 MHz	5580 MHz	5700 MHz
MCS0 20MHz	86	86	75	64	76	50

#### Power Parameters of IEEE 802.11n MCS0 40MHz

Test Software Version	Manual Tool Version: 1.0.0.10				
Frequency	5270 MHz	5310 MHz	5510 MHz	5550 MHz	5670 MHz
MCS0 40MHz	86	61	50	79	63

#### Power Parameters of IEEE 802.11a

Test Software Version	Manual Tool Version: 1.0.0.10					
Frequency	5260 MHz	5300 MHz	5320 MHz	5500 MHz	5580 MHz	5700 MHz
11a	86	86	78	66	75	57


During the test, "Manual Tool Version: 1.0.0.10" under WIN XP was executed the test program to control the EUT continuously transmit RF signal.

### 3.11. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


### 3.12. Duty Cycle

#### IEEE 802.11n MCS0 20MHz




Date: 31.JUL.2012 14:27:21

#### IEEE 802.11n MCS0 40MHz



Date: 31.JUL.2012 14:33:10


IEEE 802.11a



Date: 31.JUL.2012 14:21:03


### 3.13. Test Configurations

#### 3.13.1.AC Power Line Conduction Emissions and Radiation Emissions (30MHz~1GHz) test Configuration



Item	Connection	Shield	Length
1	Power cable	No	1.4m
2	USB cable	No	1.8m
3	RJ-45 cable	No	10m
4	Earphone cable	No	1.1m

### 3.13.2. Radiation Emissions (above 1GHz) Test Configuration



Item	Connection	Shield	Length
1	Power cable	No	1.4m
2	RJ-45 cable	No	10m

## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product that is designed to connect to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

#### 4.1.4. Test Setup Layout



#### LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50  $\Omega$ . LISN can be placed on top of, or immediately beneath, reference ground plane.
  - (3.1) All other equipment powered from additional LISN(s).
  - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
  - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

#### 4.1.5. Test Deviation


There is no deviation with the original standard.

#### 4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	25°C	Humidity	56%
Test Engineer	Kane Liu	Phase	Line
Configuration	Normal Link	Test Mode	Mode 1



	Freq	Level	Over	Limit	Read	LISN	Cable		
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Pol/Phase	Remark
			dB	dBuV	dBuV	dB	dB		
1	0.31163	34.31	-15.62	49.93	33.96	0.15	0.20	LINE	AVERAGE
2	0.31163	43.16	-16.77	59.93	42.81	0.15	0.20	LINE	QP
3	0.33562	51.95	-7.36	59.31	51.60	0.15	0.20	LINE	QP
4	0.33562	48.36	-0.95	49.31	48.01	0.15	0.20	LINE	AVERAGE
5	0.36338	44.87	-3.78	48.65	44.52	0.15	0.20	LINE	AVERAGE
6	0.36338	49.78	-8.87	58.65	49.43	0.15	0.20	LINE	QP
7	2.869	33.75	-12.25	46.00	33.35	0.20	0.20	LINE	AVERAGE
8	2.869	43.54	-12.46	56.00	43.14	0.20	0.20	LINE	QP
9	3.090	34.18	-11.82	46.00	33.75	0.21	0.22	LINE	AVERAGE
10	3.090	44.59	-11.41	56.00	44.16	0.21	0.22	LINE	QP
11	3.241	44.61	-11.39	56.00	44.15	0.21	0.25	LINE	QP
12	3.241	35.04	-10.96	46.00	34.58	0.21	0.25	LINE	AVERAGE

Temperature	25°C	Humidity	56%
Test Engineer	Kane Liu	Phase	Neutral
Configuration	Normal Link	Test Mode	Mode 1



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.30509	38.93	-11.17	50.10	38.65	0.08	0.20	NEUTRAL	AVERAGE
2	0.30509	44.77	-15.33	60.10	44.49	0.08	0.20	NEUTRAL	QP
3	0.33385	48.49	-0.86	49.35	48.21	0.08	0.20	NEUTRAL	AVERAGE
4	0.33385	51.90	-7.45	59.35	51.62	0.08	0.20	NEUTRAL	QP
5	0.35765	41.10	-7.68	48.78	40.82	0.08	0.20	NEUTRAL	AVERAGE
6	0.35765	44.21	-14.57	58.78	43.93	0.08	0.20	NEUTRAL	QP
7	1.959	32.44	-13.56	46.00	32.14	0.11	0.19	NEUTRAL	AVERAGE
8	1.959	40.44	-15.56	56.00	40.14	0.11	0.19	NEUTRAL	QP
9	2.309	39.62	-16.38	56.00	39.31	0.11	0.20	NEUTRAL	QP
10	2.309	33.54	-12.46	46.00	33.23	0.11	0.20	NEUTRAL	AVERAGE
11	2.707	31.99	-14.01	46.00	31.67	0.12	0.20	NEUTRAL	AVERAGE
12	2.707	39.20	-16.80	56.00	38.88	0.12	0.20	NEUTRAL	QP
13	2.884	42.47	-13.53	56.00	42.15	0.12	0.20	NEUTRAL	QP
14	2.884	34.06	-11.94	46.00	33.74	0.12	0.20	NEUTRAL	AVERAGE
15	3.041	34.86	-11.14	46.00	34.53	0.12	0.21	NEUTRAL	AVERAGE
16	3.041	43.95	-12.05	56.00	43.62	0.12	0.21	NEUTRAL	QP
17	3.190	44.17	-11.83	56.00	43.81	0.12	0.24	NEUTRAL	QP
18	3.190	33.49	-12.51	46.00	33.13	0.12	0.24	NEUTRAL	AVERAGE
19	14.828	33.85	-16.15	50.00	33.14	0.31	0.40	NEUTRAL	AVERAGE
20	14.828	39.66	-20.34	60.00	38.95	0.31	0.40	NEUTRAL	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.

## 4.2. 26dB Bandwidth & 99% Occupied Bandwidth Measurement

### 4.2.1. Limit

No restriction limits.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

26dB Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 26dB Bandwidth
RBW	Approximately 1% of the emission bandwidth
VBW	VBW > RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto
99% Occupied Bandwidth	
Spectrum Parameters	Setting
Span	1.5 times to 5.0 times the OBW
RBW	1 % to 5 % of the OBW
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold

### 4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

#### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Test Result of 26dB Bandwidth & 99% Occupied Bandwidth

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Benson Peng	<b>Configurations</b>	IEEE 802.11n

##### Configuration IEEE 802.11n MCS0 20MHz / Chain 3 + Chain 4

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
52	5260 MHz	43.04	25.44
60	5300 MHz	42.56	24.96
64	5320 MHz	30.24	18.24
100	5500 MHz	23.04	18.24
116	5580 MHz	38.88	22.24
140	5700 MHz	20.16	17.76

##### Configuration IEEE 802.11n MCS0 40MHz / Chain 3 + Chain 4


Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
54	5270 MHz	77.76	45.12
62	5310 MHz	38.72	36.16
102	5510MHz	38.40	36.84
110	5550 MHz	73.28	45.76
134	5670 MHz	41.60	36.16

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Benson Peng	<b>Configurations</b>	IEEE 802.11a

**Configuration IEEE 802.11a / Chain 3 + Chain 4**


Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
52	5260 MHz	39.20	21.92
60	5300 MHz	36.96	22.88
64	5320 MHz	31.20	17.92
100	5500 MHz	21.44	17.44
116	5580 MHz	35.84	19.52
140	5700 MHz	19.84	16.96

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Chain 3 + Chain 4 / 5260 MHz




Date: 15.AUG.2012 23:36:11

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Chain 3 + Chain 4 / 5300 MHz




Date: 15.AUG.2012 23:35:37

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Chain 3 + Chain 4 / 5320 MHz




Date: 15.AUG.2012 23:34:59

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Chain 3 + Chain 4 / 5500 MHz




Date: 15.AUG.2012 23:34:03

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Chain 3 + Chain 4 / 5580 MHz




Date: 15.AUG.2012 23:33:28

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Chain 3 + Chain 4 / 5700 MHz




Date: 15.AUG.2012 23:32:48

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / Chain 3 + Chain 4 / 5270 MHz




Date: 15.AUG.2012 23:29:05

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / Chain 3 + Chain 4 / 5310 MHz




Date: 15.AUG.2012 23:30:09

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / Chain 3 + Chain 4 / 5510MHz




Date: 15.AUG.2012 23:30:41

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / Chain 3 + Chain 4 / 5550 MHz




Date: 15.AUG.2012 23:31:17

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / Chain 3 + Chain 4 / 5670 MHz




Date: 15.AUG.2012 23:32:03

26 dB Bandwidth Plot on Configuration IEEE 802.11a / Chain 3 + Chain 4 / 5260 MHz




Date: 15.AUG.2012 23:39:55

26 dB Bandwidth Plot on Configuration IEEE 802.11a / Chain 3 + Chain 4 / 5300 MHz




Date: 15.AUG.2012 23:40:19

26 dB Bandwidth Plot on Configuration IEEE 802.11a / Chain 3 + Chain 4 / 5320 MHz




Date: 15.AUG.2012 23:40:49

26 dB Bandwidth Plot on Configuration IEEE 802.11a / Chain 3 + Chain 4 / 5500 MHz




Date: 15.AUG.2012 23:41:30

26 dB Bandwidth Plot on Configuration IEEE 802.11a / Chain 3 + Chain 4 / 5580 MHz



Date: 15.AUG.2012 23:41:59

26 dB Bandwidth Plot on Configuration IEEE 802.11a / Chain 3 + Chain 4 / 5700 MHz



Date: 15.AUG.2012 23:42:30

### 4.3. Maximum Conducted Output Power Measurement

#### 4.3.1. Limit

For the 5.25-5.35 GHz and 5.470-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW (24dBm) or  $11 \text{ dBm} + 10 \log B$ , where B is the 26-dB emission bandwidth in MHz. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725~5.825 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 1 W or  $17 \text{ dBm} + 10 \log B$ , where B is the 26-dB emission bandwidth in MHz. In addition, the peak power spectral density shall not exceed 17 dBm in any 1 MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain up to 23 dBi without any corresponding reduction in the transmitter peak output power or peak power spectral density. For fixed, point-to-point U-NII transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in peak transmitter power and peak power spectral density for each 1 dB of antenna gain in excess of 23 dBi would be required.

#### 4.3.2. Measuring Instruments and Setting


The following table is the setting of the peak power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	AVERAGE

### 4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Test was performed in accordance with KDB 789033 D01 v01r03 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - Part 15, Subpart E, section (E) Maximum conducted output power =>(3) Method PM (Measurement using an RF average power meter) Multiple antenna systems was performed in accordance with KDB 662911 D01 v02 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
3. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

### 4.3.4. Test Setup Layout



### 4.3.5. Test Deviation

There is no deviation with the original standard.

### 4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.3.7. Test Result of Maximum Conducted Output Power

Temperature	25°C	Humidity	56%
Test Engineer	Benson Peng	Configurations	IEEE 802.11n
Test Date	Aug. 15, 2012		

##### Configuration IEEE 802.11n MCS0 20MHz / Chain 3 + Chain 4

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 3	Chain 4			
52	5260 MHz	21.23	20.43	23.86	24.00	Complies
60	5300 MHz	21.11	20.32	23.74	24.00	Complies
64	5320 MHz	18.65	17.51	21.13	24.00	Complies
100	5500 MHz	16.28	16.93	19.63	24.00	Complies
116	5580 MHz	19.27	19.71	22.51	24.00	Complies
140	5700 MHz	12.81	13.48	16.17	24.00	Complies

##### Configuration IEEE 802.11nMCS0 40MHz / Chain 3 + Chain 4

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 3	Chain 4			
54	5270 MHz	21.05	20.88	23.98	24.00	Complies
62	5310 MHz	14.61	14.88	17.76	24.00	Complies
102	5510MHz	12.55	14.21	16.47	24.00	Complies
110	5550 MHz	19.71	20.62	23.20	24.00	Complies
134	5670 MHz	15.75	17.32	19.62	24.00	Complies

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Benson Peng	<b>Configurations</b>	IEEE 802.11a
<b>Test Date</b>	Aug. 15, 2012		

**Configuration IEEE 802.11a / Chain 3 + Chain 4**

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 3	Chain 4			
52	5260 MHz	21.35	20.33	23.88	24.00	<b>Complies</b>
60	5300 MHz	21.01	20.31	23.68	24.00	<b>Complies</b>
64	5320 MHz	19.18	18.38	21.81	24.00	<b>Complies</b>
100	5500 MHz	16.34	16.96	19.67	24.00	<b>Complies</b>
116	5580 MHz	18.72	19.51	22.14	24.00	<b>Complies</b>
140	5700 MHz	14.35	15.19	17.80	23.98	<b>Complies</b>

Note: Because 26dB Bandwidth < 20MHz , so the conducted power limit =  $11 + 10\log(19.86) = 23.98\text{dBm}$

## 4.4. Power Spectral Density Measurement

### 4.4.1. Limit

The power spectral density is defined as the highest level of power in dBm per MHz generated by the transmitter within the power envelope. The following table is power spectral density limits and decrease power density limit rule refer to section 4.3.1.

Frequency Range	Power Spectral Density limit (dBm/MHz)
5.25-5.35 GHz	11
5.470-5.725 GHz	11

### 4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	1000 kHz
VBW	3000 kHz
Detector	RMS
Trace	AVERAGE
Sweep Time	Auto
Trace Average	100 times

### 4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected RF switch to the spectrum analyzer.
2. Test was performed in accordance with KDB 789033 D01 v01r03 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - Part 15, Subpart E, section (C) Maximum conducted output power => (d) Method SA-2 (trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).
3. Multiple antenna systems was performed in accordance KDB 662911 D01 v02 in-Band Power Spectral Density (PSD) Measurements (a) Measure and sum the spectra across the outputs.
4. When measuring first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3 and so on up to the Nth output to obtain the value for the first frequency bin of the summed spectrum. The summed spectrum value for each of the other frequency bins is computed in the same way.

#### 4.4.4. Test Setup Layout



#### 4.4.5. Test Deviation

There is no deviation with the original standard.

#### 4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.4.7. Test Result of Power Spectral Density

Temperature	25°C	Humidity	56%
Test Engineer	Benson Peng	Configurations	IEEE 802.11n
Test Date	Aug. 15, 2012		

##### Configuration IEEE 802.11n MCS0 20MHz / Chain 3 + Chain 4

Channel	Frequency	Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
52	5260 MHz	6.15	11.00	Complies
60	5300 MHz	6.29	11.00	Complies
64	5320 MHz	3.67	11.00	Complies
100	5500 MHz	3.29	11.00	Complies
116	5580 MHz	6.12	11.00	Complies
140	5700 MHz	-1.94	11.00	Complies

##### Configuration IEEE 802.11n MCS0 40MHz / Chain 3 + Chain 4

Channel	Frequency	Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
54	5270 MHz	4.47	11.00	Complies
62	5310 MHz	-1.64	11.00	Complies
102	5510MHz	-1.88	11.00	Complies
110	5550 MHz	4.79	11.00	Complies
134	5670 MHz	0.45	11.00	Complies

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Benson Peng	<b>Configurations</b>	IEEE 802.11n
<b>Test Date</b>	Aug. 15, 2012		


**Configuration IEEE 802.11a / Chain 3 + Chain 4**

Channel	Frequency	Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
52	5260 MHz	6.24	11.00	<b>Complies</b>
60	5300 MHz	6.54	11.00	<b>Complies</b>
64	5320 MHz	4.65	11.00	<b>Complies</b>
100	5500 MHz	3.91	11.00	<b>Complies</b>
116	5580 MHz	6.21	11.00	<b>Complies</b>
140	5700 MHz	0.49	11.00	<b>Complies</b>


Note: All the test values were listed in the report.

For plots, only the channel with maximum results was shown.


Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Chain 3 + Chain 4 / 5300 MHz




Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Chain 3 + Chain 4 / 5580 MHz




Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / Chain 3 + Chain 4 / 5270 MHz




Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / Chain 3 + Chain 4 / 5550 MHz



Power Density Plot on Configuration IEEE 802.11a / Chain 3 + Chain 4 / 5300 MHz



Power Density Plot on Configuration IEEE 802.11a / Chain 3 + Chain 4 / 5580 MHz



## 4.5. Peak Excursion Measurement

### 4.5.1. Limit

The ratio of the peak excursion of the modulation envelope (measured using a peak hold function) to the maximum conducted output power (measured as specified above) shall not exceed 13 dB across any 1 MHz bandwidth or the emissions bandwidth whichever is less.

### 4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	1 MHz (Peak Trace) / 1 MHz (Average Trace)
VBW	≥ 3 MHz (Peak Trace) / ≥ 3 MHz (Average Trace)
Detector	Peak (Peak Trace) / RMS (Average Trace)
Trace	Trace: Max hold (Peak Trace) / Trace Average Sweep Count 100 (Average Trace)
Sweep Time	AUTO

### 4.5.3. Test Procedures

1. Trace A, Set RBW = 1MHz, VBW = 3MHz, Span >26dB bandwidth, Max. hold.
2. Delta Mark trace A Maximum frequency and trace B same frequency.
3. Repeat the above procedure until measurements for all frequencies were complete.
4. Testing each modulation mode on a single channel in single operating band at single output port. All signal types need test (DSSS, OFDM). All modulation types need test (BPSK, QPSK, 16-QAM, 64-QAM). All bandwidth modes need test.

### 4.5.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.4.4.

### 4.5.5. Test Deviation

There is no deviation with the original standard.

### 4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.5.7. Test Result of Peak Excursion

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Wen Chao	<b>Configurations</b>	IEEE 802.11n

##### Configuration IEEE 802.11n 20MHz / Chain 3 + Chain 4

Modulation	Frequency	Peak Excursion (dB)	Max. Limit (dB)	Result
BSPK(MCS0)	5260MHz	8.62	13	Complies
QPSK(MCS1)	5260MHz	8.91	13	Complies
16QAM(MCS3)	5260MHz	8.81	13	Complies
64QAM(MCS5)	5260MHz	9.60	13	Complies
BSPK(MCS0)	5580MHz	8.88	13	Complies
QPSK(MCS1)	5580MHz	8.77	13	Complies
16QAM(MCS3)	5580MHz	8.94	13	Complies
64QAM(MCS5)	5580MHz	9.03	13	Complies

##### Configuration IEEE 802.11n 40MHz / Chain 3 + Chain 4

Modulation	Frequency	Peak Excursion (dB)	Max. Limit (dB)	Result
BSPK(MCS0)	5270MHz	8.87	13	Complies
QPSK(MCS1)	5270MHz	8.60	13	Complies
16QAM(MCS3)	5270MHz	9.25	13	Complies
64QAM(MCS5)	5270MHz	9.38	13	Complies
BSPK(MCS0)	5550MHz	8.73	13	Complies
QPSK(MCS1)	5550MHz	8.91	13	Complies
16QAM(MCS3)	5550MHz	9.30	13	Complies
64QAM(MCS5)	5550MHz	9.54	13	Complies


<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Wen Chao	<b>Configurations</b>	IEEE 802.11a

**Configuration IEEE 802.11a / Chain 3 + Chain 4**

<b>Modulation</b>	<b>Frequency</b>	<b>Peak Excursion (dB)</b>	<b>Max. Limit (dB)</b>	<b>Result</b>
BSPK(6Mbps)	5260MHz	8.62	13	<b>Complies</b>
QPSK(12Mbps)	5260MHz	8.04	13	<b>Complies</b>
16QAM(24Mbps)	5260MHz	8.66	13	<b>Complies</b>
64QAM(48Mbps)	5260MHz	9.38	13	<b>Complies</b>
BSPK(6Mbps)	5580MHz	8.59	13	<b>Complies</b>
QPSK(12Mbps)	5580MHz	8.03	13	<b>Complies</b>
16QAM(24Mbps)	5580MHz	8.83	13	<b>Complies</b>
64QAM(48Mbps)	5580MHz	10.12	13	<b>Complies</b>


Note: Only the channel with maximum results was listed in the report.

**Peak Excursion Plot on Configuration IEEE 802.11n 20MHz / Chain 3 + Chain 4 / 64QAM(MCS5) / 5260MHz**




Date: 1.JUL.2013 21:15:42

**Peak Excursion Plot on Configuration IEEE 802.11n 20MHz / Chain 3 + Chain 4 / 64QAM(MCS5) / 5580MHz**




Date: 1.JUL.2013 21:20:35

**Peak Excursion Plot on Configuration IEEE 802.11n 40MHz / Chain 3 + Chain 4 / 64QAM(MCS5) / 5270MHz**




Date: 1.JUL.2013 21:22:35

**Peak Excursion Plot on Configuration IEEE 802.11n 40MHz / Chain 3 + Chain 4 / 64QAM(MCS5) / 5550MHz**




Date: 1.JUL.2013 21:30:00

**Peak Excursion Plot on Configuration IEEE 802.11a / Chain 3 + Chain 4 / 64QAM(48Mbps) / 5260MHz**



Date: 1.JUL.2013 21:04:52

**Peak Excursion Plot on Configuration IEEE 802.11a / Chain 3 + Chain 4 / 64QAM(48Mbps) / 5580MHz**



Date: 1.JUL.2013 21:10:17

## 4.6. Radiated Emissions Measurement

### 4.6.1. Limit

For transmitters operating in the 5.25-5.35 GHz band: all emissions outside of the 5.25-5.35 GHz band shall not exceed a -27dBm peak limit or average 54dBuV/m and peak 74dBuV/m limits. For transmitters operating in the 5.470-5.725 GHz band: all emissions outside of the 5.470-5.725 GHz band shall not exceed a -27dBm peak limit or average 54dBuV/m and peak 74dBuV/m limits. For transmitters operating in the 5.725-5.825 GHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an EIRP of -17 dBm/MHz (78.3dBuV/m at 3m). In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40 GHz
RBW / VBW (Emission in restricted band)	1 MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	1MHz / 3MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

#### 4.6.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

#### 4.6.4. Test Setup Layout

For radiated emissions below 1GHz



For radiated emissions above 1GHz



#### 4.6.5. Test Deviation

There is no deviation with the original standard.

#### 4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.6.7. Results of Radiated Emissions (9kHz~30MHz)

<b>Temperature</b>	20°C	<b>Humidity</b>	63%
<b>Test Engineer</b>	Magic Lai	<b>Configurations</b>	Normal Link
<b>Test Date</b>	Aug. 16, 2012		

<b>Freq. (MHz)</b>	<b>Level (dBuV)</b>	<b>Over Limit (dB)</b>	<b>Limit Line (dBuV)</b>	<b>Remark</b>
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.6.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	25°C	Humidity	57%
Test Engineer	Magic Lai	Configurations	Normal Link
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	Pol/Phase	T/Pos	A/Pos
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m			deg	cm
1	34.85	31.38	40.00	-8.62	41.56	0.92	28.00	16.90	Peak	HORIZONTAL	0	400
2	104.69	33.98	43.50	-9.52	48.22	1.53	27.77	12.00	Peak	HORIZONTAL	0	400
3	250.19	39.71	46.00	-6.29	51.38	2.38	26.95	12.90	Peak	HORIZONTAL	0	400
4	500.45	39.98	46.00	-6.02	46.73	3.38	27.93	17.80	Peak	HORIZONTAL	0	400
5	707.06	40.17	46.00	-5.83	43.06	4.17	27.09	20.03	Peak	HORIZONTAL	0	400
6	963.14	40.51	54.00	-13.49	40.11	4.85	26.43	21.98	Peak	HORIZONTAL	0	400

**Vertical**



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna		Pol/Phase	T/Pos	A/Pos
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	Remark		deg	cm
1	q	58.42	35.57	40.00	-4.43	55.11	1.15	27.95	7.26	QP	VERTICAL	90 100
2	p	81.41	36.81	40.00	-3.19	55.68	1.35	27.90	7.68	Peak	VERTICAL	360 400
3	!	250.19	41.66	46.00	-4.34	53.33	2.38	26.95	12.90	Peak	VERTICAL	360 400
4		500.45	37.15	46.00	-8.85	43.90	3.38	27.93	17.80	Peak	VERTICAL	360 400
5		676.99	38.01	46.00	-7.99	41.45	4.04	27.30	19.82	Peak	VERTICAL	360 400
6	!	951.50	40.38	46.00	-5.62	40.11	4.86	26.50	21.91	Peak	VERTICAL	360 400

**Note:**

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

#### 4.6.9. Results for Radiated Emissions (1GHz~40GHz)

<b>Temperature</b>	25°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz Ch 52 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 08, 2012		

##### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	15777.28	42.71	54.00	-11.29	34.58	6.14	37.41	35.42	Average	100	259	HORIZONTAL
2	15784.73	54.88	74.00	-19.12	46.75	6.14	37.41	35.42	Peak	100	259	HORIZONTAL

##### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	15762.77	50.51	74.00	-23.49	42.36	6.14	37.42	35.41	Peak	100	187	VERTICAL
2	15780.56	38.69	54.00	-15.31	30.56	6.14	37.41	35.42	Average	100	187	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz Ch 60 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 08, 2012		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10600.08	53.77	54.00	-0.23	45.80	5.01	38.38	35.42	Average	132	214	HORIZONTAL
2	10600.76	68.40	74.00	-5.60	60.43	5.01	38.38	35.42	Peak	132	214	HORIZONTAL
3	15897.20	54.29	74.00	-19.71	46.29	6.15	37.29	35.44	Peak	100	225	HORIZONTAL
4	15900.16	42.11	54.00	-11.89	34.11	6.15	37.29	35.44	Average	100	225	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10600.24	51.18	54.00	-2.82	43.21	5.01	38.38	35.42	Average	100	266	VERTICAL
2	10602.80	64.35	74.00	-9.65	56.38	5.01	38.38	35.42	Peak	100	266	VERTICAL
3	15919.23	37.45	54.00	-16.55	29.47	6.15	37.27	35.44	Average	100	245	VERTICAL
4	15919.47	49.87	74.00	-24.13	41.89	6.15	37.27	35.44	Peak	100	245	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz Ch 64 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 08, 2012		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10635.19	61.87	74.00	-12.13	53.88	5.01	38.37	35.39	Peak	132	212	HORIZONTAL
2	10640.08	47.30	54.00	-6.70	39.31	5.01	38.37	35.39	Average	132	212	HORIZONTAL
3	15950.14	50.97	74.00	-23.03	43.03	6.15	37.23	35.44	Peak	100	194	HORIZONTAL
4	15960.08	39.49	54.00	-14.51	31.55	6.15	37.23	35.44	Average	100	194	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10635.19	57.96	74.00	-16.04	49.97	5.01	38.37	35.39	Peak	100	267	VERTICAL
2	10640.24	44.35	54.00	-9.65	36.36	5.01	38.37	35.39	Average	100	267	VERTICAL
3	15935.24	37.40	54.00	-16.60	29.44	6.15	37.25	35.44	Average	100	244	VERTICAL
4	15937.40	49.95	74.00	-24.05	41.99	6.15	37.25	35.44	Peak	100	244	VERTICAL



<b>Temperature</b>	25°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz Ch 100 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 08, 2012		

**Horizontal**

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10995.11	63.61	74.00	-10.39	55.38	5.01	38.32	35.10	Peak	138	218	HORIZONTAL
2	11000.64	46.06	54.00	-7.94	37.83	5.01	38.32	35.10	Average	138	218	HORIZONTAL

**Vertical**

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10990.87	57.36	74.00	-16.64	49.15	5.01	38.30	35.10	Peak	100	270	VERTICAL
2	11000.80	43.92	54.00	-10.08	35.71	5.01	38.30	35.10	Average	100	270	VERTICAL



<b>Temperature</b>	25°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz Ch 116 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 08, 2012		

**Horizontal**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11154.95	69.80	74.00	-4.20	61.47	5.04	38.45	35.16	Peak	139	217	HORIZONTAL
2	11160.08	53.73	54.00	-0.27	45.39	5.04	38.47	35.17	Average	139	217	HORIZONTAL

**Vertical**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11155.99	50.56	54.00	-3.44	42.23	5.04	38.45	35.16	Average	100	216	VERTICAL
2	11160.80	63.75	74.00	-10.25	55.41	5.04	38.47	35.17	Peak	100	216	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz Ch 140 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 08, 2012		

### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11384.86	49.57	74.00	-24.43	41.05	5.09	38.68	35.25	Peak	100	165 HORIZONTAL
2	11399.20	38.03	54.00	-15.97	29.48	5.10	38.70	35.25	Average	100	165 HORIZONTAL

### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11375.56	51.00	74.00	-23.00	42.49	5.09	38.67	35.25	Peak	100	194 VERTICAL
2	11398.08	37.67	54.00	-16.33	29.12	5.10	38.70	35.25	Average	100	194 VERTICAL



<b>Temperature</b>	25°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11n MCS0 40MHz Ch 54 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 08, 2012		

**Horizontal**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	15805.11	41.38	54.00	-12.62	33.28	6.14	37.39	35.43	Average	100	219	HORIZONTAL
2	15812.16	54.03	74.00	-19.97	45.95	6.14	37.37	35.43	Peak	100	219	HORIZONTAL

**Vertical**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	15794.54	50.40	74.00	-23.60	42.30	6.14	37.39	35.43	Peak	100	200	VERTICAL
2	15796.70	38.53	54.00	-15.47	30.43	6.14	37.39	35.43	Average	100	200	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11n MCS0 40MHz Ch 62 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 08, 2012		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10612.55	53.62	74.00	-20.38	45.65	5.01	38.38	35.42	Peak	138	216	HORIZONTAL
2	10620.08	41.98	54.00	-12.02	34.01	5.01	38.38	35.42	Average	138	216	HORIZONTAL
3	15936.41	51.13	74.00	-22.87	43.17	6.15	37.25	35.44	Peak	100	254	HORIZONTAL
4	15940.10	37.78	54.00	-16.22	29.82	6.15	37.25	35.44	Average	100	254	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10620.40	38.50	54.00	-15.50	30.53	5.01	38.38	35.42	Average	100	212	VERTICAL
2	10621.44	51.18	74.00	-22.82	43.21	5.01	38.38	35.42	Peak	100	212	VERTICAL
3	15928.72	50.69	74.00	-23.31	42.71	6.15	37.27	35.44	Peak	100	214	VERTICAL
4	15932.00	37.99	54.00	-16.01	30.03	6.15	37.25	35.44	Average	100	214	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11n MCS0 40MHz Ch 102 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 08, 2012		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11020.08	42.10	54.00	-11.90	33.86	5.02	38.33	35.11	Average	139	214	HORIZONTAL
2	11021.36	54.38	74.00	-19.62	46.14	5.02	38.33	35.11	Peak	139	214	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11020.88	51.41	74.00	-22.59	43.18	5.02	38.32	35.11	Peak	100	266	VERTICAL
2	11021.20	38.20	54.00	-15.80	29.97	5.02	38.32	35.11	Average	100	266	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11n MCS0 40MHz Ch 110 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 08, 2012		

**Horizontal**

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	11099.92	53.62	54.00	-0.38	45.33	5.03	38.40	35.14	Average	132	218	HORIZONTAL
2	11100.24	66.70	74.00	-7.30	58.41	5.03	38.40	35.14	Peak	132	218	HORIZONTAL

**Vertical**

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	11100.64	61.74	74.00	-12.26	53.45	5.03	38.40	35.14	Peak	100	212	VERTICAL
2	11100.96	49.61	54.00	-4.39	41.32	5.03	38.40	35.14	Average	100	212	VERTICAL



<b>Temperature</b>	25°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11n MCS0 40MHz Ch 134 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 08, 2012		

**Horizontal**

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	11339.68	44.41	54.00	-9.59	35.94	5.08	38.63	35.24	Average	146	216	HORIZONTAL
2	11341.36	57.87	74.00	-16.13	49.39	5.09	38.63	35.24	Peak	146	216	HORIZONTAL

**Vertical**

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	11340.80	39.82	54.00	-14.18	31.34	5.09	38.63	35.24	Average	100	209	VERTICAL
2	11345.77	53.40	74.00	-20.60	44.92	5.09	38.63	35.24	Peak	100	209	VERTICAL

**Note:**

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

<b>Temperature</b>	25°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11a Ch 52 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 08, 2012		

**Horizontal**

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	15770.22	55.74	74.00	-18.26	47.60	6.14	37.42	35.42	Peak	117	234 HORIZONTAL
2	15774.71	43.74	54.00	-10.26	35.60	6.14	37.42	35.42	Average	117	234 HORIZONTAL

**Vertical**

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	15777.60	39.53	54.00	-14.47	31.40	6.14	37.41	35.42	Average	100	154 VERTICAL
2	15778.00	50.74	74.00	-23.26	42.61	6.14	37.41	35.42	Peak	100	154 VERTICAL



<b>Temperature</b>	25°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11a Ch 60 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 08, 2012		

**Horizontal**

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	10600.40	53.26	54.00	-0.74	45.29	5.01	38.38	35.42	Average	133	221 HORIZONTAL
2	10600.96	66.61	74.00	-7.39	58.64	5.01	38.38	35.42	Peak	133	221 HORIZONTAL
3	15899.52	42.45	54.00	-11.55	34.45	6.15	37.29	35.44	Average	107	232 HORIZONTAL
4	15905.29	55.38	74.00	-18.62	47.38	6.15	37.29	35.44	Peak	107	232 HORIZONTAL

**Vertical**

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	10600.48	65.11	74.00	-8.89	57.14	5.01	38.38	35.42	Peak	121	275 VERTICAL
2	10600.72	51.51	54.00	-2.49	43.54	5.01	38.38	35.42	Average	121	275 VERTICAL
3	15895.75	37.80	54.00	-16.20	29.80	6.15	37.29	35.44	Average	100	252 VERTICAL
4	15920.91	49.93	74.00	-24.07	41.95	6.15	37.27	35.44	Peak	100	252 VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11a Ch 64 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 08, 2012		

**Horizontal**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10640.24	49.19	54.00	-4.81	41.20	5.01	38.37	35.39	Average	138	223	HORIZONTAL
2	10640.72	62.31	74.00	-11.69	54.32	5.01	38.37	35.39	Peak	138	223	HORIZONTAL
3	15960.80	39.81	54.00	-14.19	31.87	6.15	37.23	35.44	Average	100	229	HORIZONTAL
4	15965.29	52.44	74.00	-21.56	44.51	6.15	37.22	35.44	Peak	100	229	HORIZONTAL

**Vertical**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10635.99	45.81	54.00	-8.19	37.82	5.01	38.37	35.39	Average	100	178	VERTICAL
2	10641.36	59.40	74.00	-14.60	51.41	5.01	38.37	35.39	Peak	100	178	VERTICAL
3	15957.20	37.75	54.00	-16.25	29.81	6.15	37.23	35.44	Average	100	353	VERTICAL
4	15957.20	49.66	74.00	-24.34	41.72	6.15	37.23	35.44	Peak	100	353	VERTICAL



<b>Temperature</b>	25°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11a Ch 100 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 08, 2012		

**Horizontal**

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	10997.92	45.65	54.00	-8.35	37.42	5.01	38.32	35.10	Average	133	251	HORIZONTAL
2	11001.92	58.56	74.00	-15.44	50.33	5.01	38.32	35.10	Peak	133	251	HORIZONTAL

**Vertical**

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	10998.00	56.17	74.00	-17.83	47.96	5.01	38.30	35.10	Peak	100	226	VERTICAL
2	10998.08	43.77	54.00	-10.23	35.56	5.01	38.30	35.10	Average	100	226	VERTICAL



<b>Temperature</b>	25°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11a Ch 116 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 08, 2012		

**Horizontal**

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11160.00	53.78	54.00	-0.22	45.44	5.04	38.47	35.17 Average	131	224	HORIZONTAL
2	11160.24	67.65	74.00	-6.35	59.31	5.04	38.47	35.17 Peak	131	224	HORIZONTAL

**Vertical**

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11151.91	61.27	74.00	-12.73	52.94	5.04	38.45	35.16 Peak	100	223	VERTICAL
2	11161.76	48.92	54.00	-5.08	40.57	5.05	38.47	35.17 Average	100	223	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11a Ch 140 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 08, 2012		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11398.72	51.45	74.00	-22.55	42.90	5.10	38.70	35.25	Peak	112	237	HORIZONTAL
2	11399.20	38.92	54.00	-15.08	30.37	5.10	38.70	35.25	Average	112	237	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11395.83	38.66	54.00	-15.34	30.13	5.10	38.68	35.25	Average	100	348	VERTICAL
2	11415.06	49.90	74.00	-24.10	41.34	5.10	38.72	35.26	Peak	100	348	VERTICAL

### Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

## 4.7. Band Edge Emissions Measurement

### 4.7.1. Limit

For transmitters operating in the 5.25-5.35 GHz band: all emissions outside of the 5.25-5.35 GHz band shall not exceed a -27dBm peak limit or average 54dBuV/m and peak 74dBuV/m limits. For transmitters operating in the 5.470-5.725 GHz band: all emissions outside of the 5.470-5.725 GHz band shall not exceed a -27dBm peak limit or average 54dBuV/m and peak 74dBuV/m limits. For transmitters operating in the 5.725-5.825 GHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an EIRP of -17 dBm/MHz (78.3dBuV/m at 3m). In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.7.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	1 MHz / 3MHz for Peak

### 4.7.3. Test Procedures

1. The test procedure is the same as section 4.6.3, only the frequency range investigated is limited to 100MHz around bandedges.

#### **4.7.4. Test Setup Layout**

This test setup layout is the same as that shown in section 4.6.4.

#### **4.7.5. Test Deviation**

There is no deviation with the original standard.

#### **4.7.6. EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

#### 4.7.7. Test Result of Band Edge and Fundamental Emissions

Temperature	25°C	Humidity	56%
Test Engineer	Will Tung	Configurations	IEEE 802.11n MCS0 20MHz Ch 52, 60, 64 / Chain 3 + Chain 4
Test Date	Aug. 01, 2012		

##### Channel 52

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5149.04	60.41	74.00	-13.59	23.31	3.43	33.67	0.00	Peak	125	78	HORIZONTAL
2	5150.00	48.19	54.00	-5.81	11.09	3.43	33.67	0.00	Average	125	78	HORIZONTAL
3	5255.67	105.84			68.53	3.46	33.85	0.00	Average	125	78	HORIZONTAL
4	5255.67	117.71			80.40	3.46	33.85	0.00	Peak	125	78	HORIZONTAL
5	5350.00	46.12	54.00	-7.88	8.60	3.49	34.03	0.00	Average	125	78	HORIZONTAL
6	5350.00	57.39	74.00	-16.61	19.87	3.49	34.03	0.00	Peak	125	78	HORIZONTAL

Item 3, 4 are the fundamental frequency at 5260 MHz.

##### Channel 60

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5295.51	116.69			79.31	3.47	33.91	0.00	Peak	137	72	HORIZONTAL
2	5302.89	105.28			67.86	3.48	33.94	0.00	Average	137	72	HORIZONTAL
3	5350.32	50.97	54.00	-3.03	13.45	3.49	34.03	0.00	Average	137	72	HORIZONTAL
4	5350.64	68.97	74.00	-5.03	31.45	3.49	34.03	0.00	Peak	137	72	HORIZONTAL

Item 1, 2 are the fundamental frequency at 5300 MHz.

##### Channel 64

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5323.21	103.48			66.02	3.49	33.97	0.00	Average	136	68	HORIZONTAL
2	5323.21	114.79			77.33	3.49	33.97	0.00	Peak	136	68	HORIZONTAL
3	5350.48	53.17	54.00	-0.83	15.65	3.49	34.03	0.00	Average	136	68	HORIZONTAL
4	5350.64	73.49	74.00	-0.51	35.97	3.49	34.03	0.00	Peak	136	68	HORIZONTAL

Item 1, 2 are the fundamental frequency at 5320 MHz.

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz Ch 100, 140 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 01, 2012		

**Channel 100**

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5458.88	65.49	74.00	-8.51	27.78	3.52	34.19	0.00	Peak	133	104	HORIZONTAL
2	5459.20	47.15	54.00	-6.85	9.44	3.52	34.19	0.00	Average	133	104	HORIZONTAL
3	5468.88	67.97	68.30	-0.33	30.24	3.52	34.21	0.00	Peak	133	104	HORIZONTAL
4	5504.17	101.55			63.76	3.54	34.25	0.00	Average	133	104	HORIZONTAL
5	5504.17	113.17			75.38	3.54	34.25	0.00	Peak	133	104	HORIZONTAL

Item 4, 5 are the fundamental frequency at 5500 MHz.

**Channel 140**

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5697.12	99.89			61.96	3.59	34.34	0.00	Average	137	87	HORIZONTAL
2	5697.44	111.06			73.13	3.59	34.34	0.00	Peak	137	87	HORIZONTAL
3	5725.00	67.66	68.30	-0.64	29.72	3.60	34.34	0.00	Peak	137	87	HORIZONTAL

Item 1, 2 are the fundamental frequency at 5700 MHz.

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11n MCS0 40MHz Ch 54, 62 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 01, 2012		

#### Channel 54

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5265.83	103.12			65.78	3.46	33.88	0.00 Average	142	72	HORIZONTAL
2	5273.21	114.57			77.22	3.47	33.88	0.00 Peak	142	72	HORIZONTAL
3	5350.64	52.09	54.00	-1.91	14.57	3.49	34.03	0.00 Average	142	72	HORIZONTAL
4	5350.64	67.48	74.00	-6.52	29.96	3.49	34.03	0.00 Peak	142	72	HORIZONTAL

Item 1, 2 are the fundamental frequency at 5270 MHz.

#### Channel 62

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5315.45	107.69			70.24	3.48	33.97	0.00 Peak	139	79	HORIZONTAL
2	5316.09	96.97			59.52	3.48	33.97	0.00 Average	139	79	HORIZONTAL
3	5350.64	52.76	54.00	-1.24	15.24	3.49	34.03	0.00 Average	139	79	HORIZONTAL
4	5350.96	70.85	74.00	-3.15	33.33	3.49	34.03	0.00 Peak	139	79	HORIZONTAL

Item 1, 2 are the fundamental frequency at 5310 MHz.

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11n MCS0 40MHz Ch 102, 110, 134 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 01, 2012		

**Channel 102**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5457.76	62.41	74.00	-11.59	24.68	3.52	34.21	0.00	Peak	100	206	VERTICAL
2	5460.00	47.74	54.00	-6.26	10.01	3.52	34.21	0.00	Average	100	206	VERTICAL
3	5469.04	68.10	68.30	-0.20	30.34	3.52	34.24	0.00	Peak	100	206	VERTICAL
4	5505.83	95.82			58.00	3.54	34.28	0.00	Average	100	206	VERTICAL
5	5506.80	108.75			70.93	3.54	34.28	0.00	Peak	100	206	VERTICAL

Item 4, 5 are the fundamental frequency at 5510MHz.

**Channel 110**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5460.00	52.91	54.00	-1.09	15.18	3.52	34.21	0.00	Average	100	162	VERTICAL
2	5460.00	66.45	74.00	-7.55	28.72	3.52	34.21	0.00	Peak	100	162	VERTICAL
3	5469.36	68.10	68.30	-0.20	30.34	3.52	34.24	0.00	Peak	100	162	VERTICAL
4	5546.80	103.01			65.15	3.55	34.31	0.00	Average	100	162	VERTICAL
5	5546.80	116.46			78.60	3.55	34.31	0.00	Peak	100	162	VERTICAL

Item 4, 5 are the fundamental frequency at 5550 MHz.

**Channel 134**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5674.49	100.57			62.65	3.59	34.33	0.00	Average	140	105	HORIZONTAL
2	5674.49	111.83			73.91	3.59	34.33	0.00	Peak	140	105	HORIZONTAL
3	5726.92	67.82	68.30	-0.48	29.88	3.60	34.34	0.00	Peak	140	105	HORIZONTAL

Item 1, 2 are the fundamental frequency at 5670 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11a Ch 52, 60, 64 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 01, 2012		

### Channel 52

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5148.08	60.31	74.00	-13.69	23.21	3.43	33.67	0.00	Peak	123	78	HORIZONTAL
2	5150.00	47.69	54.00	-6.31	10.59	3.43	33.67	0.00	Average	123	78	HORIZONTAL
3	5255.67	107.21			69.90	3.46	33.85	0.00	Average	123	78	HORIZONTAL
4	5255.67	118.57			81.26	3.46	33.85	0.00	Peak	123	78	HORIZONTAL
5	5350.00	46.66	54.00	-7.34	9.14	3.49	34.03	0.00	Average	123	78	HORIZONTAL
6	5389.42	58.49	74.00	-15.51	20.90	3.50	34.09	0.00	Peak	123	78	HORIZONTAL

Item 3, 4 are the fundamental frequency at 5260 MHz.

### Channel 60

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5295.83	117.50			80.12	3.47	33.91	0.00	Peak	136	74	HORIZONTAL
2	5296.15	106.14			68.76	3.47	33.91	0.00	Average	136	74	HORIZONTAL
3	5350.00	50.25	54.00	-3.75	12.73	3.49	34.03	0.00	Average	136	74	HORIZONTAL
4	5350.00	64.55	74.00	-9.45	27.03	3.49	34.03	0.00	Peak	136	74	HORIZONTAL

Item 1, 2 are the fundamental frequency at 5300 MHz.

### Channel 64

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5317.92	115.23			77.78	3.48	33.97	0.00	Peak	127	102	HORIZONTAL
2	5323.21	104.56			67.10	3.49	33.97	0.00	Average	127	102	HORIZONTAL
3	5350.00	52.81	54.00	-1.19	15.29	3.49	34.03	0.00	Average	127	102	HORIZONTAL
4	5350.16	71.92	74.00	-2.08	34.40	3.49	34.03	0.00	Peak	127	102	HORIZONTAL

Item 1, 2 are the fundamental frequency at 5320 MHz.

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Will Tung	<b>Configurations</b>	IEEE 802.11a Ch 100, 140 / Chain 3 + Chain 4
<b>Test Date</b>	Aug. 01, 2012		

**Channel 100**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5460.00	47.45	54.00	-6.55	9.72	3.52	34.21	0.00	Average	100	151	VERTICAL
2	5460.00	63.24	74.00	-10.76	25.51	3.52	34.21	0.00	Peak	100	151	VERTICAL
3	5469.20	67.76	68.30	-0.54	30.00	3.52	34.24	0.00	Peak	100	151	VERTICAL
4	5494.71	102.04			64.25	3.53	34.26	0.00	Average	100	151	VERTICAL
5	5495.19	113.63			75.84	3.53	34.26	0.00	Peak	100	151	VERTICAL

Item 4, 5 are the fundamental frequency at 5500 MHz.

**Channel 140**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5704.33	102.72			64.79	3.59	34.34	0.00	Average	122	86	HORIZONTAL
2	5704.33	113.83			75.90	3.59	34.34	0.00	Peak	122	86	HORIZONTAL
3	5725.16	67.78	68.30	-0.52	29.84	3.60	34.34	0.00	Peak	122	86	HORIZONTAL

Item 1, 2 are the fundamental frequency at 5700 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

## 4.8. Frequency Stability Measurement

### 4.8.1. Limit

In-band emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

The transmitter center frequency tolerance shall be  $\pm 20$  ppm maximum for the 5 GHz band (IEEE 802.11n specification).

### 4.8.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Entire absence of modulation emissions bandwidth
RBW	10 kHz
VBW	10 kHz
Sweep Time	Auto

### 4.8.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5.  $f_c$  is declaring of channel frequency. Then the frequency error formula is  $(f_c - f) / f_c \times 10^6$  ppm and the limit is less than  $\pm 20$  ppm (IEEE 802.11n specification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is  $-30^\circ\text{C} \sim 50^\circ\text{C}$ .

### 4.8.4. Test Setup Layout



#### 4.8.5. Test Deviation

There is no deviation with the original standard.

#### 4.8.6. EUT Operation during Test

The EUT was programmed to be in continuously un-modulation transmitting mode.

#### 4.8.7. Test Result of Frequency Stability

##### Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)
(V)	5300
126.50	5299.9760
110.00	5299.9760
93.50	5299.9740
Max. Deviation (MHz)	0.026000
Max. Deviation (ppm)	4.91

##### Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)
(°C)	5300
-30	5300.0439
-20	5300.0264
-10	5300.0152
0	5300.0060
10	5299.9915
20	5299.9760
30	5299.9652
40	5299.9586
50	5299.9462
Max. Deviation (MHz)	0.053800
Max. Deviation (ppm)	10.1509

## 4.9. Antenna Requirements

### 4.9.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### 4.9.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Sep. 14, 2011	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov. 14, 2011	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9 kHz ~ 30MHz	Jun. 22, 2012	Conduction (CO01-CB)
PULSE LIMITER	R&S	ESH3-Z2	100430	9 kHz ~30MHz	Feb. 03, 2012	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	0.15MHz~30MHz	Dec. 04, 2011	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Jan. 11, 2012	Radiation (O3CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 25, 2011	Radiation (O3CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 22, 2011	Radiation (O3CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 17, 2011	Radiation (O3CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 29, 2011	Radiation (O3CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 31, 2012	Radiation (O3CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9kHz ~ 2.75GHz	Mar. 20, 2012	Radiation (O3CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Sep. 09, 2011*	Radiation (O3CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N/A	Radiation (O3CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N/A	Radiation (O3CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2011	Radiation (O3CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz – 26.5 GHz	Nov. 17, 2011	Radiation (O3CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz – 26.5 GHz	Nov. 17, 2011	Radiation (O3CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 17, 2011	Radiation (O3CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 17, 2011	Radiation (O3CH01-CB)
Signal analyzer	R&S	FSV40	100979	9kHz~40GHz	Sep. 26, 2011	Conducted (TH01-CB)
Signal analyzer	R&S	FSV40	100979	9kHz~40GHz	Oct. 08, 2012	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 05, 2012	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 04, 2013	Conducted (TH01-CB)
Thermo-Hygro Meter	N/A	HC 520	#1	15~70 degree	Nov. 02, 2011	Conducted (TH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Power Divider	HP	11636A	00306	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Power Splitter	Anaren	44100	1839	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Power Splitter	Anaren	42100	17930	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	3 Way	MDC2366	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	4 Way	0120A04056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Nov. 28, 2011	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Nov. 28, 2012	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Nov. 27, 2011	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Nov. 27, 2012	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

“\*” Calibration Interval of instruments listed above is two years.

NCR means Non-Calibration required.

## 6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

## 7. MEASUREMENT UNCERTAINTY

### Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Contribution	Uncertainty of $x_i$			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	0.026	dB	normal(k=2)	0.013
Cable loss	0.002	dB	normal(k=2)	0.001
AMN/LISN specification	1.200	dB	normal(k=2)	0.600
Mismatch Receiver VSWR 1= AMN/LISN VSWR 2=	-0.080	dB	U-shaped	0.060
combined standard uncertainty $U_e(y)$	1.2			
Measuring uncertainty for a level of confidence of 95% $U=2U_e(y)$	2.4			

### Uncertainty of Conducted Emission Measurement

Contribution	Uncertainty of $x_i$			$u(x_i)$
	Value	Unit	Probability Distribution k	
Cable loss	0.038	dB	normal(k=2)	0.019
Attenuator	0.047	dB	normal(k=2)	0.024
Power Meter specification	0.300	dB	normal(k=2)	0.150
Power Sensor specification	0.300	dB	normal(k=2)	0.150
Mismatch Receiver VSWR 1= Antenna VSWR 2= Pre Amplifier VSWR 3=	-0.080	dB	U-shaped	0.060
combined standard uncertainty $U_e(y)$	0.403			
Measuring uncertainty for a level of confidence of 95% $U=2U_e(y)$	0.806			

**Uncertainty of Radiated Emission Measurement (30MHz ~ 1,000MHz)**

Contribution	Uncertainty of $x_i$			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	0.1727	dB	normal(k=1)	0.1727
Cable loss	0.1736	dB	normal(k=2)	0.0868
Antenna gain	0.1687	dB	normal(k=2)	0.0843
Site imperfection	0.4898	dB	Triangular	0.2
Pre-amplifier gain	0.3661	dB	normal(k=2)	0.183
Transmitter antenna	1.7	dB	rectangular	0.9815
Signal generator	0.5	dB	rectangular	0.2887
Mismatch	0.08	dB	u-shape	0.244
Spectrum analyzer	0.5	dB	rectangular	0.2887
combined standard uncertainty Ue(y)	1.1434			
Measuring uncertainty for a level of confidence of 95% $U=2Ue(y)$	2.2869			

**Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)**

Contribution	Uncertainty of $x_i$			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	0.1908	dB	normal(k=1)	0.1908
Cable loss	0.1685	dB	normal(k=2)	0.0843
Antenna gain	0.1912	dB	normal(k=2)	0.0956
Site imperfection	1.3091	dB	Triangular	0.5344
Pre-amplifier gain	0.3043	dB	normal(k=2)	0.1521
Transmitter antenna	1.7	dB	rectangular	0.9815
Signal generator	0.5	dB	rectangular	0.2887
Mismatch	0.08	dB	u-shape	0.244
Spectrum analyzer	0.8	dB	rectangular	0.4619
combined standard uncertainty Ue(y)	1.2965			
Measuring uncertainty for a level of confidence of 95% $U=2Ue(y)$	2.593			

**Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)**

Contribution	Uncertainty of $x_i$			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	0.1864	dB	normal(k=1)	0.1864
Cable loss	0.1666	dB	normal(k=2)	0.0833
Antenna gain	0.1904	dB	normal(k=2)	0.0952
Site imperfection	0.4882	dB	Triangular	0.1993
Pre-amplifier gain	0.2688	dB	normal(k=2)	0.1344
Transmitter antenna	1.7	dB	rectangular	0.9815
Signal generator	0.5	dB	rectangular	0.2887
Mismatch	0.08	dB	u-shape	0.244
Spectrum analyzer	0.8	dB	rectangular	0.4619
combined standard uncertainty $Ue(y)$	1.1874			
Measuring uncertainty for a level of confidence of 95% $U=2Ue(y)$	2.3749			