



SPORTON International Inc.

No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.
Ph: 886-3-656-9065 / FAX: 886-3-656-9085 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	NETGEAR, Inc.
Applicant Address	350 East Plumeria Drive, San Jose, California 95134, USA
FCC ID	PY313200233

Product Name	R7000 Smart WiFi Router
Brand Name	NETGEAR
Model No.	R7000
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Received Date	Jul. 08, 2013
Final Test Date	Jul. 25, 2013
Submission Type	Original Equipment

Statement

Test result included is only for the IEEE 802.11n, IEEE 802.11b/g part and IEEE 802.11a/ac (5725 ~ 5850MHz) of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009, 47 CFR FCC Part 15 Subpart C, KDB 558074 D01 v03 and KDB 662911 D01 v02.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	5
3.3. Table for Filed Antenna.....	6
3.4. Table for Carrier Frequencies	7
3.5. Table for Test Modes.....	8
3.6. Table for Testing Locations.....	10
3.7. Table for Supporting Units	11
3.8. Table for Parameters of Test Software Setting	12
3.9. EUT Operation during Test	13
3.10. Duty Cycle.....	14
3.11. Test Configurations	19
4. TEST RESULT	22
4.1. AC Power Line Conducted Emissions Measurement.....	22
4.2. Maximum Conducted Output Power Measurement.....	26
4.3. Power Spectral Density Measurement	30
4.4. 6dB Spectrum Bandwidth Measurement	39
4.5. Radiated Emissions Measurement	47
4.6. Emissions Measurement	75
4.7. Antenna Requirements	104
5. LIST OF MEASURING EQUIPMENTS	105
6. TEST LOCATION.....	107
7. MEASUREMENT UNCERTAINTY.....	108
APPENDIX A. TEST PHOTOS	A1 ~ A5
APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE	B1 ~ B3
APPENDIX C. CO-LOCATION REPORT.....	C1 ~ C3



History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR372429AA	Rev. 01	Initial issue of report	Aug. 06, 2013



1. CERTIFICATE OF COMPLIANCE

Product Name : R7000 Smart WiFi Router
Brand Name : NETGEAR
Model No. : R7000
Applicant : NETGEAR, Inc.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jul. 08, 2013 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads 'Sam Chen'.

Sam Chen
SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	7.54 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	0.01 dB
4.3	15.247(e)	Power Spectral Density	Complies	1.19 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	3.01 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.02 dB
4.7	15.203	Antenna Requirements	Complies	-

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n/ac

Items	Description
Product Type	WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	see the below table for IEEE 802.11n/ac
Data Modulation	For 802.11n: OFDM (BPSK / QPSK / 16QAM / 64QAM) For 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n/ac
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	For 2.4GHz Band: 11 for 20MHz bandwidth ; 7 for 40MHz bandwidth For 5GHz Band: 5 for 20MHz bandwidth ; 2 for 40MHz bandwidth ; 1 for 80MHz bandwidth
Channel Band Width (99%)	For 2.4GHz Band: 802.11ac MCS0/Nss1 (20MHz): 19.76 MHz ; 802.11ac MCS0/Nss1 (40MHz): 36.32 MHz For 5GHz Band: 802.11ac MCS0/Nss1 (20MHz): 25.84 MHz ; 802.11ac MCS0/Nss1 (40MHz): 55.04 MHz ; 802.11ac MCS0/Nss1 (80MHz): 76.48 MHz
Maximum Conducted Output Power	For 2.4GHz Band: 802.11ac MCS0/Nss1 (20MHz): 29.13 dBm ; 802.11ac MCS0/Nss1 (40MHz): 21.90 dBm For 5GHz Band: 802.11ac MCS0/Nss1 (20MHz): 29.90 dBm ; 802.11ac MCS0/Nss1 (40MHz): 29.80 dBm ; 802.11ac MCS0/Nss1 (80MHz): 27.78 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Note : The product has beamforming function for 802.11 n/ac.

802.11a/b/g

Items	Description
Product Type	WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11a/g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	11b/g: 11 ; 11a: 5
Channel Band Width (99%)	11b: 14.40 MHz ; 11g: 20.32 MHz ; 11a: 28.24 MHz
Maximum Conducted Output Power	11b: 29.15 dBm ; 11g: 29.03 dBm ; 11a: 29.99 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Note : The product has beamforming function for 802.11 n/ac.

Antenna & Band width

Antenna	Three (TX)		
	20 MHz	40 MHz	80 MHz
Band width Mode			
IEEE 802.11a	V	X	X
IEEE 802.11b	V	X	X
IEEE 802.11g	V	X	X
IEEE 802.11n	V	V	X
IEEE 802.11ac	V	V	V

Note : The product has beamforming function for 802.11 n/ac.

IEEE 11a/n/ac Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11a	3	6-54 Mbps
802.11n (HT20)	3	MCS0-23
802.11n (HT40)	3	MCS0-23
802.11ac (VHT20)	3	MCS 0-9/Nss1-3
802.11ac (VHT40)	3	MCS 0-9/Nss1-3
802.11ac (VHT80)	3	MCS 0-9/Nss1-3

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20 and HT40.

Note 2: IEEE Std. 802.11ac modulation consists of VHT20, VHT40, VHT80 and VHT160 (VHT: Very High Throughput). Then EUT support VHT20, VHT40 and VHT80.

Note 3: The test result of beam-forming mode is worse case than non beam-forming mode, so it is recorded in the test report for 802.11ac.

3.2. Accessories

Power	Brand	Model	P/N	Rating
Adapter 1	NETGEAR	AD898F20	332-10613-01	Input:100-240Vac, 50/60Hz, 1.0A Output:12Vdc, 3.5A
Adapter 2	NETGEAR	2AAF042F NA	332-10618-01	Input:100-240Vac, 50/60Hz, 1.5A Output:12Vdc, 3.5A
Others				
RJ-45 Cable*1: Shielded, 1.4m				

3.3. Table for Filed Antenna

Set	Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	
						2.4GHz	5GHz
A	1	-	-	Dipole Antenna	SMA	0.6	0.9
	2	-	-	Dipole Antenna	SMA	0.6	0.9
	3	-	-	Dipole Antenna	SMA	0.6	0.9

Note1: There are two antenna set.

Set B is long 62mm in cable loss than set A, so that set A is worse case and recorded in the report.

Note2: The EUT has three antennas

<For 2.4GHz Band:>


For IEEE 802.11b/g/n/ac mode (3TX/3RX):

Chain 1 ~ Chain 3 could transmit/receive simultaneously.

<For 5GHz Band:>

For IEEE 802.11a/n/ac mode (3TX/3RX):

Chain 1 ~ Chain 3 could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

For 2.4GHz Band:

There are two bandwidth systems.

For 20MHz bandwidth systems, use Channel 1~Channel 11.

For 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

For 5GHz Band:

There are three bandwidth systems.

For 20MHz bandwidth systems, use Channel 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 151, 159.

For 80MHz bandwidth systems, use Channel 155.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz Band 4	149	5745 MHz	157	5785 MHz
	151	5755 MHz	159	5795 MHz
	153	5765 MHz	161	5805 MHz
	155	5775 MHz	165	5825 MHz

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

For 2.4GHz Band

Test Items	Mode	Data Rate	Channel	Chain
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	11ac 20MHz	MCS0/Nss1	1/6/11	1+2+3
	11ac 40MHz	MCS0/Nss1	3/6/9	1+2+3
	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
Power Spectral Density	11ac 20MHz	MCS0/Nss1	1/6/11	1&2&3
	11ac 40MHz	MCS0/Nss1	3/6/9	1&2&3
	11b/CCK	1 Mbps	1/6/11	1&2&3
	11g/BPSK	6 Mbps	1/6/11	1&2&3
6dB Spectrum Bandwidth	11ac 20MHz	MCS0/Nss1	1/6/11	1+2+3
	11ac 40MHz	MCS0/Nss1	3/6/9	1+2+3
	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
Radiated Emissions Below 1GHz	Normal Link	-	-	-
Radiated Emissions Above 1GHz	11ac 20MHz	MCS0/Nss1	1/6/11	1+2+3
	11ac 40MHz	MCS0/Nss1	3/6/9	1+2+3
	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
Band Edge Emissions	11ac 20MHz	MCS0/Nss1	1/6/11	1+2+3
	11ac 40MHz	MCS0/Nss1	3/6/9	1+2+3
	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3

For 5GHz Band

Test Items	Mode	Data Rate	Channel	Chain
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	11ac 20MHz	MCS0/Nss1	149/157/165	1+2+3
	11ac 40MHz	MCS0/Nss1	151/159	1+2+3
	11ac 80MHz	MCS0/Nss1	155	1+2+3
	11a/BPSK	6 Mbps	149/157/165	1+2+3
Power Spectral Density	11ac 20MHz	MCS0/Nss1	149/157/165	1&2&3
	11ac 40MHz	MCS0/Nss1	151/159	1&2&3
	11ac 80MHz	MCS0/Nss1	155	1&2&3
	11a/BPSK	6 Mbps	149/157/165	1&2&3
6dB Spectrum Bandwidth	11ac 20MHz	MCS0/Nss1	149/157/165	1+2+3
	11ac 40MHz	MCS0/Nss1	151/159	1+2+3
	11ac 80MHz	MCS0/Nss1	155	1+2+3
	11a/BPSK	6 Mbps	149/157/165	1+2+3
Radiated Emissions Below 1GHz	Normal Link	-	-	-
Radiated Emissions Above 1GHz	11ac 20MHz	MCS0/Nss1	149/157/165	1+2+3
	11ac 40MHz	MCS0/Nss1	151/159	1+2+3
	11ac 80MHz	MCS0/Nss1	155	1+2+3
	11a/BPSK	6 Mbps	149/157/165	1+2+3
Band Edge Emissions	11ac 20MHz	MCS0/Nss1	149/157/165	1+2+3
	11ac 40MHz	MCS0/Nss1	151/159	1+2+3
	11ac 80MHz	MCS0/Nss1	155	1+2+3
	11a/BPSK	6 Mbps	149/157/165	1+2+3

The following test modes were performed for all tests:

For Conducted Emission test:

Mode 1. Normal Link - EUT with AC Adapter 1

Mode 2. Normal Link - EUT with AC Adapter 2

Mode 2 is the worst case, so it was selected to record in this test report.

For Radiated Emission 30MHz~1MHz test :

Mode 1. Normal Link - EUT with AC Adapter 1

Mode 2. Normal Link - EUT with AC Adapter 2

Mode 2 is the worst case, so it was selected to record in this test report.

For Radiated Emission above 1MHz test:

Mode 1. CTX - Laying of EUT

For MPE and Co-location test:

The EUT could be applied with 2.4GHz WLAN function and 5GHz WLAN function; therefore Maximum Permissible Exposure (Please refer to Appendix B) and Co-location (please refer to Appendix C) tests are added for simultaneously transmit between 2.4GHz WLAN function and 5GHz WLAN function.

Note1: The test result of beam-forming mode is worse case than non beam-forming mode, so it is recorded in the test report for 802.11ac.

Note2: Test mode evaluation description

There are two SKU for PCB board

SKU A: RF switch + internal receive antenna

SKU B. remove RF switch

SKU A is worse case than SKU B so it is recorded the test report.

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
Notebook*2	DELL	E6400	E2K4965AGNM
Notebook*2	DELL	E6430	QDS-BRCM1049LE
Flash Disk	Silicon	I-Series	DoC
Flash Disk 3.0	ADATA	C103	DoC

For Test Site No: 03CH01-CB

(Radiated Emission 30MHz~1GHz test)

Support Unit	Brand	Model	FCC ID
Notebook*2	DELL	E6400	E2K4965AGNM
Notebook*2	DELL	E6430	QDS-BRCM1049LE
Flash Disk	Silicon	I-Series	DoC
Flash Disk 3.0	ADATA	C103	DoC

(Radiated Emission above 1GHz test) (For Non-Beamforming Mode)

Support Unit	Brand	Model	FCC ID
Notebook	DELL	M1330	E2K4965AGNM

(Radiated Emission above 1GHz test) (For Beamforming Mode)

Support Unit	Brand	Model	FCC ID
Notebook	DELL	M1330	E2K4965AGNM
Notebook	DELL	E6430	QDS-BRCM1049LE
Wlan ac Card	Broadcom	Bcm4360	N/A

For Test Site No: TH01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	M1330	E2K4965AGNM

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

For 2.4GHz Band

Power Parameters of IEEE 802.11ac MCS0/Nss1 20MHz

Test Software Version	Manual Tool Version:2.0.1.0		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0/Nss1 20MHz	72	112	68

Power Parameters of IEEE 802.11ac MCS0/Nss1 40MHz

Test Software Version	Manual Tool Version:2.0.1.0		
Frequency	2422 MHz	2437 MHz	2452 MHz
MCS0/Nss1 40MHz	64	67	55

Power Parameters of IEEE 802.11b/g

Test Software Version	Manual Tool Version:2.0.1.0		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	94	112	93
IEEE 802.11g	68	112	68

For 5GHz Band

Power Parameters of IEEE 802.11ac MCS0/Nss1 20MHz

Test Software Version	Manual Tool Version:2.0.1.0		
Frequency	5745 MHz	5785 MHz	5825 MHz
MCS0/Nss1 20MHz	106	106	106

Power Parameters of IEEE 802.11ac MCS0/Nss1 40MHz

Test Software Version	Manual Tool Version:2.0.1.0	
Frequency	5755 MHz	5795 MHz
MCS0/Nss1 40MHz	106	106

Power Parameters of IEEE 802.11ac MCS0/Nss1 80MHz

Test Software Version	Manual Tool Version:2.0.1.0
Frequency	5775 MHz
MCS0/Nss1 80MHz	96

Power Parameters of IEEE 802.11a

Test Software Version	Manual Tool Version:2.0.1.0		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	106	106	106

3.9. EUT Operation during Test

For non-beamforming mode

The EUT was programmed to be in continuously transmitting mode.

For beamforming mode

For Conducted Mode:

The EUT was programmed to be in continuously transmitting mode.

For Radiated Mode:

During the test, the following programs under WIN XP were executed.


The program was executed as follows:

1. During the test, the EUT operation to normal function.
2. Executed command fixed test channel under DOS.
3. Executed "Lantest.exe " to link with the remote workstation to receive and transmit packet by Wlan ac Card and transmit duty cycle no less 98%.

3.10. Duty Cycle


For non-beamforming mode

IEEE 802.11b




Date: 19.JUL.2013 01:14:29

IEEE 802.11g



Date: 19.JUL.2013 01:15:24


IEEE 802.11a



Date: 19.JUL.2013 01:19:20


For beamforming mode

IEEE 802.11ac MCS0/Nss1 20MHz / For 2.4GHz Band




Date: 19.JUL.2013 01:16:46

IEEE 802.11ac MCS0/Nss1 40MHz / For 2.4GHz Band




Date: 19.JUL.2013 01:17:57

IEEE 802.11ac MCS0/Nss1 20MHz / For 5GHz Band




Date: 19.JUL.2013 01:20:21

IEEE 802.11ac MCS0/Nss1 40MHz / For 5GHz Band



Date: 19.JUL.2013 01:21:31

IEEE 802.11ac MCS0/Nss1 80MHz / For 5GHz Band




Date: 19.JUL.2013 01:22:54

3.11. Test Configurations

3.11.1. AC Power Line Conduction Emissions Test Configuration

Test Configuration: AC Power Line Conduction and Radiated Emission 30MHz~1GHz

Test Mode : Mode 2




Item	Connection	Shielded	Length(m)
1	AC power cable	No	1.8m
2	RJ-45 cable	Yes	1.4m
3	RJ-45 cable	No	10m
4	RJ-45 cable	No	10m
5	RJ-45 cable	No	1m

3.11.2. Radiation Emissions Test Configuration

Test Configuration: Radiated Emission above 1GHz

For Non-Beamforming Mode / Test Mode: Mode 1



Item	Connection	Shielded	Length(m)
1	AC power cable	No	1.8m
2	RJ-45 cable	No	10m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.


Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Phase	Line
Configuration	Normal Link / Mode 2		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.15816	50.17	-15.39	65.56	49.83	0.16	0.18	LINE	QP
2	0.15816	25.20	-30.36	55.56	24.86	0.16	0.18	LINE	AVERAGE
3 @	0.16589	44.52	-10.65	55.16	44.17	0.16	0.19	LINE	AVERAGE
4 @	0.16589	57.63	-7.54	65.16	57.28	0.16	0.19	LINE	QP
5	0.20075	40.72	-12.86	53.58	40.37	0.15	0.20	LINE	AVERAGE
6 @	0.20075	52.90	-10.68	63.58	52.55	0.15	0.20	LINE	QP
7	0.23436	47.05	-15.24	62.29	46.70	0.15	0.20	LINE	QP
8	0.23436	34.82	-17.47	52.29	34.47	0.15	0.20	LINE	AVERAGE
9	0.47110	39.09	-17.40	56.49	38.74	0.15	0.20	LINE	QP
10 @	0.47110	36.38	-10.11	46.49	36.03	0.15	0.20	LINE	AVERAGE
11	17.568	36.97	-23.03	60.00	36.06	0.45	0.46	LINE	QP
12	17.568	30.70	-19.30	50.00	29.79	0.45	0.46	LINE	AVERAGE

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Phase	Neutral
Configuration	Normal Link / Mode 2		



	Freq	Level	Over	Limit	Read	LISN	Cable	Pol/Phase	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss		
			dB	dBuV	dBuV	dB	dB		
1	0.15080	55.24	-10.72	65.96	54.98	0.08	0.18	NEUTRAL	QP
2	0.15080	25.05	-30.91	55.96	24.79	0.08	0.18	NEUTRAL	AVERAGE
3	0.16155	54.72	-10.66	65.38	54.46	0.08	0.18	NEUTRAL	QP
4	0.16155	43.95	-11.43	55.38	43.69	0.08	0.18	NEUTRAL	AVERAGE
5	0.17399	51.44	-13.33	64.77	51.17	0.08	0.19	NEUTRAL	QP
6	0.17399	30.76	-24.01	54.77	30.49	0.08	0.19	NEUTRAL	AVERAGE
7	0.19344	52.57	-11.32	63.89	52.29	0.08	0.20	NEUTRAL	QP
8	0.19344	38.01	-15.88	53.89	37.73	0.08	0.20	NEUTRAL	AVERAGE
9	0.48632	23.47	-22.76	46.23	23.19	0.08	0.20	NEUTRAL	AVERAGE
10	0.48632	30.40	-25.83	56.23	30.12	0.08	0.20	NEUTRAL	QP
11	17.199	38.39	-21.61	60.00	37.60	0.35	0.44	NEUTRAL	QP
12	17.199	32.29	-17.71	50.00	31.50	0.35	0.44	NEUTRAL	AVERAGE

Note:

$$\text{Level} = \text{Read Level} + \text{LISN Factor} + \text{Cable Loss}$$

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter output power.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Detector	Average

4.2.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03 section 9.2.2 Measurement using a power meter (PM).
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	26°C	Humidity	63%
Test Engineer	Wen Chao	Configurations	IEEE 802.11ac
Test Date	Jul. 19, 2013		

For 2.4GHz Band

Configuration IEEE 802.11ac MCS0/Nss1 20MHz

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3			
1	2412 MHz	17.27	16.83	17.01	21.81	30.00	Complies
6	2437 MHz	25.20	23.85	23.88	29.13	30.00	Complies
11	2462 MHz	16.79	16.43	16.35	21.30	30.00	Complies

Note: Directional gain = $G_{ANT} + 10\log(N_{ANT}/N_{ss}) = 5.37\text{dBi} < 6\text{dBi}$, so the limit doesn't reduce.

Configuration IEEE 802.11ac MCS0/Nss1 40MHz

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3			
3	2422 MHz	16.56	16.31	16.52	21.24	30.00	Complies
6	2437 MHz	17.23	16.88	17.27	21.90	30.00	Complies
9	2452 MHz	14.43	14.02	14.47	19.08	30.00	Complies

Note: Directional gain = $G_{ANT} + 10\log(N_{ANT}/N_{ss}) = 5.37\text{dBi} < 6\text{dBi}$, so the limit doesn't reduce.

For 5GHz Band

Configuration IEEE 802.11ac MCS0/Nss1 20MHz

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3			
149	5745 MHz	25.59	24.32	25.37	29.90	30.00	Complies
157	5785 MHz	25.41	24.25	25.26	29.77	30.00	Complies
165	5825 MHz	25.24	24.73	25.26	29.85	30.00	Complies

Note: Directional gain = $G_{ANT} + 10\log(N_{ANT}/N_{ss}) = 5.67\text{dBi} < 6\text{dBi}$, so the limit doesn't reduce.

Configuration IEEE 802.11ac MCS0/Nss1 40MHz

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3			
151	5755 MHz	25.41	24.52	25.12	29.80	30.00	Complies
159	5795 MHz	25.36	24.54	25.10	29.78	30.00	Complies

Note: Directional gain = $G_{ANT} + 10\log(N_{ANT}/N_{ss}) = 5.67\text{dBi} < 6\text{dBi}$, so the limit doesn't reduce.

Configuration IEEE 802.11ac MCS0/Nss1 80MHz

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3			
155	5775 MHz	23.11	22.65	23.25	27.78	30.00	Complies

Note: Directional gain = $G_{ANT} + 10\log(N_{ANT}/N_{ss}) = 5.67\text{dBi} < 6\text{dBi}$, so the limit doesn't reduce.

Temperature	26°C	Humidity	63%
Test Engineer	Wen Chao	Configurations	IEEE 802.11a/b/g
Test Date	Jul. 19, 2013		

Configuration IEEE 802.11b

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3			
1	2412 MHz	23.82	23.26	23.25	28.22	30.00	Complies
6	2437 MHz	25.57	24.00	23.22	29.15	30.00	Complies
11	2462 MHz	23.57	23.16	23.14	28.07	30.00	Complies

Configuration IEEE 802.11g

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3			
1	2412 MHz	17.03	16.61	16.81	21.59	30.00	Complies
6	2437 MHz	25.13	23.66	23.83	29.03	30.00	Complies
11	2462 MHz	16.96	16.66	16.82	21.59	30.00	Complies

Configuration IEEE 802.11a

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3			
149	5745 MHz	25.54	24.57	25.48	29.99	30.00	Complies
157	5785 MHz	25.52	24.67	25.29	29.95	30.00	Complies
165	5825 MHz	25.41	24.84	25.23	29.94	30.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.3.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03 section 10.2 Method PKPSD (peak PSD) & KDB 662911 D01 v02 section In-Band Power Spectral Density (PSD) Measurements option (2) Measure and add $10 \log(\text{NANT})$ dB.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be ≤ 8 dBm.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	23°C	Humidity	63%
Test Engineer	Wen Chao	Configurations	IEEE 802.11ac

For 2.4GHz Band

Configuration IEEE 802.11ac MCS0/Nss1 20MHz

Channel	Frequency	Power Density (dBm/3kHz)			Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Chain 3		
1	2412 MHz	-8.33	-10.27	-9.49	3.23	Complies
6	2437 MHz	-0.95	-3.04	-4.86	3.23	Complies
11	2462 MHz	-10.24	-9.19	-9.79	3.23	Complies

Note: PSD Limit = $(8\text{dBm} - (10\log(3))) = 3.23\text{dBm}/3\text{kHz}$

Note: Directional gain = $G_{\text{ANT}} + 10\log(N_{\text{ANT}}/N_{\text{ss}}) = 5.37\text{dBi} < 6\text{dBi}$, so the limit doesn't reduce.

Configuration IEEE 802.11ac MCS0/Nss1 40MHz

Channel	Frequency	Power Density (dBm/3kHz)			Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Chain 3		
3	2422 MHz	-11.96	-14.06	-14.78	3.23	Complies
6	2437 MHz	-12.00	-12.35	-12.80	3.23	Complies
9	2452 MHz	-13.93	-15.44	-15.59	3.23	Complies

Note: PSD Limit = $(8\text{dBm} - (10\log(3))) = 3.23\text{dBm}/3\text{kHz}$

Note: Directional gain = $G_{\text{ANT}} + 10\log(N_{\text{ANT}}/N_{\text{ss}}) = 5.37\text{dBi} < 6\text{dBi}$, so the limit doesn't reduce.

For 5GHz Band
Configuration IEEE 802.11ac MCS0/Nss1 20MHz

Channel	Frequency	Power Density (dBm/3kHz)			Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Chain 3		
149	5745 MHz	-0.41	-0.52	-1.41	3.23	Complies
157	5785 MHz	0.83	-0.06	-0.57	3.23	Complies
165	5825 MHz	0.35	-0.75	0.55	3.23	Complies

Note: PSD Limit = $(8\text{dBm} - (10\log(3))) = 3.23\text{dBm}/3\text{kHz}$

Note: Directional gain = $G_{\text{ANT}} + 10\log(N_{\text{ANT}}/N_{\text{ss}}) = 5.67\text{dBi} < 6\text{dBi}$, so the limit doesn't reduce.

Configuration IEEE 802.11ac MCS0/Nss1 40MHz

Channel	Frequency	Power Density (dBm/3kHz)			Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Chain 3		
151	5755 MHz	-1.65	-4.06	-2.95	3.23	Complies
159	5795 MHz	-3.03	-2.37	-3.15	3.23	Complies

Note: PSD Limit = $(8\text{dBm} - (10\log(3))) = 3.23\text{dBm}/3\text{kHz}$

Note: Directional gain = $G_{\text{ANT}} + 10\log(N_{\text{ANT}}/N_{\text{ss}}) = 5.67\text{dBi} < 6\text{dBi}$, so the limit doesn't reduce.

Configuration IEEE 802.11ac MCS0/Nss1 80MHz

Channel	Frequency	Power Density (dBm/3kHz)			Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Chain 3		
155	5775 MHz	-7.86	-7.99	-7.22	3.23	Complies

Note: PSD Limit = $(8\text{dBm} - (10\log(3))) = 3.23\text{dBm}/3\text{kHz}$

Note: Directional gain = $G_{\text{ANT}} + 10\log(N_{\text{ANT}}/N_{\text{ss}}) = 5.67\text{dBi} < 6\text{dBi}$, so the limit doesn't reduce.

Temperature	26°C	Humidity	63%
Test Engineer	Wen Chao	Configurations	IEEE 802.11a/b/g

Configuration IEEE 802.11b

Channel	Frequency	Power Density (dBm/3kHz)			Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Chain 3		
1	2412 MHz	1.54	-0.06	1.05	3.23	Complies
6	2437 MHz	2.04	-0.23	1.80	3.23	Complies
11	2462 MHz	0.90	0.15	-0.66	3.23	Complies

Note: PSD Limit $= (8\text{dBm} - (10\log(3))) = 3.23\text{dBm}/3\text{kHz}$

Configuration IEEE 802.11g

Channel	Frequency	Power Density (dBm/3kHz)			Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Chain 3		
1	2412 MHz	-7.55	-9.74	-9.90	3.23	Complies
6	2437 MHz	-2.09	-4.70	-4.34	3.23	Complies
11	2462 MHz	-9.29	-9.37	-9.63	3.23	Complies

Note: PSD Limit $= (8\text{dBm} - (10\log(3))) = 3.23\text{dBm}/3\text{kHz}$

Configuration IEEE 802.11a

Channel	Frequency	Power Density (dBm/3kHz)			Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Chain 3		
149	5745 MHz	-0.58	-0.57	0.15	3.23	Complies
157	5785 MHz	0.09	0.46	0.63	3.23	Complies
165	5825 MHz	-0.15	0.08	0.66	3.23	Complies


Note: PSD Limit $= (8\text{dBm} - (10\log(3))) = 3.23\text{dBm}/3\text{kHz}$

Note: All the test values were listed in the report.

For plots, only the channel with maximum results was shown.


For 2.4GHz Band

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / Chain 1 / 2437 MHz



Date: 19.JUL.2013 02:35:31


Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / Chain 1 / 2422 MHz



Date: 19.JUL.2013 02:41:11


For 5GHz Band

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / Chain 1 / 5785 MHz




Date: 19.JUL.2013 02:57:41

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / Chain 1 / 5755 MHz




Date: 19.JUL.2013 03:01:49

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 80MHz / Chain 3 / 5775 MHz




Date: 19.JUL.2013 03:08:11

Power Density Plot on Configuration IEEE 802.11b / Chain 1 / 2437 MHz




Date: 19.JUL.2013 02:21:37

Power Density Plot on Configuration IEEE 802.11g / Chain 1 / 2437 MHz



Date: 19.JUL.2013 02:27:52

Power Density Plot on Configuration IEEE 802.11a / Chain 3 / 5825 MHz



Date: 19.JUL.2013 02:54:58

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 D01 v03 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 8.0 DTS 6-dB signal bandwidth option 1.
3. Multiple antenna system was performed in accordance with KDB 662911 D01 v02 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	26°C	Humidity	63%
Test Engineer	Wen Chao	Configurations	IEEE 802.11ac

For 2.4GHz Band

Configuration IEEE 802.11ac MCS0/Nss1 20MHz / Chain 1 + Chain 2 + Chain 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.56	17.44	500	Complies
6	2437 MHz	16.64	19.76	500	Complies
11	2462 MHz	16.64	17.28	500	Complies

Configuration IEEE 802.11ac MCS0/Nss1 40MHz / Chain 1 + Chain 2 + Chain 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	35.84	36.32	500	Complies
6	2437 MHz	35.68	36.32	500	Complies
9	2452 MHz	35.84	36.32	500	Complies

For 5GHz Band
Configuration IEEE 802.11ac MCS0/Nss1 20MHz / Chain 1 + Chain 2 + Chain 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	16.32	25.84	500	Complies
157	5785 MHz	16.40	25.44	500	Complies
165	5825 MHz	16.32	25.52	500	Complies

Configuration IEEE 802.11ac MCS0/Nss1 40MHz / Chain 1 + Chain 2 + Chain 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	36.68	55.04	500	Complies
159	5795 MHz	36.68	53.12	500	Complies

Configuration IEEE 802.11ac MCS0/Nss1 80MHz / Chain 1 + Chain 2 + Chain 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
155	5775 MHz	75.84	76.48	500	Complies

Temperature	26°C	Humidity	63%
Test Engineer	Wen Chao	Configurations	IEEE 802.11 a/b/g

Configuration IEEE 802.11b / Chain 1 + Chain 2 + Chain 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	9.68	13.84	500	Complies
6	2437 MHz	9.52	13.68	500	Complies
11	2462 MHz	9.92	14.40	500	Complies

Configuration IEEE 802.11g / Chain 1 + Chain 2 + Chain 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	13.04	16.56	500	Complies
6	2437 MHz	15.68	20.32	500	Complies
11	2462 MHz	13.28	16.48	500	Complies

Configuration IEEE 802.11a / Chain 1 + Chain 2 + Chain 3


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	12.80	28.24	500	Complies
157	5785 MHz	13.20	28.24	500	Complies
165	5825 MHz	12.96	28.24	500	Complies

Note: All the test values were listed in the report.

For plots, only the channel with maximum results was shown.


For 2.4GHz Band

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / Chain 1 + Chain 2 + Chain 3 / 2412 MHz



Date: 19.JUL.2013 01:37:57


6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / Chain 1 + Chain 2 + Chain 3 / 2437 MHz



Date: 19.JUL.2013 01:41:25


For 5GHz Band

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / Chain 1 + Chain 2 + Chain 3 / 5745 MHz




Date: 19.JUL.2013 01:46:57

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / Chain 1 + Chain 2 + Chain 3 / 5755 MHz




Date: 19.JUL.2013 01:48:10

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 80MHz / Chain 1 + Chain 2 + Chain 3 / 5775 MHz




Date: 19.JUL.2013 01:51:15

6 dB Bandwidth Plot on Configuration IEEE 802.11b / Chain 1 + Chain 2 + Chain 3 / 2437 MHz




Date: 19.JUL.2013 01:31:57

6 dB Bandwidth Plot on Configuration IEEE 802.11g / Chain 1 + Chain 2 + Chain 3 / 2412 MHz



Date: 19.JUL.2013 01:37:07

6 dB Bandwidth Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 + Chain 3 / 5745 MHz



Date: 19.JUL.2013 01:43:31

4.5. Radiated Emissions Measurement

4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1GHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1GHz / RBW 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

For non-beamforming mode

The EUT was programmed to be in continuously transmitting mode.

For beamforming mode

The EUT was programmed to be in beamforming transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	Normal Link
Test Date	Jul. 25, 2013		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	Normal Link / Mode 2

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	94.02	35.58	43.50	-7.92	56.57	1.15	9.43	31.57	400	201	HORIZONTAL Peak
2 p	136.70	36.02	43.50	-7.48	55.04	1.39	11.13	31.54	200	170	HORIZONTAL Peak
3	500.45	38.26	46.00	-7.74	49.93	2.82	16.92	31.41	100	86	HORIZONTAL Peak
4	533.43	34.52	46.00	-11.48	45.28	2.90	17.72	31.38	100	264	HORIZONTAL Peak
5	600.36	35.02	46.00	-10.98	44.69	3.12	18.45	31.24	200	281	HORIZONTAL Peak
6	978.66	37.62	54.00	-16.38	43.37	4.14	21.20	31.09	150	238	HORIZONTAL Peak

Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1 !	30.00	35.44	40.00	-4.56	48.63	0.64	17.98	31.81	148	202	VERTICAL	QP
2 pk	34.85	36.97	40.00	-3.03	52.93	0.69	15.23	31.88	100	153	VERTICAL	Peak
3	40.67	36.99	40.00	-3.01	56.26	0.75	11.85	31.87	114	161	VERTICAL	QP
4 !	47.46	35.98	40.00	-4.02	58.35	0.82	8.62	31.81	100	67	VERTICAL	QP
5	53.28	33.54	40.00	-6.46	57.94	0.86	6.52	31.78	125	153	VERTICAL	QP
6 !	86.26	34.58	40.00	-5.42	57.20	1.10	7.94	31.66	150	186	VERTICAL	Peak

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

For 2.4GHz Band

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11ac MCS0/Nss1 20MHz Ch 1 / Chain 1 + Chain 2 + Chain 3
Test Date	Jul. 14, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	4825.17	30.13	54.00	-23.87	28.05	4.21	34.69	32.56	Average	230	100	HORIZONTAL
2	4826.37	44.10	74.00	-29.90	42.02	4.21	34.69	32.56	Peak	230	100	HORIZONTAL
3 a	4999.97	37.19	54.00	-16.81	34.67	4.24	34.62	32.90	Average	326	129	HORIZONTAL
4 p	5000.00	46.30	74.00	-27.70	43.78	4.24	34.62	32.90	Peak	326	129	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	4822.38	30.37	54.00	-23.63	28.29	4.21	34.69	32.56	Average	128	100	VERTICAL
2	4826.12	43.82	74.00	-30.18	41.74	4.21	34.69	32.56	Peak	128	100	VERTICAL
3 a	4999.94	43.33	54.00	-10.67	40.81	4.24	34.62	32.90	Average	24	100	VERTICAL
4 p	4999.97	48.81	74.00	-25.19	46.29	4.24	34.62	32.90	Peak	24	100	VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11ac MCS0/Nss1 20MHz Ch 6 / Chain 1+ Chain 2+ Chain 3
Test Date	Jul. 14, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	4871.10	43.46	74.00	-30.54	41.25	4.22	34.67	32.66	Peak	144	100	HORIZONTAL
2 a	4876.64	30.50	54.00	-23.50	28.29	4.22	34.67	32.66	Average	144	100	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	4873.96	39.91	54.00	-14.09	37.70	4.22	34.67	32.66	Average	130	176	VERTICAL
2 p	4874.48	44.78	74.00	-29.22	42.57	4.22	34.67	32.66	Peak	130	176	VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11ac MCS0/Nss1 20MHz Ch11 / Chain 1+ Chain 2+ Chain 3
Test Date	Jul. 14, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	4922.82	43.63	74.00	-30.37	41.29	4.23	34.65	32.76	Peak	130	100	HORIZONTAL
2 a	4925.64	30.53	54.00	-23.47	28.19	4.23	34.65	32.76	Average	130	100	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	4923.81	43.99	74.00	-30.01	41.65	4.23	34.65	32.76	Peak	223	100	VERTICAL
2 a	4924.02	29.92	54.00	-24.08	27.58	4.23	34.65	32.76	Average	223	100	VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11ac MCS0/Nss1 40MHz Ch 3 / Chain 1+ Chain 2+ Chain 3
Test Date	Jul. 14, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	4839.52	30.04	54.00	-23.96	27.92	4.21	34.68	32.59	Average	65	100	HORIZONTAL
2 p	4842.58	43.45	74.00	-30.55	41.33	4.21	34.68	32.59	Peak	65	100	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	4840.16	30.12	54.00	-23.88	28.00	4.21	34.68	32.59	Average	188	100	VERTICAL
2 p	4847.94	42.87	74.00	-31.13	40.75	4.21	34.68	32.59	Peak	188	100	VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11ac MCS0/Nss1 40MHz Ch 6 / Chain 1+ Chain 2+ Chain 3
Test Date	Jul. 14, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	4873.53	30.16	54.00	-23.84	27.95	4.22	34.67	32.66	Average	156	100	HORIZONTAL
2 p	4875.45	43.84	74.00	-30.16	41.63	4.22	34.67	32.66	Peak	156	100	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	4873.71	43.03	74.00	-30.97	40.82	4.22	34.67	32.66	Peak	278	100	VERTICAL
2 a	4875.91	30.04	54.00	-23.96	27.83	4.22	34.67	32.66	Average	278	100	VERTICAL



Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11ac MCS0/Nss1 20MHz Ch 9 / Chain 1+ Chain 2+ Chain 3
Test Date	Jul. 14, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	4903.24	43.26	74.00	-30.74	40.97	4.22	34.66	32.73	Peak	178	100	HORIZONTAL
2 a	4905.77	30.46	54.00	-23.54	28.17	4.22	34.66	32.73	Average	178	100	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	4905.63	43.36	74.00	-30.64	41.07	4.22	34.66	32.73	Peak	60	100	VERTICAL
2 a	4906.20	29.42	54.00	-24.58	27.13	4.22	34.66	32.73	Average	60	100	VERTICAL

For 5GHz Band

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11ac MCS0/Nss1 20MHz CH 149 / Chain 1+ Chain 2+ Chain 3
Test Date	Jul. 12, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11493.37	48.77	74.00	-25.23	40.15	5.12	38.78	35.28	Peak	100	237 HORIZONTAL
2	11497.76	35.78	54.00	-18.22	27.16	5.12	38.78	35.28	Average	100	237 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11485.00	38.41	54.00	-15.59	29.80	5.11	38.78	35.28	Average	100	277 VERTICAL
2	11485.00	47.98	74.00	-26.02	39.37	5.11	38.78	35.28	Peak	100	277 VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11ac MCS0/Nss1 20MHz CH 157 / Chain 1+ Chain 2+ Chain 3
Test Date	Jul. 12, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5061.84	47.53	74.00	-26.47	45.62	3.40	33.52	35.01	Peak	175	288 HORIZONTAL
2	5061.85	39.02	54.00	-14.98	37.11	3.40	33.52	35.01	Average	175	288 HORIZONTAL
3	11569.84	53.53	74.00	-20.47	44.86	5.14	38.83	35.30	Peak	100	351 HORIZONTAL
4	11570.02	35.65	54.00	-18.35	26.98	5.14	38.83	35.30	Average	100	351 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5061.87	52.66	74.00	-21.34	50.75	3.40	33.52	35.01	Peak	109	329 VERTICAL
2	5061.87	46.65	54.00	-7.35	44.74	3.40	33.52	35.01	Average	109	329 VERTICAL
3	11566.60	49.27	74.00	-24.73	40.62	5.13	38.82	35.30	Peak	100	290 VERTICAL
4	11569.39	37.28	54.00	-16.72	28.62	5.13	38.83	35.30	Average	100	290 VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11ac MCS0/Nss1 20MHz CH 165 / Chain 1+ Chain 2+ Chain 3
Test Date	Jul. 12, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5096.86	40.48	54.00	-13.52	38.50	3.42	33.58	35.02	Average	163	261 HORIZONTAL
2	5096.98	49.51	74.00	-24.49	47.53	3.42	33.58	35.02	Peak	163	261 HORIZONTAL
3	11649.65	36.04	54.00	-17.96	27.32	5.16	38.86	35.30	Average	100	262 HORIZONTAL
4	11650.04	51.06	74.00	-22.94	42.34	5.16	38.86	35.30	Peak	100	262 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5096.72	53.00	74.00	-21.00	51.02	3.42	33.58	35.02	Peak	108	333 VERTICAL
2	5096.89	47.10	54.00	-6.90	45.12	3.42	33.58	35.02	Average	108	333 VERTICAL
3	11649.65	50.10	74.00	-23.90	41.38	5.16	38.86	35.30	Peak	100	47 VERTICAL
4	11650.49	41.77	54.00	-12.23	33.05	5.16	38.86	35.30	Average	100	47 VERTICAL



Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11ac MCS0/Nss1 40MHz CH 151 / Chain 1+ Chain 2+ Chain 3
Test Date	Jul. 12, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11516.62	35.44	54.00	-18.56	26.81	5.12	38.80	35.29	Average	100	162	HORIZONTAL
2	11526.60	48.27	74.00	-25.73	39.63	5.13	38.80	35.29	Peak	100	162	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11490.00	35.71	54.00	-18.29	27.10	5.11	38.78	35.28	Average	100	360	VERTICAL
2	11525.83	48.94	74.00	-25.06	40.30	5.13	38.80	35.29	Peak	100	360	VERTICAL



Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11ac MCS0/Nss1 40MHz CH 159 / Chain 1+ Chain 2+ Chain 3
Test Date	Jul. 12, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11570.96	37.12	54.00	-16.88	28.45	5.14	38.83	35.30	Average	100	193	HORIZONTAL
2	11607.12	48.49	74.00	-25.51	39.80	5.15	38.84	35.30	Peak	100	193	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11583.43	36.53	54.00	-17.47	27.86	5.14	38.83	35.30	Average	100	294	VERTICAL
2	11585.26	47.80	74.00	-26.20	39.13	5.14	38.83	35.30	Peak	100	294	VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11ac MCS0/Nss1 80MHz CH 155 / Chain 1+ Chain 2+ Chain 3
Test Date	Jul. 10, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	5133.33	34.41	54.00	-19.59	30.83	5.98	33.01	35.41	100	155	HORIZONTAL	Average
2	5133.82	46.67	74.00	-27.33	43.09	5.98	33.01	35.41	100	155	HORIZONTAL	Peak
3	11530.40	40.04	54.00	-13.96	26.73	9.10	39.06	34.85	125	329	HORIZONTAL	Average
4 pk	11574.40	54.34	74.00	-19.66	41.07	9.11	39.01	34.85	125	329	HORIZONTAL	Peak

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1 pk	5133.25	54.52	74.00	-19.48	50.94	5.98	33.01	35.41	104	339	VERTICAL	Peak
2	5133.37	47.40	54.00	-6.60	43.82	5.98	33.01	35.41	104	339	VERTICAL	Average
3	11535.50	39.40	54.00	-14.60	26.09	9.10	39.06	34.85	100	306	VERTICAL	Average
4	11538.20	52.24	74.00	-21.76	38.93	9.10	39.06	34.85	100	306	VERTICAL	Peak



Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11b CH 1 / Chain 1 + Chain 2+ Chain 3
Test Date	Jul. 12, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1 pk	4823.91	47.65	74.00	-26.35	44.50	5.69	32.76	35.30	196	4	HORIZONTAL	Peak
2	4824.01	42.04	54.00	-11.96	38.89	5.69	32.76	35.30	196	4	HORIZONTAL	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1 pk	4823.91	47.11	74.00	-26.89	43.96	5.69	32.76	35.30	100	329	VERTICAL	Peak
2	4823.99	40.09	54.00	-13.91	36.94	5.69	32.76	35.30	100	329	VERTICAL	Average

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11b CH 6 / Chain 1 + Chain 2 + Chain 3
Test Date	Jul. 12, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4873.92	47.76	74.00	-26.24	44.52	5.75	32.80	35.31	189	6 HORIZONTAL	Peak
2	4873.99	41.25	54.00	-12.75	38.01	5.75	32.80	35.31	189	6 HORIZONTAL	Average
3 pk	7314.09	49.06	74.00	-24.94	40.24	7.06	37.12	35.36	100	195 HORIZONTAL	Peak
4	7315.38	36.11	54.00	-17.89	27.29	7.06	37.12	35.36	100	195 HORIZONTAL	Average

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4874.00	44.91	54.00	-9.09	41.67	5.75	32.80	35.31	124	106 VERTICAL	Average
2 pk	4874.00	49.66	74.00	-24.34	46.42	5.75	32.80	35.31	124	106 VERTICAL	Peak
3	7336.50	37.03	54.00	-16.97	28.17	7.07	37.13	35.34	100	182 VERTICAL	Average
4	7336.60	49.54	74.00	-24.46	40.68	7.07	37.13	35.34	100	182 VERTICAL	Peak

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11b CH 11 / Chain 1 + Chain 2 + Chain 3
Test Date	Jul. 12, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4924.03	42.00	54.00	-12.00	38.68	5.81	32.84	35.33	190	344	HORIZONTAL Average
2	4924.06	48.29	74.00	-25.71	44.97	5.81	32.84	35.33	190	344	HORIZONTAL Peak
3 pk	7385.82	49.00	74.00	-25.00	40.07	7.09	37.16	35.32	100	329	HORIZONTAL Peak
4	7385.94	36.78	54.00	-17.22	27.85	7.09	37.16	35.32	100	329	HORIZONTAL Average

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4924.02	43.77	54.00	-10.23	40.45	5.81	32.84	35.33	100	330	VERTICAL Average
2	4924.08	48.72	74.00	-25.28	45.40	5.81	32.84	35.33	100	330	VERTICAL Peak
3 pk	7388.67	49.77	74.00	-24.23	40.83	7.09	37.16	35.31	100	360	VERTICAL Peak
4	7390.48	37.03	54.00	-16.97	28.09	7.09	37.16	35.31	100	360	VERTICAL Average

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11g CH 1 / Chain 1 + Chain 2 + Chain 3
Test Date	Jul. 14, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	4823.47	43.51	74.00	-30.49	41.43	4.21	34.69	32.56	Peak	2	100	HORIZONTAL
2 a	4824.72	30.66	54.00	-23.34	28.58	4.21	34.69	32.56	Average	2	100	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	4823.16	30.50	54.00	-23.50	28.42	4.21	34.69	32.56	Average	199	100	VERTICAL
2 p	4824.78	43.70	74.00	-30.30	41.62	4.21	34.69	32.56	Peak	199	100	VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11g CH 6 / Chain 1+ Chain 2+ Chain 3
Test Date	Jul. 14, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	4871.82	31.50	54.00	-22.50	29.29	4.22	34.67	32.66	Average	1	100	HORIZONTAL
2 p	4872.86	43.87	74.00	-30.13	41.66	4.22	34.67	32.66	Peak	1	100	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	4870.26	33.98	54.00	-20.02	31.77	4.22	34.67	32.66	Average	329	104	VERTICAL
2 p	4872.32	47.42	74.00	-26.58	45.21	4.22	34.67	32.66	Peak	329	104	VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11g CH 11 / Chain 1+ Chain 2+ Chain 3
Test Date	Jul. 14, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	4928.92	30.79	54.00	-23.21	28.45	4.23	34.65	32.76	Average	18	100	HORIZONTAL
2 p	4930.48	43.87	74.00	-30.13	41.53	4.23	34.65	32.76	Peak	18	100	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	4925.48	43.50	74.00	-30.50	41.16	4.23	34.65	32.76	Peak	14	100	VERTICAL
2 a	4926.20	30.87	54.00	-23.13	28.53	4.23	34.65	32.76	Average	14	100	VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11a CH 149 / Chain 1 + Chain 2+ Chain 3
Test Date	Jul. 11, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5026.78	47.15	74.00	-26.85	45.31	3.40	33.45	35.01	Peak	131	335 HORIZONTAL
2	5026.85	37.55	54.00	-16.45	35.71	3.40	33.45	35.01	Average	131	335 HORIZONTAL
3	11489.76	37.09	54.00	-16.91	28.48	5.11	38.78	35.28	Average	100	332 HORIZONTAL
4	11489.82	50.29	74.00	-23.71	41.68	5.11	38.78	35.28	Peak	100	332 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5026.72	51.79	74.00	-22.21	49.94	3.40	33.46	35.01	Peak	112	335 VERTICAL
2	5026.81	46.20	54.00	-7.80	44.35	3.40	33.46	35.01	Average	112	335 VERTICAL
3	11489.75	38.55	54.00	-15.45	29.94	5.11	38.78	35.28	Average	100	248 VERTICAL
4	11489.76	50.52	74.00	-23.48	41.91	5.11	38.78	35.28	Peak	100	248 VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11a CH 157 / Chain 1 + Chain 2 + Chain 3
Test Date	Jul. 11, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5061.86	40.44	54.00	-13.56	38.53	3.40	33.52	35.01	Average	143	295 HORIZONTAL
2	5061.95	49.30	74.00	-24.70	47.39	3.40	33.52	35.01	Peak	143	295 HORIZONTAL
3	11569.96	36.53	54.00	-17.47	27.86	5.14	38.83	35.30	Average	100	158 HORIZONTAL
4	11570.06	49.16	74.00	-24.84	40.49	5.14	38.83	35.30	Peak	100	158 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5061.87	54.40	74.00	-19.60	52.49	3.40	33.52	35.01	Peak	109	335 VERTICAL
2	5061.92	47.68	54.00	-6.32	45.77	3.40	33.52	35.01	Average	109	335 VERTICAL
3	11569.50	36.79	54.00	-17.21	28.13	5.13	38.83	35.30	Average	100	303 VERTICAL
4	11569.84	49.50	74.00	-24.50	40.83	5.14	38.83	35.30	Peak	100	303 VERTICAL

Temperature	24°C	Humidity	51%
Test Engineer	David Tseng	Configurations	IEEE 802.11a CH 165 / Chain 1+ Chain 2+ Chain 3
Test Date	Jul. 14, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	5096.84	44.25	54.00	-9.75	42.27	3.42	33.58	35.02	Average	161	293	HORIZONTAL
2	5097.00	51.43	74.00	-22.57	49.45	3.42	33.58	35.02	Peak	161	293	HORIZONTAL
3	11651.54	49.46	74.00	-24.54	40.74	5.16	38.86	35.30	Peak	100	74	HORIZONTAL
4	11653.21	39.48	54.00	-14.52	30.76	5.16	38.86	35.30	Average	100	74	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	5096.88	48.65	54.00	-5.35	46.67	3.42	33.58	35.02	Average	108	339	VERTICAL
2	5096.91	55.65	74.00	-18.35	53.67	3.42	33.58	35.02	Peak	108	339	VERTICAL
3	11649.46	40.88	54.00	-13.12	32.16	5.16	38.86	35.30	Average	100	255	VERTICAL
4	11650.13	52.44	74.00	-21.56	43.72	5.16	38.86	35.30	Peak	100	255	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Emissions Measurement

4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100 kHz / 300 kHz for Peak

4.6.3. Test Procedures

For Radiated band edges Measurement:

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around band edges.

For Radiated Out of Band Emission Measurement:

1. Test was performed in accordance with KDB 558074 D01 v03 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure
2. The radiated emission test is performed on each TX port of operating mode without summing or adding $10\log(N)$ since the limit is relative emission limit. Only worst data of each operating mode is presented.

4.6.4. Test Setup Layout

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Radiated Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

For non-beamforming mode

The EUT was programmed to be in continuously transmitting mode.

For beamforming mode

The EUT was programmed to be in beamforming transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

For 2.4GHz Band

Temperature	24°C	Humidity	51%
Test Engineer	Magic Lai	Configurations	IEEE 802.11ac MCS0/Nss1 20MHz Ch 1, 6, 11 / Chain 1+ Chain 2+ Chain 3
Test date	Jul. 12, 2013		

Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1 !	2389.40	73.50	74.00	-0.50	41.92	3.68	27.90	0.00	112	14 VERTICAL	Peak
2 !	2390.00	52.08	54.00	-1.92	20.50	3.68	27.90	0.00	112	14 VERTICAL	Average
3	2409.85	102.09			70.50	3.69	27.90	0.00	112	14 VERTICAL	Average
4 pk	2410.15	114.10			82.51	3.69	27.90	0.00	112	14 VERTICAL	Peak

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2389.20	64.97	74.00	-9.03	33.39	3.68	27.90	0.00	100	181 VERTICAL	Peak
2	2390.00	49.10	74.00	-24.90	17.52	3.68	27.90	0.00	100	181 VERTICAL	Peak
3	2444.91	112.64			81.03	3.71	27.90	0.00	100	181 VERTICAL	Average
4 pk	2445.11	123.46			91.85	3.71	27.90	0.00	100	181 VERTICAL	Peak
5 !	2484.90	53.64	54.00	-0.36	22.01	3.73	27.90	0.00	100	181 VERTICAL	Average
6 !	2484.90	68.78	74.00	-5.22	37.15	3.73	27.90	0.00	100	181 VERTICAL	Peak

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2459.70	107.78			76.16	3.72	27.90	0.00	100	181 VERTICAL	Average
2 pk	2460.10	119.86			88.24	3.72	27.90	0.00	100	181 VERTICAL	Peak
3 !	2484.50	53.50	54.00	-0.50	21.87	3.73	27.90	0.00	100	181 VERTICAL	Average
4 !	2485.10	73.25	74.00	-0.75	41.62	3.73	27.90	0.00	100	181 VERTICAL	Peak

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24°C	Humidity	51%
Test Engineer	Magic Lai	Configurations	IEEE 802.11ac MCS0/Nss1 40MHz Ch 3, 6, 9 / Chain 1 + Chain 2 + Chain 3
Test date	Jul. 12, 2013		

Channel 3

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1 !	2389.20	71.74	74.00	-2.26	40.16	3.68	27.90	0.00	100	180	VERTICAL	Peak
2 !	2389.40	52.37	54.00	-1.63	20.79	3.68	27.90	0.00	100	180	VERTICAL	Average
3	2434.91	101.25			69.65	3.70	27.90	0.00	100	180	VERTICAL	Average
4 pk	2439.72	113.50			81.89	3.71	27.90	0.00	100	180	VERTICAL	Peak

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2390.00	47.22	54.00	-6.78	15.64	3.68	27.90	0.00	100	176	VERTICAL	Average
2 !	2390.00	73.12	74.00	-0.88	41.54	3.68	27.90	0.00	100	176	VERTICAL	Peak
3 pk	2449.71	116.64			85.03	3.71	27.90	0.00	100	176	VERTICAL	Peak
4	2454.72	104.80			73.18	3.72	27.90	0.00	100	176	VERTICAL	Average
5 !	2484.30	72.19	74.00	-1.81	40.56	3.73	27.90	0.00	100	176	VERTICAL	Peak
6 !	2484.50	53.46	54.00	-0.54	21.83	3.73	27.90	0.00	100	176	VERTICAL	Average

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 9

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2455.10	103.17			71.55	3.72	27.90	0.00	100	177	VERTICAL	Average
2 pk	2455.30	113.91			82.29	3.72	27.90	0.00	100	177	VERTICAL	Peak
3 !	2484.90	53.63	54.00	-0.37	22.00	3.73	27.90	0.00	100	177	VERTICAL	Average
4 !	2485.30	69.86	74.00	-4.14	38.23	3.73	27.90	0.00	100	177	VERTICAL	Peak

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	24°C	Humidity	51%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b CH 1, 6, 11 / Chain 1+ Chain 2+ Chain 3
Test Date	Jul. 12, 2013		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1 !	2390.00	53.22	54.00	-0.78	21.64	3.68	27.90	0.00	100	160	VERTICAL	Average
2	2390.00	62.24	74.00	-11.76	30.66	3.68	27.90	0.00	100	160	VERTICAL	Peak
3 pk	2411.15	110.97			79.38	3.69	27.90	0.00	100	160	VERTICAL	Peak
4	2411.25	108.34			76.75	3.69	27.90	0.00	100	160	VERTICAL	Average

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2383.99	58.38	74.00	-15.62	26.80	3.68	27.90	0.00	100	177	VERTICAL	Peak
2	2390.00	44.53	54.00	-9.47	12.95	3.68	27.90	0.00	100	177	VERTICAL	Average
3	2437.70	104.46			72.85	3.71	27.90	0.00	100	177	VERTICAL	Average
4 pk	2439.70	107.52			75.91	3.71	27.90	0.00	100	177	VERTICAL	Peak
5 !	2483.50	48.23	54.00	-5.77	16.60	3.73	27.90	0.00	100	177	VERTICAL	Average
6	2487.30	60.44	74.00	-13.56	28.81	3.73	27.90	0.00	100	177	VERTICAL	Peak

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1 pk	2461.15	117.87			86.25	3.72	27.90	0.00	100	269	VERTICAL	Peak
2	2461.25	115.41			83.79	3.72	27.90	0.00	100	269	VERTICAL	Average
3 !	2483.50	53.46	54.00	-0.54	21.83	3.73	27.90	0.00	100	269	VERTICAL	Average
4	2484.40	62.08	74.00	-11.92	30.45	3.73	27.90	0.00	100	269	VERTICAL	Peak

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24°C	Humidity	51%
Test Engineer	Magic Lai	Configurations	IEEE 802.11g CH 1, 6, 11 / Chain 1 + Chain 2 + Chain 3
Test Date	Jul. 12, 2013		

Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1 !	2389.70	73.98	74.00	-0.02	42.40	3.68	27.90	0.00	100	160	VERTICAL	Peak
2 !	2390.00	51.23	54.00	-2.77	19.65	3.68	27.90	0.00	100	160	VERTICAL	Average
3 pk	2408.95	115.64	74.00	41.64	84.05	3.69	27.90	0.00	100	160	VERTICAL	Peak
4	2409.15	105.35			73.76	3.69	27.90	0.00	100	160	VERTICAL	Average

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2386.20	62.86	74.00	-11.14	31.28	3.68	27.90	0.00	100	177	VERTICAL	Peak
2	2390.00	47.26	54.00	-6.74	15.68	3.68	27.90	0.00	100	177	VERTICAL	Average
3	2439.90	111.17			79.56	3.71	27.90	0.00	100	177	VERTICAL	Average
4 pk	2440.30	122.84			91.23	3.71	27.90	0.00	100	177	VERTICAL	Peak
5 !	2483.90	68.52	74.00	-5.48	36.89	3.73	27.90	0.00	100	177	VERTICAL	Peak
6 !	2484.10	52.70	54.00	-1.30	21.07	3.73	27.90	0.00	100	177	VERTICAL	Average

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2464.95	108.60			76.98	3.72	27.90	0.00	100	177	VERTICAL	Average
2 pk	2465.05	119.10			87.48	3.72	27.90	0.00	100	177	VERTICAL	Peak
3 !	2484.00	51.83	54.00	-2.17	20.20	3.73	27.90	0.00	100	177	VERTICAL	Average
4 !	2484.30	73.79	74.00	-0.21	42.16	3.73	27.90	0.00	100	177	VERTICAL	Peak

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band / For 2.4GHz Band

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / Reference Level




Date: 14.JUL.2013 15:15:34

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 14.JUL.2013 15:17:10

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / CH 1 / 2500MHz~2650MHz (down 30dBc)




Date: 14.JUL.2013 15:17:51

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 14.JUL.2013 15:20:10

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 14.JUL.2013 15:19:42

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / Reference Level




Date: 14.JUL.2013 14:54:50

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / CH 3 / 30MHz~2400MHz (down 30dBc)




Date: 14.JUL.2013 15:02:26

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / CH 3 / 2500MHz~26500MHz (down 30dBc)




Date: 14.JUL.2013 15:04:23

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / CH 9 / 30MHz~2400MHz (down 30dBc)



Date: 14.JUL.2013 15:06:43


Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / CH 9 / 2500MHz~2650MHz (down 30dBc)



Date: 14.JUL.2013 15:06:11


For 5GHz Band

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / Reference Level




Date: 12.JUL.2013 06:13:35

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / CH 149 / 30MHz~5725MHz (down 30dBc)




Date: 12.JUL.2013 06:14:22

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / CH 149 / 5850MHz~40000MHz (down 30dBc)




Date: 12.JUL.2013 06:15:08

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / CH 165 / 30MHz~5725MHz (down 30dBc)




Date: 12.JUL.2013 06:16:31

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / CH 165 / 5850MHz~40000MHz (down 30dBc)




Date: 12.JUL.2013 06:15:54

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / Reference Level




Date: 12.JUL.2013 06:17:56

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / CH 151 / 30MHz~5725MHz (down 30dBc)




Date: 12.JUL.2013 06:20:37

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / CH 151 / 5850MHz~40000MHz (down 30dBc)




Date: 12.JUL.2013 06:20:14

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / CH 159 / 30MHz~5725MHz (down 30dBc)




Date: 12.JUL.2013 06:18:55

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / CH 159 / 5850MHz~40000MHz (down 30dBc)




Date: 12.JUL.2013 06:19:25

Plot on Configuration IEEE 802.11ac MCS0/Nss1 80MHz / Reference Level




Date: 12.JUL.2013 06:25:00

Plot on Configuration IEEE 802.11ac MCS0/Nss1 80MHz / CH 155 / 30MHz~5725MHz (down 30dBc)




Date: 12.JUL.2013 06:25:29

Plot on Configuration IEEE 802.11b / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 14.JUL.2013 15:42:31

Plot on Configuration IEEE 802.11b / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 14.JUL.2013 15:43:45

Plot on Configuration IEEE 802.11b / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 14.JUL.2013 15:43:15

Plot on Configuration IEEE 802.11g / Reference Level




Date: 14.JUL.2013 15:32:06

Plot on Configuration IEEE 802.11g / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 14.JUL.2013 15:35:06

Plot on Configuration IEEE 802.11g / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 14.JUL.2013 15:35:38

Plot on Configuration IEEE 802.11g / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 14.JUL.2013 15:36:47

Plot on Configuration IEEE 802.11g / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 14.JUL.2013 15:36:17

Plot on Configuration IEEE 802.11a / Reference Level




Date: 12.JUL.2013 06:29:19

Plot on Configuration IEEE 802.11a / CH 149 / 30MHz~5725MHz (down 30dBc)



Date: 12.JUL.2013 06:30:23

Plot on Configuration IEEE 802.11a / CH 165 / 5850MHz~40000MHz (down 30dBc)



Date: 12.JUL.2013 06:31:41

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Oct. 23, 2012	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov. 26, 2012	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127478	9kHz ~ 30MHz	Jul. 17, 2012	Conduction (CO01-CB)
Impulsbegrenzer Pulse Limiter	Rohde&Schwarz	ESH3-Z2	100430	9kHz~30MHz	Feb. 21, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	0.15MHz~30MHz	Dec. 04, 2012	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	-	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Apr. 16, 2013	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 31, 2012	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100056	9kHz~40GHz	Nov. 16, 2012	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9kHz ~ 2.75GHz	Apr. 12, 2013	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz - 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz - 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
Signal analyzer	R&S	F5V40	100979	9kHz~40GHz	Oct. 08, 2012	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 04, 2013	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	3 Way	MDC2366	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	4 Way	0120A04056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz - 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz - 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz - 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz - 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz - 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Nov. 28, 2012	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Nov. 27, 2012	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

“*” Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

7. MEASUREMENT UNCERTAINTY

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	0.026	dB	normal(k=2)	0.013
Cable loss	0.002	dB	normal(k=2)	0.001
AMN/LISN specification	1.200	dB	normal(k=2)	0.600
Mismatch				
Receiver VSWR 1=	-0.080	dB	U-shaped	0.060
AMN/LISN VSWR 2=				
Combined standard uncertainty $U_c(y)$				1.2
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				2.4

Uncertainty of Radiated Emission Measurement (30MHz ~ 1,000MHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	± 0.173	dB	K=1	0.086
Cable loss	± 0.174	dB	K=2	0.087
Antenna gain	± 0.169	dB	K=2	0.084
Site imperfection	± 0.433	dB	Triangular	0.214
Pre-amplifier gain	± 0.366	dB	K=2	0.183
Transmitter antenna	± 1.200	dB	Rectangular	0.600
Signal generator	± 0.461	dB	Rectangular	0.231
Mismatch	± 0.080	dB	U-shape	0.040
Spectrum analyzer	± 0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.778
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.555

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	±0.191	dB	K=1	0.095
Cable loss	±0.169	dB	K=2	0.084
Antenna gain	±0.191	dB	K=2	0.096
Site imperfection	±0.582	dB	Triangular	0.291
Pre-amplifier gain	±0.304	dB	K=2	0.152
Transmitter antenna	±1.200	dB	Rectangular	0.600
Signal generator	±0.461	dB	Rectangular	0.231
Mismatch	±0.080	dB	U-shape	0.040
Spectrum analyzer	±0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.839
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.678

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	±0.186	dB	K=1	0.093
Cable loss	±0.167	dB	K=2	0.083
Antenna gain	±0.190	dB	K=2	0.095
Site imperfection	±0.488	dB	Triangular	0.244
Pre-amplifier gain	±0.269	dB	K=2	0.134
Transmitter antenna	±1.200	dB	Rectangular	0.600
Signal generator	±0.461	dB	Rectangular	0.231
Mismatch	±0.080	dB	U-shape	0.040
Spectrum analyzer	±0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.771
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.541

Uncertainty of Conducted Emission Measurement

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Cable loss	±0.038	dB	K=2	0.019
Attenuator	±0.047	dB	K=2	0.024
Power Meter specification	±0.300	dB	Triangular	0.150
Power Sensor specification	±0.300	dB	Rectangular	0.150
Signal generator	±0.461	dB	Rectangular	0.231
Mismatch	±0.080	dB	U-shape	0.040
Spectrum analyzer	±0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				0.863
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				1.726