

RF Exposure Report

Report No.: SA140812C13F

FCC ID: PY314100252

Test Model: C7100V-100NAS

Received Date: Jan. 16, 2017

Test Date: Jan. 20, 2017

Issued Date: Feb. 02, 2017

Applicant: NETGEAR INC.

Address: 350 E. Plumeria Drive, San Jose CA 95134, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

| | |
|---|----------|
| Release Control Record | 3 |
| 1 Certificate of Conformity | 4 |
| 2 RF Exposure | 5 |
| 2.1 Limits For Maximum Permissible Exposure (MPE) | 5 |
| 2.2 MPE Calculation Formula | 5 |
| 2.3 Classification | 5 |
| 2.4 Antenna Gain | 6 |
| 2.5 Calculation Result Of Maximum Conducted Power | 7 |

Release Control Record

| Issue No. | Description | Date Issued |
|--------------|-------------------|---------------|
| SA140812C13F | Original release. | Feb. 02, 2017 |

1 Certificate of Conformity

Product: Wireless Cable Data Gateway

Brand: Netgear

Test Model: C7100V-100NAS

Sample Status: ENGINEERING SAMPLE

Applicant: NETGEAR INC.

Test Date: Jan. 20, 2017

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Wendy Wu , **Date:** Feb. 02, 2017
Wendy Wu / Specialist

Approved by : May Chen , **Date:** Feb. 02, 2017
May Chen / Manager

2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| Limits For General Population / Uncontrolled Exposure | | | | |
| 300-1500 | ... | ... | F/1500 | 30 |
| 1500-100,000 | ... | ... | 1.0 | 30 |

F = Frequency in MHz

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 25cm away from the body of the user.

So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

| 2.4GHz antenna | | | | | |
|----------------|---------------------|------------------------------------|---------------------------------|--------------|----------------|
| No. | Transmitter Circuit | Gain (dBi) (Include cable loss) | Frequency range (GHz to GHz) | Antenna Type | Connector Type |
| 1 | 0 | 2.07 | 2.4~2.4835 | PIFA | i-pex(MHF) |
| 2 | 1 | 2.07 | 2.4~2.4835 | PIFA | i-pex(MHF) |
| 3 | 2 | 2.07 | 2.4~2.4835 | PIFA | i-pex(MHF) |
| 5GHz antenna | | | | | |
| No. | Transmitter Circuit | Gain (dBi) (Include cable loss) | Frequency range (GHz to GHz) | Antenna Type | Connector Type |
| 4 | 0 | 3.33 | 5.15~5.25 | PIFA | i-pex(MHF) |
| | | 3.32 | 5.25~5.35 | PIFA | i-pex(MHF) |
| | | 3.29 | 5.47~5.725 | PIFA | i-pex(MHF) |
| | | 3.28 | 5.725~5.850 | PIFA | i-pex(MHF) |
| 5 | 1 | 3.33 | 5.15~5.25 | PIFA | i-pex(MHF) |
| | | 3.32 | 5.25~5.35 | PIFA | i-pex(MHF) |
| | | 3.29 | 5.47~5.725 | PIFA | i-pex(MHF) |
| | | 3.28 | 5.725~5.850 | PIFA | i-pex(MHF) |
| 6 | 2 | 3.33 | 5.15~5.25 | PIFA | i-pex(MHF) |
| | | 3.32 | 5.25~5.35 | PIFA | i-pex(MHF) |
| | | 3.29 | 5.47~5.725 | PIFA | i-pex(MHF) |
| | | 3.28 | 5.725~5.850 | PIFA | i-pex(MHF) |

2.5 Calculation Result Of Maximum Conducted Power

For 2.4GHz data was copied from the original test report (Report No.: SA140812C13C)

| Frequency Band (MHz) | Max Power (mW) | Antenna Gain (dBi) | Distance (cm) | Power Density (mW/cm ²) | Limit (mW/cm ²) |
|----------------------|----------------|--------------------|---------------|-------------------------------------|-----------------------------|
| 2412-2462 | 713.576 | 6.84 | 25 | 0.43888 | 1 |
| 5180-5240 | 603.761 | 8.1 | 25 | 0.49633 | 1 |
| 5745-5825 | 605.463 | 8.05 | 25 | 0.49204 | 1 |

NOTE:

2.4GHz: Directional gain = 2.07dBi + 10log(3) = 6.84dBi

5GHz:

For UNII-1: Directional gain = 3.33dBi + 10log(3) = 8.1dBi

For UNII-3: Directional gain = 3.28dBi + 10log(3) = 8.05dBi

Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz = 0.43888 / 1 + 0.49633 / 1 = 0.93521

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---