



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	NETGEAR, Inc.
Applicant Address	350 East Plumeria Drive, San Jose, California 95134, USA
FCC ID	PY314300288

Product Name	AC2350 Smart WiFi Router
Brand Name	NETGEAR
Model No.	R7500
Test Rule Part(s)	47 CFR FCC Part 15 Subpart E § 15.407
Test Freq. Range	5250 ~ 5350MHz / 5470 ~ 5725MHz
Received Date	Mar. 30, 2014
Final Test Date	Oct. 17, 2014
Submission Type	Class II Change
Operating Mode	Master

Statement

Test result included is for the IEEE 802.11n and IEEE 802.11a/ac of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2013, 47 CFR FCC Part 15 Subpart E, KDB789033 D01 v01r04, KDB662911 D01 v02r01, KDB644545 D01 v01r02.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.




Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	6
3.3. Table for Filed Antenna.....	7
3.4. Table for Carrier Frequencies	8
3.5. Table for Test Modes	9
3.6. Table for Testing Locations.....	12
3.7. Table for Class II Change	12
3.8. Table for Supporting Units	12
3.9. Table for Parameters of Test Software Setting	13
3.10. EUT Operation during Test	14
3.11. Duty Cycle.....	15
3.12. Test Configurations	16
4. TEST RESULT	19
4.1. AC Power Line Conducted Emissions Measurement.....	19
4.2. 26dB Bandwidth and 99% Occupied Bandwidth Measurement.....	23
4.3. Maximum Conducted Output Power Measurement.....	44
4.4. Power Spectral Density Measurement	49
4.5. Radiated Emissions Measurement	63
4.6. Band Edge Emissions Measurement	102
4.7. Frequency Stability Measurement	116
4.8. Antenna Requirements	118
5. LIST OF MEASURING EQUIPMENTS	119
6. MEASUREMENT UNCERTAINTY.....	121
APPENDIX A. TEST PHOTOS	A1 ~ A5
APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE	B1 ~ B3
APPENDIX C. RADIATED EMISSION CO-LOCATION REPORT	C1 ~ C3
APPENDIX D. 20DB BANDWIDTH REPORT.....	D1 ~ D5

1. CERTIFICATE OF COMPLIANCE

Product Name : AC2350 Smart WiFi Router
Brand Name : NETGEAR
Model No. : R7500
Applicant : NETGEAR, Inc.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart E § 15.407

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Mar. 30, 2014 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart E				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	15.04 dB
4.2	15.407(a)	26dB Spectrum Bandwidth and 99% Occupied Bandwidth	Complies	-
4.3	15.407(a)	Maximum Conducted Output Power	Complies	0.09 dB
4.4	15.407(a)	Power Spectral Density	Complies	0.03 dB
4.5	15.407(b)	Radiated Emissions	Complies	3.51 dB
4.6	15.407(b)	Band Edge Emissions	Complies	0.01 dB
4.7	15.407(g)	Frequency Stability	Complies	-
4.8	15.203	Antenna Requirements	Complies	-

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n/ac

Items	Description
Product Type	WLAN (4TX, 4RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter
Modulation	see the below table for IEEE 802.11n/ac
Data Modulation	For 802.11n: OFDM (BPSK / QPSK / 16QAM / 64QAM) For 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n/ac
Frequency Range	5250 ~ 5350MHz / 5470 ~ 5725MHz
Channel Number	12 for 20MHz bandwidth ; 5 for 40MHz bandwidth 2 for 80MHz bandwidth
Channel Band Width (99%)	<p>For non-beamforming mode:</p> <p>Band 2: 802.11ac MCS0/Nss1 (VHT20): 19.20 MHz ; 802.11ac MCS0/Nss1 (VHT40): 34.88 MHz ; 802.11ac MCS0/Nss1 (VHT80): 72.32 MHz</p> <p>Band 3: 802.11ac MCS0/Nss1 (VHT20): 18.88 MHz ; 802.11ac MCS0/Nss1 (VHT40): 32.96 MHz ; 802.11ac MCS0/Nss1 (VHT80): 72.96 MHz</p> <p>For beamforming mode:</p> <p>Band 2: 802.11ac MCS0/Nss2 (VHT20): 18.24 MHz ; 802.11ac MCS0/Nss2 (VHT40): 36.48 MHz ; 802.11ac MCS0/Nss2 (VHT80): 76.16 MHz</p> <p>Band 3: 802.11ac MCS0/Nss2 (VHT20): 18.24 MHz ; 802.11ac MCS0/Nss2 (VHT40): 36.48 MHz ; 802.11ac MCS0/Nss2 (VHT80): 76.16 MHz</p>

Maximum Conducted Output Power	<p>For non-beamforming mode:</p> <p>Band 2:</p> <p>802.11ac MCS0/Nss1 (VHT20): 21.98 dBm ; 802.11ac MCS0/Nss1 (VHT40): 23.91 dBm ; 802.11ac MCS0/Nss1 (VHT80): 21.65 dBm</p> <p>Band 3:</p> <p>802.11ac MCS0/Nss1 (VHT20): 21.57 dBm ; 802.11ac MCS0/Nss1 (VHT40): 23.67 dBm ; 802.11ac MCS0/Nss1 (VHT80): 21.36 dBm</p> <p>For beamforming mode:</p> <p>Band 2:</p> <p>802.11ac MCS0/Nss2 (VHT20): 23.70 dBm ; 802.11ac MCS0/Nss2 (VHT40): 23.81 dBm ; 802.11ac MCS0/Nss2 (VHT80): 20.34 dBm</p> <p>Band 3:</p> <p>802.11ac MCS0/Nss2 (VHT20): 23.39 dBm ; 802.11ac MCS0/Nss2 (VHT40): 23.46 dBm ; 802.11ac MCS0/Nss2 (VHT80): 21.16 dBm</p>
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

IEEE 802.11a

Items	Description
Product Type	WLAN (4TX, 4RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter
Modulation	OFDM for IEEE 802.11a
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	OFDM (6/9/12/18/24/36/48/54)
Frequency Range	5250 ~ 5350MHz / 5470 ~ 5725MHz
Channel Number	12
Channel Band Width (99%)	Band 2: 17.92 MHz ; Band 3: 17.92 MHz
Maximum Conducted Output Power	Band 2: 21.91 dBm ; Band 3: 21.46 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Items	Description	
Communication Mode	<input checked="" type="checkbox"/> IP Based (Load Based)	<input type="checkbox"/> Frame Based
TPC Function	<input checked="" type="checkbox"/> With TPC	<input type="checkbox"/> Without TPC
Weather Band (5600~5650MHz)	<input type="checkbox"/> With 5600~5650MHz	<input checked="" type="checkbox"/> Without 5600~5650MHz
Beamforming Function	<input checked="" type="checkbox"/> With beamforming for 802.11ac in 5GHz	<input type="checkbox"/> Without beamforming

Note: The beamforming function doesn't support MCS0/Nss1 in band2/3.

Antenna and Band width

Antenna	Four (TX)		
	20 MHz	40 MHz	80 MHz
IEEE 802.11a	V	X	X
IEEE 802.11n	V	V	X
IEEE 802.11ac	V	V	V

IEEE 11n/ac Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
For Non-Beamforming Mode		
802.11n (HT20)	4	MCS 0-31
802.11n (HT40)	4	MCS 0-31
802.11ac (VHT20)	4	MCS 0-9/Nss1-4
802.11ac (VHT40)	4	MCS 0-9/Nss1-4
802.11ac (VHT80)	4	MCS 0-9/Nss1-4
For Beamforming Mode		
802.11ac (VHT20)	4	MCS 0-9/Nss2-4
802.11ac (VHT40)	4	MCS 0-9/Nss2-4
802.11ac (VHT80)	4	MCS 0-9/Nss2-4
<p>Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20 and HT40.</p> <p>Note 2: IEEE Std. 802.11ac modulation consists of VHT20, VHT40, VHT80 and VHT160 (VHT: Very High Throughput). Then EUT support VHT20, VHT40 and VHT80.</p> <p>Note 3: Modulation modes consist of below configuration: HT20/HT40: IEEE 802.11n, VHT20/VHT40/VHT80: IEEE 802.11ac</p>		

3.2. Accessories

Power	Brand	Model No.	P/N	Rating
Adapter 1	NETGEAR	AD898F20	332-10613-01	Input: 100-240Vac, 50/60Hz, 1.0A Output: 12Vdc, 3.5A
Adapter 2	LEI	MU42-1120350-A1	332-10728-01	Input: 100-240Vac, 50/60Hz, 1.5A Output: 12Vdc, 3.5A

3.3. Table for Filed Antenna

Ant.	Brand	Model No.	Antenna Type	Connector
1	NETGEAR	R7500	Dipole Antenna	Reversed-SMA

Note: The EUT has four external antennas.

2.4GHz Band			
Frequency	Gain (dBi)	Frequency	Gain (dBi)
2412 MHz	0.9	2452 MHz	0.9
2422 MHz	1.1	2462 MHz	0.8
2437 MHz	1.1	-	-

5GHz Band 2		5GHz Band 3	
Frequency	Gain (dBi)	Frequency	Gain (dBi)
5260 MHz	2.3	5500 MHz	2.9
5270 MHz	2.4	5510 MHz	3.0
5290 MHz	2.5	5530 MHz	3.0
5300 MHz	2.5	5550 MHz	3.0
5310 MHz	2.5	5580 MHz	2.9
5320 MHz	2.5	5670 MHz	3.0
-	-	5700 MHz	2.9


Note:

For 2.4GHz Band (3TX/3RX)

Chain 2, Chain 3 and Chain 4 could transmit/receive simultaneously.

For 5GHz Band (4TX/4RX)

Chain 1, Chain 2, Chain 3 and Chain 4 could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

There are three bandwidth systems.

For 20MHz bandwidth systems, use Channel 52, 56, 60, 64, 100, 104, 108, 112, 116, 132, 136, 140.

For 40MHz bandwidth systems, use Channel 54, 62, 102, 110, 134.

For 80MHz bandwidth systems, use Channel 58, 106.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5250~5350 MHz Band 2	52	5260 MHz	60	5300 MHz
	54	5270 MHz	62	5310 MHz
	56	5280 MHz	64	5320 MHz
	58	5290 MHz	-	-
5470~5725 MHz Band 3	100	5500 MHz	112	5560 MHz
	102	5510 MHz	116	5580 MHz
	104	5520 MHz	132	5660 MHz
	106	5530 MHz	134	5670 MHz
	108	5540 MHz	136	5680 MHz
	110	5550 MHz	140	5700 MHz

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode		Data Rate	Channel	Chain
AC Power Conducted Emission	CTX		-	-	-
Max. Conducted Output Power	Non-beamforming Mode				
	11ac VHT20	Band 2-3	MCS0/Nss1	52/60/64/100/ 116/140	1+2+3+4
	11ac VHT40	Band 2-3	MCS0/Nss1	54/62/102/110 /134	1+2+3+4
	11ac VHT80	Band 2-3	MCS0/Nss1	58/106	1+2+3+4
	11a/BPSK	Band 2-3	6Mbps	52/60/64/100/ 116/140	1+2+3+4
	Beamforming Mode				
	11ac VHT20	Band 2-3	MCS0/Nss2	52/60/64/100/ 116/140	1+2+3+4
	11ac VHT40	Band 2-3	MCS0/Nss2	54/62/102/110 /134	1+2+3+4
	11ac VHT80	Band 2-3	MCS0/Nss2	58/106	1+2+3+4
	Power Spectral Density	Non-beamforming Mode			
11ac VHT20		Band 2-3	MCS0/Nss1	52/60/64/100/ 116/140	1+2+3+4
11ac VHT40		Band 2-3	MCS0/Nss1	54/62/102/110 /134	1+2+3+4
11ac VHT80		Band 2-3	MCS0/Nss1	58/106	1+2+3+4
11a/BPSK		Band 2-3	6Mbps	52/60/64/100/ 116/140	1+2+3+4
Beamforming Mode					
11ac VHT20		Band 2-3	MCS0/Nss2	52/60/64/100/ 116/140	1+2+3+4
11ac VHT40		Band 2-3	MCS0/Nss2	54/62/102/110 /134	1+2+3+4
11ac VHT80		Band 2-3	MCS0/Nss2	58/106	1+2+3+4

26dB Spectrum Bandwidth 99% Occupied Bandwidth Measurement	Non-beamforming Mode				
	11ac VHT20	Band 2-3	MCS0/Nss1	52/60/64/100/ 116/140	1+2+3+4
	11ac VHT40	Band 2-3	MCS0/Nss1	54/62/102/110 /134	1+2+3+4
	11ac VHT80	Band 2-3	MCS0/Nss1	58/106	1+2+3+4
	11a/BPSK	Band 2-3	6Mbps	52/60/64/100/ 116/140	1+2+3+4
	Beamforming Mode				
	11ac VHT20	Band 2-3	MCS0/Nss2	52/60/64/100/ 116/140	1+2+3+4
	11ac VHT40	Band 2-3	MCS0/Nss2	54/62/102/110 /134	1+2+3+4
	11ac VHT80	Band 2-3	MCS0/Nss2	58/106	1+2+3+4
	Radiated Emission Below 1GHz	CTX	-	-	-
Radiated Emission Above 1GHz	Non-beamforming Mode				
	11ac VHT20	Band 2-3	MCS0/Nss1	52/60/64/100/ 116/140	1+2+3+4
	11ac VHT40	Band 2-3	MCS0/Nss1	54/62/102/110 /134	1+2+3+4
	11ac VHT80	Band 2-3	MCS0/Nss1	58/106	1+2+3+4
	11a/BPSK	Band 2-3	6Mbps	52/60/64/100/ 116/140	1+2+3+4
	Beamforming Mode				
	11ac VHT20	Band 2-3	MCS0/Nss2	52/60/64/100/ 116/140	1+2+3+4
	11ac VHT40	Band 2-3	MCS0/Nss2	54/62/102/110 /134	1+2+3+4
	11ac VHT80	Band 2-3	MCS0/Nss2	58/106	1+2+3+4

Band Edge Emission	Non-beamforming Mode				
	11ac VHT20	Band 2-3	MCS0/Nss1	52/60/64/100/ 116/140	1+2+3+4
	11ac VHT40	Band 2-3	MCS0/Nss1	54/62/102/110 /134	1+2+3+4
	11ac VHT80	Band 2-3	MCS0/Nss1	58/106	1+2+3+4
	11a/BPSK	Band 2-3	6Mbps	52/60/64/100/ 116/140	1+2+3+4
	Beamforming Mode				
	11ac VHT20	Band 2-3	MCS0/Nss2	52/60/64/100/ 116/140	1+2+3+4
	11ac VHT40	Band 2-3	MCS0/Nss2	54/62/102/110 /134	1+2+3+4
	11ac VHT80	Band 2-3	MCS0/Nss2	58/106	1+2+3+4
	Frequency Stability	Un-modulation	-	60/100	1+2+3+4

Note 1: VHT20/VHT40 covers HT20/HT40, due to same modulation.

Note 2: There are two modes of EUT, one is beamforming mode, and the other is non-beamforming mode for 802.11ac in 5GHz, beamforming mode and non-beamforming mode has been test and record in this test report.

The following test modes were performed for all tests:

For AC Power Line Conducted Emissions test:

Mode 1. EUT + Adapter 1

Mode 2. EUT + Adapter 2

Mode 1 is the worst case, so it was selected to record in this test report.

For Radiated Emission below 1GHz test:

Mode 1. EUT laying + Adapter 1

Mode 2. EUT standing + Adapter 1

Mode 1 has been evaluated to be the worst case among Mode 1~2, thus measurement for Mode 3 will follow this same test mode.

Mode 3. EUT laying + Adapter 2

Mode 1 is the worst case, so it was selected to record in this test report.

For Radiated Emission above 1GHz and Radiated Emission Co-location tests:

There are two modes of EUT, one is laying, and the other is standing.

Laying has been evaluated to be the worst case after evaluating.

Consequently, measurement for Radiated Emission above 1GHz and Radiated Emission Co-location tests will follow this same test mode.

For Co-location MPE and Radiated Emission Co-location Test:

The EUT could be applied with 2.4GHz WLAN function and 5GHz WLAN function; therefore Co-location Maximum Permissible Exposure (Please refer to Appendix B) and Radiated Emission Co-location (please refer to Appendix C) tests are added for simultaneously transmit between 2.4GHz WLAN function and 5GHz WLAN function.

3.6. Table for Testing Locations

Test Site Location					
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.				
TEL:	886-3-656-9065				
FAX:	886-3-656-9085				
Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D	-
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D	-
TH01-CB	OVEN Room	Hsin Chu	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.7. Table for Class II Change

This product is an extension of original one reported under Sporton project number: FR433001-03

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
Adding 5GHz Band 2 and Band 3 (5250~5350 MHz, 5470~5725 MHz) for this device.	1. 26dB Bandwidth and 99% Occupied Bandwidth Measurement 2. Maximum Conducted Output Power Measurement 3. Power Spectral Density Measurement 4. Radiated Emissions Measurement Above 1GHz 5. Band Edge Emissions Measurement 6. Frequency Stability Measurement

3.8. Table for Supporting Units

Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
NB	DELL	E6430	DoC

Test Site No: 03CH01-CB (below 1GHz)

Support Unit	Brand	Model	FCC ID
NB	DELL	E6430	DoC

Test Site No: 03CH01-CB (above 1GHz)

For non-beamforming Mode:

Support Unit	Brand	Model	FCC ID
NB	DELL	E6430	DoC

For beamforming Mode:

Support Unit	Brand	Model	FCC ID
NB	DELL	E6430	DoC
NB	DELL	M1330	DoC
WLAN ac Dongle	NETGEAR	A6200	PY312200200

Test Site No: TH01-CB

Support Unit	Brand	Model	FCC ID
NB	DELL	E6220	DoC

3.9. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

For non-beamforming mode:
Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT20

Test Software Version	DOS					
	5260 MHz	5300 MHz	5320 MHz	5500 MHz	5580 MHz	5700 MHz
MCS0/Nss1 VHT20	15	15	15	14	14	14

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT40

Test Software Version	DOS				
	5270 MHz	5310 MHz	5510 MHz	5550 MHz	5670 MHz
MCS0/Nss1 VHT40	17	17	15	16	16

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT80

Test Software Version	DOS	
	5290 MHz	5530 MHz
MCS0/Nss1 VHT80	15	14

Power Parameters of IEEE 802.11a

Test Software Version	DOS					
	5260 MHz	5300 MHz	5320 MHz	5500 MHz	5580 MHz	5700 MHz
802.11a	15	15	15	14	14	14

For beamforming mode:

Power Parameters of IEEE 802.11ac MCS0/Nss2 VHT20

Test Software Version	DOS					
Frequency	5260 MHz	5300 MHz	5320 MHz	5500 MHz	5580 MHz	5700 MHz
MCS0/Nss2 VHT20	17	17	17	16	16	16

Power Parameters of IEEE 802.11ac MCS0/Nss2 VHT40

Test Software Version	DOS				
Frequency	5270 MHz	5310 MHz	5510 MHz	5550 MHz	5670 MHz
MCS0/Nss2 VHT40	17	15	14	16	16

Power Parameters of IEEE 802.11ac MCS0/Nss2 VHT80

Test Software Version	DOS	
Frequency	5290 MHz	5530 MHz
MCS0/Nss2 VHT80	14	14

3.10. EUT Operation during Test

For non-beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

For beamforming mode:

For Conducted Mode:

The EUT was programmed to be in continuously transmitting mode.

For Radiated Mode:

During the test, the following programs under WIN XP were executed.

The program was executed as follows:

1. During the test, the EUT operation to normal function.
2. Executed command fixed test channel under DOS.
3. Executed "Lantest.exe " to link with the remote workstation to receive and transmit packet by WLAN ac Dongle and transmit duty cycle no less 98%

3.11. Duty Cycle

For non-beamforming mode:


Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
802.11ac MCS0/Nss1 VHT20	4.9855	5.0435	98.85%	0.05	0.01
802.11ac MCS0/Nss1 VHT40	2.4203	2.4783	97.66%	0.10	0.41
802.11ac MCS0/Nss1 VHT80	1.14203	1.18841	96.10%	0.17	0.88
802.11a	5.3768	5.4203	99.20%	0.03	0.01

For beamforming mode:

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
802.11ac MCS0/Nss2 VHT20	4.754	4.942	96.19%	0.17	0.21
802.11ac MCS0/Nss2 VHT40	2.246	2.4783	90.64%	0.43	0.45
802.11ac MCS0/Nss2 VHT80	2.290	2.391	95.77%	0.19	0.44

3.12. Test Configurations


3.12.1. AC Power Line Conduction Emissions and Radiation Emissions Below 1GHz Test Configuration



Item	Connection	Shielded	Length
1	Power cable	No	1.8m
2	RJ-45 cable	No	10m


3.12.2. Radiation Emissions Above 1GHz Test Configuration

For non-beamforming mode:



Item	Connection	Shielded	Length
1	Power cable	No	1.8m
2	RJ-45 cable	No	10m

For beamforming mode:



Item	Connection	Shielded	Length
1	Power cable	No	1.8m
2	RJ-45 cable	No	10m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product that is designed to connect to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	24°C	Humidity	51%
Test Engineer	Parody Lin	Phase	Line
Configuration	CTX	Test Mode	Mode 1



	Freq	Level	Over Limit	Limit Line	LISN Factor	Read Level	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dB	dBuV	dB		
1	0.16327	45.15	-20.15	65.30	0.08	44.91	0.16	LINE	QP
2	0.16327	31.28	-24.02	55.30	0.08	31.04	0.16	LINE	AVERAGE
3	0.24552	31.50	-30.41	61.91	0.08	31.25	0.17	LINE	QP
4	0.24552	25.71	-26.20	51.91	0.08	25.46	0.17	LINE	AVERAGE
5	0.53215	30.96	-15.04	46.00	0.08	30.69	0.19	LINE	AVERAGE
6	0.53215	36.21	-19.79	56.00	0.08	35.94	0.19	LINE	QP
7	1.203	20.27	-25.73	46.00	0.10	19.96	0.21	LINE	AVERAGE
8	1.203	26.24	-29.76	56.00	0.10	25.93	0.21	LINE	QP
9	3.799	26.78	-29.22	56.00	0.15	26.34	0.30	LINE	QP
10	3.799	20.63	-25.37	46.00	0.15	20.19	0.30	LINE	AVERAGE
11	11.080	34.23	-25.77	60.00	0.27	33.57	0.39	LINE	QP
12	11.080	28.61	-21.39	50.00	0.27	27.95	0.39	LINE	AVERAGE

Temperature	24°C	Humidity	51%
Test Engineer	Parody Lin	Phase	Neutral
Configuration	CTX	Test Mode	Mode 1



	Freq	Level	Over Limit	Limit Line	LISN Factor	Read Level	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dB	dBuV	dB		
1	0.16155	31.34	-24.04	55.38	0.08	31.10	0.16	NEUTRAL	AVERAGE
2	0.16155	43.91	-21.47	65.38	0.08	43.67	0.16	NEUTRAL	QP
3	0.20944	37.27	-25.96	63.23	0.08	37.02	0.17	NEUTRAL	QP
4	0.20944	27.72	-25.51	53.23	0.08	27.47	0.17	NEUTRAL	AVERAGE
5	0.52934	35.12	-20.88	56.00	0.09	34.84	0.19	NEUTRAL	QP
6	0.52934	28.59	-17.41	46.00	0.09	28.31	0.19	NEUTRAL	AVERAGE
7	1.129	19.26	-26.74	46.00	0.09	18.96	0.21	NEUTRAL	AVERAGE
8	1.129	25.04	-30.96	56.00	0.09	24.74	0.21	NEUTRAL	QP
9	3.720	27.54	-28.46	56.00	0.15	27.09	0.29	NEUTRAL	QP
10	3.720	21.32	-24.68	46.00	0.15	20.87	0.29	NEUTRAL	AVERAGE
11	11.080	34.03	-25.97	60.00	0.27	33.37	0.39	NEUTRAL	QP
12	11.080	28.42	-21.58	50.00	0.27	27.76	0.39	NEUTRAL	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. 26dB Bandwidth and 99% Occupied Bandwidth Measurement

4.2.1. Limit

No restriction limits.

4.2.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

26dB Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 26dB Bandwidth
RBW	Approximately 1% of the emission bandwidth
VBW	VBW > RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto
99% Occupied Bandwidth	
Spectrum Parameters	Setting
Span	1.5 times to 5.0 times the OBW
RBW	1 % to 5 % of the OBW
VBW	$\geq 3 \times$ RBW
Detector	Peak
Trace	Max Hold

4.2.3. Test Procedures

For Radiated 26dB Bandwidth and 99% Occupied Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

4.2.4. Test Setup Layout

For Radiated 26dB Bandwidth and 99% Occupied Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of 26dB Bandwidth and 99% Occupied Bandwidth

For non-beamforming mode:

Temperature	20°C	Humidity	53%
Test Engineer	Jim Huang	Configurations	IEEE 802.11ac/a

Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
52	5260 MHz	22.24	19.20
60	5300 MHz	22.24	19.04
64	5320 MHz	22.40	19.04
100	5500 MHz	24.00	18.88
116	5580 MHz	23.36	18.88
140	5700 MHz	22.56	18.56

Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
54	5270 MHz	38.08	34.88
62	5310 MHz	38.08	34.24
102	5510 MHz	38.72	32.32
110	5550 MHz	38.40	32.64
134	5670 MHz	39.04	32.96

Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2 + Chain 3 + Chain 4

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
58	5290 MHz	79.36	72.32
106	5530 MHz	80.00	72.96

Configuration IEEE 802.11a / Chain 1 + Chain 2 + Chain 3 + Chain 4

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
52	5260 MHz	20.96	17.92
60	5300 MHz	20.96	17.92
64	5320 MHz	21.12	17.92
100	5500 MHz	22.72	17.92
116	5580 MHz	21.76	17.60
140	5700 MHz	20.00	16.96

For beamforming mode:

Temperature	20°C	Humidity	53%
Test Engineer	Jim Huang	Configurations	IEEE 802.11ac

Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
52	5260 MHz	23.84	18.24
60	5300 MHz	23.52	18.24
64	5320 MHz	23.36	18.24
100	5500 MHz	23.52	18.24
116	5580 MHz	23.68	18.08
140	5700 MHz	23.52	18.24

Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4


Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
54	5270 MHz	41.92	36.48
62	5310 MHz	41.28	36.48
102	5510 MHz	41.28	36.48
110	5550 MHz	41.92	36.48
134	5670 MHz	41.60	36.48

Configuration IEEE 802.11ac MCS0/Nss2 VHT80 / Chain 1 + Chain 2 + Chain 3 + Chain 4

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
58	5290 MHz	81.28	76.16
106	5530 MHz	82.56	76.16


For non-beamforming mode:

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5260 MHz




Date: 30.SEP.2014 17:07:52

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5300 MHz




Date: 30.SEP.2014 17:08:18

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5320 MHz




Date: 30.SEP.2014 17:08:47

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5500 MHz




Date: 30.SEP.2014 17:09:17

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5580 MHz




Date: 30.SEP.2014 17:09:42

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5700 MHz




Date: 30.SEP.2014 17:10:06

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5270 MHz




Date: 30.SEP.2014 17:10:54

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5310 MHz




Date: 30.SEP.2014 17:11:23

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5510 MHz




Date: 30.SEP.2014 17:12:08

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5550 MHz




Date: 30.SEP.2014 17:12:57

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5670 MHz




Date: 30.SEP.2014 17:13:28

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5290 MHz




Date: 30.SEP.2014 17:14:05

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5530 MHz




Date: 30.SEP.2014 17:14:40

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5260 MHz




Date: 30.SEP.2014 17:04:46

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5300 MHz




Date: 30.SEP.2014 17:05:14

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5320 MHz




Date: 30.SEP.2014 17:05:39

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5500 MHz




Date: 30.SEP.2014 17:06:12

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5580 MHz



Date: 30.SEP.2014 17:06:39


26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5700 MHz



Date: 30.SEP.2014 17:07:08


For beamforming mode:

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5260 MHz




Date: 1.OCT.2014 06:38:30

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5300 MHz




Date: 1.OCT.2014 06:40:14

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5320 MHz




Date: 1.OCT.2014 06:40:41

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5500 MHz




Date: 1.OCT.2014 06:41:17

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5580 MHz




Date: 1.OCT.2014 06:41:48

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5700 MHz




Date: 1.OCT.2014 06:42:13

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5270 MHz




Date: 1.OCT.2014 06:42:56

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5310 MHz




Date: 1.OCT.2014 06:43:25

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5510 MHz




Date: 1.OCT.2014 06:43:58

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5550 MHz




Date: 1.OCT.2014 06:44:27

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5670 MHz




Date: 1.OCT.2014 06:44:55

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT80 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5290 MHz



Date: 1.OCT.2014 06:45:48

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT80 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5530 MHz



Date: 1.OCT.2014 06:46:23

4.3. Maximum Conducted Output Power Measurement

4.3.1. Limit

For the 5.25-5.35 GHz and 5.470-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW (24dBm) or $11 \text{ dBm} + 10\log B$, where B is the 26-dB emission bandwidth in MHz. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report The following table is the setting of the power meter.

Power Meter Parameter	Setting
Detector	AVERAGE

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Test was performed in accordance with KDB789033 D01 v01r04 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (E) Maximum conducted output power =>3) Measurement using a power meter (PM) =>b) Method PM-G (Measurement using a gated RF average power meter).
3. Multiple antenna systems was performed in accordance with KDB662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. When measuring maximum conducted output power with multiple antenna systems,add every result of the values by mathematic formula.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Maximum Conducted Output Power

For non-beamforming mode:

Temperature	20°C	Humidity	53%
Test Engineer	Jim Huang	Configurations	IEEE 802.11ac/a
Test Date	Sep. 30, 2014		

Configuration IEEE 802.11ac MCS0/Nss1 VHT20

Channel	Frequency	Conducted Power (dBm)					Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3	Chain 4	Total		
52	5260 MHz	16.78	15.10	15.77	16.02	21.98	24.00	Complies
60	5300 MHz	16.54	15.02	15.15	15.65	21.65	24.00	Complies
64	5320 MHz	16.36	14.99	15.17	15.67	21.60	24.00	Complies
100	5500 MHz	16.05	14.41	15.22	16.29	21.57	24.00	Complies
116	5580 MHz	15.58	14.87	15.58	16.09	21.57	24.00	Complies
140	5700 MHz	15.58	14.45	15.36	15.41	21.24	24.00	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT40

Channel	Frequency	Conducted Power (dBm)					Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3	Chain 4	Total		
54	5270 MHz	18.71	17.11	17.62	17.96	23.91	24.00	Complies
62	5310 MHz	18.53	17.12	17.12	17.92	23.73	24.00	Complies
102	5510 MHz	16.85	15.55	16.56	17.24	22.61	24.00	Complies
110	5550 MHz	17.94	16.86	17.42	17.95	23.59	24.00	Complies
134	5670 MHz	17.75	17.22	17.76	17.84	23.67	24.00	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT80

Channel	Frequency	Conducted Power (dBm)					Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3	Chain 4	Total		
58	5290 MHz	16.51	15.05	15.25	15.57	21.65	24.00	Complies
106	5530 MHz	15.81	14.23	15.25	15.86	21.36	24.00	Complies

Configuration IEEE 802.11a

Channel	Frequency	Conducted Power (dBm)					Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3	Chain 4	Total		
52	5260 MHz	16.53	15.04	15.89	15.96	21.91	24.00	Complies
60	5300 MHz	16.75	15.29	15.28	15.68	21.81	24.00	Complies
64	5320 MHz	16.51	14.82	15.32	15.67	21.64	24.00	Complies
100	5500 MHz	15.68	14.42	15.45	15.96	21.44	24.00	Complies
116	5580 MHz	15.93	14.33	15.32	15.98	21.46	24.00	Complies
140	5700 MHz	15.64	14.71	15.32	15.32	21.28	24.00	Complies

For beamforming mode:

Temperature	20°C	Humidity	53%
Test Engineer	Jim Huang	Configurations	IEEE 802.11ac
Test Date	Oct. 01, 2014		

Configuration IEEE 802.11ac MCS0/Nss2 VHT20

Channel	Frequency	Conducted Power (dBm)					Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3	Chain 4	Total		
52	5260 MHz	18.52	16.99	17.32	17.75	23.70	24.00	Complies
60	5300 MHz	18.53	17.02	17.18	17.45	23.61	24.00	Complies
64	5320 MHz	18.48	17.01	16.68	17.45	23.48	24.00	Complies
100	5500 MHz	17.76	16.45	16.94	18.02	23.36	24.00	Complies
116	5580 MHz	17.72	16.37	17.43	17.82	23.39	24.00	Complies
140	5700 MHz	17.72	16.48	17.15	17.38	23.23	24.00	Complies

Note:

$$\text{CH52} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^N \left\{ \sum_{k=1}^N g_{j,k} \right\}^2}{N_{ANT}} \right] = 5.31 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

$$\text{CH60} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^N \left\{ \sum_{k=1}^N g_{j,k} \right\}^2}{N_{ANT}} \right] = 5.51 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

$$\text{CH64} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^N \left\{ \sum_{k=1}^N g_{j,k} \right\}^2}{N_{ANT}} \right] = 5.51 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

$$\text{CH100} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^N \left\{ \sum_{k=1}^N g_{j,k} \right\}^2}{N_{ANT}} \right] = 5.91 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

$$\text{CH116} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^N \left\{ \sum_{k=1}^N g_{j,k} \right\}^2}{N_{ANT}} \right] = 5.91 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

$$\text{CH140} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^N \left\{ \sum_{k=1}^N g_{j,k} \right\}^2}{N_{ANT}} \right] = 5.91 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

Configuration IEEE 802.11ac MCS0/Nss2 VHT40

Channel	Frequency	Conducted Power (dBm)					Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3	Chain 4	Total		
54	5270 MHz	18.88	16.93	17.36	17.72	23.81	24.00	Complies
62	5310 MHz	16.72	15.18	15.05	15.92	21.79	24.00	Complies
102	5510 MHz	15.83	14.02	15.36	16.24	21.46	23.99	Complies
110	5550 MHz	17.62	16.66	17.45	17.88	23.45	23.99	Complies
134	5670 MHz	17.95	16.96	17.15	17.62	23.46	24.00	Complies

Note:

$$\text{CH54} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{SS}} G_{j,k} \right\}^2}{N_{ANT}} \right] = 5.41 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

$$\text{CH62} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{SS}} G_{j,k} \right\}^2}{N_{ANT}} \right] = 5.51 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

$$\text{CH102} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{SS}} G_{j,k} \right\}^2}{N_{ANT}} \right] = 6.01 \text{ dBi} > 6 \text{ dBi, so power limit} = 24 - (6.01 - 6) = 23.99 \text{ dBm}$$

$$\text{CH110} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{SS}} G_{j,k} \right\}^2}{N_{ANT}} \right] = 6.01 \text{ dBi} > 6 \text{ dBi, so power limit} = 24 - (6.01 - 6) = 23.99 \text{ dBm}$$

$$\text{CH134} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{SS}} G_{j,k} \right\}^2}{N_{ANT}} \right] = 5.91 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

Configuration IEEE 802.11ac MCS0/Nss2 VHT80

Channel	Frequency	Conducted Power (dBm)					Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3	Chain 4	Total		
58	5290 MHz	15.18	13.48	14.08	14.36	20.34	24.00	Complies
106	5530 MHz	15.54	14.05	15.05	15.72	21.16	23.99	Complies

Note:

$$\text{CH58} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{SS}} G_{j,k} \right\}^2}{N_{ANT}} \right] = 5.51 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

$$\text{CH106} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{SS}} G_{j,k} \right\}^2}{N_{ANT}} \right] = 6.01 \text{ dBi} > 6 \text{ dBi, so power limit} = 24 - (6.01 - 6) = 23.99 \text{ dBm}$$

4.4. Power Spectral Density Measurement

4.4.1. Limit

The power spectral density is defined as the highest level of power in dBm per MHz generated by the transmitter within the power envelope. The following table is power spectral density limits and decrease power density limit rule refer to section 4.3.1.

Frequency Range	Power Spectral Density limit (dBm/MHz)
5.25-5.35 GHz	11
5.470-5.725 GHz	11

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	1000 kHz
VBW	3000 kHz
Detector	RMS
Trace	AVERAGE
Sweep Time	Auto
Trace Average	100 times

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected RF switch to the spectrum analyzer.
2. Test was performed in accordance with KDB789033 D01 v01r04 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (F) Peak power spectral density (PPSD).
3. Multiple antenna systems was performed in accordance KDB662911 D01 v02r01 in-Band Power Spectral Density (PSD) Measurements (a) Measure and sum the spectra across the outputs.
4. When measuring first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3 and so on up to the Nth output to obtain the value for the first frequency bin of the summed spectrum. The summed spectrum value for each of the other frequency bins is computed in the same way.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of Power Spectral Density

For non-beamforming mode:

Temperature	20°C	Humidity	53%
Test Engineer	Jim Huang	Configurations	IEEE 802.11ac/a
Test Date	Sep. 30, 2014		

Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
52	5260 MHz	8.45	8.68	Complies
60	5300 MHz	8.35	8.48	Complies
64	5320 MHz	8.32	8.48	Complies
100	5500 MHz	8.05	8.08	Complies
116	5580 MHz	7.96	8.08	Complies
140	5700 MHz	7.97	8.08	Complies

Note:

$$\text{CH52} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^N \left\{ \sum_{l=1}^N |S_{j,l}|^2 \right\}}{N_{\text{ANT}}} \right] = 8.32\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (8.32 - 6) = 8.68\text{dBm/MHz}$$

$$\text{CH60} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^N \left\{ \sum_{l=1}^N |S_{j,l}|^2 \right\}}{N_{\text{ANT}}} \right] = 8.52\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (8.52 - 6) = 8.48\text{dBm/MHz}$$

$$\text{CH64} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^N \left\{ \sum_{l=1}^N |S_{j,l}|^2 \right\}}{N_{\text{ANT}}} \right] = 8.52\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (8.52 - 6) = 8.48\text{dBm/MHz}$$

$$\text{CH100} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^N \left\{ \sum_{l=1}^N |S_{j,l}|^2 \right\}}{N_{\text{ANT}}} \right] = 8.92\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (8.92 - 6) = 8.08\text{dBm/MHz}$$

$$\text{CH116} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^N \left\{ \sum_{l=1}^N |S_{j,l}|^2 \right\}}{N_{\text{ANT}}} \right] = 8.92\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (8.92 - 6) = 8.08\text{dBm/MHz}$$

$$\text{CH140} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^N \left\{ \sum_{l=1}^N |S_{j,l}|^2 \right\}}{N_{\text{ANT}}} \right] = 8.92\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (8.92 - 6) = 8.08\text{dBm/MHz}$$

Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
54	5270 MHz	7.45	8.58	Complies
62	5310 MHz	7.54	8.48	Complies
102	5510 MHz	6.16	7.98	Complies
110	5550 MHz	7.12	7.98	Complies
134	5670 MHz	7.11	7.98	Complies

Note:

$$\text{CH54} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \frac{M}{N_{ANT}} \right\}^{2} \right] = 8.42\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (8.42 - 6) = 8.58\text{dBm/MHz}$$

$$\text{CH62} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \frac{M}{N_{ANT}} \right\}^{2} \right] = 8.52\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (8.52 - 6) = 8.48\text{dBm/MHz}$$

$$\text{CH102} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \frac{M}{N_{ANT}} \right\}^{2} \right] = 9.02\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (9.02 - 6) = 7.98\text{dBm/MHz}$$

$$\text{CH110} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \frac{M}{N_{ANT}} \right\}^{2} \right] = 9.02\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (9.02 - 6) = 7.98\text{dBm/MHz}$$

$$\text{CH134} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \frac{M}{N_{ANT}} \right\}^{2} \right] = 9.02\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (9.02 - 6) = 7.98\text{dBm/MHz}$$

Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2 + Chain 3 + Chain 4

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
58	5290 MHz	2.45	8.48	Complies
106	5530 MHz	2.14	7.98	Complies

Note:

$$\text{CH58} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \frac{M}{N_{ANT}} \right\}^{2} \right] = 8.52\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (8.52 - 6) = 8.48\text{dBm/MHz}$$

$$\text{CH106} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \frac{M}{N_{ANT}} \right\}^{2} \right] = 9.02\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (9.02 - 6) = 7.98\text{dBm/MHz}$$

Configuration IEEE 802.11a / Chain 1 + Chain 2 + Chain 3 + Chain 4

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
52	5260 MHz	8.53	8.68	Complies
60	5300 MHz	8.33	8.48	Complies
64	5320 MHz	8.20	8.48	Complies
100	5500 MHz	7.91	8.08	Complies
116	5580 MHz	8.03	8.08	Complies
140	5700 MHz	8.01	8.08	Complies

Note:

$$\text{CH52} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \sum_{j=1}^N S_{j,A} \right\}^2 \right] = 8.32\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (8.32 - 6) = 8.68\text{dBm/MHz}$$

$$\text{CH60} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \sum_{j=1}^N S_{j,A} \right\}^2 \right] = 8.52\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (8.52 - 6) = 8.48\text{dBm/MHz}$$

$$\text{CH64} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \sum_{j=1}^N S_{j,A} \right\}^2 \right] = 8.52\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (8.52 - 6) = 8.48\text{dBm/MHz}$$

$$\text{CH100} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \sum_{j=1}^N S_{j,A} \right\}^2 \right] = 8.92\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (8.92 - 6) = 8.08\text{dBm/MHz}$$

$$\text{CH116} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \sum_{j=1}^N S_{j,A} \right\}^2 \right] = 8.92\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (8.92 - 6) = 8.08\text{dBm/MHz}$$

$$\text{CH140} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \sum_{j=1}^N S_{j,A} \right\}^2 \right] = 8.92\text{dBi} > 6\text{dBi}, \text{ so power density limit} = 11 - (8.92 - 6) = 8.08\text{dBm/MHz}$$

For beamforming mode:

Temperature	20°C	Humidity	53%
Test Engineer	Jim Huang	Configurations	IEEE 802.11ac
Test Date	Oct. 01, 2014		

Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
52	5260 MHz	10.24	11.00	Complies
60	5300 MHz	10.11	11.00	Complies
64	5320 MHz	10.06	11.00	Complies
100	5500 MHz	10.23	11.00	Complies
116	5580 MHz	10.05	11.00	Complies
140	5700 MHz	9.74	11.00	Complies

Note:

$$\text{CH52} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{M_{\text{ANT}}} \left[\frac{M_{\text{SJA}}}{N_{\text{ANT}}} \right]^2 \right] = 5.31 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

$$\text{CH60} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{M_{\text{ANT}}} \left[\frac{M_{\text{SJA}}}{N_{\text{ANT}}} \right]^2 \right] = 5.51 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

$$\text{CH64} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{M_{\text{ANT}}} \left[\frac{M_{\text{SJA}}}{N_{\text{ANT}}} \right]^2 \right] = 5.51 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

$$\text{CH100} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{M_{\text{ANT}}} \left[\frac{M_{\text{SJA}}}{N_{\text{ANT}}} \right]^2 \right] = 5.91 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

$$\text{CH116} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{M_{\text{ANT}}} \left[\frac{M_{\text{SJA}}}{N_{\text{ANT}}} \right]^2 \right] = 5.91 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

$$\text{CH140} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{M_{\text{ANT}}} \left[\frac{M_{\text{SJA}}}{N_{\text{ANT}}} \right]^2 \right] = 5.91 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
54	5270 MHz	7.14	11.00	Complies
62	5310 MHz	5.40	11.00	Complies
102	5510 MHz	5.22	10.99	Complies
110	5550 MHz	7.37	10.99	Complies
134	5670 MHz	7.00	10.99	Complies

Note:

$$\text{CH54} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \frac{M}{N_{ANT}} \right\}^{2} \right] = 5.41 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

$$\text{CH62} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \frac{M}{N_{ANT}} \right\}^{2} \right] = 5.51 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

$$\text{CH102} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \frac{M}{N_{ANT}} \right\}^{2} \right] = 6.01 \text{ dBi} > 6 \text{ dBi, so power density limit} = 11 - (6.01 - 6) = 10.99 \text{ dBm/MHz}$$

$$\text{CH110} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \frac{M}{N_{ANT}} \right\}^{2} \right] = 6.01 \text{ dBi} > 6 \text{ dBi, so power density limit} = 11 - (6.01 - 6) = 10.99 \text{ dBm/MHz}$$

$$\text{CH134} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \frac{M}{N_{ANT}} \right\}^{2} \right] = 6.01 \text{ dBi} > 6 \text{ dBi, so power density limit} = 11 - (6.01 - 6) = 10.99 \text{ dBm/MHz}$$

Configuration IEEE 802.11ac MCS0/Nss2 VHT80 / Chain 1 + Chain 2 + Chain 3 + Chain 4

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
58	5290 MHz	0.94	11.00	Complies
106	5530 MHz	2.02	10.99	Complies

Note:


$$\text{CH58} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \frac{M}{N_{ANT}} \right\}^{2} \right] = 5.51 \text{ dBi} < 6 \text{ dBi, so the limit doesn't reduce.}$$

$$\text{CH106} = \text{DirectionalGain} = 10 \cdot \log \left[\frac{M}{N_{ANT}} \left\{ \frac{M}{N_{ANT}} \right\}^{2} \right] = 6.01 \text{ dBi} > 6 \text{ dBi, so power density limit} = 11 - (6.01 - 6) = 10.99 \text{ dBm/MHz}$$


Note: All the test values were listed in the report.

For plots, only the channel with worse result was shown.


Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5310 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5550 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5290 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5530 MHz



Power Density Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5260 MHz




Power Density Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5580 MHz




For beamforming mode:


Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5260 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5500 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5270 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5550 MHz



Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT80 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5290 MHz



Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT80 / Chain 1 + Chain 2 + Chain 3 + Chain 4 / 5530 MHz



4.5. Radiated Emissions Measurement

4.5.1. Limit

For transmitters operating in the 5.15-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed a -27dBm peak limit or average 54dBuV/m and peak 74dBuV/m limits. For transmitters operating in the 5.470-5.725 GHz band: all emissions outside of the 5.470-5.725 GHz band shall not exceed a -27dBm peak limit or average 54dBuV/m and peak 74dBuV/m limits. In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40 GHz
RBW / VBW (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	1 MHz / 3MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

For Non-beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

For beamforming mode:

The EUT was programmed to be in beamforming transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	CTX
Test Date	May 27, 2014	Test Mode	Mode 1

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	CTX
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	125.06	33.91	43.50	-9.59	52.42	1.33	11.73	31.57	300	268	HORIZONTAL	Peak
2	354.95	33.62	46.00	-12.38	48.14	2.33	14.49	31.34	100	327	HORIZONTAL	Peak
3	375.32	34.78	46.00	-11.22	48.84	2.44	14.93	31.43	100	122	HORIZONTAL	Peak
4	570.29	31.57	46.00	-14.43	41.41	3.00	18.37	31.21	150	140	HORIZONTAL	Peak
5	749.74	33.02	46.00	-12.98	41.17	3.53	19.69	31.37	100	215	HORIZONTAL	Peak
6	874.87	32.60	46.00	-13.40	39.62	3.89	20.24	31.15	100	110	HORIZONTAL	Peak

Vertical



	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	cm	deg		
1	40.67	35.51	40.00	-4.49	54.78	0.75	11.85	31.87	100	89 VERTICAL	Peak
2	359.80	33.17	46.00	-12.83	47.49	2.35	14.66	31.33	100	185 VERTICAL	Peak
3	375.32	36.80	46.00	-9.20	50.86	2.44	14.93	31.43	125	205 VERTICAL	Peak
4	459.71	33.48	46.00	-12.52	45.66	2.68	16.33	31.19	125	97 VERTICAL	Peak
5	624.61	32.56	46.00	-13.44	42.17	3.18	18.61	31.40	100	5 VERTICAL	Peak
6	749.74	34.56	46.00	-11.44	42.71	3.53	19.69	31.37	150	18 VERTICAL	Peak

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~40GHz)

For non-beamforming mode:

Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 52 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	15780.40	44.56	54.00	-9.44	31.55	10.80	37.75	35.54	Average	100	112	HORIZONTAL
2	15780.43	57.49	74.00	-16.51	44.48	10.80	37.75	35.54	Peak	100	112	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	15780.13	57.57	74.00	-16.43	44.56	10.80	37.75	35.54	Peak	100	30	VERTICAL
2	15780.65	45.07	54.00	-8.93	32.06	10.80	37.75	35.54	Average	100	30	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 60 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10600.35	56.96	74.00	-17.04	43.56	8.64	39.90	35.14	Peak	100	29	HORIZONTAL
2	10600.89	44.91	54.00	-9.09	31.51	8.64	39.90	35.14	Average	100	29	HORIZONTAL
3	15899.52	57.66	74.00	-16.34	44.81	10.81	37.56	35.52	Peak	100	296	HORIZONTAL
4	15900.31	44.00	54.00	-10.00	31.15	10.81	37.56	35.52	Average	100	296	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10599.84	48.87	54.00	-5.13	35.47	8.64	39.90	35.14	Average	107	102	VERTICAL
2	10600.36	63.23	74.00	-10.77	49.83	8.64	39.90	35.14	Peak	107	102	VERTICAL
3	15900.13	44.46	54.00	-9.54	31.61	10.81	37.56	35.52	Average	107	286	VERTICAL
4	15900.36	56.69	74.00	-17.31	43.84	10.81	37.56	35.52	Peak	100	286	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 64 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10639.69	43.89	54.00	-10.11	30.46	8.66	39.86	35.09	Average	100	289	HORIZONTAL
2	10640.37	56.50	74.00	-17.50	43.07	8.66	39.86	35.09	Peak	100	289	HORIZONTAL
3	15959.82	44.04	54.00	-9.96	31.25	10.82	37.48	35.51	Average	100	346	HORIZONTAL
4	15960.19	57.33	74.00	-16.67	44.54	10.82	37.48	35.51	Peak	100	346	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10639.92	45.05	54.00	-8.95	31.62	8.66	39.86	35.09	Average	115	117	VERTICAL
2	10640.84	59.92	74.00	-14.08	46.49	8.66	39.86	35.09	Peak	115	117	VERTICAL
3	15960.47	56.67	74.00	-17.33	43.88	10.82	37.48	35.51	Peak	100	312	VERTICAL
4	15960.61	43.92	54.00	-10.08	31.13	10.82	37.48	35.51	Average	100	312	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 100 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10999.90	42.77	54.00	-11.23	29.14	8.93	39.50	34.80	Average	100	295	HORIZONTAL
2	11000.32	56.92	74.00	-17.08	43.29	8.93	39.50	34.80	Peak	114	295	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10999.40	56.67	74.00	-17.33	43.04	8.93	39.50	34.80	Peak	115	81	VERTICAL
2	10999.55	44.17	54.00	-9.83	30.54	8.93	39.50	34.80	Average	115	81	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 116 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11159.73	46.00	54.00	-8.00	32.35	9.04	39.50	34.89	Average	100	94	HORIZONTAL
2	11159.79	59.12	74.00	-14.88	45.47	9.04	39.50	34.89	Peak	100	94	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11159.18	63.40	74.00	-10.60	49.75	9.04	39.50	34.89	Peak	100	96	VERTICAL
2	11159.70	48.54	54.00	-5.46	34.89	9.04	39.50	34.89	Average	100	96	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 140 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11400.25	43.05	54.00	-10.95	29.40	9.19	39.50	35.04	Average	100	263	HORIZONTAL
2	11400.96	56.06	74.00	-17.94	42.41	9.19	39.50	35.04	Peak	100	263	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11399.05	55.73	74.00	-18.27	42.08	9.19	39.50	35.04	Peak	100	10	VERTICAL
2	11399.54	43.90	54.00	-10.10	30.25	9.19	39.50	35.04	Average	100	10	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 54 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 30, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	15819.32	46.32	54.00	-7.68	32.09	10.35	38.74	34.86	100	195 HORIZONTAL	Average
2	15819.52	59.23	74.00	-14.77	45.00	10.35	38.74	34.86	100	195 HORIZONTAL	Peak

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	15802.76	48.45	54.00	-5.55	34.20	10.35	38.74	34.84	100	270 VERTICAL	Average
2	15815.41	59.15	74.00	-14.85	44.92	10.35	38.74	34.86	100	270 VERTICAL	Peak



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 62 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 30, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	PoI/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	10612.62	41.81	54.00	-12.19	29.28	8.48	38.91	34.86	100	84	HORIZONTAL Average
2	10629.58	55.08	74.00	-18.92	42.50	8.49	38.95	34.86	100	84	HORIZONTAL Peak
3	15927.37	46.89	54.00	-7.11	32.69	10.34	38.86	35.00	100	188	HORIZONTAL Average
4	15927.37	59.89	74.00	-14.11	45.69	10.34	38.86	35.00	100	188	HORIZONTAL Peak

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	PoI/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	10618.55	54.75	74.00	-19.25	42.22	8.48	38.91	34.86	100	304	VERTICAL Peak
2	10630.00	41.37	54.00	-12.63	28.79	8.49	38.95	34.86	100	304	VERTICAL Average
3	15923.98	46.50	54.00	-7.50	32.29	10.34	38.86	34.99	100	218	VERTICAL Average
4	15930.32	59.17	74.00	-14.83	44.97	10.34	38.86	35.00	100	218	VERTICAL Peak



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 102 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 30, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11019.77	42.64	54.00	-11.36	29.66	8.73	39.10	34.85	100	195 HORIZONTAL	Average
2	11019.77	55.13	74.00	-18.87	42.15	8.73	39.10	34.85	100	195 HORIZONTAL	Peak

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11019.25	55.40	74.00	-18.60	42.42	8.73	39.10	34.85	100	250 VERTICAL	Peak
2	11026.05	42.72	54.00	-11.28	29.74	8.73	39.10	34.85	100	250 VERTICAL	Average

Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 110 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 30, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	11092.45	55.45	74.00	-18.55	42.42	8.78	39.10	34.85	100	291	HORIZONTAL	Peak
2	11099.77	43.13	54.00	-10.87	30.09	8.79	39.10	34.85	100	291	HORIZONTAL	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	11096.29	55.71	74.00	-18.29	42.67	8.79	39.10	34.85	100	236	VERTICAL	Peak
2	11098.67	42.68	54.00	-11.32	29.64	8.79	39.10	34.85	100	236	VERTICAL	Average



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 134 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 30, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	11336.21	43.36	54.00	-10.64	30.14	8.97	39.10	34.85	100	354	HORIZONTAL Average
2	11339.57	55.76	74.00	-18.24	42.53	8.98	39.10	34.85	100	354	HORIZONTAL Peak

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	11330.39	56.93	74.00	-17.07	43.71	8.97	39.10	34.85	100	32	VERTICAL Peak
2	11339.59	43.84	54.00	-10.16	30.61	8.98	39.10	34.85	100	32	VERTICAL Average



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 58 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 30, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	15860.62	59.49	74.00	-14.51	45.28	10.35	38.78	34.92	100	181	HORIZONTAL	Peak
2	15865.28	46.44	54.00	-7.56	32.23	10.35	38.78	34.92	100	181	HORIZONTAL	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	15860.94	58.72	74.00	-15.28	44.51	10.35	38.78	34.92	100	144	VERTICAL	Peak
2	15878.19	46.16	54.00	-7.84	31.93	10.35	38.82	34.94	100	144	VERTICAL	Average

Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 106 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 30, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	11050.56	55.20	74.00	-18.80	42.20	8.75	39.10	34.85	100	131	HORIZONTAL	Peak
2	11063.94	42.40	54.00	-11.60	29.39	8.76	39.10	34.85	100	131	HORIZONTAL	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	11061.79	55.92	74.00	-18.08	42.91	8.76	39.10	34.85	100	174	VERTICAL	Peak
2	11067.96	42.43	54.00	-11.57	29.42	8.76	39.10	34.85	100	174	VERTICAL	Average

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11a CH 52 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	15780.77	44.69	54.00	-9.31	31.68	10.80	37.75	35.54	Average	100	324	HORIZONTAL
2	15780.77	59.04	74.00	-14.96	46.03	10.80	37.75	35.54	Peak	100	324	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	15780.37	44.59	54.00	-9.41	31.58	10.80	37.75	35.54	Average	100	16	VERTICAL
2	15780.60	57.71	74.00	-16.29	44.70	10.80	37.75	35.54	Peak	100	16	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11a CH 60 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	10599.68	45.15	54.00	-8.85	31.75	8.64	39.90	35.14	Average	100	80 HORIZONTAL
2	10600.25	57.84	74.00	-16.16	44.44	8.64	39.90	35.14	Peak	100	80 HORIZONTAL
3	15899.83	56.80	74.00	-17.20	43.95	10.81	37.56	35.52	Peak	100	328 HORIZONTAL
4	15900.99	44.54	54.00	-9.46	31.69	10.81	37.56	35.52	Average	100	328 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	10599.30	62.53	74.00	-11.47	49.13	8.64	39.90	35.14	Peak	108	102 VERTICAL
2	10599.90	48.65	54.00	-5.35	35.25	8.64	39.90	35.14	Average	108	102 VERTICAL
3	15900.28	57.22	74.00	-16.78	44.37	10.81	37.56	35.52	Peak	100	5 VERTICAL
4	15900.93	44.36	54.00	-9.64	31.51	10.81	37.56	35.52	Average	106	5 VERTICAL

Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11a CH 64 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10639.56	43.42	54.00	-10.58	29.99	8.66	39.86	35.09	Average	100	339	HORIZONTAL
2	10640.34	55.90	74.00	-18.10	42.47	8.66	39.86	35.09	Peak	100	339	HORIZONTAL
3	15959.68	57.56	74.00	-16.44	44.77	10.82	37.48	35.51	Peak	100	251	HORIZONTAL
4	15960.70	43.90	54.00	-10.10	31.11	10.82	37.48	35.51	Average	100	251	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10639.54	42.80	54.00	-11.20	29.37	8.66	39.86	35.09	Average	100	120	VERTICAL
2	10640.17	57.57	74.00	-16.43	44.14	8.66	39.86	35.09	Peak	100	120	VERTICAL
3	15959.20	57.10	74.00	-16.90	44.31	10.82	37.48	35.51	Peak	100	345	VERTICAL
4	15960.26	44.07	54.00	-9.93	31.28	10.82	37.48	35.51	Average	100	345	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11a CH 100 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10999.93	57.33	74.00	-16.67	43.70	8.93	39.50	34.80	Peak	100	265	HORIZONTAL
2	11000.27	42.66	54.00	-11.34	29.03	8.93	39.50	34.80	Average	100	265	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10999.58	43.75	54.00	-10.25	30.12	8.93	39.50	34.80	Average	100	10	VERTICAL
2	11000.97	55.41	74.00	-18.59	41.78	8.93	39.50	34.80	Peak	100	10	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11a CH 116 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11159.88	58.44	74.00	-15.56	44.79	9.04	39.50	34.89	Peak	101	94	HORIZONTAL
2	11159.97	46.61	54.00	-7.39	32.96	9.04	39.50	34.89	Average	101	94	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11159.97	50.49	54.00	-3.51	36.84	9.04	39.50	34.89	Average	110	113	VERTICAL
2	11160.33	63.75	74.00	-10.25	50.10	9.04	39.50	34.89	Peak	110	113	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11a CH 140 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11399.33	43.39	54.00	-10.61	29.74	9.19	39.50	35.04	Average	107	265	HORIZONTAL
2	11399.80	55.57	74.00	-18.43	41.92	9.19	39.50	35.04	Peak	100	265	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11399.83	61.55	74.00	-12.45	47.90	9.19	39.50	35.04	Peak	108	114	VERTICAL
2	11399.87	47.16	54.00	-6.84	33.51	9.19	39.50	35.04	Average	108	114	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



For beamforming mode:

Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss2 VHT20 CH 52 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	15782.08	58.94	74.00	-15.06	45.93	10.80	37.75	35.54	Peak	100	304	HORIZONTAL
2	15789.41	45.48	54.00	-8.52	32.47	10.80	37.75	35.54	Average	100	304	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	15778.75	58.76	74.00	-15.24	45.75	10.80	37.75	35.54	Peak	100	78	VERTICAL
2	15786.14	45.46	54.00	-8.54	32.45	10.80	37.75	35.54	Average	100	78	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss2 VHT20 CH 60 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10600.62	58.16	74.00	-15.84	44.76	8.64	39.90	35.14	Peak	100	289	HORIZONTAL
2	10600.89	44.88	54.00	-9.12	31.48	8.64	39.90	35.14	Average	100	289	HORIZONTAL
3	15900.14	58.93	74.00	-15.07	46.08	10.81	37.56	35.52	Peak	100	123	HORIZONTAL
4	15900.69	44.96	54.00	-9.04	32.11	10.81	37.56	35.52	Average	100	123	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10599.31	59.19	74.00	-14.81	45.79	8.64	39.90	35.14	Peak	100	89	VERTICAL
2	10600.81	44.93	54.00	-9.07	31.53	8.64	39.90	35.14	Average	100	89	VERTICAL
3	15900.87	58.20	74.00	-15.80	45.35	10.81	37.56	35.52	Peak	100	263	VERTICAL
4	15900.91	45.06	54.00	-8.94	32.21	10.81	37.56	35.52	Average	100	263	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss2 VHT20 CH 64 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10639.18	44.42	54.00	-9.58	30.99	8.66	39.86	35.09	Average	100	165	HORIZONTAL
2	10639.95	59.17	74.00	-14.83	45.74	8.66	39.86	35.09	Peak	100	165	HORIZONTAL
3	15959.95	58.52	74.00	-15.48	45.73	10.82	37.48	35.51	Peak	100	265	HORIZONTAL
4	15960.92	45.07	54.00	-8.93	32.28	10.82	37.48	35.51	Average	100	265	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10639.12	44.16	54.00	-9.84	30.73	8.66	39.86	35.09	Average	100	286	VERTICAL
2	10639.47	57.34	74.00	-16.66	43.91	8.66	39.86	35.09	Peak	100	286	VERTICAL
3	15959.97	59.19	74.00	-14.81	46.40	10.82	37.48	35.51	Peak	100	321	VERTICAL
4	15960.92	45.07	54.00	-8.93	32.28	10.82	37.48	35.51	Average	100	321	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss2 VHT20 CH 100 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10999.02	57.43	74.00	-16.57	43.80	8.93	39.50	34.80	Peak	100	126	HORIZONTAL
2	10999.57	44.52	54.00	-9.48	30.89	8.93	39.50	34.80	Average	100	126	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10999.36	58.13	74.00	-15.87	44.50	8.93	39.50	34.80	Peak	100	248	VERTICAL
2	10999.44	44.37	54.00	-9.63	30.74	8.93	39.50	34.80	Average	100	248	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss2 VHT20 CH 116 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11159.46	58.63	74.00	-15.37	44.98	9.04	39.50	34.89	Peak	100	268	HORIZONTAL
2	11160.45	44.90	54.00	-9.10	31.25	9.04	39.50	34.89	Average	100	268	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11160.49	57.91	74.00	-16.09	44.26	9.04	39.50	34.89	Peak	100	84	VERTICAL
2	11160.53	45.04	54.00	-8.96	31.39	9.04	39.50	34.89	Average	100	84	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss2 VHT20 CH 140 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11400.22	57.91	74.00	-16.09	44.26	9.19	39.50	35.04	Peak	100	102	HORIZONTAL
2	11400.82	44.09	54.00	-9.91	30.44	9.19	39.50	35.04	Average	100	102	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11400.22	57.91	74.00	-16.09	44.26	9.19	39.50	35.04	Peak	100	268	VERTICAL
2	11400.58	44.04	54.00	-9.96	30.39	9.19	39.50	35.04	Average	100	268	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss2 VHT40 CH 54 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	15797.55	59.87	74.00	-14.13	46.89	10.80	37.72	35.54	Peak	100	304	HORIZONTAL
2	15802.07	45.91	54.00	-8.09	32.93	10.80	37.72	35.54	Average	100	304	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	15802.18	58.53	74.00	-15.47	45.55	10.80	37.72	35.54	Peak	100	84	VERTICAL
2	15827.13	45.93	54.00	-8.07	32.97	10.80	37.69	35.53	Average	100	84	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss2 VHT40 CH 62 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10619.12	45.17	54.00	-8.83	31.76	8.65	39.88	35.12	Average	100	53	HORIZONTAL
2	10619.41	57.78	74.00	-16.22	44.37	8.65	39.88	35.12	Peak	100	53	HORIZONTAL
3	15929.00	44.90	54.00	-9.10	32.07	10.81	37.53	35.51	Average	100	153	HORIZONTAL
4	15929.00	56.20	74.00	-17.80	43.37	10.81	37.53	35.51	Peak	100	153	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10615.56	45.29	54.00	-8.71	31.88	8.65	39.88	35.12	Average	100	312	VERTICAL
2	10618.84	59.74	74.00	-14.26	46.33	8.65	39.88	35.12	Peak	100	312	VERTICAL
3	15928.84	59.16	74.00	-14.84	46.33	10.81	37.53	35.51	Peak	100	245	VERTICAL
4	15929.00	45.22	54.00	-8.78	32.39	10.81	37.53	35.51	Average	100	245	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss2 VHT40 CH 102 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11019.91	43.94	54.00	-10.06	30.31	8.94	39.50	34.81	Average	100	165 HORIZONTAL
2	11020.19	57.92	74.00	-16.08	44.29	8.94	39.50	34.81	Peak	100	165 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11019.09	44.11	54.00	-9.89	30.48	8.94	39.50	34.81	Average	100	81 VERTICAL
2	11019.12	57.07	74.00	-16.93	43.44	8.94	39.50	34.81	Peak	100	81 VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss2 VHT40 CH 110 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11100.16	56.81	74.00	-17.19	43.18	8.99	39.50	34.86	Peak	100	283	HORIZONTAL
2	11100.24	44.26	54.00	-9.74	30.63	8.99	39.50	34.86	Average	100	283	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11099.64	58.47	74.00	-15.53	44.84	8.99	39.50	34.86	Peak	100	120	VERTICAL
2	11100.16	44.50	54.00	-9.50	30.87	8.99	39.50	34.86	Average	100	120	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss2 VHT40 CH 134 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11339.24	45.06	54.00	-8.94	31.41	9.14	39.50	34.99	Average	100	256	HORIZONTAL
2	11339.35	58.57	74.00	-15.43	44.92	9.14	39.50	34.99	Peak	100	256	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11339.41	45.26	54.00	-8.74	31.61	9.14	39.50	34.99	Average	100	65	VERTICAL
2	11340.49	58.12	74.00	-15.88	44.47	9.14	39.50	34.99	Peak	100	65	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss2 VHT80 CH 58 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	15869.51	59.19	74.00	-14.81	46.30	10.81	37.61	35.53	Peak	100	124	HORIZONTAL
2	15869.81	45.67	54.00	-8.33	32.78	10.81	37.61	35.53	Average	100	124	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	15870.15	45.71	54.00	-8.29	32.82	10.81	37.61	35.53	Average	100	246	VERTICAL
2	15870.21	59.34	74.00	-14.66	46.45	10.81	37.61	35.53	Peak	100	246	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss2 VHT80 CH 106 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11059.87	57.50	74.00	-16.50	43.86	8.97	39.50	34.83	Peak	100	8	HORIZONTAL
2	11060.92	44.02	54.00	-9.98	30.38	8.97	39.50	34.83	Average	100	8	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11060.77	56.73	74.00	-17.27	43.09	8.97	39.50	34.83	Peak	100	54	VERTICAL
2	11060.92	44.18	54.00	-9.82	30.54	8.97	39.50	34.83	Average	100	54	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Band Edge Emissions Measurement

4.6.1. Limit

For transmitters operating in the 5.15-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed a -27dBm peak limit or average 54dBuV/m and peak 74dBuV/m limits. For transmitters operating in the 5.470-5.725 GHz band: all emissions outside of the 5.470-5.725 GHz band shall not exceed a -27dBm peak limit or average 54dBuV/m and peak 74dBuV/m limits. In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	1 MHz / 3MHz for Peak

4.6.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

For Non-beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

For beamforming mode:

The EUT was programmed to be in beamforming transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

For non-beamforming mode:

Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 52, 60, 64 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Channel 52

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5265.21	112.52			107.26	6.21	34.25	35.20	Average	213	144	VERTICAL
2	5265.21	122.72			117.46	6.21	34.25	35.20	Peak	213	144	VERTICAL
3	5351.45	63.02	74.00	-10.98	57.54	6.26	34.42	35.20	Peak	213	144	VERTICAL
4	5354.92	50.76	54.00	-3.24	45.28	6.26	34.42	35.20	Average	213	144	VERTICAL

Item 1, 2 are the fundamental frequency at 5260 MHz.

Channel 60

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5293.63	124.92			119.60	6.23	34.29	35.20	Peak	181	344	VERTICAL
2	5294.50	114.97			109.65	6.23	34.29	35.20	Average	181	344	VERTICAL
3	5355.21	53.34	54.00	-0.66	47.86	6.26	34.42	35.20	Average	181	344	VERTICAL
4	5355.50	66.86	74.00	-7.14	61.38	6.26	34.42	35.20	Peak	181	344	VERTICAL

Item 1, 2 are the fundamental frequency at 5300 MHz.

Channel 64

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5311.61	107.68			102.32	6.24	34.32	35.20	Average	214	181	VERTICAL
2	5312.47	117.39			112.03	6.24	34.32	35.20	Peak	214	181	VERTICAL
3	5352.03	53.65	54.00	-0.35	48.17	6.26	34.42	35.20	Average	214	181	VERTICAL
4	5352.89	66.85	74.00	-7.15	61.37	6.26	34.42	35.20	Peak	214	181	VERTICAL

Item 1, 2 are the fundamental frequency at 5320 MHz.

Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 100, 140 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Channel 100

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5458.26	64.83	74.00	-9.17	59.07	6.33	34.63	35.20	Peak	194	356	VERTICAL
2	5459.71	51.75	54.00	-2.25	45.99	6.33	34.63	35.20	Average	194	356	VERTICAL
3	5465.95	53.69	54.00	-0.31	47.92	6.34	34.63	35.20	Average	194	356	VERTICAL
4	5467.11	68.88	74.00	-5.12	63.07	6.34	34.67	35.20	Peak	194	356	VERTICAL
5	5505.21	120.97			115.10	6.36	34.71	35.20	Peak	194	356	VERTICAL
6	5505.79	110.72			104.85	6.36	34.71	35.20	Average	194	356	VERTICAL

Item 5, 6 are the fundamental frequency at 5500 MHz.

Channel 140

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5698.26	109.59			103.50	6.43	34.86	35.20	Average	192	41	VERTICAL
2	5699.13	119.89			113.80	6.43	34.86	35.20	Peak	192	41	VERTICAL
3	5725.00	53.41	54.00	-0.59	47.27	6.45	34.89	35.20	Average	192	41	VERTICAL
4	5725.14	68.37	74.00	-5.63	62.23	6.45	34.89	35.20	Peak	192	41	VERTICAL

Item 1, 2 are the fundamental frequency at 5700 MHz.



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 54, 62 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Channel 54

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5285.34	111.28			105.97	6.22	34.29	35.20	Average	196	16	VERTICAL
2	5286.21	121.21			115.90	6.22	34.29	35.20	Peak	196	16	VERTICAL
3	5357.81	66.49	74.00	-7.51	61.01	6.26	34.42	35.20	Peak	196	16	VERTICAL
4	5363.89	53.03	54.00	-0.97	47.54	6.27	34.42	35.20	Average	196	16	VERTICAL

Item 1, 2 are the fundamental frequency at 5270 MHz.

Channel 62

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5304.50	106.59			101.24	6.23	34.32	35.20	Average	191	344	VERTICAL
2	5304.79	116.22			110.87	6.23	34.32	35.20	Peak	191	344	VERTICAL
3	5363.02	67.94	74.00	-6.06	62.45	6.27	34.42	35.20	Peak	191	344	VERTICAL
4	5363.31	53.80	54.00	-0.20	48.31	6.27	34.42	35.20	Average	191	344	VERTICAL

Item 1, 2 are the fundamental frequency at 5310 MHz.

Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 102, 110, 134 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Channel 102

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5457.11	53.46	54.00	-0.54	47.70	6.33	34.63	35.20	Average	193	354	VERTICAL
2	5457.97	66.35	74.00	-7.65	60.59	6.33	34.63	35.20	Peak	193	354	VERTICAL
3	5470.00	53.85	54.00	-0.15	48.04	6.34	34.67	35.20	Average	193	354	VERTICAL
4	5470.00	66.67	74.00	-7.33	60.86	6.34	34.67	35.20	Peak	193	354	VERTICAL
5	5516.95	105.54			99.66	6.37	34.71	35.20	Average	193	354	VERTICAL
6	5516.95	115.98			110.10	6.37	34.71	35.20	Peak	193	354	VERTICAL

Item 5, 6 are the fundamental frequency at 5510 MHz.

Channel 110

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5455.08	53.61	54.00	-0.39	47.85	6.33	34.63	35.20	Average	197	358	VERTICAL
2	5455.95	67.30	74.00	-6.70	61.54	6.33	34.63	35.20	Peak	197	358	VERTICAL
3	5467.40	52.73	54.00	-1.27	46.92	6.34	34.67	35.20	Average	197	358	VERTICAL
4	5467.40	65.73	74.00	-8.27	59.92	6.34	34.67	35.20	Peak	197	358	VERTICAL
5	5554.05	121.36			115.43	6.38	34.75	35.20	Peak	197	358	VERTICAL
6	5555.21	111.13			105.20	6.38	34.75	35.20	Average	197	358	VERTICAL

Item 5, 6 are the fundamental frequency at 5550 MHz.

Channel 134

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5672.32	118.17			112.09	6.43	34.85	35.20	Peak	182	328	VERTICAL
2	5672.89	108.14			102.06	6.43	34.85	35.20	Average	182	328	VERTICAL
3	5733.10	53.99	54.00	-0.01	47.85	6.45	34.89	35.20	Average	182	328	VERTICAL
4	5733.10	70.88	74.00	-3.12	64.74	6.45	34.89	35.20	Peak	182	328	VERTICAL

Item 1, 2 are the fundamental frequency at 5670 MHz.

Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 58, 106 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014 ~ Sep. 30, 2014		

Channel 58

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5254.69	99.30			94.08	6.20	34.22	35.20	Average	208	141	VERTICAL
2	5254.69	110.45			105.23	6.20	34.22	35.20	Peak	208	141	VERTICAL
3	5354.05	53.54	54.00	-0.46	48.06	6.26	34.42	35.20	Average	208	141	VERTICAL
4	5354.34	66.96	74.00	-7.04	61.48	6.26	34.42	35.20	Peak	208	141	VERTICAL

Item 1, 2 are the fundamental frequency at 5290 MHz.

Channel 106

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	5459.87	66.97	74.00	-7.03	62.57	6.18	33.75	35.53	192	199	VERTICAL	Peak
2	5460.00	53.61	54.00	-0.39	49.21	6.18	33.75	35.53	192	199	VERTICAL	Average
3	5467.11	48.67	54.00	-5.33	44.22	6.18	33.80	35.53	192	199	VERTICAL	Average
4	5467.83	64.05	74.00	-9.95	59.60	6.18	33.80	35.53	192	199	VERTICAL	Peak
5	5526.38	97.02			92.40	6.22	33.92	35.52	192	199	VERTICAL	Average
6	5527.11	108.96			104.32	6.22	33.94	35.52	192	199	VERTICAL	Peak
7	5725.00	45.77	54.00	-8.23	40.58	6.35	34.18	35.34	192	199	VERTICAL	Average
8	5738.75	58.21	74.00	-15.79	52.98	6.36	34.20	35.33	192	199	VERTICAL	Peak

Item 5, 6 are the fundamental frequency at 5530 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11a CH 52, 60, 64 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Channel 52

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5253.05	116.12			110.90	6.20	34.22	35.20	Average	196	345	VERTICAL
2	5253.63	125.74			120.52	6.20	34.22	35.20	Peak	196	345	VERTICAL
3	5350.58	64.15	74.00	-9.85	58.67	6.26	34.42	35.20	Peak	196	345	VERTICAL
4	5353.76	51.97	54.00	-2.03	46.49	6.26	34.42	35.20	Average	196	345	VERTICAL

Item 1, 2 are the fundamental frequency at 5260 MHz.

Channel 60

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5307.24	115.40			110.05	6.23	34.32	35.20	Average	191	356	VERTICAL
2	5307.24	124.97			119.62	6.23	34.32	35.20	Peak	191	356	VERTICAL
3	5350.00	53.18	54.00	-0.82	47.70	6.26	34.42	35.20	Average	191	356	VERTICAL
4	5358.39	66.42	74.00	-7.58	60.94	6.26	34.42	35.20	Peak	191	356	VERTICAL

Item 1, 2 are the fundamental frequency at 5300 MHz.

Channel 64

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5313.20	110.59			105.23	6.24	34.32	35.20	Average	191	346	VERTICAL
2	5313.63	120.13			114.77	6.24	34.32	35.20	Peak	191	346	VERTICAL
3	5352.75	53.83	54.00	-0.17	48.35	6.26	34.42	35.20	Average	191	346	VERTICAL
4	5353.04	67.40	74.00	-6.60	61.92	6.26	34.42	35.20	Peak	191	346	VERTICAL

Item 1, 2 are the fundamental frequency at 5320 MHz.

Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11a CH 100, 116, 140 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Channel 100

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5458.99	64.21	74.00	-9.79	58.45	6.33	34.63	35.20	Peak	191	355	VERTICAL
2	5459.86	51.75	54.00	-2.25	45.99	6.33	34.63	35.20	Average	191	355	VERTICAL
3	5466.38	53.24	54.00	-0.76	47.47	6.34	34.63	35.20	Average	191	355	VERTICAL
4	5467.25	67.92	74.00	-6.08	62.11	6.34	34.67	35.20	Peak	191	355	VERTICAL
5	5506.22	110.41			104.54	6.36	34.71	35.20	Average	191	355	VERTICAL
6	5506.80	120.02			114.15	6.36	34.71	35.20	Peak	191	355	VERTICAL

Item 5, 6 are the fundamental frequency at 5500 MHz.

Channel 140

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5698.12	111.49			105.40	6.43	34.86	35.20	Average	196	135	VERTICAL
2	5698.12	121.41			115.32	6.43	34.86	35.20	Peak	196	135	VERTICAL
3	5737.16	53.86	54.00	-0.14	47.72	6.45	34.89	35.20	Average	196	135	VERTICAL
4	5737.30	69.28	74.00	-4.72	63.14	6.45	34.89	35.20	Peak	196	135	VERTICAL

Item 1, 2 are the fundamental frequency at 5700 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

For beamforming mode:

Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss2 VHT20 CH 52, 60, 64 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Channel 52

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5252.62	124.04			118.82	6.20	34.22	35.20 Peak	208	201	VERTICAL
2	5253.49	114.44			109.22	6.20	34.22	35.20 Average	208	201	VERTICAL
3	5350.00	64.00	74.00	-10.00	58.52	6.26	34.42	35.20 Peak	208	201	VERTICAL
4	5353.91	52.17	54.00	-1.83	46.69	6.26	34.42	35.20 Average	208	201	VERTICAL

Item 1, 2 are the fundamental frequency at 5260 MHz.

Channel 60

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5292.76	122.84			117.52	6.23	34.29	35.20 Peak	198	348	VERTICAL
2	5306.37	112.64			107.29	6.23	34.32	35.20 Average	198	348	VERTICAL
3	5350.00	53.20	54.00	-0.80	47.72	6.26	34.42	35.20 Average	198	348	VERTICAL
4	5351.16	65.60	74.00	-8.40	60.12	6.26	34.42	35.20 Peak	198	348	VERTICAL

Item 1, 2 are the fundamental frequency at 5300 MHz.

Channel 64

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5326.37	109.34			103.94	6.24	34.36	35.20 Average	176	16	VERTICAL
2	5326.37	119.33			113.93	6.24	34.36	35.20 Peak	176	16	VERTICAL
3	5355.79	53.99	54.00	-0.01	48.51	6.26	34.42	35.20 Average	176	16	VERTICAL
4	5361.29	67.61	74.00	-6.39	62.12	6.27	34.42	35.20 Peak	176	16	VERTICAL

Item 1, 2 are the fundamental frequency at 5320 MHz.

Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss2 VHT20 CH 100, 116, 140 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Channel 100

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5460.00	53.64	54.00	-0.36	47.88	6.33	34.63	35.20	Average	188	15	VERTICAL
2	5460.00	67.22	74.00	-6.78	61.46	6.33	34.63	35.20	Peak	188	15	VERTICAL
3	5469.57	73.11	74.00	-0.89	67.30	6.34	34.67	35.20	Peak	188	15	VERTICAL
4	5470.00	53.72	54.00	-0.28	47.91	6.34	34.67	35.20	Average	188	15	VERTICAL
5	5493.63	120.63			114.78	6.35	34.70	35.20	Peak	188	15	VERTICAL
6	5507.81	109.47			103.60	6.36	34.71	35.20	Average	188	15	VERTICAL

Item 5, 6 are the fundamental frequency at 5500 MHz.

Channel 116

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5413.11	53.30	54.00	-0.70	47.66	6.31	34.53	35.20	Average	176	14	VERTICAL
2	5447.84	65.73	74.00	-8.27	60.00	6.33	34.60	35.20	Peak	176	14	VERTICAL
3	5463.05	53.06	54.00	-0.94	47.29	6.34	34.63	35.20	Average	176	14	VERTICAL
4	5468.26	65.69	74.00	-8.31	59.88	6.34	34.67	35.20	Peak	176	14	VERTICAL
5	5573.63	116.18			110.22	6.39	34.77	35.20	Average	176	14	VERTICAL
6	5573.63	126.81			120.85	6.39	34.77	35.20	Peak	176	14	VERTICAL

Item 5, 6 are the fundamental frequency at 5580 MHz.

Channel 140

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5702.32	119.10			113.00	6.44	34.86	35.20	Peak	177	211	VERTICAL
2	5702.46	107.90			101.80	6.44	34.86	35.20	Average	177	211	VERTICAL
3	5725.00	53.95	54.00	-0.05	47.81	6.45	34.89	35.20	Average	177	211	VERTICAL
4	5725.58	71.23	74.00	-2.77	65.09	6.45	34.89	35.20	Peak	177	211	VERTICAL

Item 1, 2 are the fundamental frequency at 5700 MHz.



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss2 VHT40 CH 54, 62 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 26, 2014		

Channel 54

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5267.68	122.75			117.49	6.21	34.25	35.20	Peak	193	358	VERTICAL
2	5277.53	109.84			104.57	6.22	34.25	35.20	Average	193	358	VERTICAL
3	5350.00	53.69	54.00	-0.31	48.21	6.26	34.42	35.20	Average	193	358	VERTICAL
4	5356.95	67.00	74.00	-7.00	61.52	6.26	34.42	35.20	Peak	193	358	VERTICAL

Item 1, 2 are the fundamental frequency at 5270 MHz.

Channel 62

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5293.79	116.03			110.71	6.23	34.29	35.20	Peak	188	347	VERTICAL
2	5298.42	102.38			97.03	6.23	34.32	35.20	Average	188	347	VERTICAL
3	5350.00	53.30	54.00	-0.70	47.82	6.26	34.42	35.20	Average	188	347	VERTICAL
4	5351.45	67.50	74.00	-6.50	62.02	6.26	34.42	35.20	Peak	188	347	VERTICAL

Item 1, 2 are the fundamental frequency at 5310 MHz.

Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss2 VHT40 CH 102, 110, 134 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 26, 2014		

Channel 102

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5458.26	64.50	74.00	-9.50	58.74	6.33	34.63	35.20	Peak	195	356	VERTICAL
2	5460.00	51.35	54.00	-2.65	45.59	6.33	34.63	35.20	Average	195	356	VERTICAL
3	5466.96	66.57	74.00	-7.43	60.80	6.34	34.63	35.20	Peak	195	356	VERTICAL
4	5467.83	53.49	54.00	-0.51	47.68	6.34	34.67	35.20	Average	195	356	VERTICAL
5	5505.22	115.72			109.85	6.36	34.71	35.20	Peak	195	356	VERTICAL
6	5517.81	105.23			99.35	6.37	34.71	35.20	Average	195	356	VERTICAL

Item 5, 6 are the fundamental frequency at 5510 MHz.

Channel 110

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5457.40	65.25	74.00	-8.75	59.49	6.33	34.63	35.20	Peak	202	350	VERTICAL
2	5460.00	52.11	54.00	-1.89	46.35	6.33	34.63	35.20	Average	202	350	VERTICAL
3	5463.05	66.15	74.00	-7.85	60.38	6.34	34.63	35.20	Peak	202	350	VERTICAL
4	5470.00	53.30	54.00	-0.70	47.49	6.34	34.67	35.20	Average	202	350	VERTICAL
5	5532.63	120.44			114.54	6.37	34.73	35.20	Peak	202	350	VERTICAL
6	5566.50	110.03			104.09	6.39	34.75	35.20	Average	202	350	VERTICAL

Item 5, 6 are the fundamental frequency at 5550 MHz.

Channel 134

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5671.16	118.73			112.67	6.43	34.83	35.20	Peak	197	42	VERTICAL
2	5673.18	107.79			101.71	6.43	34.85	35.20	Average	197	42	VERTICAL
3	5725.00	53.94	54.00	-0.06	47.80	6.45	34.89	35.20	Average	197	42	VERTICAL
4	5726.45	73.05	74.00	-0.95	66.91	6.45	34.89	35.20	Peak	197	42	VERTICAL

Item 1, 2 are the fundamental frequency at 5670 MHz.



Temperature	24°C	Humidity	57%
Test Engineer	James Chou	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 58, 106 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 28, 2014		

Channel 58

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5264.53	116.38			111.12	6.21	34.25	35.20	Peak	194	0	VERTICAL
2	5285.37	99.72			94.41	6.22	34.29	35.20	Average	194	0	VERTICAL
3	5350.00	53.33	54.00	-0.67	47.85	6.26	34.42	35.20	Average	194	0	VERTICAL
4	5383.57	68.49	74.00	-5.51	62.92	6.28	34.49	35.20	Peak	194	0	VERTICAL

Item 1, 2 are the fundamental frequency at 5290 MHz.

Channel 106

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5457.40	66.97	74.00	-7.03	61.21	6.33	34.63	35.20	Peak	194	216	VERTICAL
2	5460.00	53.44	54.00	-0.56	47.68	6.33	34.63	35.20	Average	194	216	VERTICAL
3	5465.22	68.22	74.00	-5.78	62.45	6.34	34.63	35.20	Peak	194	216	VERTICAL
4	5470.00	53.94	54.00	-0.06	48.13	6.34	34.67	35.20	Average	194	216	VERTICAL
5	5503.52	117.06			111.19	6.36	34.71	35.20	Peak	194	216	VERTICAL
6	5562.13	101.22			95.29	6.38	34.75	35.20	Average	194	216	VERTICAL

Item 5, 6 are the fundamental frequency at 5530 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

4.7. Frequency Stability Measurement

4.7.1. Limit

In-band emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band (IEEE 802.11n specification).

4.7.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Entire absence of modulation emissions bandwidth
RBW	10 kHz
VBW	10 kHz
Sweep Time	Auto

4.7.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f) / f_c \times 10^6$ ppm and the limit is less than ± 20 ppm (IEEE 802.11n specification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is $-30^\circ\text{C} \sim 50^\circ\text{C}$.

4.7.4. Test Setup Layout



4.7.5. Test Deviation

There is no deviation with the original standard.

4.7.6. EUT Operation during Test

The EUT was programmed to be in continuously un-modulation transmitting mode.

4.7.7. Test Result of Frequency Stability

Temperature	20°C	Humidity	53%
Test Engineer	Jim Huang	Test Date	Sep. 30, 2014

Voltage vs. Frequency Stability

Voltage (V)	Measurement Frequency (MHz)	
	5300 MHz	5500 MHz
126.50	5299.9292	5499.9228
110.00	5299.9310	5499.9244
93.50	5299.9344	5499.9262
Max. Deviation (MHz)	0.070800	0.077200
Max. Deviation (ppm)	13.36	14.04

Temperature vs. Frequency Stability

Temperature (°C)	Measurement Frequency (MHz)	
	5300 MHz	5500 MHz
-30	5300.0000	5500.0000
-20	5300.0000	5500.0000
-10	5300.0000	5500.0000
0	5299.9262	5499.9184
10	5299.9288	5499.9208
20	5299.9310	5499.9244
30	5299.9344	5499.9272
40	5299.9418	5499.9306
50	5300.0000	5500.0000
Max. Deviation (MHz)	0.073800	0.081600
Max. Deviation (ppm)	13.92	14.84

4.8. Antenna Requirements

4.8.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.8.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
MXE EMI Receiver	Agilent	N9038A	MY52260140	9kHz ~ 8 GHz	Dec. 25, 2013	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150 kHz ~ 100 MHz	Nov. 23, 2013	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127478	9kHz ~ 30MHz	Nov. 11, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150 kHz ~ 30 MHz	Dec. 04, 2013	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	N.C.R.	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	May 26, 2014	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 01, 2013	Radiation (03CH01-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Aug. 22, 2014	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 12, 2013	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Dec. 16, 2013	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26GHz ~ 40GHz	Oct. 23, 2013	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100019	9kHz~40GHz	Dec. 02, 2013	Radiation (03CH01-CB)
EMI Test Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8GHz	Dec. 12, 2013	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R.	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO 2000	N/A	1 m - 4 m	N.C.R.	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9kHz~40GHz	Nov. 29, 2013	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 03, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz - 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz - 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz - 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz - 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz - 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Power Sensor	Agilent	E9327A	US40442088	50MHz~18GHz	Dec. 02, 2013	Conducted (TH01-CB)
Power Meter	Agilent	E4416A	GB41291199	50MHz~18GHz	Dec. 02, 2013	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

“*” Calibration Interval of instruments listed above is two years.

NCR means Non-Calibration required.

6. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	2.4 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%