



## RF Exposure Report

**Report No.:** SA150430E02

**FCC ID:** PY315200309

**Test Model:** R8500

**Received Date:** May 06, 2015

**Test Date:** May 14 to 15, 2015

**Issued Date:** May 21, 2015

**Applicant:** NETGEAR, Inc.

**Address:** 350 East Plumeria Drive San Jose, CA 95134

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Hsin Chu Laboratory

**Lab Address:** No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin  
Chu Hsien 307, Taiwan R.O.C.

**Test Location (1):** No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin  
Chu Hsien 307, Taiwan R.O.C.

**Test Location (2):** No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin  
Chu Hsien 307, Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.



## Table of Contents

<b>Release Control Record</b> .....	<b>3</b>
<b>1 Certificate of Conformity</b> .....	<b>4</b>
<b>2 RF Exposure</b> .....	<b>5</b>
2.1 Limits For Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula .....	5
2.3 Classification .....	5
<b>3 Antenna Gain</b> .....	<b>6</b>
<b>4 Calculation Result of Maximum Conducted Power</b> .....	<b>7</b>



A D T

### Release Control Record

Issue No.	Description	Date Issued
SA150430E02	Original release.	May 21, 2015



A D T

## 1 Certificate of Conformity

**Product:** Nighthawk X8 Tri Band WiFi Router

**Brand:** NETGEAR

**Test Model:** R8500

**Sample Status:** ENGINEERING SAMPLE

**Applicant:** NETGEAR, Inc.

**Test Date:** May 14 to 15, 2015

**Standards:** FCC Part 2 (Section 2.1091)

KDB 447498 D03

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :**



**Date:**

May 21, 2015

Midoli Peng / Specialist

**Approved by :**



**Date:**

May 21, 2015

May Chen / Manager

## 2 RF Exposure

### 2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

### 2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * pi * r^2)$$

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

### 2.3 Classification

The antenna of this product, under normal use condition, is at least 43cm away from the body of the user.

So, this device is classified as **Mobile Device**.

### 3 Antenna Gain

The antennas provided to the EUT, please refer to the following table:

Antenna No.	Ant. Gain(dBi)	Frequency range (GHz to GHz)	Antenna Type	Connector Type
Internal (1)	3.99	5.15~5.25GHz	Dipole	i-pex(MHF)
Internal (2)	3.71	5.25~5.35GHz	Dipole	i-pex(MHF)
Internal (3)	3.71	5.47~5.725GHz	Dipole	i-pex(MHF)
Internal (4)	3.98	5.725~5.85GHz	Dipole	i-pex(MHF)
External (1)	0.67	2.4~2.4835GHz	Dipole	i-pex(MHF)
	-0.84	5.15~5.25GHz	Dipole	i-pex(MHF)
	-1.38	5.25~5.35GHz	Dipole	i-pex(MHF)
	-1.6	5.47~5.725GHz	Dipole	i-pex(MHF)
	-1.79	5.725~5.85GHz	Dipole	i-pex(MHF)
External (2)	0.67	2.4~2.4835GHz	Dipole	i-pex(MHF)
	-0.84	5.15~5.25GHz	Dipole	i-pex(MHF)
	-1.38	5.25~5.35GHz	Dipole	i-pex(MHF)
	-1.6	5.47~5.725GHz	Dipole	i-pex(MHF)
	-1.79	5.725~5.85GHz	Dipole	i-pex(MHF)
External (3)	0.67	2.4~2.4835GHz	Dipole	i-pex(MHF)
	-0.84	5.15~5.25GHz	Dipole	i-pex(MHF)
	-1.38	5.25~5.35GHz	Dipole	i-pex(MHF)
	-1.6	5.47~5.725GHz	Dipole	i-pex(MHF)
	-1.79	5.725~5.85GHz	Dipole	i-pex(MHF)
External (4)	0.67	2.4~2.4835GHz	Dipole	i-pex(MHF)
	-0.84	5.15~5.25GHz	Dipole	i-pex(MHF)
	-1.38	5.25~5.35GHz	Dipole	i-pex(MHF)
	-1.6	5.47~5.725GHz	Dipole	i-pex(MHF)
	-1.79	5.725~5.85GHz	Dipole	i-pex(MHF)

#### 4 Calculation Result of Maximum Conducted Power

##### For 15.247(2.4GHz)

CDD Mode					
Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2412-2462	940.551	6.69	43	0.18890	1

NOTE:

Directional gain = 0.67dBi + 10log(4) = 6.69dBi

##### For 15.247(5GHz)

##### With Internal antenna

CDD Mode					
Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
5745-5825	949.109	10	43	0.40848	1

##### Beamforming Mode

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
5745-5825	391.755	10	43	0.16080	1

NOTE:

Directional gain = 3.98dBi + 10log(4) = 10dBi

##### With External antenna

CDD Mode					
Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
5745-5825	922.296	4.23	43	0.10513	1

##### Beamforming Mode

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
5745-5825	957.105	4.23	43	0.10910	1

NOTE:

Directional gain = -1.79dBi + 10log(4) = 4.23dBi

**For 15.407(5GHz)  
With Internal antenna**

<b>CDD Mode</b>					
Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
5180-5240	965.588	10.01	43	0.41653	1

  

<b>Beamforming Mode</b>					
Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
5180-5240	389.388	10.01	43	0.16797	1

NOTE:  
Directional gain = 3.99dBi + 10log(4) = 10.01dBi

**With External antenna**

<b>CDD Mode</b>					
Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
5180-5240	862.421	5.18	43	0.12234	1

  

<b>Beamforming Mode</b>					
Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
5180-5240	997.542	5.18	43	0.14151	1

NOTE:  
Directional gain = -0.84dBi + 10log(4) = 5.18dBi

**Conclusion:**

The formula of calculated the MPE is:  
 $CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$   
 CPD = Calculation power density  
 LPD = Limit of power density

Condition	Technology		
1	WLAN(2.4GHz) - External Antenna	WLAN(5GHz <5150~5250MHz>) - External Antenna	WLAN(5GHz <5725~5850MHz>) - Internal Antenna
2	WLAN(2.4GHz) - External Antenna	WLAN(5GHz <5150~5250MHz>) - Internal Antenna	WLAN(5GHz <5725~5850MHz>) - External Antenna

Condition 1 : 0.18890 + 0.14151 + 0.40848 = 0.73889

Condition 2 : 0.18890 + 0.41653 + 0.10910 = 0.71453

**Therefore the maximum calculations of above situations are less than the “1” limit.**

**--- END ---**