

RF Exposure Report

Report No.: SA150430E10

FCC ID: PY315200310

Test Model: R7800

Received Date: Mar. 25, 2015

Test Date: May 14 to 15, 2015

Issued Date: May 21, 2015

Applicant: NETGEAR, Inc.

Address: 350 East Plumeria Drive San Jose, CA 95134

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

Test Location (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.



Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 RF Exposure.....	5
2.1 Limits For Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Antenna Gain.....	6
4 Calculation Result of Maximum Conducted Power.....	7



A D T

Release Control Record

Issue No.	Description	Date Issued
SA150430E10	Original release.	May 21, 2015

1 Certificate of Conformity

Product: Nighthawk X4S Smart WIFI Router

Brand: NETGEAR

Test Model: R7800

Sample Status: ENGINEERING SAMPLE

Applicant: NETGEAR, Inc.

Test Date: May 14 to 15, 2015


Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D03

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :


Lori Chung / Specialist

Date: May 21, 2015

Approved by :


May Chen / Manager

Date: May 21, 2015

2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 32cm away from the body of the user.

So, this device is classified as **Mobile Device**.

3 Antenna Gain

The antennas provided to the EUT, please refer to the following table:

Antenna No.	Ant. Gain(dBi)	Frequency range (GHz to GHz)	Antenna Type	Connector Type
External (1)	0.67	2.4~2.4835	Dipole	i-pex(MHF)
	1.16	5.15~5.25	Dipole	i-pex(MHF)
	0.62	5.25~5.35	Dipole	i-pex(MHF)
	0.4	5.47~5.725	Dipole	i-pex(MHF)
	0.21	5.725~5.85	Dipole	i-pex(MHF)
External (2)	0.67	2.4~2.4835	Dipole	i-pex(MHF)
	1.16	5.15~5.25	Dipole	i-pex(MHF)
	0.62	5.25~5.35	Dipole	i-pex(MHF)
	0.4	5.47~5.725	Dipole	i-pex(MHF)
	0.21	5.725~5.85	Dipole	i-pex(MHF)
External (3)	0.67	2.4~2.4835	Dipole	i-pex(MHF)
	1.16	5.15~5.25	Dipole	i-pex(MHF)
	0.62	5.25~5.35	Dipole	i-pex(MHF)
	0.4	5.47~5.725	Dipole	i-pex(MHF)
	0.21	5.725~5.85	Dipole	i-pex(MHF)
External (4)	0.67	2.4~2.4835	Dipole	i-pex(MHF)
	1.16	5.15~5.25	Dipole	i-pex(MHF)
	0.62	5.25~5.35	Dipole	i-pex(MHF)
	0.4	5.47~5.725	Dipole	i-pex(MHF)
	0.21	5.725~5.85	Dipole	i-pex(MHF)

4 Calculation Result of Maximum Conducted Power

For 15.247(2.4GHz)

CDD Mode

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	962.497	6.69	32	0.34905	1

NOTE:

Directional gain = 0.67dBi + 10log(4) = 6.69dBi

For 15.247(5GHz)

CDD Mode

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5745-5825	944.69	6.23	32	0.30816	1

Beamforming Mode

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5745-5825	937.418	6.23	32	0.30579	1

NOTE:

Directional gain = 0.21dBi + 10log(4) = 6.23dBi

For 15.407(5GHz)

CDD Mode

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5180-5240	951.947	7.18	32	0.38646	1

Beamforming Mode

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5180-5240	744.333	7.18	32	0.30217	1

NOTE:

Directional gain = 1.16dBi + 10log(4) = 7.18dBi

Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz = 0.34905 + 0.38646 = 0.73551

Therefore the maximum calculations of above situations are less than the "1" limit.

-

-- END ---