

RF Exposure Report

Report No.: SA160913E02A

FCC ID: PY316200342

Test Model: R6400v2

Received Date: Nov. 02, 2016

Test Date: Nov. 16, 2016

Issued Date: Mar. 29, 2017

Applicant: NETGEAR, Inc.

Address: 350 East Plumeria Drive San Jose, CA 95134

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits For Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	5
2.5 Calculation Result Of Maximum Conducted Power	7

Release Control Record

Issue No.	Description	Date Issued
SA160913E02A	Original release.	Mar. 29, 2017

1 Certificate of Conformity

Product: AC1750 Smart WiFi Router

Brand: NETGEAR

Test Model: R6400v2

Sample Status: ENGINEERING SAMPLE

Applicant: NETGEAR, Inc.

Test Date: Nov. 16, 2016

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :



Date:

Mar. 29, 2017

Wendy Wu / Specialist

Approved by :



Date:

Mar. 29, 2017

May Chen / Manager

2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 23cm away from the body of the user.

So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Antenna No.	Brand	Model	Antenna Gain(dBi)	Frequency range (GHz ~ GHz)	Antenna Type	Connector Type
98612PIPF003	NA	NA	3.4	2.4~2.4835	Dipole	I-pex (MHF)
			3.94	5.15~5.25		
			3.44	5.25~5.35		
			3.44	5.47~5.725		
			3.73	5.725~5.85		
98612PIPF004	NA	NA	3.23	2.4~2.4835	Dipole	I-pex (MHF)
			3.66	5.15~5.25		
			3.83	5.25~5.35		
			3.83	5.47~5.725		
			3.77	5.725~5.85		
98612PIPF005	NA	NA	3.36	2.4~2.4835	Dipole	I-pex (MHF)
			3.32	5.15~5.25		
			3.63	5.25~5.35		
			3.63	5.47~5.725		
			3.74	5.725~5.85		

The Directional gain table:

Frequency (MHz)	Max Gain (dBi)
2412-2462	5.65
5180-5240	5.95
5260-5320	5.95
5500-5700	5.98
5745-5825	5.98

Note:

1. Non-TxBF mode & TxBF mode antenna gain refer to KDB 662911 F 2) f) (ii)

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k/20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;

G_k is the gain in dBi of the k th antenna.

2.5 Calculation Result Of Maximum Conducted Power

For 2.4GHz and 5GHz (U-NII-1 and UNII-3 band) data was copied from the original test report (Report No.: SA160913E02)

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	579.66	5.65	23	0.32026	1
5180-5240	664.278	5.95	23	0.39326	1
5260-5320	235.09	5.95	23	0.13918	1
5500-5700	245.947	5.98	23	0.14661	1
5745-5825	988.92	5.98	23	0.58951	1

NOTE:

2.4GHz: Directional gain = 5.65dBi

5GHz:

UNII-1: Directional gain = 5.95dBi

UNII-2A: Directional gain = 5.95dBi

UNII-2C: Directional gain = 5.98dBi

UNII-3: Directional gain = 5.98dBi

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz = $0.32026 / 1 + 0.58951 / 1 = 0.90977$

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---