

RF Exposure Report

Report No.: SA170905C13A

FCC ID: PY317200377

Test Model: RBS50Y

Received Date: Sep. 05, 2017

Test Date: Sep. 11 ~ Oct. 16, 2017

Issued Date: May 29, 2018

Applicant: NETGEAR, INC.

Address: 350 East Plumeria Drive San Jose, CA 95134

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA170905C13A	Original release.	May 29, 2018

1 Certificate of Conformity

Product: Orbi Router, Orbi Satellite, Orbi AC3000 Tri-band WiFi System

Brand: NETGEAR

Test Model: RBS50Y

Sample Status: Engineering sample

Applicant: NETGEAR, INC.

Test Date: Sep. 11 ~ Oct. 16, 2017

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Celine Chou , **Date:** May 29, 2018
Celine Chou / Specialist

Approved by : Bruce Chen , **Date:** May 29, 2018
Bruce Chen / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 27cm away from the body of the user. So, this device is classified as Mobile Device.

3 Calculation Result of Maximum Conducted Power

Function	Frequency Band (MHz)	TX Function	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN	CDD Mode						
	2412-2462	2TX	29.14	5.31	27	0.304	1
	5180-5240	1TX	17.16	3.71	27	0.013	1
		2TX	17.17	5.97	27	0.022	1
	5260-5320	2TX	23.74	5.41	27	0.090	1
	5500-5700	4TX	23.64	8.74	27	0.189	1
	5745-5825	4TX	29.69	7.57	27	0.581	1
	Beamforming Mode						
	2412-2462	2TX	27.56	5.31	27	0.211	1
	5180-5240	2TX	14.18	5.97	27	0.011	1
	5260-5320	2TX	23.72	5.41	27	0.089	1
	5500-5700	4TX	21.25	8.74	27	0.109	1
	5745-5825	4TX	28.20	7.57	27	0.412	1
BT LE	2402-2480	1TX	7.83	1.50	27	0.001	1

Note: The Max Power = Max tune up power

2412~2462MHz Directional gain = 5.31dBi

5180~5240MHz Directional gain = 5.97dBi

5260~5320MHz Directional gain = 5.41dBi

5500~5700MHz Directional gain = 8.74dBi

5745~5825MHz Directional gain = 7.57dBi

Frequency Band	Max Power (dBm)		Total Power (dBm)	Power Limit (dBm)
	WLAN	BT LE		
2.4GHz	29.14	7.83	29.17	30

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz band 1 (1TX) + WLAN 5GHz band 4 + BT LE = $0.304 + 0.013 + 0.581 + 0.001$
= $0.899 < 1$

WLAN 2.4GHz + WLAN 5GHz band 1 (2TX) + WLAN 5GHz band 4 + BT LE = $0.304 + 0.022 + 0.581 + 0.001$
= $0.908 < 1$

WLAN 2.4GHz + WLAN 5GHz band 1 (2TX) + WLAN 5GHz band 3 + BT LE = $0.304 + 0.022 + 0.189 + 0.001$
= $0.516 < 1$

WLAN 2.4GHz + WLAN 5GHz band 2 + WLAN 5GHz band 3 + BT LE = $0.304 + 0.090 + 0.189 + 0.001$
= $0.584 < 1$

WLAN 2.4GHz + WLAN 5GHz band 2 + WLAN 5GHz band 4 + BT LE = $0.304 + 0.090 + 0.581 + 0.001$
= $0.976 < 1$

---END---