

RF Exposure Report

Report No.: SA170515E06

FCC ID: PY317200381

Test Model: NM8207

Received Date: May 16, 2017

Test Date: June 04, 2017

Issued Date: June 22, 2017

Applicant: NETGEAR, INC.

Address: 350 East Plumeria Drive San Jose, CA 95134

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 RF Exposure.....	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	5
2.5 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA170515E06	Original release.	June 22, 2017

1 Certificate of Conformity

Product: WWAN module

Brand: Netgear

Test Model: NM8207

Sample Status: ENGINEERING SAMPLE

Applicant: NETGEAR, INC.

Test Date: June 04, 2017

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :  , **Date:** June 22, 2017
Claire Kuan / Specialist

Approved by :  , **Date:** June 22, 2017
May Chen / Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Antenna	Antenna Gain(dBi)	Frequency range (MHz to MHz)	Antenna Type	Connector Type
1	3.4	824 to 849	PIFA	I-PEX MHF IV
	4.39	880 to 915		
2	2.62	1850 to 1915	PIFA	I-PEX MHF IV
	4.25	1710 to 1785		
	3.82	1920 to 1980		

2.5 Calculation Result of Maximum Conducted Power

GPRS & EDGE

Operation Mode	Directional Gain		The Worst Case			Total Peak. Power Output		Time average power (mW)		Power Density (mW/cm ²)		
	dBi	Linear	Mode	Channel Number	Freq. (MHz)	dBm	mW	mW	dBm	Value	Limit	Result
850 band	3.40	2.1878	GPRS	251	848.8	32.19	1655.77	413.943	26.17	0.18016	0.5659	PASS
850 band	3.40	2.1878	EDGE	251	848.8	32.15	1640.59	410.148	26.13	0.17851	0.5659	PASS
1900 band	2.62	1.8281	GPRS	661	1880	29.63	918.333	229.583	23.61	0.08350	1	PASS
1900 band	2.62	1.8281	EDGE	810	1909.8	29.54	899.498	224.875	23.52	0.08178	1	PASS

Note: 1. Limit of Power Density = $F/1500$ (For frequency below 1500MHz)

2. Calculations for RF Exposure compliance in the cellular and PCS bands are base on the maximum source based time-average power obtained from 2-Slot GPRS operation. The resulting duty cycle factor is 2/8, or 6.02dB.

WCDMA

Operation Mode	Directional Gain		The Worst Case			Total Peak. Power Output		Power Density (mW/cm ²)				
	dBi	Linear	Mode	Channel Number	Freq. (MHz)	dBm	mW	Value	Limit	Result		
850 band	3.40	2.1878	WCDMA V	4233	846.6	21.92	155.597	0.06772	0.5644	PASS		
1900 band	2.62	1.8281	WCDMA II	9662	1852.4	21.51	141.579	0.05149	1	PASS		

Note: 1. Limit of Power Density = $F/1500$ (For frequency below 1500MHz)

--- END ---