

RF Exposure Report

Report No.: SA180613C24B

FCC ID: PY317300397

Model: Leopard

Received Date: Jun. 13, 2018

Test Date: Jun. 07 ~ Oct. 18, 2018

Issued Date: Oct. 24, 2018

Applicant: NETGEAR, INC.

Address: 350 East Plumeria Drive San Jose, CA 95134

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)

FCC Registration / 788550 / TW0003

Designation Number:



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA180613C24B	Original release.	Oct. 24, 2018

1 Certificate of Conformity

Product: Leopard

Brand: NETGEAR

Model: Leopard

Sample Status: Engineering sample

Applicant: NETGEAR, INC.

Test Date: Jun. 07 ~ Oct. 18, 2018

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :



Date:

Oct. 24, 2018

Suntee Liu / Specialist

Approved by :



Date:

Oct. 24, 2018

Bruce Chen / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 22cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Mode	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN 2412~2462	CDD 4TX	29.98	3.29	22	0.349	1
WLAN 5180~5240	CDD 8TX	29.46	3.22	22	0.305	1
	Beamforming_NSS1 8TX	24.31	11.37	22	0.608	1
	Beamforming_NSS2 8TX	26.87	8.76	22	0.601	1
	CDD 4TX	24.08	3.22	22	0.088	1
WLAN 5260~5320	CDD 8TX	23.72	3.25	22	0.082	1
	Beamforming_NSS1 8TX	18.18	11.72	22	0.161	1
	Beamforming_NSS2 8TX	21.12	8.81	22	0.162	1
	CDD 4TX	23.50	3.25	22	0.078	1
WLAN 5500~5700	CDD 8TX	23.65	3.32	22	0.082	1
	Beamforming_NSS1 8TX	18.54	11.38	22	0.161	1
	Beamforming_NSS2 8TX	21.38	8.40	22	0.156	1
	CDD 4TX	23.46	3.32	22	0.078	1
WLAN 5745~5825	CDD	29.98	3.10	22	0.334	1
	Beamforming_NSS1 8TX	24.33	11.55	22	0.637	1
	Beamforming_NSS2 8TX	27.34	8.32	22	0.605	1
	CDD 4TX	24.06	3.10	22	0.085	1

Note:

CDD Mode 8TX

2412~2462MHz Directional Gain = 3.29dBi

5180~5240MHz Directional Gain = 3.22dBi

5260~5320MHz Directional Gain = 3.25dBi

5500~5700MHz Directional Gain = 3.32dBi

5745~5825MHz Directional Gain = 3.10dBi

Beamforming_NSS1 Mode 8TX

5180~5240MHz Directional Gain = 11.37dBi

5260~5320MHz Directional Gain = 11.72dBi

5500~5700MHz Directional Gain = 11.38dBi

5745~5825MHz Directional Gain = 11.55dBi

Beamforming_NSS2 Mode 8TX

5180~5240MHz Directional Gain = 8.76dBi

5260~5320MHz Directional Gain = 8.81dBi

5500~5700MHz Directional Gain = 8.40dBi

5745~5825MHz Directional Gain = 8.32dBi

CDD Mode 4TX

5180~5240MHz Directional Gain = 3.22dBi

5260~5320MHz Directional Gain = 3.25dBi

5500~5700MHz Directional Gain = 3.32dBi

5745~5825MHz Directional Gain = 3.10dBi

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

Worst case: WLAN 2.4GHz + WLAN 5GHz band 4 (8TX) = $0.349 + 0.637 = 0.986 < 1$

Worst case: WLAN 2.4GHz + WLAN 5GHz band 1 (4TX) + WLAN 5GHz band 4 (4TX) = $0.349 + 0.088 + 0.085 = 0.522 < 1$

---END---