

RF Mode	TX 802.11ax (HE20)	Channel	CH 97 : 6435 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6435.00	113.7 PK			1.51 H	127	108.3	5.4
2	*6435.00	101.8 AV			1.51 H	127	96.4	5.4
3	#12870.00	42.2 PK	88.2	-46.0	1.58 H	27	28.8	13.4
4	#12870.00	37.1 AV	68.2	-31.1	1.58 H	27	23.7	13.4
5	19305.00	40.8 PK	74.0	-33.2	1.37 H	319	47.5	-6.7
6	19305.00	29.6 AV	54.0	-24.4	1.37 H	319	36.3	-6.7
7	#25740.00	40.0 PK	88.2	-48.2	1.50 H	306	41.4	-1.4
8	#25740.00	38.3 AV	68.2	-29.9	1.50 H	306	39.7	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6435.00	116.0 PK			1.51 V	109	110.6	5.4
2	*6435.00	104.1 AV			1.51 V	109	98.7	5.4
3	#12870.00	46.0 PK	88.2	-42.2	2.58 V	17	32.6	13.4
4	#12870.00	40.3 AV	68.2	-27.9	2.58 V	17	26.9	13.4
5	19305.00	36.7 PK	74.0	-37.3	1.74 V	230	43.4	-6.7
6	19305.00	26.3 AV	54.0	-27.7	1.74 V	230	33.0	-6.7
7	#25740.00	39.8 PK	88.2	-48.4	1.54 V	35	41.2	-1.4
8	#25740.00	34.4 AV	68.2	-33.8	1.54 V	35	35.8	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 105 : 6475 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6475.00	113.2 PK			1.49 H	108	107.5	5.7
2	*6475.00	101.3 AV			1.49 H	108	95.6	5.7
3	#12950.00	42.5 PK	88.2	-45.7	1.58 H	24	29.2	13.3
4	#12950.00	37.5 AV	68.2	-30.7	1.58 H	24	24.2	13.3
5	19425.00	41.1 PK	74.0	-32.9	1.47 H	323	47.9	-6.8
6	19425.00	29.4 AV	54.0	-24.6	1.47 H	323	36.2	-6.8
7	#25900.00	40.5 PK	88.2	-47.7	1.41 H	300	42.5	-2.0
8	#25900.00	38.9 AV	68.2	-29.3	1.41 H	300	40.9	-2.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6475.00	116.2 PK			1.56 V	118	110.5	5.7
2	*6475.00	104.6 AV			1.56 V	118	98.9	5.7
3	#12950.00	45.9 PK	88.2	-42.3	2.54 V	19	32.6	13.3
4	#12950.00	39.8 AV	68.2	-28.4	2.54 V	19	26.5	13.3
5	19425.00	36.8 PK	74.0	-37.2	1.72 V	223	43.6	-6.8
6	19425.00	26.6 AV	54.0	-27.4	1.72 V	223	33.4	-6.8
7	#25900.00	39.9 PK	88.2	-48.3	1.57 V	30	41.9	-2.0
8	#25900.00	34.4 AV	68.2	-33.8	1.57 V	30	36.4	-2.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 113 : 6515 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6515.00	113.3 PK			1.47 H	110	107.3	6.0
2	*6515.00	101.8 AV			1.47 H	110	95.8	6.0
3	#13030.00	42.2 PK	88.2	-46.0	1.48 H	31	28.9	13.3
4	#13030.00	37.3 AV	68.2	-30.9	1.48 H	31	24.0	13.3
5	19545.00	41.0 PK	74.0	-33.0	1.36 H	311	47.2	-6.2
6	19545.00	29.6 AV	54.0	-24.4	1.36 H	311	35.8	-6.2
7	#26060.00	40.5 PK	88.2	-47.7	1.41 H	317	41.9	-1.4
8	#26060.00	38.7 AV	68.2	-29.5	1.41 H	317	40.1	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6515.00	116.4 PK			1.52 V	121	110.4	6.0
2	*6515.00	105.0 AV			1.52 V	121	99.0	6.0
3	#13030.00	46.3 PK	88.2	-41.9	2.57 V	0	33.0	13.3
4	#13030.00	40.6 AV	68.2	-27.6	2.57 V	0	27.3	13.3
5	19545.00	36.7 PK	74.0	-37.3	1.79 V	243	42.9	-6.2
6	19545.00	26.6 AV	54.0	-27.4	1.79 V	243	32.8	-6.2
7	#26060.00	39.9 PK	88.2	-48.3	1.52 V	31	41.3	-1.4
8	#26060.00	34.4 AV	68.2	-33.8	1.52 V	31	35.8	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 117 : 6535 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6535.00	113.4 PK			1.58 H	119	107.4	6.0
2	*6535.00	101.8 AV			1.58 H	119	95.8	6.0
3	#13070.00	42.8 PK	88.2	-45.4	1.49 H	10	29.4	13.4
4	#13070.00	37.4 AV	68.2	-30.8	1.49 H	10	24.0	13.4
5	19605.00	41.1 PK	74.0	-32.9	1.39 H	318	47.2	-6.1
6	19605.00	29.7 AV	54.0	-24.3	1.39 H	318	35.8	-6.1
7	#26140.00	40.2 PK	88.2	-48.0	1.49 H	325	41.5	-1.3
8	#26140.00	38.7 AV	68.2	-29.5	1.49 H	325	40.0	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6535.00	116.3 PK			1.50 V	121	110.3	6.0
2	*6535.00	104.9 AV			1.50 V	121	98.9	6.0
3	#13070.00	46.3 PK	88.2	-41.9	2.51 V	16	32.9	13.4
4	#13070.00	40.6 AV	68.2	-27.6	2.51 V	16	27.2	13.4
5	19605.00	36.8 PK	74.0	-37.2	1.78 V	221	42.9	-6.1
6	19605.00	26.4 AV	54.0	-27.6	1.78 V	221	32.5	-6.1
7	#26140.00	40.8 PK	88.2	-47.4	1.59 V	8	42.1	-1.3
8	#26140.00	35.2 AV	68.2	-33.0	1.59 V	8	36.5	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 153 : 6715 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6715.00	114.0 PK			1.48 H	118	107.9	6.1
2	*6715.00	102.0 AV			1.48 H	118	95.9	6.1
3	#13430.00	43.0 PK	88.2	-45.2	1.52 H	25	28.1	14.9
4	#13430.00	37.7 AV	68.2	-30.5	1.52 H	25	22.8	14.9
5	20145.00	40.2 PK	74.0	-33.8	1.38 H	332	45.6	-5.4
6	20145.00	29.0 AV	54.0	-25.0	1.38 H	332	34.4	-5.4
7	#26860.00	40.1 PK	88.2	-48.1	1.43 H	323	41.2	-1.1
8	#26860.00	38.3 AV	68.2	-29.9	1.43 H	323	39.4	-1.1

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6715.00	116.7 PK			1.49 V	131	110.6	6.1
2	*6715.00	104.8 AV			1.49 V	131	98.7	6.1
3	#13430.00	45.4 PK	88.2	-42.8	2.54 V	15	30.5	14.9
4	#13430.00	39.7 AV	68.2	-28.5	2.54 V	15	24.8	14.9
5	20145.00	36.7 PK	74.0	-37.3	1.79 V	230	42.1	-5.4
6	20145.00	26.5 AV	54.0	-27.5	1.79 V	230	31.9	-5.4
7	#26860.00	40.7 PK	88.2	-47.5	1.52 V	27	41.8	-1.1
8	#26860.00	35.2 AV	68.2	-33.0	1.52 V	27	36.3	-1.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 181 : 6855 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6855.00	113.2 PK			1.56 H	116	106.4	6.8
2	*6855.00	101.6 AV			1.56 H	116	94.8	6.8
3	#13710.00	42.6 PK	88.2	-45.6	1.56 H	20	26.9	15.7
4	#13710.00	37.8 AV	68.2	-30.4	1.56 H	20	22.1	15.7
5	20565.00	41.1 PK	74.0	-32.9	1.40 H	315	46.0	-4.9
6	20565.00	29.5 AV	54.0	-24.5	1.40 H	315	34.4	-4.9
7	#27420.00	40.5 PK	88.2	-47.7	1.46 H	307	42.1	-1.6
8	#27420.00	38.9 AV	68.2	-29.3	1.46 H	307	40.5	-1.6

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6855.00	116.2 PK			1.56 V	112	109.4	6.8
2	*6855.00	104.3 AV			1.56 V	112	97.5	6.8
3	#13710.00	46.2 PK	88.2	-42.0	2.54 V	9	30.5	15.7
4	#13710.00	40.2 AV	68.2	-28.0	2.54 V	9	24.5	15.7
5	20565.00	37.3 PK	74.0	-36.7	1.77 V	243	42.2	-4.9
6	20565.00	26.9 AV	54.0	-27.1	1.77 V	243	31.8	-4.9
7	#27420.00	40.6 PK	88.2	-47.6	1.51 V	25	42.2	-1.6
8	#27420.00	34.7 AV	68.2	-33.5	1.51 V	25	36.3	-1.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 185 : 6875 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6875.00	113.3 PK			1.52 H	132	106.3	7.0
2	*6875.00	101.7 AV			1.52 H	132	94.7	7.0
3	#13750.00	42.3 PK	88.2	-45.9	1.53 H	30	26.5	15.8
4	#13750.00	37.4 AV	68.2	-30.8	1.53 H	30	21.6	15.8
5	20625.00	41.1 PK	74.0	-32.9	1.45 H	314	45.9	-4.8
6	20625.00	29.6 AV	54.0	-24.4	1.45 H	314	34.4	-4.8
7	#27500.00	40.4 PK	88.2	-47.8	1.46 H	317	41.6	-1.2
8	#27500.00	38.4 AV	68.2	-29.8	1.46 H	317	39.6	-1.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6875.00	116.1 PK			1.54 V	131	109.1	7.0
2	*6875.00	104.6 AV			1.54 V	131	97.6	7.0
3	#13750.00	46.1 PK	88.2	-42.1	2.55 V	4	30.3	15.8
4	#13750.00	39.9 AV	68.2	-28.3	2.55 V	4	24.1	15.8
5	20625.00	37.3 PK	74.0	-36.7	1.70 V	232	42.1	-4.8
6	20625.00	26.8 AV	54.0	-27.2	1.70 V	232	31.6	-4.8
7	#27500.00	40.8 PK	88.2	-47.4	1.56 V	25	42.0	-1.2
8	#27500.00	35.2 AV	68.2	-33.0	1.56 V	25	36.4	-1.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 213 : 7015 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7015.00	113.4 PK			1.54 H	125	105.5	7.9
2	*7015.00	101.5 AV			1.54 H	125	93.6	7.9
3	#14030.00	41.9 PK	88.2	-46.3	1.52 H	5	26.0	15.9
4	#14030.00	36.9 AV	68.2	-31.3	1.52 H	5	21.0	15.9
5	21045.00	40.8 PK	74.0	-33.2	1.44 H	328	45.2	-4.4
6	21045.00	29.1 AV	54.0	-24.9	1.44 H	328	33.5	-4.4
7	#28060.00	40.7 PK	88.2	-47.5	1.49 H	301	42.1	-1.4
8	#28060.00	38.8 AV	68.2	-29.4	1.49 H	301	40.2	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7015.00	116.2 PK			1.48 V	136	108.3	7.9
2	*7015.00	104.6 AV			1.48 V	136	96.7	7.9
3	#14030.00	45.8 PK	88.2	-42.4	2.54 V	1	29.9	15.9
4	#14030.00	39.8 AV	68.2	-28.4	2.54 V	1	23.9	15.9
5	21045.00	37.5 PK	74.0	-36.5	1.79 V	232	41.9	-4.4
6	21045.00	26.8 AV	54.0	-27.2	1.79 V	232	31.2	-4.4
7	#28060.00	40.2 PK	88.2	-48.0	1.56 V	33	41.6	-1.4
8	#28060.00	34.5 AV	68.2	-33.7	1.56 V	33	35.9	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 229 : 7095 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7095.00	113.7 PK			1.63 H	311	107.7	6.0
2	*7095.00	102.0 AV			1.63 H	311	96.0	6.0
3	#7125.00	63.5 PK	88.2	-24.7	1.63 H	311	57.2	6.3
4	#7125.00	50.2 AV	68.2	-18.0	1.63 H	311	43.9	6.3
5	#14190.00	41.7 PK	88.2	-46.5	1.57 H	16	27.3	14.4
6	#14190.00	36.5 AV	68.2	-31.7	1.57 H	16	22.1	14.4
7	21285.00	41.0 PK	74.0	-33.0	1.46 H	321	45.2	-4.2
8	21285.00	29.5 AV	54.0	-24.5	1.46 H	321	33.7	-4.2
9	#28380.00	40.0 PK	88.2	-48.2	1.52 H	292	41.7	-1.7
10	#28380.00	38.4 AV	68.2	-29.8	1.52 H	292	40.1	-1.7

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7095.00	116.5 PK			1.80 V	347	110.5	6.0
2	*7095.00	104.7 AV			1.80 V	347	98.7	6.0
3	#7125.00	67.0 PK	88.2	-21.2	1.80 V	347	60.7	6.3
4	#7125.00	54.0 AV	68.2	-14.2	1.80 V	347	47.7	6.3
5	#14190.00	45.2 PK	88.2	-43.0	2.52 V	1	30.8	14.4
6	#14190.00	39.4 AV	68.2	-28.8	2.52 V	1	25.0	14.4
7	21285.00	37.2 PK	74.0	-36.8	1.81 V	244	41.4	-4.2
8	21285.00	26.5 AV	54.0	-27.5	1.81 V	244	30.7	-4.2
9	#28380.00	40.7 PK	88.2	-47.5	1.58 V	28	42.4	-1.7
10	#28380.00	34.9 AV	68.2	-33.3	1.58 V	28	36.6	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 233 : 7115 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7115.00	91.3 PK			1.56 H	120	83.2	8.1
2	*7115.00	78.3 AV			1.56 H	120	70.2	8.1
3	#7125.00	81.5 PK	88.2	-6.7	1.56 H	120	73.3	8.2
4	#7125.00	66.4 AV	68.2	-1.8	1.56 H	120	58.2	8.2
5	#14230.00	42.8 PK	88.2	-45.4	1.54 H	26	25.7	17.1
6	#14230.00	37.8 AV	68.2	-30.4	1.54 H	26	20.7	17.1
7	21345.00	40.0 PK	74.0	-34.0	1.44 H	334	44.2	-4.2
8	21345.00	28.9 AV	54.0	-25.1	1.44 H	334	33.1	-4.2
9	#28460.00	40.3 PK	88.2	-47.9	1.47 H	324	41.7	-1.4
10	#28460.00	38.3 AV	68.2	-29.9	1.47 H	324	39.7	-1.4

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7115.00	93.5 PK			1.98 V	210	85.4	8.1
2	*7115.00	81.1 AV			1.98 V	210	73.0	8.1
3	#7125.00	83.1 PK	88.2	-5.1	1.98 V	210	74.9	8.2
4	#7125.00	67.9 AV	68.2	-0.3	1.98 V	210	59.7	8.2
5	#14230.00	45.6 PK	88.2	-42.6	2.63 V	14	28.5	17.1
6	#14230.00	39.6 AV	68.2	-28.6	2.63 V	14	22.5	17.1
7	21345.00	36.6 PK	74.0	-37.4	1.76 V	239	40.8	-4.2
8	21345.00	26.4 AV	54.0	-27.6	1.76 V	239	30.6	-4.2
9	#28460.00	40.6 PK	88.2	-47.6	1.61 V	14	42.0	-1.4
10	#28460.00	34.9 AV	68.2	-33.3	1.61 V	14	36.3	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 35 : 6125 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	48.9 PK	88.2	-39.3	1.60 H	93	45.2	3.7
2	#5925.00	39.0 AV	68.2	-29.2	1.60 H	93	35.3	3.7
3	*6125.00	111.8 PK			1.60 H	93	107.5	4.3
4	*6125.00	99.7 AV			1.60 H	93	95.4	4.3
5	12250.00	42.2 PK	74.0	-31.8	1.46 H	40	29.0	13.2
6	12250.00	37.5 AV	54.0	-16.5	1.46 H	40	24.3	13.2
7	18375.00	41.3 PK	74.0	-32.7	1.43 H	303	48.5	-7.2
8	18375.00	29.8 AV	54.0	-24.2	1.43 H	303	37.0	-7.2
9	#24500.00	39.8 PK	88.2	-48.4	1.43 H	307	41.9	-2.1
10	#24500.00	37.7 AV	68.2	-30.5	1.43 H	307	39.8	-2.1

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	50.5 PK	88.2	-37.7	2.22 V	200	46.8	3.7
2	#5925.00	38.8 AV	68.2	-29.4	2.22 V	200	35.1	3.7
3	*6125.00	114.5 PK			2.22 V	200	110.2	4.3
4	*6125.00	102.8 AV			2.22 V	200	98.5	4.3
5	12250.00	41.1 PK	74.0	-32.9	2.52 V	10	27.9	13.2
6	12250.00	35.5 AV	54.0	-18.5	2.52 V	10	22.3	13.2
7	18375.00	38.2 PK	74.0	-35.8	1.68 V	232	45.4	-7.2
8	18375.00	27.4 AV	54.0	-26.6	1.68 V	232	34.6	-7.2
9	#24500.00	40.8 PK	88.2	-47.4	1.54 V	26	42.9	-2.1
10	#24500.00	35.0 AV	68.2	-33.2	1.54 V	26	37.1	-2.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 59 : 6245 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6245.00	111.7 PK			1.65 H	99	107.0	4.7
2	*6245.00	99.7 AV			1.65 H	99	95.0	4.7
3	12490.00	42.5 PK	74.0	-31.5	1.48 H	27	30.0	12.5
4	12490.00	37.2 AV	54.0	-16.8	1.48 H	27	24.7	12.5
5	18735.00	41.0 PK	74.0	-33.0	1.33 H	318	47.8	-6.8
6	18735.00	29.4 AV	54.0	-24.6	1.33 H	318	36.2	-6.8
7	#24980.00	40.2 PK	88.2	-48.0	1.48 H	321	42.0	-1.8
8	#24980.00	38.3 AV	68.2	-29.9	1.48 H	321	40.1	-1.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6245.00	115.0 PK			2.34 V	164	110.3	4.7
2	*6245.00	102.6 AV			2.34 V	164	97.9	4.7
3	12490.00	40.3 PK	74.0	-33.7	2.51 V	27	27.8	12.5
4	12490.00	35.1 AV	54.0	-18.9	2.51 V	27	22.6	12.5
5	18735.00	37.2 PK	74.0	-36.8	1.74 V	244	44.0	-6.8
6	18735.00	26.8 AV	54.0	-27.2	1.74 V	244	33.6	-6.8
7	#24980.00	41.0 PK	88.2	-47.2	1.57 V	7	42.8	-1.8
8	#24980.00	35.5 AV	68.2	-32.7	1.57 V	7	37.3	-1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 91 : 6405 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6405.00	112.1 PK			1.55 H	104	106.8	5.3
2	*6405.00	99.8 AV			1.55 H	104	94.5	5.3
3	#12810.00	42.9 PK	88.2	-45.3	1.49 H	44	29.4	13.5
4	#12810.00	37.7 AV	68.2	-30.5	1.49 H	44	24.2	13.5
5	19215.00	41.2 PK	74.0	-32.8	1.36 H	305	47.9	-6.7
6	19215.00	29.6 AV	54.0	-24.4	1.36 H	305	36.3	-6.7
7	#25620.00	39.7 PK	88.2	-48.5	1.43 H	307	41.4	-1.7
8	#25620.00	38.0 AV	68.2	-30.2	1.43 H	307	39.7	-1.7

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6405.00	114.9 PK			2.35 V	177	109.6	5.3
2	*6405.00	102.7 AV			2.35 V	177	97.4	5.3
3	#12810.00	40.5 PK	88.2	-47.7	2.57 V	2	27.0	13.5
4	#12810.00	34.8 AV	68.2	-33.4	2.57 V	2	21.3	13.5
5	19215.00	38.1 PK	74.0	-35.9	1.65 V	241	44.8	-6.7
6	19215.00	27.5 AV	54.0	-26.5	1.65 V	241	34.2	-6.7
7	#25620.00	41.4 PK	88.2	-46.8	1.49 V	2	43.1	-1.7
8	#25620.00	35.6 AV	68.2	-32.6	1.49 V	2	37.3	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 99 : 6445 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6445.00	111.4 PK			1.63 H	100	105.9	5.5
2	*6445.00	99.6 AV			1.63 H	100	94.1	5.5
3	#12890.00	42.9 PK	88.2	-45.3	1.49 H	49	29.6	13.3
4	#12890.00	37.6 AV	68.2	-30.6	1.49 H	49	24.3	13.3
5	19335.00	40.7 PK	74.0	-33.3	1.37 H	333	47.5	-6.8
6	19335.00	29.3 AV	54.0	-24.7	1.37 H	333	36.1	-6.8
7	#25780.00	39.2 PK	88.2	-49.0	1.52 H	305	40.6	-1.4
8	#25780.00	37.5 AV	68.2	-30.7	1.52 H	305	38.9	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6445.00	114.9 PK			2.43 V	174	109.4	5.5
2	*6445.00	102.5 AV			2.43 V	174	97.0	5.5
3	#12890.00	40.9 PK	88.2	-47.3	2.53 V	7	27.6	13.3
4	#12890.00	35.3 AV	68.2	-32.9	2.53 V	7	22.0	13.3
5	19335.00	37.6 PK	74.0	-36.4	1.69 V	234	44.4	-6.8
6	19335.00	27.0 AV	54.0	-27.0	1.69 V	234	33.8	-6.8
7	#25780.00	41.2 PK	88.2	-47.0	1.56 V	0	42.6	-1.4
8	#25780.00	35.4 AV	68.2	-32.8	1.56 V	0	36.8	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 107 : 6485 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6485.00	111.8 PK			1.57 H	93	106.0	5.8
2	*6485.00	99.7 AV			1.57 H	93	93.9	5.8
3	#12970.00	42.2 PK	88.2	-46.0	1.44 H	26	28.9	13.3
4	#12970.00	37.0 AV	68.2	-31.2	1.44 H	26	23.7	13.3
5	19455.00	40.7 PK	74.0	-33.3	1.41 H	307	47.3	-6.6
6	19455.00	29.3 AV	54.0	-24.7	1.41 H	307	35.9	-6.6
7	#25940.00	40.0 PK	88.2	-48.2	1.43 H	303	41.8	-1.8
8	#25940.00	38.1 AV	68.2	-30.1	1.43 H	303	39.9	-1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6485.00	114.9 PK			2.29 V	167	109.1	5.8
2	*6485.00	102.7 AV			2.29 V	167	96.9	5.8
3	#12970.00	40.6 PK	88.2	-47.6	2.51 V	13	27.3	13.3
4	#12970.00	35.5 AV	68.2	-32.7	2.51 V	13	22.2	13.3
5	19455.00	38.2 PK	74.0	-35.8	1.70 V	220	44.8	-6.6
6	19455.00	27.3 AV	54.0	-26.7	1.70 V	220	33.9	-6.6
7	#25940.00	40.9 PK	88.2	-47.3	1.45 V	7	42.7	-1.8
8	#25940.00	35.3 AV	68.2	-32.9	1.45 V	7	37.1	-1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 115 : 6525 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6525.00	111.5 PK			1.59 H	87	105.5	6.0
2	*6525.00	99.4 AV			1.59 H	87	93.4	6.0
3	#13050.00	42.7 PK	88.2	-45.5	1.54 H	41	29.4	13.3
4	#13050.00	37.7 AV	68.2	-30.5	1.54 H	41	24.4	13.3
5	19575.00	41.4 PK	74.0	-32.6	1.37 H	329	47.6	-6.2
6	19575.00	29.9 AV	54.0	-24.1	1.37 H	329	36.1	-6.2
7	#26100.00	39.4 PK	88.2	-48.8	1.53 H	302	40.8	-1.4
8	#26100.00	37.9 AV	68.2	-30.3	1.53 H	302	39.3	-1.4

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6525.00	114.5 PK			2.42 V	164	108.5	6.0
2	*6525.00	102.0 AV			2.42 V	164	96.0	6.0
3	#13050.00	40.7 PK	88.2	-47.5	2.55 V	23	27.4	13.3
4	#13050.00	35.4 AV	68.2	-32.8	2.55 V	23	22.1	13.3
5	19575.00	38.0 PK	74.0	-36.0	1.65 V	215	44.2	-6.2
6	19575.00	27.2 AV	54.0	-26.8	1.65 V	215	33.4	-6.2
7	#26100.00	40.3 PK	88.2	-47.9	1.57 V	18	41.7	-1.4
8	#26100.00	35.0 AV	68.2	-33.2	1.57 V	18	36.4	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 123 : 6565 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6565.00	111.5 PK			1.63 H	104	105.4	6.1
2	*6565.00	99.6 AV			1.63 H	104	93.5	6.1
3	#13130.00	42.2 PK	88.2	-46.0	1.50 H	41	28.7	13.5
4	#13130.00	37.1 AV	68.2	-31.1	1.50 H	41	23.6	13.5
5	19695.00	40.6 PK	74.0	-33.4	1.35 H	323	46.6	-6.0
6	19695.00	29.3 AV	54.0	-24.7	1.35 H	323	35.3	-6.0
7	#26260.00	40.1 PK	88.2	-48.1	1.52 H	311	41.5	-1.4
8	#26260.00	38.0 AV	68.2	-30.2	1.52 H	311	39.4	-1.4

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6565.00	114.5 PK			2.50 V	155	108.4	6.1
2	*6565.00	102.0 AV			2.50 V	155	95.9	6.1
3	#13130.00	40.6 PK	88.2	-47.6	2.52 V	13	27.1	13.5
4	#13130.00	35.4 AV	68.2	-32.8	2.52 V	13	21.9	13.5
5	19695.00	38.4 PK	74.0	-35.6	1.67 V	220	44.4	-6.0
6	19695.00	27.6 AV	54.0	-26.4	1.67 V	220	33.6	-6.0
7	#26260.00	40.4 PK	88.2	-47.8	1.48 V	3	41.8	-1.4
8	#26260.00	34.8 AV	68.2	-33.4	1.48 V	3	36.2	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 155 : 6725 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6725.00	112.1 PK			1.54 H	77	105.9	6.2
2	*6725.00	100.0 AV			1.54 H	77	93.8	6.2
3	#13450.00	42.0 PK	88.2	-46.2	1.50 H	24	27.2	14.8
4	#13450.00	37.1 AV	68.2	-31.1	1.50 H	24	22.3	14.8
5	20175.00	41.5 PK	74.0	-32.5	1.39 H	333	46.9	-5.4
6	20175.00	29.7 AV	54.0	-24.3	1.39 H	333	35.1	-5.4
7	#26900.00	39.8 PK	88.2	-48.4	1.53 H	302	41.1	-1.3
8	#26900.00	38.0 AV	68.2	-30.2	1.53 H	302	39.3	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6725.00	115.1 PK			2.34 V	164	108.9	6.2
2	*6725.00	102.7 AV			2.34 V	164	96.5	6.2
3	#13450.00	40.2 PK	88.2	-48.0	2.51 V	29	25.4	14.8
4	#13450.00	35.1 AV	68.2	-33.1	2.51 V	29	20.3	14.8
5	20175.00	37.1 PK	74.0	-36.9	1.66 V	217	42.5	-5.4
6	20175.00	26.7 AV	54.0	-27.3	1.66 V	217	32.1	-5.4
7	#26900.00	40.7 PK	88.2	-47.5	1.52 V	16	42.0	-1.3
8	#26900.00	35.0 AV	68.2	-33.2	1.52 V	16	36.3	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 179 : 6845 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6845.00	111.6 PK			1.59 H	103	104.9	6.7
2	*6845.00	99.2 AV			1.59 H	103	92.5	6.7
3	#13690.00	41.8 PK	88.2	-46.4	1.45 H	47	26.3	15.5
4	#13690.00	37.0 AV	68.2	-31.2	1.45 H	47	21.5	15.5
5	20535.00	41.2 PK	74.0	-32.8	1.38 H	331	46.1	-4.9
6	20535.00	29.4 AV	54.0	-24.6	1.38 H	331	34.3	-4.9
7	#27380.00	40.3 PK	88.2	-47.9	1.54 H	323	42.0	-1.7
8	#27380.00	38.3 AV	68.2	-29.9	1.54 H	323	40.0	-1.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6845.00	114.3 PK			2.46 V	167	107.6	6.7
2	*6845.00	102.2 AV			2.46 V	167	95.5	6.7
3	#13690.00	40.8 PK	88.2	-47.4	2.52 V	33	25.3	15.5
4	#13690.00	35.7 AV	68.2	-32.5	2.52 V	33	20.2	15.5
5	20535.00	37.3 PK	74.0	-36.7	1.65 V	216	42.2	-4.9
6	20535.00	26.7 AV	54.0	-27.3	1.65 V	216	31.6	-4.9
7	#27380.00	39.9 PK	88.2	-48.3	1.46 V	18	41.6	-1.7
8	#27380.00	34.6 AV	68.2	-33.6	1.46 V	18	36.3	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 187 : 6885 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6885.00	111.6 PK			1.62 H	83	104.5	7.1
2	*6885.00	99.4 AV			1.62 H	83	92.3	7.1
3	#13770.00	41.7 PK	88.2	-46.5	1.50 H	35	25.9	15.8
4	#13770.00	36.9 AV	68.2	-31.3	1.50 H	35	21.1	15.8
5	20655.00	41.4 PK	74.0	-32.6	1.41 H	307	46.3	-4.9
6	20655.00	29.9 AV	54.0	-24.1	1.41 H	307	34.8	-4.9
7	#27540.00	40.3 PK	88.2	-47.9	1.43 H	300	41.6	-1.3
8	#27540.00	38.2 AV	68.2	-30.0	1.43 H	300	39.5	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6885.00	114.4 PK			2.35 V	155	107.3	7.1
2	*6885.00	102.2 AV			2.35 V	155	95.1	7.1
3	#13770.00	40.2 PK	88.2	-48.0	2.50 V	7	24.4	15.8
4	#13770.00	34.7 AV	68.2	-33.5	2.50 V	7	18.9	15.8
5	20655.00	38.1 PK	74.0	-35.9	1.66 V	222	43.0	-4.9
6	20655.00	27.6 AV	54.0	-26.4	1.66 V	222	32.5	-4.9
7	#27540.00	40.4 PK	88.2	-47.8	1.52 V	24	41.7	-1.3
8	#27540.00	35.0 AV	68.2	-33.2	1.52 V	24	36.3	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 211 : 7005 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7005.00	111.8 PK			1.62 H	94	103.9	7.9
2	*7005.00	99.8 AV			1.62 H	94	91.9	7.9
3	#14010.00	42.6 PK	88.2	-45.6	1.47 H	48	26.9	15.7
4	#14010.00	37.7 AV	68.2	-30.5	1.47 H	48	22.0	15.7
5	21015.00	40.7 PK	74.0	-33.3	1.39 H	306	45.1	-4.4
6	21015.00	29.2 AV	54.0	-24.8	1.39 H	306	33.6	-4.4
7	#28020.00	40.1 PK	88.2	-48.1	1.43 H	317	41.4	-1.3
8	#28020.00	38.4 AV	68.2	-29.8	1.43 H	317	39.7	-1.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7005.00	114.8 PK			2.34 V	159	106.9	7.9
2	*7005.00	102.3 AV			2.34 V	159	94.4	7.9
3	#14010.00	39.9 PK	88.2	-48.3	2.59 V	29	24.2	15.7
4	#14010.00	34.7 AV	68.2	-33.5	2.59 V	29	19.0	15.7
5	21015.00	37.1 PK	74.0	-36.9	1.67 V	242	41.5	-4.4
6	21015.00	26.7 AV	54.0	-27.3	1.67 V	242	31.1	-4.4
7	#28020.00	40.8 PK	88.2	-47.4	1.56 V	7	42.1	-1.3
8	#28020.00	35.0 AV	68.2	-33.2	1.56 V	7	36.3	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 227 : 7085 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7085.00	112.2 PK			1.80 H	84	104.1	8.1
2	*7085.00	100.1 AV			1.80 H	84	92.0	8.1
3	#7125.00	78.5 PK	88.2	-9.7	1.80 H	84	70.3	8.2
4	#7125.00	66.7 AV	68.2	-1.5	1.80 H	84	58.5	8.2
5	#14170.00	42.8 PK	88.2	-45.4	1.44 H	57	26.0	16.8
6	#14170.00	37.8 AV	68.2	-30.4	1.44 H	57	21.0	16.8
7	21255.00	40.8 PK	74.0	-33.2	1.45 H	298	45.0	-4.2
8	21255.00	29.4 AV	54.0	-24.6	1.45 H	298	33.6	-4.2
9	#28340.00	39.4 PK	88.2	-48.8	1.48 H	315	40.7	-1.3
10	#28340.00	37.9 AV	68.2	-30.3	1.48 H	315	39.2	-1.3

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7085.00	114.7 PK			2.40 V	170	106.6	8.1
2	*7085.00	102.3 AV			2.40 V	170	94.2	8.1
3	#7140.00	79.5 PK	88.2	-8.7	2.40 V	170	71.1	8.4
4	#7140.00	67.7 AV	68.2	-0.5	2.40 V	170	59.3	8.4
5	#14170.00	40.8 PK	88.2	-47.4	2.49 V	19	24.0	16.8
6	#14170.00	35.6 AV	68.2	-32.6	2.49 V	19	18.8	16.8
7	21255.00	37.6 PK	74.0	-36.4	1.65 V	220	41.8	-4.2
8	21255.00	27.2 AV	54.0	-26.8	1.65 V	220	31.4	-4.2
9	#28340.00	40.7 PK	88.2	-47.5	1.48 V	31	42.0	-1.3
10	#28340.00	34.9 AV	68.2	-33.3	1.48 V	31	36.2	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 39 : 6145 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	50.9 PK	88.2	-37.3	1.32 H	121	47.2	3.7
2	#5925.00	38.9 AV	68.2	-29.3	1.32 H	121	35.2	3.7
3	*6145.00	107.1 PK			1.32 H	121	102.8	4.3
4	*6145.00	95.5 AV			1.32 H	121	91.2	4.3
5	12290.00	42.2 PK	74.0	-31.8	1.53 H	35	28.9	13.3
6	12290.00	37.3 AV	54.0	-16.7	1.53 H	35	24.0	13.3
7	18435.00	41.0 PK	74.0	-33.0	1.42 H	333	48.2	-7.2
8	18435.00	29.2 AV	54.0	-24.8	1.42 H	333	36.4	-7.2
9	#24580.00	39.4 PK	88.2	-48.8	1.46 H	302	41.3	-1.9
10	#24580.00	37.5 AV	68.2	-30.7	1.46 H	302	39.4	-1.9

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	50.5 PK	88.2	-37.7	2.29 V	242	46.8	3.7
2	#5925.00	38.9 AV	68.2	-29.3	2.29 V	242	35.2	3.7
3	*6145.00	109.7 PK			2.29 V	242	105.4	4.3
4	*6145.00	98.1 AV			2.29 V	242	93.8	4.3
5	12290.00	40.4 PK	74.0	-33.6	2.52 V	24	27.1	13.3
6	12290.00	34.9 AV	54.0	-19.1	2.52 V	24	21.6	13.3
7	18435.00	38.0 PK	74.0	-36.0	1.64 V	219	45.2	-7.2
8	18435.00	27.6 AV	54.0	-26.4	1.64 V	219	34.8	-7.2
9	#24580.00	41.0 PK	88.2	-47.2	1.54 V	0	42.9	-1.9
10	#24580.00	35.2 AV	68.2	-33.0	1.54 V	0	37.1	-1.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 55 : 6225 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6225.00	106.9 PK			1.36 H	134	102.3	4.6
2	*6225.00	95.1 AV			1.36 H	134	90.5	4.6
3	12450.00	41.8 PK	74.0	-32.2	1.48 H	22	29.1	12.7
4	12450.00	37.1 AV	54.0	-16.9	1.48 H	22	24.4	12.7
5	18675.00	40.6 PK	74.0	-33.4	1.32 H	322	47.5	-6.9
6	18675.00	29.1 AV	54.0	-24.9	1.32 H	322	36.0	-6.9
7	#24900.00	39.4 PK	88.2	-48.8	1.49 H	306	41.2	-1.8
8	#24900.00	37.7 AV	68.2	-30.5	1.49 H	306	39.5	-1.8

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6225.00	109.6 PK			2.27 V	227	105.0	4.6
2	*6225.00	97.9 AV			2.27 V	227	93.3	4.6
3	12450.00	41.2 PK	74.0	-32.8	2.55 V	22	28.5	12.7
4	12450.00	35.6 AV	54.0	-18.4	2.55 V	22	22.9	12.7
5	18675.00	37.3 PK	74.0	-36.7	1.63 V	243	44.2	-6.9
6	18675.00	26.8 AV	54.0	-27.2	1.63 V	243	33.7	-6.9
7	#24900.00	40.4 PK	88.2	-47.8	1.53 V	6	42.2	-1.8
8	#24900.00	35.0 AV	68.2	-33.2	1.53 V	6	36.8	-1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 87 : 6385 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6385.00	107.3 PK			1.35 H	133	102.1	5.2
2	*6385.00	95.7 AV			1.35 H	133	90.5	5.2
3	#12770.00	42.3 PK	88.2	-45.9	1.44 H	32	29.0	13.3
4	#12770.00	37.6 AV	68.2	-30.6	1.44 H	32	24.3	13.3
5	19155.00	40.5 PK	74.0	-33.5	1.44 H	330	47.2	-6.7
6	19155.00	29.1 AV	54.0	-24.9	1.44 H	330	35.8	-6.7
7	#25540.00	40.0 PK	88.2	-48.2	1.44 H	316	41.7	-1.7
8	#25540.00	38.2 AV	68.2	-30.0	1.44 H	316	39.9	-1.7

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6385.00	109.7 PK			2.33 V	244	104.5	5.2
2	*6385.00	98.3 AV			2.33 V	244	93.1	5.2
3	#12770.00	40.5 PK	88.2	-47.7	2.56 V	15	27.2	13.3
4	#12770.00	35.1 AV	68.2	-33.1	2.56 V	15	21.8	13.3
5	19155.00	37.8 PK	74.0	-36.2	1.65 V	229	44.5	-6.7
6	19155.00	27.5 AV	54.0	-26.5	1.65 V	229	34.2	-6.7
7	#25540.00	40.2 PK	88.2	-48.0	1.50 V	14	41.9	-1.7
8	#25540.00	34.7 AV	68.2	-33.5	1.50 V	14	36.4	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 103 : 6465 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6465.00	107.1 PK			1.39 H	121	101.5	5.6
2	*6465.00	95.6 AV			1.39 H	121	90.0	5.6
3	#12930.00	42.5 PK	88.2	-45.7	1.55 H	26	29.2	13.3
4	#12930.00	37.4 AV	68.2	-30.8	1.55 H	26	24.1	13.3
5	19395.00	41.1 PK	74.0	-32.9	1.41 H	309	47.9	-6.8
6	19395.00	29.6 AV	54.0	-24.4	1.41 H	309	36.4	-6.8
7	#25860.00	40.0 PK	88.2	-48.2	1.48 H	302	41.7	-1.7
8	#25860.00	38.0 AV	68.2	-30.2	1.48 H	302	39.7	-1.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6465.00	110.0 PK			2.35 V	244	104.4	5.6
2	*6465.00	98.5 AV			2.35 V	244	92.9	5.6
3	#12930.00	40.2 PK	88.2	-48.0	2.51 V	8	26.9	13.3
4	#12930.00	34.7 AV	68.2	-33.5	2.51 V	8	21.4	13.3
5	19395.00	37.9 PK	74.0	-36.1	1.65 V	226	44.7	-6.8
6	19395.00	27.5 AV	54.0	-26.5	1.65 V	226	34.3	-6.8
7	#25860.00	41.1 PK	88.2	-47.1	1.52 V	12	42.8	-1.7
8	#25860.00	35.5 AV	68.2	-32.7	1.52 V	12	37.2	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 119 : 6545 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6545.00	107.5 PK			1.36 H	118	101.5	6.0
2	*6545.00	95.7 AV			1.36 H	118	89.7	6.0
3	#13090.00	42.0 PK	88.2	-46.2	1.48 H	36	28.5	13.5
4	#13090.00	37.2 AV	68.2	-31.0	1.48 H	36	23.7	13.5
5	19635.00	40.6 PK	74.0	-33.4	1.37 H	326	46.7	-6.1
6	19635.00	29.1 AV	54.0	-24.9	1.37 H	326	35.2	-6.1
7	#26180.00	40.0 PK	88.2	-48.2	1.46 H	299	41.2	-1.2
8	#26180.00	38.5 AV	68.2	-29.7	1.46 H	299	39.7	-1.2

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6545.00	109.4 PK			2.32 V	242	103.4	6.0
2	*6545.00	97.8 AV			2.32 V	242	91.8	6.0
3	#13090.00	40.8 PK	88.2	-47.4	2.51 V	9	27.3	13.5
4	#13090.00	35.6 AV	68.2	-32.6	2.51 V	9	22.1	13.5
5	19635.00	37.9 PK	74.0	-36.1	1.67 V	228	44.0	-6.1
6	19635.00	27.4 AV	54.0	-26.6	1.67 V	228	33.5	-6.1
7	#26180.00	40.7 PK	88.2	-47.5	1.55 V	20	41.9	-1.2
8	#26180.00	35.0 AV	68.2	-33.2	1.55 V	20	36.2	-1.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 135 : 6625 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6625.00	107.1 PK			1.41 H	136	100.9	6.2
2	*6625.00	95.7 AV			1.41 H	136	89.5	6.2
3	13250.00	42.3 PK	74.0	-31.7	1.50 H	43	28.0	14.3
4	13250.00	37.3 AV	54.0	-16.7	1.50 H	43	23.0	14.3
5	19875.00	41.4 PK	74.0	-32.6	1.41 H	315	47.5	-6.1
6	19875.00	29.9 AV	54.0	-24.1	1.41 H	315	36.0	-6.1
7	#26500.00	39.8 PK	88.2	-48.4	1.45 H	300	40.6	-0.8
8	#26500.00	38.1 AV	68.2	-30.1	1.45 H	300	38.9	-0.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6625.00	109.2 PK			2.28 V	252	103.0	6.2
2	*6625.00	97.8 AV			2.28 V	252	91.6	6.2
3	13250.00	41.1 PK	74.0	-32.9	2.56 V	22	26.8	14.3
4	13250.00	35.5 AV	54.0	-18.5	2.56 V	22	21.2	14.3
5	19875.00	37.8 PK	74.0	-36.2	1.62 V	228	43.9	-6.1
6	19875.00	27.4 AV	54.0	-26.6	1.62 V	228	33.5	-6.1
7	#26500.00	40.2 PK	88.2	-48.0	1.46 V	5	41.0	-0.8
8	#26500.00	34.9 AV	68.2	-33.3	1.46 V	5	35.7	-0.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 151 : 6705 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6705.00	107.0 PK			1.40 H	123	100.9	6.1
2	*6705.00	95.5 AV			1.40 H	123	89.4	6.1
3	#13410.00	42.4 PK	88.2	-45.8	1.55 H	47	27.6	14.8
4	#13410.00	37.1 AV	68.2	-31.1	1.55 H	47	22.3	14.8
5	20115.00	41.6 PK	74.0	-32.4	1.35 H	334	47.1	-5.5
6	20115.00	29.7 AV	54.0	-24.3	1.35 H	334	35.2	-5.5
7	#26820.00	40.5 PK	88.2	-47.7	1.47 H	318	41.5	-1.0
8	#26820.00	38.4 AV	68.2	-29.8	1.47 H	318	39.4	-1.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6705.00	109.3 PK			2.27 V	228	103.2	6.1
2	*6705.00	97.8 AV			2.27 V	228	91.7	6.1
3	#13410.00	40.6 PK	88.2	-47.6	2.50 V	31	25.8	14.8
4	#13410.00	35.5 AV	68.2	-32.7	2.50 V	31	20.7	14.8
5	20115.00	37.8 PK	74.0	-36.2	1.74 V	214	43.3	-5.5
6	20115.00	26.9 AV	54.0	-27.1	1.74 V	214	32.4	-5.5
7	#26820.00	40.9 PK	88.2	-47.3	1.52 V	31	41.9	-1.0
8	#26820.00	35.1 AV	68.2	-33.1	1.52 V	31	36.1	-1.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 167 : 6785 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6785.00	107.8 PK			1.38 H	143	101.5	6.3
2	*6785.00	96.0 AV			1.38 H	143	89.7	6.3
3	#13570.00	42.5 PK	88.2	-45.7	1.52 H	38	27.6	14.9
4	#13570.00	37.7 AV	68.2	-30.5	1.52 H	38	22.8	14.9
5	20355.00	40.7 PK	74.0	-33.3	1.39 H	314	46.3	-5.6
6	20355.00	29.3 AV	54.0	-24.7	1.39 H	314	34.9	-5.6
7	#27140.00	40.1 PK	88.2	-48.1	1.42 H	311	41.4	-1.3
8	#27140.00	38.0 AV	68.2	-30.2	1.42 H	311	39.3	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6785.00	109.6 PK			2.34 V	244	103.3	6.3
2	*6785.00	98.1 AV			2.34 V	244	91.8	6.3
3	#13570.00	40.4 PK	88.2	-47.8	2.54 V	4	25.5	14.9
4	#13570.00	35.0 AV	68.2	-33.2	2.54 V	4	20.1	14.9
5	20355.00	38.3 PK	74.0	-35.7	1.71 V	213	43.9	-5.6
6	20355.00	27.4 AV	54.0	-26.6	1.71 V	213	33.0	-5.6
7	#27140.00	41.1 PK	88.2	-47.1	1.54 V	6	42.4	-1.3
8	#27140.00	35.6 AV	68.2	-32.6	1.54 V	6	36.9	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 183 : 6865 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6865.00	107.8 PK			1.29 H	133	100.9	6.9
2	*6865.00	96.0 AV			1.29 H	133	89.1	6.9
3	#13730.00	42.1 PK	88.2	-46.1	1.54 H	44	26.4	15.7
4	#13730.00	37.3 AV	68.2	-30.9	1.54 H	44	21.6	15.7
5	20595.00	41.2 PK	74.0	-32.8	1.35 H	309	45.9	-4.7
6	20595.00	29.4 AV	54.0	-24.6	1.35 H	309	34.1	-4.7
7	#27460.00	39.6 PK	88.2	-48.6	1.51 H	315	41.0	-1.4
8	#27460.00	37.7 AV	68.2	-30.5	1.51 H	315	39.1	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6865.00	110.1 PK			2.34 V	249	103.2	6.9
2	*6865.00	98.6 AV			2.34 V	249	91.7	6.9
3	#13730.00	40.6 PK	88.2	-47.6	2.57 V	21	24.9	15.7
4	#13730.00	35.4 AV	68.2	-32.8	2.57 V	21	19.7	15.7
5	20595.00	37.8 PK	74.0	-36.2	1.72 V	228	42.5	-4.7
6	20595.00	27.3 AV	54.0	-26.7	1.72 V	228	32.0	-4.7
7	#27460.00	40.2 PK	88.2	-48.0	1.52 V	27	41.6	-1.4
8	#27460.00	34.9 AV	68.2	-33.3	1.52 V	27	36.3	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 199 : 6945 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6945.00	107.3 PK			1.30 H	134	100.0	7.3
2	*6945.00	95.8 AV			1.30 H	134	88.5	7.3
3	#13890.00	42.4 PK	88.2	-45.8	1.47 H	40	26.6	15.8
4	#13890.00	37.2 AV	68.2	-31.0	1.47 H	40	21.4	15.8
5	20835.00	40.5 PK	74.0	-33.5	1.39 H	315	45.3	-4.8
6	20835.00	29.1 AV	54.0	-24.9	1.39 H	315	33.9	-4.8
7	#27780.00	39.5 PK	88.2	-48.7	1.52 H	306	41.4	-1.9
8	#27780.00	37.9 AV	68.2	-30.3	1.52 H	306	39.8	-1.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6945.00	109.6 PK			2.25 V	245	102.3	7.3
2	*6945.00	97.9 AV			2.25 V	245	90.6	7.3
3	#13890.00	40.7 PK	88.2	-47.5	2.50 V	33	24.9	15.8
4	#13890.00	35.4 AV	68.2	-32.8	2.50 V	33	19.6	15.8
5	20835.00	38.1 PK	74.0	-35.9	1.64 V	229	42.9	-4.8
6	20835.00	27.3 AV	54.0	-26.7	1.64 V	229	32.1	-4.8
7	#27780.00	40.5 PK	88.2	-47.7	1.57 V	29	42.4	-1.9
8	#27780.00	35.0 AV	68.2	-33.2	1.57 V	29	36.9	-1.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 215 : 7025 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7025.00	109.0 PK			1.48 H	121	101.0	8.0
2	*7025.00	97.2 AV			1.48 H	121	89.2	8.0
3	#7125.00	74.8 PK	88.2	-13.4	1.48 H	121	66.6	8.2
4	#7125.00	62.3 AV	68.2	-5.9	1.48 H	121	54.1	8.2
5	#14050.00	42.6 PK	88.2	-45.6	1.53 H	22	26.5	16.1
6	#14050.00	37.3 AV	68.2	-30.9	1.53 H	22	21.2	16.1
7	21075.00	40.9 PK	74.0	-33.1	1.43 H	328	45.2	-4.3
8	21075.00	29.1 AV	54.0	-24.9	1.43 H	328	33.4	-4.3
9	#28100.00	39.8 PK	88.2	-48.4	1.42 H	309	41.2	-1.4
10	#28100.00	37.7 AV	68.2	-30.5	1.42 H	309	39.1	-1.4

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7025.00	111.4 PK			1.95 V	210	103.4	8.0
2	*7025.00	99.5 AV			1.95 V	210	91.5	8.0
3	#7125.00	74.4 PK	88.2	-13.8	1.95 V	210	66.2	8.2
4	#7125.00	61.7 AV	68.2	-6.5	1.95 V	210	53.5	8.2
5	#14050.00	40.4 PK	88.2	-47.8	2.49 V	18	24.3	16.1
6	#14050.00	34.8 AV	68.2	-33.4	2.49 V	18	18.7	16.1
7	21075.00	37.7 PK	74.0	-36.3	1.74 V	233	42.0	-4.3
8	21075.00	26.8 AV	54.0	-27.2	1.74 V	233	31.1	-4.3
9	#28100.00	40.7 PK	88.2	-47.5	1.54 V	21	42.1	-1.4
10	#28100.00	35.3 AV	68.2	-32.9	1.54 V	21	36.7	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE160)	Channel	CH 47 : 6185 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	50.9 PK	88.2	-37.3	1.39 H	118	47.2	3.7
2	#5925.00	38.9 AV	68.2	-29.3	1.39 H	118	35.2	3.7
3	*6185.00	104.3 PK			1.39 H	118	99.8	4.5
4	*6185.00	92.5 AV			1.39 H	118	88.0	4.5
5	#7125.00	55.6 PK	88.2	-32.6	1.39 H	118	47.4	8.2
6	#7125.00	44.1 AV	68.2	-24.1	1.39 H	118	35.9	8.2
7	12370.00	42.3 PK	74.0	-31.7	1.53 H	30	29.3	13.0
8	12370.00	37.1 AV	54.0	-16.9	1.53 H	30	24.1	13.0
9	18555.00	41.3 PK	74.0	-32.7	1.36 H	323	48.5	-7.2
10	18555.00	29.7 AV	54.0	-24.3	1.36 H	323	36.9	-7.2
11	#24740.00	39.8 PK	88.2	-48.4	1.51 H	305	41.5	-1.7
12	#24740.00	37.9 AV	68.2	-30.3	1.51 H	305	39.6	-1.7

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	51.1 PK	88.2	-37.1	2.23 V	123	47.4	3.7
2	#5925.00	39.4 AV	68.2	-28.8	2.23 V	123	35.7	3.7
3	*6185.00	107.4 PK			2.23 V	123	102.9	4.5
4	*6185.00	96.1 AV			2.23 V	123	91.6	4.5
5	#7125.00	56.8 PK	88.2	-31.4	2.23 V	123	48.6	8.2
6	#7125.00	44.2 AV	68.2	-24.0	2.23 V	123	36.0	8.2
7	12370.00	40.7 PK	74.0	-33.3	2.51 V	27	27.7	13.0
8	12370.00	35.3 AV	54.0	-18.7	2.51 V	27	22.3	13.0
9	18555.00	37.9 PK	74.0	-36.1	1.62 V	228	45.1	-7.2
10	18555.00	27.2 AV	54.0	-26.8	1.62 V	228	34.4	-7.2
11	#24740.00	40.4 PK	88.2	-47.8	1.53 V	10	42.1	-1.7
12	#24740.00	34.8 AV	68.2	-33.4	1.53 V	10	36.5	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE160)	Channel	CH 79 : 6345 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6345.00	103.9 PK			1.44 H	110	98.7	5.2
2	*6345.00	92.1 AV			1.44 H	110	86.9	5.2
3	12690.00	42.0 PK	74.0	-32.0	1.49 H	38	29.3	12.7
4	12690.00	37.2 AV	54.0	-16.8	1.49 H	38	24.5	12.7
5	19035.00	41.1 PK	74.0	-32.9	1.33 H	321	48.0	-6.9
6	19035.00	29.2 AV	54.0	-24.8	1.33 H	321	36.1	-6.9
7	#25380.00	39.9 PK	88.2	-48.3	1.42 H	310	41.7	-1.8
8	#25380.00	38.2 AV	68.2	-30.0	1.42 H	310	40.0	-1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6345.00	107.2 PK			2.19 V	137	102.0	5.2
2	*6345.00	95.9 AV			2.19 V	137	90.7	5.2
3	12690.00	40.1 PK	74.0	-33.9	2.60 V	16	27.4	12.7
4	12690.00	34.7 AV	54.0	-19.3	2.60 V	16	22.0	12.7
5	19035.00	37.1 PK	74.0	-36.9	1.72 V	243	44.0	-6.9
6	19035.00	26.8 AV	54.0	-27.2	1.72 V	243	33.7	-6.9
7	#25380.00	40.7 PK	88.2	-47.5	1.52 V	9	42.5	-1.8
8	#25380.00	35.3 AV	68.2	-32.9	1.52 V	9	37.1	-1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE160)	Channel	CH 111 : 6505 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6505.00	103.9 PK			1.34 H	117	97.9	6.0
2	*6505.00	92.3 AV			1.34 H	117	86.3	6.0
3	#13010.00	42.1 PK	88.2	-46.1	1.52 H	30	28.8	13.3
4	#13010.00	37.0 AV	68.2	-31.2	1.52 H	30	23.7	13.3
5	19515.00	40.8 PK	74.0	-33.2	1.44 H	317	47.1	-6.3
6	19515.00	29.0 AV	54.0	-25.0	1.44 H	317	35.3	-6.3
7	#26020.00	39.7 PK	88.2	-48.5	1.49 H	322	41.1	-1.4
8	#26020.00	37.7 AV	68.2	-30.5	1.49 H	322	39.1	-1.4

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6505.00	107.5 PK			2.28 V	117	101.5	6.0
2	*6505.00	96.2 AV			2.28 V	117	90.2	6.0
3	#13010.00	41.1 PK	88.2	-47.1	2.58 V	11	27.8	13.3
4	#13010.00	35.7 AV	68.2	-32.5	2.58 V	11	22.4	13.3
5	19515.00	37.1 PK	74.0	-36.9	1.63 V	217	43.4	-6.3
6	19515.00	26.6 AV	54.0	-27.4	1.63 V	217	32.9	-6.3
7	#26020.00	40.6 PK	88.2	-47.6	1.57 V	1	42.0	-1.4
8	#26020.00	35.2 AV	68.2	-33.0	1.57 V	1	36.6	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE160)	Channel	CH 143 : 6665 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6665.00	104.5 PK			1.36 H	103	98.4	6.1
2	*6665.00	92.6 AV			1.36 H	103	86.5	6.1
3	13330.00	42.9 PK	74.0	-31.1	1.53 H	50	28.1	14.8
4	13330.00	37.6 AV	54.0	-16.4	1.53 H	50	22.8	14.8
5	19995.00	41.2 PK	74.0	-32.8	1.37 H	330	46.9	-5.7
6	19995.00	29.8 AV	54.0	-24.2	1.37 H	330	35.5	-5.7
7	#26660.00	40.2 PK	88.2	-48.0	1.46 H	299	40.8	-0.6
8	#26660.00	38.2 AV	68.2	-30.0	1.46 H	299	38.8	-0.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6665.00	107.9 PK			2.20 V	109	101.8	6.1
2	*6665.00	96.4 AV			2.20 V	109	90.3	6.1
3	13330.00	40.6 PK	74.0	-33.4	2.51 V	14	25.8	14.8
4	13330.00	35.3 AV	54.0	-18.7	2.51 V	14	20.5	14.8
5	19995.00	38.4 PK	74.0	-35.6	1.73 V	220	44.1	-5.7
6	19995.00	27.5 AV	54.0	-26.5	1.73 V	220	33.2	-5.7
7	#26660.00	41.1 PK	88.2	-47.1	1.55 V	2	41.7	-0.6
8	#26660.00	35.4 AV	68.2	-32.8	1.55 V	2	36.0	-0.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE160)	Channel	CH 175 : 6825 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6825.00	104.2 PK			1.36 H	106	97.7	6.5
2	*6825.00	92.4 AV			1.36 H	106	85.9	6.5
3	#13650.00	42.0 PK	88.2	-46.2	1.51 H	41	26.7	15.3
4	#13650.00	37.1 AV	68.2	-31.1	1.51 H	41	21.8	15.3
5	20475.00	41.3 PK	74.0	-32.7	1.33 H	316	46.4	-5.1
6	20475.00	29.5 AV	54.0	-24.5	1.33 H	316	34.6	-5.1
7	#27300.00	39.4 PK	88.2	-48.8	1.42 H	310	41.2	-1.8
8	#27300.00	37.5 AV	68.2	-30.7	1.42 H	310	39.3	-1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6825.00	107.5 PK			2.24 V	133	101.0	6.5
2	*6825.00	95.9 AV			2.24 V	133	89.4	6.5
3	#13650.00	40.3 PK	88.2	-47.9	2.58 V	27	25.0	15.3
4	#13650.00	35.0 AV	68.2	-33.2	2.58 V	27	19.7	15.3
5	20475.00	37.9 PK	74.0	-36.1	1.64 V	223	43.0	-5.1
6	20475.00	27.2 AV	54.0	-26.8	1.64 V	223	32.3	-5.1
7	#27300.00	40.6 PK	88.2	-47.6	1.52 V	0	42.4	-1.8
8	#27300.00	35.1 AV	68.2	-33.1	1.52 V	0	36.9	-1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.