

## FCC 47 CFR PART 15 SUBPART C

### RF Test Report

Applicant : Netgear Incorporated  
Applicant Address : 350 East Plumeria Drive, San Jose, California, United States  
95134  
Product Type : AirCard 815S Mobile Hotspot  
Trade Name : NETGEAR  
Model Number : AC815S  
Applicable Standard : FCC 47 CFR PART 15 SUBPART C  
ANSI C63.10:2013  
Receive Date : Sep. 21, 2015  
Test Period : Oct. 26 ~ Nov. 06, 2015  
Issue Date : Nov. 27, 2015

#### Issue by

A Test Lab Techno Corp.  
No. 140-1, Changan Street, Bade District,  
Taoyuan City 33465, Taiwan (R.O.C)  
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330

**Note:** This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.

**Revision History**

Rev.	Issue Date	Revisions	Revised By
00	Nov. 27, 2015	Initial Issue	

## Verification of Compliance

Issued Date: 11/27/2015

Applicant : Netgear Incorporated  
Address Applicant : 350 East Plumeria Drive, San Jose, California, United States  
95134  
Product Type : AirCard 815S Mobile Hotspot  
Trade Name : NETGEAR  
Model Number : AC815S  
FCC ID : PY3AC815S  
EUT Rated Voltage : DC 5V, 1A  
Test Voltage : 120 Vac / 60 Hz  
Applicable Standard : FCC 47 CFR PART 15 SUBPART C  
ANSI C63.10:2013  
Test Result : Complied  
Performing Lab. : A Test Lab Techno Corp.

No. 140-1, Changan Street, Bade District,  
Taoyuan City 33465, Taiwan (R.O.C)  
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330  
<http://www.atl-lab.com.tw/e-index.htm>

A Test Lab Techno Corp. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by A Test Lab Techno Corp. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Approved By



(Manager)

(Fly Lu)

Reviewed By



(Testing Engineer)

(Eric Ou Yang)

## TABLE OF CONTENTS

<b>1</b>	<b>General Information .....</b>	<b>6</b>
<b>2</b>	<b>EUT Description.....</b>	<b>7</b>
<b>3</b>	<b>Test Methodology.....</b>	<b>8</b>
	3.1. Mode of Operation.....	8
	3.2. EUT Exercise Software .....	12
	3.3. Configuration of Test System Details.....	13
	3.4. Test Site Environment.....	14
<b>4</b>	<b>Conducted Emission Measurement.....</b>	<b>15</b>
	4.1. Limit.....	15
	4.2. Test Instruments .....	15
	4.3. Test Setup .....	15
	4.4. Test Procedure .....	16
	4.5. Test Result.....	17
<b>5</b>	<b>Radiated Emission Measurement .....</b>	<b>19</b>
	5.1. Limit.....	19
	5.2. Test Instruments .....	19
	5.3. Setup.....	20
	5.4. Test Procedure .....	22
	5.5. Test Result.....	24
<b>6</b>	<b>Maximum Conducted Output Power Measurement.....</b>	<b>35</b>
	6.1. Limit.....	35
	6.2. Test Setup .....	35
	6.3. Test Instruments .....	35
	6.4. Test Procedure .....	35
	6.5. Test Result.....	36
<b>7</b>	<b>6dB RF Bandwidth Measurement.....</b>	<b>40</b>
	7.1. Limit.....	40
	7.2. Test Setup .....	40
	7.3. Test Instruments .....	40
	7.4. Test Procedure .....	40
	7.5. Test Result.....	41
	7.6. Test Graphs .....	42

<b>8</b>	<b>Maximum Power Density Measurement .....</b>	<b>49</b>
8.1.	Limit.....	49
8.2.	Test Setup .....	49
8.3.	Test Instruments .....	49
8.4.	Test Procedure .....	49
8.5.	Test Result.....	50
8.6.	Test Graphs .....	51
<b>9</b>	<b>Out of Band Conducted Emissions Measurement .....</b>	<b>58</b>
9.1.	Limit.....	58
9.2.	Test Setup .....	58
9.3.	Test Instruments .....	58
9.4.	Test Procedure .....	58
9.5.	Test Graphs .....	59
<b>10</b>	<b>Antenna Measurement .....</b>	<b>80</b>
10.1.	Limit.....	80
10.2.	Antenna Connector Construction .....	80

## 1 General Information

### 1.1 Summary of Test Result

Standard	Item	Result	Remark
15.247			
15.207	AC Power Conducted Emission	PASS	----
Standard	Item	Result	Remark
15.247			
15.247(d)	Transmitter Radiated Emissions	PASS	----
15.247(b)(3)	Max. Output Power	PASS	----
15.247(a)(2)	6dB RF Bandwidth	PASS	----
15.247(e)	Power Spectral Density	PASS	----
15.247(d)	Out of Band Conducted Spurious Emission	PASS	----
15.203	Antenna Requirement	PASS	----

The test results of this report relate only to the tested sample(s) identified in this report. Manufacturer or whom it may concern should recognize the pass or fail of the test result.

### 1.2 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty (dB)
Conducted Emission	9kHz ~ 150KHz	2.7
	150kHz ~ 30MHz	2.8
Radiated Emission	30MHz ~ 1000MHz	6.300
	1000MHz ~ 18000MHz	5.474
	18000MHz ~ 26500MHz	5.630
	26500MHz ~ 40000MHz	5.054

## 2 EUT Description

Applicant	Netgear Incorporated			
Applicant Address	350 East Plumeria Drive, San Jose, California, United States 95134			
Manufacturer	Netgear Inc.			
Manufacturer Address	Suite 168 – 10760 Shellbridge Way, Richmond, BC Canada V6X 3H1			
Product Type	AirCard 815S Mobile Hotspot			
Trade Name	NETGEAR			
Model Number	AC815S			
FCC ID	PY3AC815S			
Hardware Version	DV3.2			
Software Version	NTG9X40C_11.06.04.00			
Operate Freq. Band	Frequency Range (MHz)	Modulation	Channel Bandwidth	Data Rate 400 / 800 GI (ns)
IEEE 802.11b	2412 ~ 2462	DSSS	20MHz	Up to 11Mbps
IEEE 802.11g	2412 ~ 2462	DSSS+OFDM	20MHz	Up to 54Mbps
IEEE 802.11n 2.4GHz 20MHz	2412 ~ 2462	OFDM	20MHz	Up to 144.4Mbps
IEEE 802.11n 2.4GHz 40MHz	2422 ~ 2452	OFDM	40MHz	Up to 300Mbps
Antenna Delivery	IEEE 802.11b: 1TX+ 1RX IEEE 802.11g / IEEE 802.11n 2.4GHz 20MHz / IEEE 802.11n 2.4GHz 40MHz : 2TX + 2RX			
Antenna Type	Chip Antenna			
Antenna Gain	1.2 dBi			

Frequency Band	Max. RF Output Power (W)
IEEE 802.11b	0.014
IEEE 802.11g	0.060
IEEE 802.11n 2.4GHz 20MHz	0.071
IEEE 802.11n 2.4GHz 40MHz	0.076

### 3 Test Methodology

#### 3.1. Mode of Operation

Decision of Test ATL has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: Normal operation mode
Mode 2: IEEE 802.11b link mode
Mode 3: IEEE 802.11g link mode
Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode
Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz and power line conducted emissions below 30MHz, which worst case was in normal link mode only.

Test Mode	ANT-0	ANT-1	ANT-0+1
Mode 2: IEEE 802.11b link mode	V	V	
Mode 3: IEEE 802.11g link mode	V	V	V
Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode	V	V	V
Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode	V	V	V


Test Mode	Antenna Delivery	Test Channel	Data Rate 800GI (ns)
Mode 2: IEEE 802.11b link mode	1TX / 1RX	1, 6, 11	1
Mode 3: IEEE 802.11g link mode	2TX / 2RX	1, 6, 11	6
Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode	2TX / 2RX	1, 6, 11	13
Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode	2TX / 2RX	3, 6, 9	27

#### Duty cycle

Test Mode	Frequency (MHz)	on time (ms)	on+off time (ms)	Duty cycle	Duty Factor (dB)	1/T Minimum VBW (kHz)
Mode 2: IEEE 802.11b link mode	2412.0	12.490	12.530	0.997	0.014	0.010
Mode 3: IEEE 802.11g link mode	2412.0	2.125	2.200	0.966	0.151	0.471
Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode	2412.0	1.975	2.050	0.963	0.162	0.506
Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode	2422.0	1.000	1.075	0.930	0.314	1.000


**Duty Cycle Graphs**

Mode 2: IEEE 802.11b link mode




Mode 3: IEEE 802.11g Mode


On time




On+off time



Mode 4: IEEE 802.11n 2.4GHz 20MHz Mode






### 3.2. EUT Exercise Software


- |  |
|--|
| 1. Setup the EUT shown on 3.3.         |
| 2. Turn on the power of all equipment. |
| 3. Turn on Wi-Fi function.             |
| 4. EUT run test program.               |

### 3.3. Configuration of Test System Details

#### Conducted Emissions



#### Radiated Emissions



**3.4. Test Site Environment**

Items	Required (IEC 60068-1)	Actual
Temperature (°C)	15-35	26
Humidity (%RH)	25-75	60
Barometric pressure (mbar)	860-1060	950

## 4 Conducted Emission Measurement

### 4.1. Limit

Frequency (MHz)	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50


### 4.2. Test Instruments

Describe	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Test Receiver	R&S	ESCI	100367	06/25/2015	(1)
LISN	R&S	ENV216	101040	03/10/2015	(1)
LISN	R&S	ENV216	101041	03/06/2015	(1)
RF Cable	Woken	00100D1380194M	TE-02-02	06/26/2015	(1)
Test Site	ATL	TE02	TE02	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

### 4.3. Test Setup



#### 4.4. Test Procedure


The power line conducted emission measurements were performed in a shielded enclosure. The EUT was assembled on a wooden table which is 80 centimeters high, was placed 40 centimeters from the back wall and at least 1 meter from the sidewall.

Power was fed to the EUT from the public utility power grid through a line filter and EMCO Model 3162/2 SH Line Impedance Stabilization Networks (LISN). The LISN housing, measuring instrumentation case, ground plane, etc., were electrically bonded together at the same RF potential. The Spectrum analyzer was connected to the AC line through an isolation transformer. The 50-ohm output of the LISN was connected to the spectrum analyzer directly. Conducted emission levels were in the CISPR quasi-peak detection mode. The analyzer's 6 dB bandwidth was set to 9 KHz. No post-detector video filter was used.

The spectrum was scanned from 150 KHz to 30 MHz. The physical arrangement of the test system and associated cabling was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude and frequency. All spurious emission frequencies were observed. The highest emission amplitudes relative to the appropriate limit were measured and have been recorded in paragraph 4.1.

#### 4.5. Test Result

Standard:	FCC Part 15C	Line:	L1
Test item:	Conducted Emission	Power:	AC 120V/60Hz
Model Number:	AC815S	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 1	Date:	10/08/2015
		Test By:	Eric Ou Yang
Description:			




No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1500	37.18	22.35	9.69	46.87	32.04	66.00	56.00	-19.13	-23.96	Pass
2	0.1740	30.66	16.81	9.69	40.35	26.50	64.77	54.77	-24.42	-28.27	Pass
3	0.8140	26.52	23.67	9.71	36.23	33.38	56.00	46.00	-19.77	-12.62	Pass
4	1.2460	27.91	20.36	9.73	37.64	30.09	56.00	46.00	-18.36	-15.91	Pass
5	1.5300	26.40	18.66	9.75	36.15	28.41	56.00	46.00	-19.85	-17.59	Pass
6	3.7780	23.83	16.73	9.83	33.66	26.56	56.00	46.00	-22.34	-19.44	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

Standard:	FCC Part 15C	Line:	N
Test item:	Conducted Emission	Power:	AC 120V/60Hz
Model Number:	AC815S	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 1	Date:	10/08/2015
		Test By:	Eric Ou Yang
Description:			



No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1500	38.00	22.65	9.66	47.66	32.31	66.00	56.00	-18.34	-23.69	Pass
2	0.2780	32.84	22.10	9.66	42.50	31.76	60.88	50.88	-18.38	-19.12	Pass
3	0.8620	31.87	24.92	9.68	41.55	34.60	56.00	46.00	-14.45	-11.40	Pass
4	1.0740	30.54	23.26	9.69	40.23	32.95	56.00	46.00	-15.77	-13.05	Pass
5	1.2140	33.21	25.14	9.70	42.91	34.84	56.00	46.00	-13.09	-11.16	Pass
6	3.6460	21.37	10.44	9.80	31.17	20.24	56.00	46.00	-24.83	-25.76	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

## 5 Radiated Emission Measurement

### 5.1. Limit

According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu\text{V}/\text{m}$ at meter)	Measurement Distance (meters)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 - 88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

### 5.2. Test Instruments


3 Meter Chamber					
Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
RF Pre-selector	Agilent	N9039A	MY46520256	01/06/2015	(1)
Spectrum Analyzer	Agilent	E4446A	MY46180578	01/06/2015	(1)
Pre Amplifier	Agilent	8449B	3008A02237	02/24/2015	(1)
Pre Amplifier	Agilent	8447D	2944A10961	02/24/2015	(1)
Broadband Antenna (30MHz~1GHz)	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	9163-270	08/11/2015	(1)
Horn Antenna (1~18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	9120D-550	06/12/2015	(1)
Horn Antenna (18~40GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9170	9170-320	07/06/2015	(1)
Loop Antenna	COM-POWER CORPORATION	AL-130	121014	02/02/2015	(1)
Microwave Cable	EMCI	EMC-104-SM-S M-14000	140202	02/24/2015	(1)
Microwave Cable	EMCI	EMC104-SM-S M-600	140301	02/24/2015	(1)
Test Site	ATL	TE01	888001	08/27/2015	(1)

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.


Note: N.C.R. = No Calibration Request.

### 5.3. Setup


9kHz ~ 30MHz



Below 1GHz



Above 1GHz



## 5.4. Test Procedure

Final radiation measurements were made on a three-meter, Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 or 1.5 meters height (below 1GHz use 0.8m turntable / above 1GHz use 1.5m turntable), top surface 1.0 x 1.5 meter. The spectrum was examined from 250 MHz to 2.5 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 9 kHz to 26.5 GHz is investigated.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements when Duty cycle  $>0.98$  /  $1/T$  for average measurements when Duty cycle  $<0.98$ . A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

SCHWARZBECK MESS-ELEKTRONIK Biconilog Antenna (mode VULB9163) at 3 Meter and the SCHWARZBECK Double Ridged Guide Antenna (model BBHA9120D&9170) was used in frequencies 1 –26.5 GHz at a distance of 3 meter. The antenna at an angle toward the source of the emission. All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20dB/decade).

For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test.

The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels referenced to 1 microvolt (dBuV) into field intensity in micro volts pre meter ( $\mu\text{V}/\text{m}$ ).

The actual field intensity in decibels referenced to 1 microvolt in to field intensity in micro volts per meter ( $\text{dBuV}/\text{m}$ ).

The actual field intensity in referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

(1)  $\text{Amplitude (dBuV/m)} = \text{FI (dBuV)} + \text{AF (dBuV)} + \text{CL (dBuV)} - \text{Gain (dB)}$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.

(2)  $\text{Actual Amplitude (dBuV/m)} = \text{Amplitude (dBuV)} - \text{Dis(dB)}$

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

(a) For fundamental frequency : Transmitter Output < +30dBm

(b) For spurious frequency : Spurious emission limits = fundamental emission limit /10

Data of measurement within this frequency range without mark in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

## 5.5. Test Result

### Below 1GHz

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	AC815S	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 1	Date:	11/06/2015
		Test By:	Eric Ou Yang

Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
185.5000	33.53	-15.45	18.08	43.50	-25.42	QP	H
272.5000	34.05	-13.32	20.73	46.00	-25.27	QP	H
345.5000	26.23	-11.10	15.13	46.00	-30.87	QP	H
495.0000	27.14	-9.85	17.29	46.00	-28.71	QP	H
643.5000	26.29	-7.88	18.41	46.00	-27.59	QP	H
777.5000	26.92	-6.18	20.74	46.00	-25.26	QP	H
253.5000	24.93	-13.64	11.29	46.00	-34.71	QP	V
319.5000	26.56	-11.94	14.62	46.00	-31.38	QP	V
416.5000	26.34	-11.01	15.33	46.00	-30.67	QP	V
590.5000	25.46	-8.67	16.79	46.00	-29.21	QP	V
755.5000	26.15	-6.26	19.89	46.00	-26.11	QP	V
830.5000	25.24	-5.55	19.69	46.00	-26.31	QP	V

Note: No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz).

**Above 1GHz**

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	AC815S			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 2			Date:	10/26/2015		
Frequency:	2412MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3184.000	39.06	7.33	46.39	74.00	-27.61	peak	H
4472.000	37.42	10.10	47.52	74.00	-26.48	peak	H
6740.000	36.18	14.92	51.10	74.00	-22.90	peak	H
3114.000	39.47	7.27	46.74	74.00	-27.26	peak	V
4563.000	37.64	10.26	47.90	74.00	-26.10	peak	V
6747.000	35.87	14.93	50.80	74.00	-23.20	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	AC815S			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 2			Date:	10/26/2015		
Frequency:	2437MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3163.000	38.12	7.30	45.42	74.00	-28.58	peak	H
4640.000	36.33	10.39	46.72	74.00	-27.28	peak	H
6712.000	34.48	14.89	49.37	74.00	-24.63	peak	H
3142.000	38.45	7.28	45.73	74.00	-28.27	peak	V
4584.000	36.69	10.29	46.98	74.00	-27.02	peak	V
6621.000	35.51	14.79	50.30	74.00	-23.70	peak	V

Standard:	FCC Part 15C		Test Distance:	3m			
Test item:	Radiated Emission		Power:	AC 120V/60Hz			
Model Number:	AC815S		Temp.(°C)/Hum.(%RH):	26(°C)/60%RH			
Mode:	Mode 2		Date:	10/26/2015			
Frequency:	2462MHz		Test By:	Eric Ou Yang			
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3037.000	38.74	7.21	45.95	74.00	-28.05	peak	H
4577.000	36.74	10.28	47.02	74.00	-26.98	peak	H
6635.000	36.01	14.81	50.82	74.00	-23.18	peak	H
3205.000	38.58	7.34	45.92	74.00	-28.08	peak	V
4577.000	36.63	10.28	46.91	74.00	-27.09	peak	V
6705.000	35.27	14.88	50.15	74.00	-23.85	peak	V

Standard:	FCC Part 15C		Test Distance:	3m			
Test item:	Radiated Emission		Power:	AC 120V/60Hz			
Model Number:	AC815S		Temp.(°C)/Hum.(%RH):	26(°C)/60%RH			
Mode:	Mode 3		Date:	10/26/2015			
Frequency:	2412MHz		Test By:	Eric Ou Yang			
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3072.000	38.12	7.23	45.35	74.00	-28.65	peak	H
4647.000	36.34	10.41	46.75	74.00	-27.25	peak	H
6621.000	35.06	14.79	49.85	74.00	-24.15	peak	H
3051.000	38.50	7.22	45.72	74.00	-28.28	peak	V
4570.000	36.51	10.28	46.79	74.00	-27.21	peak	V
6726.000	35.89	14.90	50.79	74.00	-23.21	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	AC815S			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 3			Date:	10/26/2015		
Frequency:	2437MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3058.000	37.68	7.22	44.90	74.00	-29.10	peak	H
4542.000	35.95	10.23	46.18	74.00	-27.82	peak	H
6754.000	34.62	14.93	49.55	74.00	-24.45	peak	H
3093.000	38.34	7.24	45.58	74.00	-28.42	peak	V
4563.000	36.10	10.26	46.36	74.00	-27.64	peak	V
6698.000	34.73	14.88	49.61	74.00	-24.39	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	AC815S			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 3			Date:	10/26/2015		
Frequency:	2462MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3163.000	38.20	7.30	45.50	74.00	-28.50	peak	H
4619.000	37.35	10.36	47.71	74.00	-26.29	peak	H
6726.000	34.12	14.90	49.02	74.00	-24.98	peak	H
3177.000	37.85	7.31	45.16	74.00	-28.84	peak	V
4626.000	36.34	10.37	46.71	74.00	-27.29	peak	V
6607.000	36.21	14.78	50.99	74.00	-23.01	peak	V

Standard:	FCC Part 15C		Test Distance:	3m			
Test item:	Radiated Emission		Power:	AC 120V/60Hz			
Model Number:	AC815S		Temp.(°C)/Hum.(%RH):	26(°C)/60%RH			
Mode:	Mode 4		Date:	10/26/2015			
Frequency:	2412MHz		Test By:	Eric Ou Yang			
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3191.000	38.23	7.33	45.56	74.00	-28.44	peak	H
4612.000	35.98	10.34	46.32	74.00	-27.68	peak	H
6614.000	35.00	14.78	49.78	74.00	-24.22	peak	H
3177.000	37.77	7.31	45.08	74.00	-28.92	peak	V
4570.000	36.39	10.28	46.67	74.00	-27.33	peak	V
6614.000	35.49	14.78	50.27	74.00	-23.73	peak	V

Standard:	FCC Part 15C		Test Distance:	3m			
Test item:	Radiated Emission		Power:	AC 120V/60Hz			
Model Number:	AC815S		Temp.(°C)/Hum.(%RH):	26(°C)/60%RH			
Mode:	Mode 4		Date:	10/26/2015			
Frequency:	2437MHz		Test By:	Eric Ou Yang			
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3219.000	37.69	7.35	45.04	74.00	-28.96	peak	H
4584.000	35.99	10.29	46.28	74.00	-27.72	peak	H
6740.000	34.88	14.92	49.80	74.00	-24.20	peak	H
2939.000	39.22	7.00	46.22	74.00	-27.78	peak	V
4605.000	35.98	10.33	46.31	74.00	-27.69	peak	V
6621.000	35.22	14.79	50.01	74.00	-23.99	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	AC815S			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 4			Date:	10/26/2015		
Frequency:	2462MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3107.000	39.48	7.26	46.74	74.00	-27.26	peak	H
4563.000	37.23	10.26	47.49	74.00	-26.51	peak	H
6607.000	35.21	14.78	49.99	74.00	-24.01	peak	H
3107.000	37.80	7.26	45.06	74.00	-28.94	peak	V
4556.000	35.72	10.24	45.96	74.00	-28.04	peak	V
6628.000	34.56	14.80	49.36	74.00	-24.64	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	AC815S			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 5			Date:	10/26/2015		
Frequency:	2422MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3079.000	37.83	7.23	45.06	74.00	-28.94	peak	H
4507.000	36.34	10.16	46.50	74.00	-27.50	peak	H
6726.000	34.37	14.90	49.27	74.00	-24.73	peak	H
3121.000	37.80	7.27	45.07	74.00	-28.93	peak	V
4598.000	36.14	10.32	46.46	74.00	-27.54	peak	V
6565.000	34.85	14.73	49.58	74.00	-24.42	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	AC815S			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 5			Date:	10/26/2015		
Frequency:	2437MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3107.000	37.44	7.26	44.70	74.00	-29.30	peak	H
4521.000	36.57	10.19	46.76	74.00	-27.24	peak	H
6614.000	35.51	14.78	50.29	74.00	-23.71	peak	H
3142.000	37.53	7.28	44.81	74.00	-29.19	peak	V
4535.000	35.38	10.20	45.58	74.00	-28.42	peak	V
6628.000	34.87	14.80	49.67	74.00	-24.33	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	AC815S			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 5			Date:	10/26/2015		
Frequency:	2452MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3002.000	38.21	7.17	45.38	74.00	-28.62	peak	H
4563.000	36.62	10.26	46.88	74.00	-27.12	peak	H
6621.000	34.90	14.79	49.69	74.00	-24.31	peak	H
3135.000	37.83	7.28	45.11	74.00	-28.89	peak	V
4752.000	36.08	10.59	46.67	74.00	-27.33	peak	V
6824.000	35.47	15.01	50.48	74.00	-23.52	peak	V

**Band Edge**

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	AC815S			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 2			Date:	10/26/2015		
Frequency:	2412 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2388.980	42.56	5.45	48.01	74.00	-25.99	peak	H
2390.000	40.38	5.45	45.83	74.00	-28.17	peak	H
2342.230	41.50	5.33	46.83	74.00	-27.17	peak	V
2390.000	39.38	5.45	44.83	74.00	-29.17	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	AC815S			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 2			Date:	10/26/2015		
Frequency:	2462 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2483.500	40.56	5.70	46.26	74.00	-27.74	peak	H
2490.280	42.93	5.71	48.64	74.00	-25.36	peak	H
2483.500	40.85	5.70	46.55	74.00	-27.45	peak	V
2488.920	42.20	5.70	47.90	74.00	-26.10	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	AC815S			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 3			Date:	10/26/2015		
Frequency:	2412 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2389.420	44.56	5.45	50.01	74.00	-23.99	peak	H
2390.000	46.05	5.45	51.50	74.00	-22.50	peak	H
2388.980	41.84	5.45	47.29	74.00	-26.71	peak	V
2390.000	42.81	5.45	48.26	74.00	-25.74	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	AC815S			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 3			Date:	10/26/2015		
Frequency:	2462 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2483.500	42.82	5.70	48.52	74.00	-25.48	peak	H
2484.400	45.98	5.71	51.69	74.00	-22.31	peak	H
2483.500	43.77	5.70	49.47	74.00	-24.53	peak	V
2484.360	44.66	5.70	50.36	74.00	-23.64	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	AC815S			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 4			Date:	10/26/2015		
Frequency:	2412 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2387.770	46.53	5.45	51.98	74.00	-22.02	peak	H
2390.000	45.10	5.45	50.55	74.00	-23.45	peak	H
2388.980	45.99	5.45	51.44	74.00	-22.56	peak	V
2390.000	42.27	5.45	47.72	74.00	-26.28	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	AC815S			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 4			Date:	10/26/2015		
Frequency:	2462 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2483.500	41.40	5.70	47.10	74.00	-26.90	peak	H
2485.120	44.23	5.71	49.94	74.00	-24.06	peak	H
2483.500	42.48	5.70	48.18	74.00	-25.82	peak	V
2483.640	45.44	5.70	51.14	74.00	-22.86	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	AC815S			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 5			Date:	10/26/2015		
Frequency:	2422 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2389.320	51.22	5.45	56.67	74.00	-17.33	peak	H
2389.320	32.83	5.45	38.28	54.00	-15.72	AVG	H
2390.000	49.33	5.45	54.78	74.00	-19.22	peak	H
2390.000	32.85	5.45	38.30	54.00	-15.70	AVG	H
2389.320	49.00	5.45	54.45	74.00	-19.55	peak	V
2389.320	32.00	5.45	37.45	54.00	-16.55	AVG	V
2390.000	46.00	5.45	51.45	74.00	-22.55	peak	V
2389.320	49.00	5.45	54.45	74.00	-19.55	AVG	V


Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	AC815S			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 5			Date:	10/26/2015		
Frequency:	2452 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2483.500	41.20	5.70	46.90	74.00	-27.10	peak	H
2484.150	45.78	5.70	51.48	74.00	-22.52	AVG	H
2483.500	44.33	5.70	50.03	74.00	-23.97	peak	V
2484.100	52.90	5.70	58.60	74.00	-15.40	peak	V
2484.100	31.15	5.70	36.85	54.00	-17.15	AVG	V

## 6 Maximum Conducted Output Power Measurement

### 6.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for maximum output power is 30dBm.

### 6.2. Test Setup



### 6.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Power Sensor	Anritsu	MA2411B	1126022	08/24/2015	(1)
Power Meter	Anritsu	ML2495A	1135009	08/24/2015	(1)
Test Site	ATL	TE05	TE05	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

### 6.4. Test Procedure

The tests below are run with the EUT's transmitter set at high power in TX mode. The EUT is needed to force selection of output power level and channel number. While testing, EUT was set to transmit continuously. Remove the Subjective device's antenna and connect the RF output port to power sensor. The maximum output power shall not exceed 1 watt.

Use a direct connection between the antenna port of transmitter and the power sensor, for prevent the power sensor input attenuation 40-50 dB. Set the RBW Bandwidth of the emission or use a channel power meter mode.

For antennas with gains of 6 dBi or less, maximum allowed transmitter output is 1 watt (+30 dBm). For antennas with gains greater than 6 dBi, transmitter output level must be decreased by an amount equal to (GAIN - 6)/3 dBm.

The antenna port of the EUT was connected to the input of a power sensor. Power was read directly and cable loss correction was added to the reading to obtain power at the EUT antenna terminals.

**6.5. Test Result**

Model Number	AC815S										
Test Item	Maximum Conducted Output Power										
Test Mode	Mode 2: IEEE 802.11b link mode										
Date of Test	10/26/2015							Test Site		TE05	
Frequency (MHz)	Data Rate	Average Power				Peak Power				Limit (dBm)	
		ANT-0		ANT-1		ANT-0		ANT-1			
		(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	(dBm)	(W)		
2412	1M	8.58	0.007	8.54	0.007	11.38	0.014	11.35	0.014	< 30	
2437		8.72	0.007	8.66	0.007	11.61	0.014	11.49	0.014	< 30	
2462		8.33	0.007	8.49	0.007	11.13	0.013	11.30	0.013	< 30	
2437	2M	8.71	0.007	8.64	0.007	11.39	0.014	11.47	0.014	< 30	
2437	5.5M	8.69	0.007	8.63	0.007	11.38	0.014	11.46	0.014	< 30	
2437	11M	8.68	0.007	8.61	0.007	11.36	0.014	11.44	0.014	< 30	

Model Number	AC815S										
Test Item	Maximum Conducted Output Power										
Test Mode	Mode 3: IEEE 802.11g link mode										
Date of Test	10/26/2015							Test Site	TE05		
Frequency (MHz)	Data Rate	Average Power				Peak Power				Limit (dBm)	
		ANT-0		ANT-1		ANT-0		ANT-1			
		(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	(dBm)	(W)		
2412	6M	8.56	0.007	8.29	0.007	14.98	0.031	14.55	0.029	< 30	
2437		8.41	0.007	8.39	0.007	14.71	0.030	14.67	0.029	< 30	
2462		8.11	0.006	8.23	0.007	14.60	0.029	14.48	0.028	< 30	
2437	9M	8.40	0.007	8.37	0.007	14.72	0.030	14.65	0.029	< 30	
2437	12M	8.38	0.007	8.35	0.007	14.69	0.029	14.64	0.029	< 30	
2437	18M	8.36	0.007	8.34	0.007	14.68	0.029	14.63	0.029	< 30	
2437	24M	8.35	0.007	8.33	0.007	14.66	0.029	14.62	0.029	< 30	
2437	36M	8.32	0.007	8.31	0.007	14.65	0.029	14.60	0.029	< 30	
2437	48M	8.31	0.007	8.29	0.007	14.63	0.029	14.59	0.029	< 30	
2437	54M	8.29	0.007	8.28	0.007	14.62	0.029	14.57	0.029	< 30	
Frequency (MHz)	Data Rate	Average Power		Peak Power		Limit (dBm)					
		ANT-0+1		ANT-0+1							
		(dBm)	(W)	(dBm)	(W)						
2412	6M	11.44	0.014	17.78	0.060	< 30					
2437		11.41	0.014	17.70	0.059	< 30					
2462		11.18	0.013	17.55	0.057	< 30					
2437	9M	11.40	0.014	17.70	0.059	< 30					
2437	12M	11.38	0.014	17.68	0.059	< 30					
2437	18M	11.36	0.014	17.67	0.058	< 30					
2437	24M	11.35	0.014	17.65	0.058	< 30					
2437	36M	11.33	0.014	17.64	0.058	< 30					
2437	48M	11.31	0.014	17.62	0.058	< 30					
2437	54M	11.30	0.013	17.61	0.058	< 30					

Model Number	AC815S										
Test Item	Maximum Conducted Output Power										
Test Mode	Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode										
Date of Test	10/26/2015							Test Site	TE05		
Frequency (MHz)	Data Rate	Average Power				Peak Power				Limit (dBm)	
		ANT-0		ANT-1		ANT-0		ANT-1			
		(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	(dBm)	(W)		
2412	13M	8.08	0.006	8.01	0.006	15.26	0.034	15.14	0.033	< 30	
2437		8.43	0.007	8.36	0.007	15.53	0.036	15.44	0.035	< 30	
2462		8.03	0.006	8.16	0.007	15.20	0.033	15.26	0.034	< 30	
2437	26M	8.42	0.007	8.35	0.007	15.01	0.032	15.43	0.035	< 30	
2437	39M	8.41	0.007	8.34	0.007	15.00	0.032	15.41	0.035	< 30	
2437	52M	8.39	0.007	8.33	0.007	14.97	0.031	15.39	0.035	< 30	
2437	78M	8.38	0.007	8.31	0.007	14.96	0.031	15.38	0.035	< 30	
2437	104M	8.36	0.007	8.29	0.007	14.94	0.031	15.36	0.034	< 30	
2437	117M	8.34	0.007	8.28	0.007	14.93	0.031	15.34	0.034	< 30	
2437	130M	8.33	0.007	8.26	0.007	14.91	0.031	15.32	0.034	< 30	
Frequency (MHz)	Data Rate	Average Power		Peak Power		Limit (dBm)					
		ANT-0+1		ANT-0+1							
		(dBm)	(W)	(dBm)	(W)						
2412	13M	11.06	0.013	18.21	0.066	< 30					
2437		11.41	0.014	18.50	0.071	< 30					
2462		11.11	0.013	18.24	0.067	< 30					
2437	26M	11.40	0.014	18.23	0.067	< 30					
2437	39M	11.39	0.014	18.22	0.066	< 30					
2437	52M	11.37	0.014	18.20	0.066	< 30					
2437	78M	11.36	0.014	18.19	0.066	< 30					
2437	104M	11.34	0.014	18.17	0.066	< 30					
2437	117M	11.32	0.014	18.15	0.065	< 30					
2437	130M	11.31	0.014	18.13	0.065	< 30					


Model Number	AC815S										
Test Item	Maximum Conducted Output Power										
Test Mode	Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode										
Date of Test	10/26/2015							Test Site	TE05		
Frequency (MHz)	Data Rate	Average Power				Peak Power				Limit (dBm)	
		ANT-0		ANT-1		ANT-0		ANT-1			
		(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	(dBm)	(W)		
2422	27M	8.27	0.007	8.14	0.007	15.26	0.034	15.41	0.035	< 30	
2437		8.48	0.007	8.33	0.007	15.53	0.036	15.72	0.037	< 30	
2452		8.34	0.007	8.00	0.006	15.20	0.033	15.18	0.033	< 30	
2437	54M	8.43	0.007	8.30	0.007	15.01	0.032	15.68	0.037	< 30	
2437	81M	8.40	0.007	8.26	0.007	15.00	0.032	15.65	0.037	< 30	
2437	108M	8.34	0.007	8.21	0.007	14.97	0.031	15.60	0.036	< 30	
2437	162M	8.29	0.007	8.17	0.007	14.96	0.031	15.54	0.036	< 30	
2437	216M	8.25	0.007	8.11	0.006	14.94	0.031	15.48	0.035	< 30	
2437	243M	8.19	0.007	8.07	0.006	14.93	0.031	15.43	0.035	< 30	
2437	270M	8.14	0.007	8.03	0.006	14.91	0.031	15.39	0.035	< 30	
Frequency (MHz)	Data Rate	Average Power		Peak Power		Limit (dBm)					
		ANT-0+1		ANT-0+1							
		(dBm)	(W)	(dBm)	(W)						
2412	13M	11.22	0.013	18.47	0.070	< 30					
2437		11.42	0.014	18.79	0.076	< 30					
2462		11.18	0.013	18.46	0.070	< 30					
2437	26M	11.38	0.014	18.74	0.075	< 30					
2437	39M	11.34	0.014	18.71	0.074	< 30					
2437	52M	11.29	0.013	18.63	0.073	< 30					
2437	78M	11.24	0.013	18.58	0.072	< 30					
2437	104M	11.19	0.013	18.52	0.071	< 30					
2437	117M	11.14	0.013	18.46	0.070	< 30					
2437	130M	11.10	0.013	18.42	0.069	< 30					

## 7 6dB RF Bandwidth Measurement

### 7.1. Limit

6dB RF Bandwidth: Systems using digital modulation techniques may operate in the 2400–2483.5 MHz bands. The minimum 6 dB band-width shall be at least 500 kHz.

### 7.2. Test Setup



### 7.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/16/2014	(1)
Test Site	ATL	TE05	TE05	N.C.R.	----

dRemark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

### 7.4. Test Procedure

The EUT tested to DTS test procedure of KDB558074D01 for compliance to FCC 47CFR 15.247 requirements.

6dB RF Bandwidth: The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES RBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A peak output reading was taken, a DISPLAY line was drawn 6 dB lower than peak level. The 6 dB bandwidth was determined from where the channel output spectrum intersected the display line.

The test was performed at 3 channels (Channel low, middle, high)

99 % Occupied Bandwidth: The transmitter shall be operated at its maximum carrier power measured under normal test conditions.

The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual.

The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded.

**7.5. Test Result**

Model Number	AC815S			
Test Item	6dB RF Bandwidth			
Test Mode	Mode 2: IEEE 802.11b link mode Mode 3: IEEE 802.11g link mode Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode			
Date of Test	10/29/2015	Test Site	TE05	
Test Mode	Frequency (MHz)	Measurement (MHz)		Limit (MHz)
		ANT-0	ANT-1	
Mode 2	2412	8.081	---	> 0.500
	2437	7.646	---	> 0.500
	2462	7.161	---	> 0.500
Mode 3	2412	15.858	15.695	> 0.500
	2437	16.324	16.382	> 0.500
	2462	15.83	15.962	> 0.500
Mode 4	2412	16.525	15.045	> 0.500
	2437	16.902	17.578	> 0.500
	2462	16.361	16.074	> 0.500
Mode 5	2422	32.657	33.969	> 0.500
	2437	36.011	36.076	> 0.500
	2452	31.435	28.939	> 0.500




**7.6. Test Graphs**

Mode 2: IEEE 802.11b link mode_ANT-0	
2412	<p>Agilent R T</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/Offset 10.8 dB</p> <p>Center 2.412 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p><b>Occupied Bandwidth</b> 12.6057 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -90.163 kHz</p> <p>x dB Bandwidth 8.081 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.4120000 GHz</p> <p>Start Freq 2.3970000 GHz</p> <p>Stop Freq 2.4270000 GHz</p> <p>CF Step 3.0000000 MHz Auto Man</p> <p>Freq Offset 0.0000000 Hz</p> <p>Signal Track On Off</p>
2437	<p>Agilent R T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/Offset 10.8 dB</p> <p>Center 2.437 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p><b>Occupied Bandwidth</b> 13.1962 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 94.509 kHz</p> <p>x dB Bandwidth 7.646 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.4370000 GHz</p> <p>Start Freq 2.4220000 GHz</p> <p>Stop Freq 2.4520000 GHz</p> <p>CF Step 3.0000000 MHz Auto Man</p> <p>Freq Offset 0.0000000 Hz</p> <p>Signal Track On Off</p>
2462	<p>Agilent R T</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/Offset 10.8 dB</p> <p>Center 2.462 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p><b>Occupied Bandwidth</b> 12.7506 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -84.157 kHz</p> <p>x dB Bandwidth 7.161 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.4620000 GHz</p> <p>Start Freq 2.4470000 GHz</p> <p>Stop Freq 2.4770000 GHz</p> <p>CF Step 3.0000000 MHz Auto Man</p> <p>Freq Offset 0.0000000 Hz</p> <p>Signal Track On Off</p>

Mode 3: IEEE 802.11g link mode\_ANT-0

<p>2412</p>	<p>Agilent R T</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/Offset 10.8 dB</p> <p>Center 2.412 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p><b>Occupied Bandwidth 16.2671 MHz</b></p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -14.190 kHz x dB Bandwidth 15.858 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.42700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2437</p>	<p>Agilent R T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/Offset 10.8 dB</p> <p>Center 2.437 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p><b>Occupied Bandwidth 16.3634 MHz</b></p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 28.952 kHz x dB Bandwidth 16.324 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42200000 GHz</p> <p>Stop Freq 2.45200000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2462</p>	<p>Agilent R T</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/Offset 10.8 dB</p> <p>Center 2.462 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p><b>Occupied Bandwidth 16.2569 MHz</b></p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -11.522 kHz x dB Bandwidth 15.830 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44700000 GHz</p> <p>Stop Freq 2.47700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>

Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode\_ANT-0

<p>2412</p>	
<p>2437</p>	
<p>2462</p>	

Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode\_ANT-0

2422	<p>Agilent R T</p> <p>Ch Freq 2.422 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/ Offst 10.8 dB</p> <p>Center 2.422 GHz Span 50 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 5.18 ms (401 pts)</p> <p><b>Occupied Bandwidth 35.8464 MHz</b></p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -75.268 kHz x dB Bandwidth 32.657 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.42200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.44700000 GHz</p> <p>CF Step 5.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
2437	<p>Agilent R T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/ Offst 10.8 dB</p> <p>Center 2.437 GHz Span 50 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 5.18 ms (401 pts)</p> <p><b>Occupied Bandwidth 36.1237 MHz</b></p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 41.710 kHz x dB Bandwidth 36.011 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.41200000 GHz</p> <p>Stop Freq 2.46200000 GHz</p> <p>CF Step 5.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
2452	<p>Agilent R T</p> <p>Ch Freq 2.452 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/ Offst 10.8 dB</p> <p>Center 2.452 GHz Span 50 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 5.18 ms (401 pts)</p> <p><b>Occupied Bandwidth 35.7563 MHz</b></p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 72.007 kHz x dB Bandwidth 31.435 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.45200000 GHz</p> <p>Start Freq 2.42700000 GHz</p> <p>Stop Freq 2.47700000 GHz</p> <p>CF Step 5.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>

Mode 3: IEEE 802.11g link mode\_ANT-1

<p>2412</p>	
<p>2437</p>	
<p>2462</p>	

Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode\_ANT-1

<p>2412</p>	<p>Agilent R T</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/Offset 10.8 dB</p> <p>Center 2.412 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p><b>Occupied Bandwidth</b> 17.4242 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -10.186 kHz x dB Bandwidth 16.525 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.42700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2437</p>	<p>Agilent R T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/Offset 10.8 dB</p> <p>Center 2.437 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p><b>Occupied Bandwidth</b> 17.5622 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 21.673 kHz x dB Bandwidth 17.578 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42200000 GHz</p> <p>Stop Freq 2.45200000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2462</p>	<p>Agilent R T</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/Offset 10.8 dB</p> <p>Center 2.462 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p><b>Occupied Bandwidth</b> 17.4501 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -12.619 kHz x dB Bandwidth 16.074 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44700000 GHz</p> <p>Stop Freq 2.47700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>

Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode\_ANT-1


<p>2422</p>	<p>Agilent R T</p> <p>Ch Freq 2.422 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/Offset 10.8 dB</p> <p>Center 2.422 GHz Span 50 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 5.18 ms (401 pts)</p> <p><b>Occupied Bandwidth</b> 35.8125 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -52.036 kHz x dB Bandwidth 33.969 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.42200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.44700000 GHz</p> <p>CF Step 5.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2437</p>	<p>Agilent R T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/Offset 10.8 dB</p> <p>Center 2.437 GHz Span 50 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 5.18 ms (401 pts)</p> <p><b>Occupied Bandwidth</b> 36.1514 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 26.741 kHz x dB Bandwidth 36.076 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.41200000 GHz</p> <p>Stop Freq 2.46200000 GHz</p> <p>CF Step 5.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2452</p>	<p>Agilent R T</p> <p>Ch Freq 2.452 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/Offset 10.8 dB</p> <p>Center 2.452 GHz Span 50 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 5.18 ms (401 pts)</p> <p><b>Occupied Bandwidth</b> 35.7315 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 92.799 kHz x dB Bandwidth 28.939 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.45200000 GHz</p> <p>Start Freq 2.42700000 GHz</p> <p>Stop Freq 2.47700000 GHz</p> <p>CF Step 5.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>

## 8 Maximum Power Density Measurement

### 8.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 8.2. Test Setup



### 8.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/16/2014	(1)
Test Site	ATL	TE05	TE05	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

### 8.4. Test Procedure

The EUT tested to DTS test procedure of KDB558074D01 for compliance to FCC 47CFR 15.247 requirements.

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
4. Set the VBW  $\geq 3 \times \text{RBW}$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

**8.5. Test Result**

Model Number	AC815S				
Test Item	Maximum Power Density				
Test Mode	Mode 2: IEEE 802.11b link mode Mode 3: IEEE 802.11g link mode Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode				
Date of Test	10/26/2015			Test Site	TE05
Test Mode	Frequency (MHz)	Measurement (dBm/3KHz)			Limit (dBm/3KHz)
		ANT-0	ANT-1	ANT-0+1	
Mode 2	2412	-4.183	---	---	< 8
	2437	-2.140	---	---	< 8
	2462	-1.489	---	---	< 8
Mode 3	2412	-17.440	-18.490	-14.92	< 8
	2437	-17.660	-16.700	-14.14	< 8
	2462	-17.600	-19.170	-15.30	< 8
Mode 4	2412	-18.580	-16.940	-14.67	< 8
	2437	-17.950	-17.560	-14.74	< 8
	2462	-19.440	-17.800	-15.53	< 8
Mode 5	2422	-19.250	-19.540	-16.38	< 8
	2437	-19.770	-18.120	-15.86	< 8
	2452	-19.180	-18.800	-15.98	< 8




**8.6. Test Graphs**

Mode 2: IEEE 802.11b link mode_ANT-0	
2412	<p>Agilent R T          Ref 10 dBm Atten 10 dB Mkr1 2.4080025 GHz 4.183 dBm          Peak Log 10 dB/Offst 10.8 dB          M1 S2 S3 FC AA          Center 2.412 GHz Span 13 MHz          #Res BW 3 kHz #VBW 10 kHz Sweep 1.487 s (401 pts)</p> <p>Freq/Channel          Center Freq 2.41200000 GHz          Start Freq 2.40550000 GHz          Stop Freq 2.41850000 GHz          CF Step 1.30000000 MHz Auto Man          Freq Offset 0.00000000 Hz          Signal Track On Off</p>
2437	<p>Agilent R T          Ref 10 dBm Atten 10 dB Mkr1 2.4340100 GHz 2.14 dBm          Peak Log 10 dB/Offst 10.8 dB          M1 S2 S3 FC AA          Center 2.437 GHz Span 13 MHz          #Res BW 3 kHz #VBW 10 kHz Sweep 1.487 s (401 pts)</p> <p>Freq/Channel          Center Freq 2.43700000 GHz          Start Freq 2.43050000 GHz          Stop Freq 2.44350000 GHz          CF Step 1.30000000 MHz Auto Man          Freq Offset 0.00000000 Hz          Signal Track On Off</p>
2462	<p>Agilent R T          Ref 10 dBm Atten 10 dB Mkr1 2.4640150 GHz -1.489 dBm          Peak Log 10 dB/Offst 10.8 dB          M1 S2 S3 FC AA          Center 2.462 GHz Span 13 MHz          #Res BW 3 kHz #VBW 10 kHz Sweep 1.487 s (401 pts)</p> <p>Freq/Channel          Center Freq 2.46200000 GHz          Start Freq 2.45550000 GHz          Stop Freq 2.46850000 GHz          CF Step 1.30000000 MHz Auto Man          Freq Offset 0.00000000 Hz          Signal Track On Off</p>

Mode 3: IEEE 802.11g link mode\_ANT-0

<p>2412</p>	
<p>2437</p>	
<p>2462</p>	



Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode\_ANT-0

<p>2412</p>	
<p>2437</p>	
<p>2462</p>	

Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode\_ANT-0

<p>2422</p>	<p>Agilent R T</p> <p>Ref 10 dBm Atten 10 dB Mkr1 2.40976 GHz -19.25 dBm</p> <p>Peak Log 10 dB/Offst 10.8 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.422 GHz Span 55 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 6.29 s (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.42200000 GHz</p> <p>Start Freq 2.39450000 GHz</p> <p>Stop Freq 2.44950000 GHz</p> <p>CF Step 5.50000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2437</p>	<p>Agilent R T</p> <p>Ref 10 dBm Atten 10 dB Mkr1 2.40976 GHz -19.25 dBm</p> <p>Peak Log 10 dB/Offst 10.8 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.422 GHz Span 55 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 6.29 s (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.42200000 GHz</p> <p>Start Freq 2.39450000 GHz</p> <p>Stop Freq 2.44950000 GHz</p> <p>CF Step 5.50000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2452</p>	<p>Agilent R T</p> <p>Ref 10 dBm Atten 10 dB Mkr1 2.45984 GHz -19.18 dBm</p> <p>Peak Log 10 dB/Offst 10.8 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.452 GHz Span 55 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 6.29 s (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.45200000 GHz</p> <p>Start Freq 2.42450000 GHz</p> <p>Stop Freq 2.47950000 GHz</p> <p>CF Step 5.50000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>

Mode 3: IEEE 802.11g link mode\_ANT-1

<p>2412</p>	
<p>2437</p>	
<p>2462</p>	

Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode\_ANT-1

<p>2412</p>	
<p>2437</p>	
<p>2462</p>	

Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode\_ANT-1


<p>2422</p>	
<p>2437</p>	
<p>2452</p>	

## 9 Out of Band Conducted Emissions Measurement

### 9.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

### 9.2. Test Setup



### 9.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/16/2014	(1)
Spectrum Analyzer	Agilent	E4408B	MY45107753	07/27/2015	(1)
Test Site	ATL	TE05	TE05	N.C.R.	----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

### 9.4. Test Procedure

In any 100 kHz bandwidth outside the EUT pass band, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the pass band.




The test was performed at 3 channels.

### 9.5. Test Graphs

#### Reference level

Mode 2: IEEE 802.11b link mode_ANT-0	
2412	
2437	
2462	

Mode 3: IEEE 802.11g link mode\_ANT-0

<p>2412</p>	
<p>2437</p>	
<p>2462</p>	




Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode\_ANT-0

<p>2412</p>	<p>Agilent R T</p> <p>Ref 10 dBm Atten 10 dB Mkr1 2.4095025 GHz -3.294 dBm</p> <p>Peak Log 10 dB/Offst 10.8 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.412 GHz Span 27 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39850000 GHz</p> <p>Stop Freq 2.42550000 GHz</p> <p>CF Step 2.70000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2437</p>	<p>Agilent R T</p> <p>Ref 10 dBm Atten 10 dB Mkr1 2.4444925 GHz -3.376 dBm</p> <p>Peak Log 10 dB/Offst 10.8 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.437 GHz Span 27 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42350000 GHz</p> <p>Stop Freq 2.45050000 GHz</p> <p>CF Step 2.70000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2462</p>	<p>Agilent R T</p> <p>Ref 10 dBm Atten 10 dB Mkr1 2.4657800 GHz -4.121 dBm</p> <p>Peak Log 10 dB/Offst 10.8 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.462 GHz Span 27 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44850000 GHz</p> <p>Stop Freq 2.47550000 GHz</p> <p>CF Step 2.70000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>

Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode\_ANT-0

<p>2422</p>	<p>Agilent</p> <p>Ref 10 dBm Atten 10 dB Mkr1 2.4170000 GHz -2.329 dBm</p> <p>Peak Log 10 dB/Offset 10.8 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.412 GHz #Res BW 100 kHz #VBW 300 kHz Span 25 MHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39950000 GHz</p> <p>Stop Freq 2.42450000 GHz</p> <p>CF Step 2.50000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2437</p>	<p>Agilent</p> <p>Ref 10 dBm Atten 10 dB Mkr1 2.4420000 GHz -1.06 dBm</p> <p>Peak Log 10 dB/Offset 10.8 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.437 GHz #Res BW 100 kHz #VBW 300 kHz Span 25 MHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42450000 GHz</p> <p>Stop Freq 2.44950000 GHz</p> <p>CF Step 2.50000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2452</p>	<p>Agilent</p> <p>Ref 10 dBm Atten 10 dB Mkr1 2.4595000 GHz -3.319 dBm</p> <p>Peak Log 10 dB/Offset 10.8 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.462 GHz #Res BW 100 kHz #VBW 300 kHz Span 25 MHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44950000 GHz</p> <p>Stop Freq 2.47450000 GHz</p> <p>CF Step 2.50000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>

Mode 3: IEEE 802.11g link mode\_ANT-1

<p>2412</p>	
<p>2437</p>	
<p>2462</p>	

Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode\_ANT-1

<p>2412</p>	<p>Agilent R T</p> <p>Ref 10 dBm Atten 10 dB Mkr1 2.4169950 GHz -2.523 dBm</p> <p>Peak Log 10 dB/Offst 10.8 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.412 GHz Span 27 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39850000 GHz</p> <p>Stop Freq 2.42550000 GHz</p> <p>CF Step 2.70000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2437</p>	<p>Agilent R T</p> <p>Ref 10 dBm Atten 10 dB Mkr1 2.4407800 GHz -2.489 dBm</p> <p>Peak Log 10 dB/Offst 10.8 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.437 GHz Span 27 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42350000 GHz</p> <p>Stop Freq 2.45050000 GHz</p> <p>CF Step 2.70000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2462</p>	<p>Agilent R T</p> <p>Ref 10 dBm Atten 10 dB Mkr1 2.4595025 GHz -3.567 dBm</p> <p>Peak Log 10 dB/Offst 10.8 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.462 GHz Span 27 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44850000 GHz</p> <p>Stop Freq 2.47550000 GHz</p> <p>CF Step 2.70000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>

Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode\_ANT-1

<p>2412</p>	<p>Agilent R T</p> <p>Ref 10 dBm Atten 10 dB Mkr1 2.41073 GHz -3.89 dBm</p> <p>Peak Log 10 dB/Offst 10.8 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.422 GHz Span 55 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 5.698 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.4220000 GHz</p> <p>Start Freq 2.39450000 GHz</p> <p>Stop Freq 2.44950000 GHz</p> <p>CF Step 5.50000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2437</p>	<p>Agilent R T</p> <p>Ref 10 dBm Atten 10 dB Mkr1 2.45364 GHz -18.12 dBm</p> <p>Peak Log 10 dB/Offst 10.8 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.437 GHz Span 55 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 6.29 s (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.40950000 GHz</p> <p>Stop Freq 2.46450000 GHz</p> <p>CF Step 5.50000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2462</p>	<p>Agilent R T</p> <p>Ref 10 dBm Atten 10 dB Mkr1 2.46080 GHz 4.747 dBm</p> <p>Peak Log 10 dB/Offst 10.8 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.452 GHz Span 55 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 5.698 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.45200000 GHz</p> <p>Start Freq 2.42450000 GHz</p> <p>Stop Freq 2.47950000 GHz</p> <p>CF Step 5.50000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>


**Out of Band Conducted Emissions**

Mode 2: IEEE 802.11b link mode\_ANT-0


<p>2412</p>	<p>Agilent R T</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.41 GHz 0.933 dBm</p> <p>Peak Log 10 dB/Offst 10.8 dB DI -17.8 dBm</p> <p>Start 30 MHz #Res BW 100 kHz #VBW 300 kHz Stop 26.5 GHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.41 GHz</td> <td>0.933 dBm</td> </tr> </tbody> </table> <p>Freq/Channel: Center Freq 13.2650000 GHz, Start Freq 30.0000000 MHz, Stop Freq 26.5000000 GHz, CF Step 2.64700000 GHz, Freq Offset 0.0000000 Hz, Signal Track On</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.41 GHz	0.933 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.41 GHz	0.933 dBm							
<p>2437</p>	<p>Agilent R T</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.44 GHz 1.006 dBm</p> <p>Peak Log 10 dB/Offst 10.8 dB DI -19.5 dBm</p> <p>Start 30 MHz #Res BW 100 kHz #VBW 300 kHz Stop 26.5 GHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.44 GHz</td> <td>1.006 dBm</td> </tr> </tbody> </table> <p>Freq/Channel: Center Freq 13.2650000 GHz, Start Freq 30.0000000 MHz, Stop Freq 26.5000000 GHz, CF Step 2.64700000 GHz, Freq Offset 0.0000000 Hz, Signal Track On</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.44 GHz	1.006 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.44 GHz	1.006 dBm							
<p>2462</p>	<p>Agilent R T</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.46 GHz -2.482 dBm</p> <p>Peak Log 10 dB/Offst 10.8 dB DI -20.3 dBm</p> <p>Start 30 MHz #Res BW 100 kHz #VBW 300 kHz Stop 26.5 GHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.46 GHz</td> <td>-2.482 dBm</td> </tr> </tbody> </table> <p>Freq/Channel: Center Freq 13.2650000 GHz, Start Freq 30.0000000 MHz, Stop Freq 26.5000000 GHz, CF Step 2.64700000 GHz, Freq Offset 0.0000000 Hz, Signal Track On</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.46 GHz	-2.482 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.46 GHz	-2.482 dBm							

Mode 3: IEEE 802.11g link mode\_ANT-0


2412



2437



2462



Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode\_ANT-0


2412	<p>Agilent R T</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.41 GHz 5.161 dBm</p> <p>Peak Log 10 dB/ Offst 10.8 dB DI -23.3 dBm</p> <p>Start 30 MHz #Res BW 100 kHz #VBW 300 kHz Stop 26.5 GHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.41 GHz</td> <td>-5.161 dBm</td> </tr> </tbody> </table> <p>Freq/Channel</p> <p>Center Freq 13.2650000 GHz</p> <p>Start Freq 30.0000000 MHz</p> <p>Stop Freq 26.5000000 GHz</p> <p>CF Step 2.64700000 GHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.41 GHz	-5.161 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.41 GHz	-5.161 dBm							
2437	<p>Agilent R T</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.44 GHz 5.882 dBm</p> <p>Peak Log 10 dB/ Offst 10.8 dB DI -23.4 dBm</p> <p>Start 30 MHz #Res BW 100 kHz #VBW 300 kHz Stop 26.5 GHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.44 GHz</td> <td>-5.882 dBm</td> </tr> </tbody> </table> <p>Freq/Channel</p> <p>Center Freq 13.2650000 GHz</p> <p>Start Freq 30.0000000 MHz</p> <p>Stop Freq 26.5000000 GHz</p> <p>CF Step 2.64700000 GHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.44 GHz	-5.882 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.44 GHz	-5.882 dBm							
2462	<p>Agilent R T</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.46 GHz 5.746 dBm</p> <p>Peak Log 10 dB/ Offst 10.8 dB DI -24.1 dBm</p> <p>Start 30 MHz #Res BW 100 kHz #VBW 300 kHz Stop 26.5 GHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.46 GHz</td> <td>-5.746 dBm</td> </tr> </tbody> </table> <p>Freq/Channel</p> <p>Center Freq 13.2650000 GHz</p> <p>Start Freq 30.0000000 MHz</p> <p>Stop Freq 26.5000000 GHz</p> <p>CF Step 2.64700000 GHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.46 GHz	-5.746 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.46 GHz	-5.746 dBm							

Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode\_ANT-0


2422	<p>Agilent R T</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.42 GHz 4.396 dBm</p> <p>Peak Log 10 dB/ Offst 10.8 dB DI -23.9 dBm</p> <p>Start 30 MHz Stop 26.5 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.42 GHz</td> <td>-4.396 dBm</td> </tr> </tbody> </table> <p>Freq/Channel</p> <p>Center Freq 13.2650000 GHz</p> <p>Start Freq 30.0000000 MHz</p> <p>Stop Freq 26.5000000 GHz</p> <p>CF Step 2.64700000 GHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.42 GHz	-4.396 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.42 GHz	-4.396 dBm							
2437	<p>Agilent R T</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.44 GHz 9.686 dBm</p> <p>Peak Log 10 dB/ Offst 10.8 dB DI -25.5 dBm</p> <p>Start 30 MHz Stop 26.5 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.44 GHz</td> <td>-9.686 dBm</td> </tr> </tbody> </table> <p>Freq/Channel</p> <p>Center Freq 13.2650000 GHz</p> <p>Start Freq 30.0000000 MHz</p> <p>Stop Freq 26.5000000 GHz</p> <p>CF Step 2.64700000 GHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.44 GHz	-9.686 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.44 GHz	-9.686 dBm							
2452	<p>Agilent R T</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.45 GHz 4.781 dBm</p> <p>Peak Log 10 dB/ Offst 10.8 dB DI -24.6 dBm</p> <p>Start 30 MHz Stop 26.5 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.45 GHz</td> <td>-4.781 dBm</td> </tr> </tbody> </table> <p>Freq/Channel</p> <p>Center Freq 13.2650000 GHz</p> <p>Start Freq 30.0000000 MHz</p> <p>Stop Freq 26.5000000 GHz</p> <p>CF Step 2.64700000 GHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.45 GHz	-4.781 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.45 GHz	-4.781 dBm							

Mode 3: IEEE 802.11g link mode\_ANT-1


2412



2437



2462



Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode\_ANT-1

2412	<p>Agilent R T</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.41 GHz 5.92 dBm</p> <p>Peak Log 10 dB/ Offst 10.8 dB DI -22.5 dBm</p> <p>Start 30 MHz #Res BW 100 kHz #VBW 300 kHz Stop 26.5 GHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.41 GHz</td> <td>-5.92 dBm</td> </tr> </tbody> </table> <p>Freq/Channel</p> <p>Center Freq 13.2650000 GHz</p> <p>Start Freq 30.0000000 MHz</p> <p>Stop Freq 26.5000000 GHz</p> <p>CF Step 2.64700000 GHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.41 GHz	-5.92 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.41 GHz	-5.92 dBm							
2437	<p>Agilent R T</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.44 GHz 5.795 dBm</p> <p>Peak Log 10 dB/ Offst 10.8 dB DI -22.5 dBm</p> <p>Start 30 MHz #Res BW 100 kHz #VBW 300 kHz Stop 26.5 GHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.44 GHz</td> <td>-5.795 dBm</td> </tr> </tbody> </table> <p>Freq/Channel</p> <p>Center Freq 13.2650000 GHz</p> <p>Start Freq 30.0000000 MHz</p> <p>Stop Freq 26.5000000 GHz</p> <p>CF Step 2.64700000 GHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.44 GHz	-5.795 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.44 GHz	-5.795 dBm							
2462	<p>Agilent R T</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.46 GHz 5.471 dBm</p> <p>Peak Log 10 dB/ Offst 10.8 dB DI -23.6 dBm</p> <p>Start 30 MHz #Res BW 100 kHz #VBW 300 kHz Stop 26.5 GHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.46 GHz</td> <td>-5.471 dBm</td> </tr> </tbody> </table> <p>Freq/Channel</p> <p>Center Freq 13.2650000 GHz</p> <p>Start Freq 30.0000000 MHz</p> <p>Stop Freq 26.5000000 GHz</p> <p>CF Step 2.64700000 GHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.46 GHz	-5.471 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.46 GHz	-5.471 dBm							


Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode\_ANT-1

2422	<p>Agilent R T</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.42 GHz Peak 10 dB/ -5.992 dBm</p> <p>Log dB/ Offst 10.8 dB DI -23.9 dBm</p> <p>Start 30 MHz Stop 26.5 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.42 GHz</td> <td>-5.992 dBm</td> </tr> </tbody> </table> <p>Freq/Channel Center Freq 13.2650000 GHz Start Freq 30.0000000 MHz Stop Freq 26.5000000 GHz CF Step 2.64700000 GHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.42 GHz	-5.992 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.42 GHz	-5.992 dBm							
2437	<p>Agilent R T</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.44 GHz Peak 10 dB/ -7.246 dBm</p> <p>Log dB/ Offst 10.8 dB DI -23.9 dBm</p> <p>Start 30 MHz Stop 26.5 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.44 GHz</td> <td>-7.246 dBm</td> </tr> </tbody> </table> <p>Freq/Channel Center Freq 13.2650000 GHz Start Freq 30.0000000 MHz Stop Freq 26.5000000 GHz CF Step 2.64700000 GHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.44 GHz	-7.246 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.44 GHz	-7.246 dBm							
2452	<p>Agilent R T</p> <p>Ref 15 dBm #Atten 20 dB Mkr1 2.45 GHz Peak 10 dB/ -8.895 dBm</p> <p>Log dB/ Offst 10.8 dB DI -24.7 dBm</p> <p>Start 30 MHz Stop 26.5 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.45 GHz</td> <td>-8.895 dBm</td> </tr> </tbody> </table> <p>Freq/Channel Center Freq 13.2650000 GHz Start Freq 30.0000000 MHz Stop Freq 26.5000000 GHz CF Step 2.64700000 GHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.45 GHz	-8.895 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.45 GHz	-8.895 dBm							


**Conducted Band Edge**

Mode 2: IEEE 802.11b link mode\_ANT-0

2412




2462




Mode 3: IEEE 802.11g link mode\_ANT-0

2412




2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode\_ANT-0

2412




2462




Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode\_ANT-0

2422




2452




Mode 3: IEEE 802.11g link mode\_ANT-1

2412




2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode\_ANT-1

2412




2462




Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode\_ANT-1

2422



2452



## **10 Antenna Measurement**

### **10.1.Limit**

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And According to 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **10.2.Antenna Connector Construction**

The antenna used in this product is Chip Antenna. And the maximum Gain of this antenna is only 1.2 dBi.