



# Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec.4 Chung Hsing Rd., ChuTugn Chen, Hsinchu, Taiwan 310, R.O.C  
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : PY3WG111U  
Report No. : ER04-11-043FRF  
Page  1  of  2

## Uncertainty of Conducted Emission

The uncertainty of conducted emission is  $\pm 1.82$ dB.

## Test Results

<b>Company</b>	Netgear Incorporated	<b>Test Date</b>	2004/12/13
<b>Product Name</b>	Double 108 Mbps Wireless USB 2.0 Adapter WG111U	<b>Test By</b>	Alan Fan
<b>Model Name</b>	WG111U	<b>TEMP &amp; Humidity</b>	21.1°C, 63%

Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
Low	5745	16.00	30	PASS
Middle	5785	16.39	30	PASS
High	5825	16.11	30	PASS

Note :

1. For normal 802.11a mode.
2. At final test to get the worst-case emission at 54Mbps.
3. Cable loss = 0.5dB.
4. The results are calculated as the following equation :  
Peak Power Output = Peak Power Reading + Cable loss

Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
1	2412	19.14	30	PASS
6	2437	18.89	30	PASS
11	2462	18.88	30	PASS

Note :

1. For 802.11b mode.
2. At final test to get the worst-case emission at 11Mbps.
3. Cable loss = 0.5dB.
4. The results are calculated as the following equation :  
Peak Power Output = Peak Power Reading + Cable loss



## Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec.4 Chung Hsing Rd., ChuTugn Chen, Hsinchu, Taiwan 310, R.O.C  
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : PY3WG111U  
Report No. : ER04-11-043FRF  
Page 2 of 2

Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
1	2412	19.08	30	PASS
6	2437	19.24	30	PASS
11	2462	19.29	30	PASS

Note :

1. For normal 802.11g mode.
2. At final test to get the worst-case emission at 6Mbps.
3. Cable loss = 0.5dB.
4. The results are calculated as the following equation :  
Peak Power Output = Peak Power Reading + Cable loss

Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
Low	5760	16.00	30	PASS
High	5800	15.95	30	PASS

Note :

1. For Super A mode.
2. At final test to get the worst-case emission at 108Mbps.
3. Cable loss = 0.5dB.
4. The results are calculated as the following equation :  
Peak Power Output = Peak Power Reading + Cable loss

Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
Middle	2437	18.73	30	PASS

Note :

1. For Super G mode.
2. At final test to get the worst-case emission at 108Mbps.
3. Cable loss = 0.5dB.
4. The results are calculated as the following equation :  
Peak Power Output = Peak Power Reading + Cable loss