

FCC Test Report

(PART 27)

Report No.: RF160705C01-8

FCC ID: PY7-93041M

Received Date: Jul. 05, 2016

Test Date: Jul. 17, 2016 ~ Jul. 20, 2016

Issued Date: Jul. 29, 2016

Applicant: Sony Mobile Communications Inc.

Address: 4-12-3 Higashi-Shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
(R.O.C)

Test Location (1): No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan
Hsien 333, Taiwan, R.O.C.

Test Location (2): No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan,
R.O.C



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agency

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results.....	5
2.1 Measurement Uncertainty.....	6
2.2 Test Site and Instruments	7
3 General Information	8
3.1 General Description of EUT	8
3.2 Configuration of System under Test.....	10
3.2.1 Description of Support Units	10
3.3 Test Mode Applicability and Tested Channel Detail	11
3.4 EUT Operating Conditions	13
3.5 General Description of Applied Standards.....	13
4 Test Types and Results	14
4.1 Output Power Measurement.....	14
4.1.1 Limits of Output Power Measurement	14
4.1.2 Test Procedures.....	14
4.1.3 Test Setup.....	15
4.1.4 Test Results	16
4.2 Frequency Stability Measurement	21
4.2.1 Limits of Frequency Stability Measurement.....	21
4.2.2 Test Procedure	21
4.2.3 Test Setup.....	21
4.2.4 Test Results	22
4.3 Occupied Bandwidth Measurement.....	23
4.3.1 Limits of Occupied Bandwidth Measurement	23
4.3.2 Test Procedure	23
4.3.3 Test Setup.....	23
4.3.4 Test Result	24
4.4 Band Edge Measurement	27
4.4.1 Limits of Band Edge Measurement	27
4.4.2 Test Setup.....	27
4.4.3 Test Procedures.....	27
4.4.4 Test Results	28
4.5 Peak to Average Ratio	34
4.5.1 Limits of Peak to Average Ratio Measurement	34
4.5.2 Test Setup.....	34
4.5.3 Test Procedures.....	34
4.5.4 Test Results	35
4.6 Conducted Spurious Emissions	38
4.6.1 Limits of Conducted Spurious Emissions Measurement.....	38
4.6.2 Test Setup.....	38
4.6.3 Test Procedure	38
4.6.4 Test Results	39
4.7 Radiated Emission Measurement.....	40
4.7.1 Limits of Radiated Emission Measurement	40
4.7.2 Test Procedure	40
4.7.3 Deviation from Test Standard	40
4.7.4 Test Setup.....	40
4.7.5 Test Results	41
5 Pictures of Test Arrangements.....	45
Appendix – Information on the Testing Laboratories	46

Release Control Record

Issue No.	Description	Date Issued
RF160705C01-8	Original Release	Jul. 29, 2016

1 Certificate of Conformity

Product: Mobile Phone

Brand: Sony

Sample Status: Identical Prototype

Applicant: Sony Mobile Communications Inc.

Test Date: Jul. 17, 2016 ~ Jul. 20, 2016

Standards: FCC Part 27, Subpart C, L

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Gina Liu , **Date:** Jul. 29, 2016
Gina Liu / Specialist

Approved by : Stanley Wu , **Date:** Jul. 29, 2016
Stanley Wu / Assistant Manager

2 Summary of Test Results

Applied Standard: FCC Part 27 & Part 2 (LTE 12)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(C)(10)	Maximum Peak Output Power	Pass	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	Pass	Meet the requirement of limit.
2.1049 27.53(g)	Occupied Bandwidth	Pass	Meet the requirement of limit.
27.50(d)(5)	Peak to Average Ratio	Pass	Meet the requirement of limit.
27.53(g)	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 27.53(g)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53(g)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -41.02 dB at 54.30 MHz.

Applied Standard: FCC Part 27 & Part 2 (LTE 17)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(C)(10)	Maximum Peak Output Power	Pass	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	Pass	Meet the requirement of limit.
2.1049 27.53(g)	Occupied Bandwidth	Pass	Meet the requirement of limit.
27.50(d)(5)	Peak to Average Ratio	Pass	Meet the requirement of limit.
27.53(g)	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 27.53(g)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53(g)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -41.57 dB at 48.63 MHz.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ($\pm$)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.44 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.0153 dB
	200 MHz ~ 1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
	18 GHz ~ 40 GHz	1.1508 dB

2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9038A	MY51210203	Jan. 21, 2016	Jan. 20, 2017
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 17, 2015	Dec. 16, 2016
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Jan. 07, 2016	Jan. 06, 2017
HORN Antenna ETS-Lindgren	3117	00143293	Jan. 04, 2016	Jan. 03, 2017
Double Ridge Guide Horn Antenna EMCO	3115	5619	Jan. 04, 2016	Jan. 03, 2017
BILOG Antenna SCHWARZBECK	VULB 9168	9168-153	Jan. 07, 2016	Jan. 06, 2017
Agilent Communications Tester-Wireless	8960 Series 10	MY53201073	Jul. 03, 2015	Jul. 02, 2017
Preamplifier Agilent	310N	187226	Jun. 24, 2016	Jun. 23, 2017
Preamplifier Agilent	83017A	MY39501357	Jun. 24, 2016	Jun. 23, 2017
Power Meter Anritsu	ML2495A	1232002	Sep. 21, 2015	Sep. 20, 2016
Power Sensor Anritsu	MA2411B	1207325	Sep. 21, 2015	Sep. 20, 2016
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(R FC-SMS-100-SM S-120+RFC-SMS -100-SMS-400)	Jun. 24, 2016	Jun. 23, 2017
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(R FC-SMS-100-SM S-24)	Jun. 24, 2016	Jun. 23, 2017
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Communications Tester-Wireless Agilent	8960 Series 10	MY53201073	Jul. 03, 2015	Jul. 02, 2017
Radio Communication Analyzer Anritsu	MT8820C	6201240432	Jul. 06, 2015	Jul. 05, 2017

- Note: 1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HsinTien Chamber 1.
3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1 GHz if tested.
4. The FCC Site Registration No. is 149147.
5. The IC Site Registration No. is IC7450I-1.

3 General Information

3.1 General Description of EUT

Product	Mobile Phone	
Brand	Sony	
Status of EUT	Identical Prototype	
Power Supply Rating	3.8Vdc (Embedded Battery) 5Vdc or 9Vdc or 12Vdc (Adapter)	
Modulation Type	LTE	QPSK, 16QAM
Frequency Range	LTE Band 12 (Channel Bandwidth: 1.4 MHz)	699.7 ~ 715.3 MHz
	LTE Band 12 (Channel Bandwidth: 3 MHz)	700.5 ~ 714.5 MHz
	LTE Band 12 (Channel Bandwidth: 5 MHz)	701.5 ~ 713.5 MHz
	LTE Band 12 (Channel Bandwidth: 10 MHz)	704.0 ~ 711.0 MHz
	LTE Band 17 (Channel Bandwidth: 5 MHz)	706.5 ~ 713.5 MHz
	LTE Band 17 (Channel Bandwidth: 10 MHz)	709 ~ 711 MHz
Emission Designator	LTE Band 12 (Channel Bandwidth: 1.4 MHz)	QPSK: 1M09G7D 16QAM: 1M09W7D
	LTE Band 12 (Channel Bandwidth: 3 MHz)	QPSK: 2M70G7D 16QAM: 2M70W7D
	LTE Band 12 (Channel Bandwidth: 5 MHz)	QPSK: 4M49G7D 16QAM: 4M49W7D
	LTE Band 12 (Channel Bandwidth: 10 MHz)	QPSK: 8M96G7D 16QAM: 8M95W7D
	LTE Band 17 (Channel Bandwidth: 5 MHz)	QPSK: 4M49G7D 16QAM: 4M49W7D
	LTE Band 17 (Channel Bandwidth: 10 MHz)	QPSK: 8M96G7D 16QAM: 8M95W7D
Max. ERP Power	LTE Band 12 (Channel Bandwidth: 1.4 MHz)	QPSK: 26.19mW 16QAM: 20.61mW
	LTE Band 12 (Channel Bandwidth: 3 MHz)	QPSK: 25.59mW 16QAM: 20.38mW
	LTE Band 12 (Channel Bandwidth: 5 MHz)	QPSK: 25.77mW 16QAM: 20.32mW
	LTE Band 12 (Channel Bandwidth: 10 MHz)	QPSK: 25.52mW 16QAM: 20.88mW
	LTE Band 17 (Channel Bandwidth: 5 MHz)	QPSK: 16.68mW 16QAM: 13.06mW
	LTE Band 17 (Channel Bandwidth: 10 MHz)	QPSK: 16.17mW 16QAM: 12.79mW
Antenna Type	Fixed Internal Antenna	
Accessory Device	Refer to Note as below	
Data Cable Supplied	Refer to Note as below	

Note:


1. The EUT contains following accessory devices.

Product	Brand	Model	Type	Description
Adapter	Sony	UCH12	AC-0051	I/P: 100- 240Vac, 400mA, 50~60 Hz,
Earphone	Sony	MH410c	AG-1100	1.5m non-shielded cable w/o core
USB Cable	Sony	UCB20	AI-0160	0.95m shielded cable w/o core


2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Configuration of System under Test

<Radiated Emission Test>



<E.R.P. / E.I.R.P. Test>



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

Band	ERP	Radiated Emission
LTE Band 12	Y-plane	Y-axis
LTE Band 17	X-plane	X-axis

LTE Band 12

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	ERP	23017 to 23173	23017, 23095, 23173	1.4 MHz	QPSK, 16QAM	1 RB / 2 RB Offset
		23025 to 23165	23025, 23095, 23165	3 MHz	QPSK, 16QAM	1 RB / 7 RB Offset
		23035 to 23155	23035, 23095, 23155	5 MHz	QPSK, 16QAM	1 RB / 12 RB Offset
		23060 to 23130	23060, 23095, 23130	10 MHz	QPSK, 16QAM	1 RB / 24 RB Offset
-	Frequency Stability	23017 to 23173	23095	1.4 MHz	QPSK	1 RB / 2 RB Offset
		23025 to 23165	23095	3 MHz	QPSK	1 RB / 7 RB Offset
		23035 to 23155	23095	5 MHz	QPSK	1 RB / 12 RB Offset
		23060 to 23130	23095	10 MHz	QPSK	1 RB / 24 RB Offset
-	Occupied Bandwidth	23017 to 23173	23017, 23095, 23173	1.4 MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		23025 to 23165	23025, 23095, 23165	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		23035 to 23155	23035, 23095, 23155	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		23060 to 23130	23060, 23095, 23130	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
-	Peak to Average Ratio	23017 to 23173	23017, 23095, 23173	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23025 to 23165	23025, 23095, 23165	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23035 to 23155	23035, 23095, 23155	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23060 to 23130	23060, 23095, 23130	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Band Edge	23017 to 23173	23017	1.4 MHz	QPSK	1 RB / 0 RB Offset
						6 RB / 0 RB Offset
			23173	1.4 MHz	QPSK	1 RB / 5 RB Offset
						6 RB / 0 RB Offset
		23025 to 23165	23025	3 MHz	QPSK	1 RB / 0 RB Offset
						15 RB / 0 RB Offset
			23165	3 MHz	QPSK	1 RB / 14 RB Offset
						15 RB / 0 RB Offset
		23035 to 23155	23035	5 MHz	QPSK	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
			23155	5 MHz	QPSK	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		23060 to 23130	23060	10 MHz	QPSK	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
			23130	10 MHz	QPSK	1 RB / 49 RB Offset
						50 RB / 0 RB Offset

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	Conducted Emission	23017 to 23173	23095	1.4 MHz	QPSK	1 RB / 0 RB Offset
		23025 to 23165	23095	3 MHz	QPSK	1 RB / 0 RB Offset
		23035 to 23155	23095	5 MHz	QPSK	1 RB / 0 RB Offset
		23060 to 23130	23095	10 MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission	23060 to 23130	23095	10 MHz	QPSK	1 RB / 24 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

LTE Band 17

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	ERP	23755 to 23825	23755, 23790, 23825	5 MHz	QPSK, 16QAM	1 RB / 12 RB Offset
		23780 to 23800	23780, 23790, 23800	10 MHz	QPSK, 16QAM	1 RB / 24 RB Offset
-	Frequency Stability	23755 to 23825	23790	5 MHz	QPSK	1 RB / 12 RB Offset
		23780 to 23800	23790	10 MHz	QPSK	1 RB / 24 RB Offset
-	Occupied Bandwidth	23755 to 23825	23755, 23790, 23825	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		23780 to 23800	23780, 23790, 23800	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
-	Peak to Average Ratio	23755 to 23825	23755, 23790, 23825	5 MHz	QPSK, 16QAM	1 RB / 12 RB Offset
		23780 to 23800	23780, 23790, 23800	10 MHz	QPSK, 16QAM	1 RB / 24 RB Offset
-	Band Edge	23755 to 23825	23755	5 MHz	QPSK	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
		23780 to 23800	23825	5 MHz	QPSK	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		23780 to 23800	23780	10 MHz	QPSK	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
-	Conducted Emission	23755 to 23825	23790	5 MHz	QPSK	1 RB / 12 RB Offset
		23780 to 23800	23790	10 MHz	QPSK	1 RB / 24 RB Offset
-	Radiated Emission	23780 to 23800	23790	10 MHz	QPSK	1 RB / 24 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
ERP	25 deg. C, 65 % RH	3.8 Vdc	Charles Hsiao
Frequency Stability	25 deg. C, 65 % RH	3.8 Vdc	Carlos Chen
Occupied Bandwidth	25 deg. C, 65 % RH	3.8 Vdc	Carlos Chen
Band Edge	25 deg. C, 65 % RH	3.8 Vdc	Carlos Chen
Peak to Average Ratio	25 deg. C, 65 % RH	3.8 Vdc	Carlos Chen
Condcudeted Emission	25 deg. C, 65 % RH	3.8 Vdc	Carlos Chen
Radiated Emission	25 deg. C, 65 % RH	120 Vac, 60 Hz	Charles Hsiao

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 27

KDB 971168 D01 Power Meas License Digital Systems v02r02

ANSI/TIA/EIA-603-D 2010

Note: All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Portable stations (hand-held devices) operating in the 698-716 MHz band are limited to 3 watts ERP

4.1.2 Test Procedures

EIRP / ERP Measurement:


- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 5 MHz for WCDMA and 10 MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G.
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$. E.R.P power can be calculated from E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15 \text{ dBi}$.

Conducted Power Measurement:

- a. The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- b. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

4.1.3 Test Setup

ERP Measurement:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Conducted Power Measurement:



4.1.4 Test Results

Conducted Output Power (dBm)

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 23017	Mid Ch 23095	High Ch 23173		Low Ch 23017	Mid Ch 23095	High Ch 23173	
			699.7 MHz	707.5 MHz	715.3 MHz		699.7 MHz	707.5 MHz	715.3 MHz	
12 / 1.4M	1	0	23.24	23.21	23.15	0	22.39	22.48	22.41	1
	1	2	23.23	23.20	23.14	0	22.36	22.46	22.39	1
	1	5	23.20	23.18	23.11	0	22.31	22.40	22.33	1
	3	0	23.18	23.14	23.08	0	22.29	22.38	22.31	1
	3	1	23.16	23.21	23.07	0	22.30	22.39	22.34	1
	3	3	23.22	23.20	23.11	0	22.35	22.45	22.39	1
	6	0	22.19	22.08	22.04	1	20.51	20.55	20.51	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 23025	Mid Ch 23095	High Ch 23165		Low Ch 23025	Mid Ch 23095	High Ch 23165	
			700.5 MHz	707.5 MHz	714.5 MHz		700.5 MHz	707.5 MHz	714.5 MHz	
12 / 3M	1	0	23.26	23.22	23.23	0	22.41	22.28	22.24	1
	1	7	23.24	23.25	23.22	0	22.27	22.33	22.30	1
	1	14	23.27	23.23	23.24	0	22.40	22.50	22.46	1
	8	0	22.20	22.17	22.19	1	21.04	21.09	21.05	2
	8	3	22.28	22.25	22.27	1	21.20	21.26	21.24	2
	8	7	22.20	22.17	22.19	1	21.14	21.22	21.20	2
	15	0	22.19	22.15	22.17	1	21.10	21.15	21.12	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 23035	Mid Ch 23095	High Ch 23155		Low Ch 23035	Mid Ch 23095	High Ch 23155	
			701.5 MHz	707.5 MHz	713.5 MHz		701.5 MHz	707.5 MHz	713.5 MHz	
12 / 5M	1	0	23.27	23.15	23.21	0	22.27	22.52	22.22	1
	1	12	23.28	23.27	23.23	0	22.14	22.39	22.04	1
	1	24	23.21	23.26	23.26	0	21.96	22.12	21.83	1
	12	0	22.29	22.16	22.23	1	20.58	20.82	20.53	2
	12	6	22.35	22.25	22.28	1	20.88	21.04	20.75	2
	12	13	22.29	22.15	22.21	1	20.70	20.94	20.64	2
	25	0	22.24	22.12	22.15	1	20.81	20.98	20.70	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 23060	Mid Ch 23095	High Ch 23130		Low Ch 23060	Mid Ch 23095	High Ch 23130	
			704.0 MHz	707.5 MHz	711.0 MHz		704.0 MHz	707.5 MHz	711.0 MHz	
12 / 10M	1	0	23.26	23.12	23.21	0	22.54	22.46	22.21	1
	1	24	23.29	23.23	23.22	0	22.52	22.72	22.74	1
	1	49	23.11	23.08	23.12	0	22.38	22.53	22.30	1
	25	0	22.25	22.23	22.29	1	21.17	20.98	20.89	2
	25	12	22.37	22.29	22.31	1	21.07	21.07	20.96	2
	25	25	22.21	22.22	22.25	1	21.20	21.08	20.88	2
	50	0	22.23	22.21	22.21	1	20.99	21.05	21.04	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 23755	Mid Ch 23790	High Ch 23825		Low Ch 23755	Mid Ch 23790	High Ch 23825	
			706.5 MHz	710.0 MHz	713.5 MHz		706.5 MHz	710.0 MHz	713.5 MHz	
17 / 5M	1	0	23.25	23.30	23.20	0	22.32	22.15	22.14	1
	1	12	23.22	23.29	23.19	0	22.30	22.17	22.16	1
	1	24	23.30	23.35	23.23	0	22.29	22.07	21.97	1
	12	0	22.17	22.21	22.13	1	21.04	20.90	20.89	2
	12	6	22.14	22.19	22.08	1	21.31	21.12	21.09	2
	12	13	22.08	22.11	22.03	1	21.37	21.18	21.16	2
	25	0	22.17	22.20	22.11	1	21.15	21.00	20.99	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 23780	Mid Ch 23790	High Ch 23800		Low Ch 23780	Mid Ch 23790	High Ch 23800	
			709.0 MHz	710.0 MHz	711.0 MHz		709.0 MHz	710.0 MHz	711.0 MHz	
17 / 10M	1	0	23.14	23.17	23.29	0	22.12	22.06	22.04	1
	1	24	23.31	23.33	23.37	0	22.05	22.07	22.10	1
	1	49	23.15	23.21	23.22	0	22.10	22.09	22.35	1
	25	0	22.29	22.31	22.30	1	21.04	21.06	21.11	2
	25	12	22.36	22.34	22.35	1	21.07	21.13	21.01	2
	25	25	22.28	22.23	22.25	1	21.09	21.21	21.08	2
	50	0	22.23	22.28	22.32	1	20.98	21.14	20.99	2

ERP Power (dBm)

LTE Band 12							
Channel Bandwidth: 1.4 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	23017	699.7	-16.46	32.719	14.11	25.76	H
	23095	707.5	-16.42	32.736	14.17	26.10	
	23173	715.3	-16.26	32.591	14.18	26.19	
	23017	699.7	-19.42	32.69	11.12	12.94	V
	23095	707.5	-19.46	32.81	11.20	13.18	
	23173	715.3	-19.45	32.74	11.14	13.00	
Channel Bandwidth: 1.4 MHz / 16QAM							
Y	23017	699.7	-17.46	32.719	13.11	20.46	H
	23095	707.5	-17.46	32.736	13.13	20.54	
	23173	715.3	-17.30	32.591	13.14	20.61	
	23017	699.7	-20.53	32.69	10.01	10.02	V
	23095	707.5	-20.63	32.81	10.03	10.07	
	23173	715.3	-20.54	32.74	10.05	10.12	

LTE Band 12							
Channel Bandwidth: 3 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	23025	700.5	-16.56	32.719	14.01	25.17	H
	23095	707.5	-16.54	32.736	14.05	25.39	
	23165	714.5	-16.36	32.591	14.08	25.59	
	23025	700.5	-19.52	32.69	11.02	12.65	V
	23095	707.5	-19.61	32.81	11.05	12.74	
	23165	714.5	-19.57	32.74	11.02	12.65	
Channel Bandwidth: 3 MHz / 16QAM							
Y	23025	700.5	-17.53	32.719	13.04	20.13	H
	23095	707.5	-17.54	32.736	13.05	20.17	
	23165	714.5	-17.35	32.591	13.09	20.38	
	23025	700.5	-20.51	32.69	10.03	10.07	V
	23095	707.5	-20.61	32.81	10.05	10.12	
	23165	714.5	-20.52	32.74	10.07	10.16	

LTE Band 12							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	23035	701.5	-16.53	32.719	14.04	25.35	H
	23095	707.5	-16.54	32.736	14.05	25.39	
	23155	713.5	-16.33	32.591	14.11	25.77	
	23035	701.5	-19.50	32.69	11.04	12.71	V
	23095	707.5	-19.62	32.81	11.04	12.71	
	23155	713.5	-19.52	32.74	11.07	12.79	
Channel Bandwidth: 5 MHz / 16QAM							
Y	23035	701.5	-17.49	32.719	13.08	20.32	H
	23095	707.5	-17.53	32.736	13.06	20.21	
	23155	713.5	-17.41	32.591	13.03	20.10	
	23035	701.5	-20.51	32.69	10.03	10.07	V
	23095	707.5	-20.60	32.81	10.06	10.14	
	23155	713.5	-20.56	32.74	10.03	10.07	

LTE Band 12							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	23060	704.0	-16.52	32.727	14.06	25.45	H
	23095	707.5	-16.56	32.739	14.03	25.29	
	23130	711.0	-16.51	32.728	14.07	25.52	
	23060	704.0	-19.57	32.75	11.03	12.68	V
	23095	707.5	-19.62	32.81	11.04	12.71	
	23130	711.0	-19.65	32.84	11.04	12.71	
Channel Bandwidth: 10 MHz / 16QAM							
Y	23060	704.0	-17.41	32.727	13.17	20.73	H
	23095	707.5	-17.43	32.739	13.16	20.70	
	23130	711.0	-17.38	32.728	13.20	20.88	
	23060	704.0	-20.52	32.75	10.08	10.19	V
	23095	707.5	-20.65	32.81	10.01	10.02	
	23130	711.0	-20.66	32.84	10.03	10.07	

LTE Band 17							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	23755	706.5	-18.46	32.719	12.11	16.25	H
	23790	710.0	-18.46	32.736	12.13	16.32	
	23825	713.5	-18.22	32.591	12.22	16.68	
	23755	706.5	-23.46	32.69	7.08	5.11	V
	23790	710.0	-23.61	32.81	7.05	5.07	
	23825	713.5	-23.53	32.74	7.06	5.08	
Channel Bandwidth: 5 MHz / 16QAM							
X	23755	706.5	-19.46	32.719	11.11	12.91	H
	23790	710.0	-19.45	32.736	11.14	12.99	
	23825	713.5	-19.28	32.591	11.16	13.06	
	23755	706.5	-24.45	32.69	6.09	4.06	V
	23790	710.0	-24.63	32.81	6.03	4.01	
	23825	713.5	-24.54	32.74	6.05	4.03	

LTE Band 17							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	23780	709.0	-18.52	32.727	12.06	16.06	H
	23790	710.0	-18.52	32.739	12.07	16.10	
	23800	711.0	-18.49	32.728	12.09	16.17	
	23780	709.0	-23.52	32.75	7.08	5.11	V
	23790	710.0	-23.53	32.81	7.13	5.16	
	23800	711.0	-23.64	32.84	7.05	5.07	
Channel Bandwidth: 10 MHz / 16QAM							
X	23780	709.0	-19.52	32.727	11.06	12.76	H
	23790	710.0	-19.52	32.739	11.07	12.79	
	23800	711.0	-19.51	32.728	11.07	12.79	
	23780	709.0	-24.53	32.75	6.07	4.05	V
	23790	710.0	-24.52	32.81	6.14	4.11	
	23800	711.0	-24.54	32.84	6.15	4.12	

4.2 Frequency Stability Measurement

4.2.1 Limits of Frequency Stability Measurement


The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

4.2.2 Test Procedure

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ± 0.5 °C during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

Note: The frequency error was recorded frequency error from the communication simulator.

4.2.3 Test Setup



4.2.4 Test Results

Frequency Error vs. Voltage

Voltage (Volts)	Frequency Error (ppm)						Limit (ppm)
	LTE Band 12				LTE Band 17		
	1.4 MHz	3 MHz	5 MHz	10 MHz	5 MHz	10 MHz	
3.8	0.004805654	0.003816254	0.004522968	0.00565371	0.001690141	0.003098592	2.5
3.6	0.004240283	0.00409894	0.002826855	0.003674912	0.004788732	0.001549296	2.5
4.2	0.00409894	0.003957597	0.004946996	0.001837456	0.005492958	0.002535211	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.6 Vdc to 4.2 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	Frequency Error (ppm)						Limit (ppm)
	LTE Band 12			LTE Band 17			
	1.4 MHz	3 MHz	5 MHz	10 MHz	5 MHz	10 MHz	
-30	0.003392226	0.001413428	0.001413428	0.002826855	0.002394366	0.001971831	2.5
-20	0.001837456	0.004240283	0.004240283	0.005088339	0.004788732	0.005352113	2.5
-10	0.004381625	0.002261484	0.002261484	0.004381625	0.003380282	0.004929577	2.5
0	0.004664311	0.00155477	0.00155477	0.003250883	0.003098592	0.004084507	2.5
10	0.005229682	0.004240283	0.004240283	0.004381625	0.004507042	0.003239437	2.5
20	-0.003816254	-0.004240283	-0.004240283	-0.002968198	-0.002112676	-0.001549296	2.5
30	-0.003533569	-0.005229682	-0.005229682	-0.005371025	-0.004225352	-0.004225352	2.5
40	-0.001696113	-0.003957597	-0.003957597	-0.004664311	-0.001830986	-0.002253521	2.5
50	-0.005229682	-0.002826855	-0.002826855	-0.002120141	-0.005492958	-0.003943662	2.5
55	-0.002120141	-0.005229682	-0.005229682	-0.003109541	-0.001408451	-0.002112676	2.5

4.3 Occupied Bandwidth Measurement


4.3.1 Limits of Occupied Bandwidth Measurement

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

4.3.2 Test Procedure


- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.3 Test Setup



4.3.4 Test Result

LTE Band 12							
Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
23017	699.7	1.0909	1.0881	23025	700.5	2.6959	2.6962
23095	707.5	1.0911	1.0890	23095	707.5	2.6943	2.6931
23173	715.3	1.0918	1.0891	23165	714.5	2.6932	2.6934




LTE Band 12


Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
23035	701.5	4.4887	4.4854	23060	704.0	8.9542	8.9532
23095	707.5	4.4845	4.4768	23095	707.5	8.9453	8.9454
23155	713.5	4.4844	4.4843	23130	711.0	8.9578	8.9487

Spectrum Plot of Worst Value


5 MHz / QPSK




5 MHz / 16QAM




10 MHz / QPSK



10 MHz / 16QAM



LTE Band 17							
Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
23755	706.5	4.4850	4.4792	23780	709.0	8.9414	8.9411
23790	710.0	4.4868	4.4843	23790	710.0	8.9454	8.9486
23825	713.5	4.4837	4.4865	23800	711.0	8.9554	8.9465



4.4 Band Edge Measurement


4.4.1 Limits of Band Edge Measurement

For operations in the 698-716 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater.

However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

For operations in the 1710–1755 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.


4.4.2 Test Setup





4.4.3 Test Procedures


- All measurements were done at low and high operational frequency range.
- The center frequency of spectrum is the band edge frequency and span is 5 MHz. RB of the spectrum is 100 kHz and VB of the spectrum is 300 kHz (WCDMA).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 13 kHz and VB of the spectrum is 51 kHz (LTE Bandwidth 1.4 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 30 kHz and VB of the spectrum is 100 kHz (LTE Bandwidth 3 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 100 kHz and VB of the spectrum is 300 kHz (LTE Bandwidth 5 MHz/10 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 150 kHz and VB of the spectrum is 470 kHz (LTE Bandwidth 15 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 180 kHz and VB of the spectrum is 560 kHz (LTE Bandwidth 20 MHz).
- Record the max trace plot into the test report.


4.4.4 Test Results















4.5 Peak to Average Ratio

4.5.1 Limits of Peak to Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

4.5.2 Test Setup




4.5.3 Test Procedures

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1 %.

4.5.4 Test Results

LTE Band 12							
Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
23017	699.7	3.50	4.17	23025	700.5	3.48	4.20
23095	707.5	3.88	4.53	23095	707.5	3.88	4.62
23173	715.3	3.74	4.49	23165	714.5	3.63	4.47




LTE Band 12


Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
23035	701.5	3.39	4.21	23060	704.0	3.42	4.15
23095	707.5	3.75	4.52	23095	707.5	3.73	4.46
23155	713.5	3.62	4.42	23130	711.0	3.82	4.60

Spectrum Plot of Worst Value


5 MHz / QPSK




5 MHz / 16QAM



10 MHz / QPSK



10 MHz / 16QAM




LTE Band 17


Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
23755	706.5	3.60	4.45	23780	709.0	3.60	4.53
23790	710.0	3.61	4.52	23790	710.0	3.63	4.53
23825	713.5	3.47	4.40	23800	711.0	3.63	4.52

Spectrum Plot of Worst Value


5 MHz / QPSK




5 MHz / 16QAM



10 MHz / QPSK



10 MHz / 16QAM




4.6 Conducted Spurious Emissions

4.6.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission is equal to -13 dBm.

4.6.2 Test Setup




4.6.3 Test Procedure

- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 30 MHz to 8 GHz for LTE Band 17 and from 30 MHz to 18 GHz for LTE Band 4. 10 dB attenuation pad is connected with spectrum. RBW=1 MHz and VBW=3 MHz are used for conducted emission measurement.

4.6.4 Test Results

Frequency Range: 30 MHz ~ 8 GHz



4.7 Radiated Emission Measurement

4.7.1 Limits of Radiated Emission Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission is equal to -13 dBm.

4.7.2 Test Procedure


- Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G.
- EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.
- E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power - 2.15 dBi.

Note: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

4.7.3 Deviation from Test Standard

No deviation.

4.7.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.7.5 Test Results

LTE Band 12

Channel Bandwidth: 10 MHz / QPSK




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2016-07-20



Site : 966 chamber 1

Condition: PART 22/24/27 Horizontal

Remark : LTE_Band 12_Link_CH23095

Tested by: Charles Hsiao

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	121.80	-58.56	-50.43	-13.00	-45.56	-8.13	Peak
2 pp	146.10	-55.68	-47.82	-13.00	-42.68	-7.86	Peak
3	192.27	-60.56	-54.74	-13.00	-47.56	-5.82	Peak
4	325.20	-69.07	-63.40	-13.00	-56.07	-5.67	Peak
5	462.40	-73.24	-69.03	-13.00	-60.24	-4.21	Peak
6	556.90	-70.24	-68.86	-13.00	-57.24	-1.38	Peak
7	1415.00	-58.56	-64.92	-13.00	-45.56	6.36	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2016-07-20



Site : 966 chamber 1
Condition: PART 22/24/27 Vertical
Remark : LTE_Band 12_Link_CH23095
Tested by: Charles Hsiao

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	54.30	-54.02	-39.96	-13.00	-41.02	-14.06	Peak
2	96.69	-58.42	-48.13	-13.00	-45.42	-10.29	Peak
3	146.91	-58.02	-50.14	-13.00	-45.02	-7.88	Peak
4	393.10	-70.81	-67.71	-13.00	-57.81	-3.10	Peak
5	618.50	-67.16	-67.38	-13.00	-54.16	0.22	Peak
6	888.00	-66.20	-68.75	-13.00	-53.20	2.55	Peak
7	1415.00	-57.51	-63.87	-13.00	-44.51	6.36	Peak

LTE Band 17

Channel Bandwidth: 10 MHz / QPSK




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2016-07-20



Site : 966 chamber 1

Condition: PART 27(B4/B17) Horizontal

Remark : LTE_Band 17_Link_CH23790

Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	101.55	-58.67	-48.78	-13.00	-45.67	-9.89	Peak
2 pp	151.77	-56.69	-48.80	-13.00	-43.69	-7.89	Peak
3	186.33	-62.09	-56.42	-13.00	-49.09	-5.67	Peak
4	346.90	-70.05	-64.64	-13.00	-57.05	-5.41	Peak
5	462.40	-73.24	-69.03	-13.00	-60.24	-4.21	Peak
6	918.10	-64.84	-68.55	-13.00	-51.84	3.71	Peak
7	1420.00	-58.46	-64.82	-13.00	-45.46	6.36	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2016-07-20



Site : 966 chamber 1
Condition: PART 27(B4/B17) Vertical
Remark : LTE_Band 17_Link_CH23790
Tested by: Karl Lee

		Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	pp	48.63	-54.57	-41.14	-13.00	-41.57	-13.43 Peak
2		112.62	-61.49	-52.73	-13.00	-48.49	-8.76 Peak
3		170.94	-65.91	-59.31	-13.00	-52.91	-6.60 Peak
4		328.00	-71.13	-65.50	-13.00	-58.13	-5.63 Peak
5		440.00	-71.40	-67.77	-13.00	-58.40	-3.63 Peak
6		888.00	-66.20	-68.75	-13.00	-53.20	2.55 Peak
7		1420.00	-58.56	-64.92	-13.00	-45.56	6.36 Peak

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---