



Prepared (also subject responsible if other)

SEM/BGLDB, Monica Towman

Approved

SEM/BGLDB (Monica Towman)

Checked

Company Internal
MARKING DRAWING
No.

1202-5917 Uen

Date

2007-07-06

Rev

1.1

Reference

4

Approved according to 000 21–LXE 107 42/1

Mobile Phone label content, China

1 General information

Core Unit label part no	1200-0787
Core Unit label content part no	1202-5908
Bar code	Standard: according to Ericsson corporate standard 102 01–109 Uen Print quality: C, according to ANSI X3.182-1990 as stated in Ericsson corporate standard 102 01–1003 Uen Quiet zone: No bar codes are allowed to be closer to a label edge than 2 mm!
Text	If applicable, or nothing else specified, Zebra printer Scaleable Smooth Font CG Triumvirate Bold Condensed is imposed. When needed, the text is adjusted to fit the label.
Coordinates	“(x/y)” under each line number specifies the bottom / left alignment for text, graphics and bar codes, x is measured vertically, and y horizontally from the upper left corner of the label (landscape format), both in mm. When needed, the alignment is adjusted to fit the label.

MLCI= Main Label Content Information-document.

2 Printing information

	Content	Format
Line 1 (2,2/23,2)	The notified body number “0682”	Text, height 1,2 mm.
Line 2 (5,9/16,2)	CE approval symbol	Graphics, height 5 mm. According to 1202-5482.
Line 3a (7,5/1,0)	Sony Ericsson stylized name.	Graphics, height 1,5 mm. According to 1200-1925.
Line 3b (7,35/14,0)	型号:	Text, height 1,2 mm.
Line 3c (7,5/17,5)	Model Name “T658c”	Text, height 1,2 mm.
Line 4a (9,4/1,0)	“TYPE: AAB-1022101-BV”	Text, height 1,2 mm.
Line 4b (9,4/15,6)	HW & SW identification field, if applicable; “FG”	Text, height 1,2 mm. According to Type-testing report in BOM pos 1C.
Line 4c (9,4/18,1)	Location code of where the phone is flashed, if applicable, “XXX”	Text, height 1,2 mm.
Line 5a (11,1/1,0)	“FCC ID: PY7A1022101”	Text, height 1,2 mm.
Line 5b (11,1/15,1)	Production week (flash), “yy’W’ww” (yy = year, ww = week)	Text, height 1,2 mm.
Line 5c (11,1/30,5)	CCC-sticker with S&E	Graphics, height 5 mm. According to 1201-7981.



Prepared (also subject responsible if other)

SEM/BGLDB, Monica Towman

Approved

SEM/BGLDB (Monica Towman)

Checked

Company Internal
MARKING DRAWING
No.

1202-5917 Uen

Date

2007-07-06

Rev

1.1

Reference

4

	Content	Format
Line 6a (12,7/1,0)	"IC: 4170B-A1022101"	Text, height 1,2 mm.
Line 6b (12,7/14,3)	Product number without revision of the Sales Item in which the phone is packed, if applicable. "SI XXXX-XXXX"	Text, height 1,2 mm.
Line 6c (12,7/25,0)	Repair week, if applicable. "Ry"W'ww" (y = year, ww = week)	Text, height 1,2 mm.
Line 6d (13,1/32,5)	"CMII ID: 2007XXXXXX"	Text, height 1,5mm with frame around. Rotated 90 degrees
Line 7 (15,1/1,0)	Line 8a in bar code. As desired by supplier (e.g. only actual number).	Bar code, height 2,0 mm. As desired by supplier (e.g. Code 128 symbology).
Line 8a (16,9/1,0)	Supplier's identification for trace-ability of the telephone, as desired by supplier (e.g. "S/N: nnn...." for serial number).	Text, height 1,2 mm. Defined by supplier.
Line 8b (16,9/16,1)	Actual electronic serial number (IMEI) of the Mobile Phone, "00000000-000000-0"	Text, height 1,2 mm. In the format TAC-SNR-CD. TAC and SNR derived from pos 500 in BOM. CD = check digit according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
Line 9 (19,1/1,0)	Line 8b in bar code (only actual number, without data identifier).	Bar code, height 2,0 mm. Code 128 symbology, code C subset. If uneven number of digits, code B subset shall be used for the last digit.
Line 10a (21,0/1,0)	Marking of origin: 中国制造	Text, height 1,2 mm.
Line 10b (21,0/6,8)	索尼爱立信移动通信产品(中国)有限公司	Text, height 1,2 mm.
Line 10c (21,0/32,5)	GSM/GPRS 移动电话机	Text, height 1,2 mm. Two rows, aligned from bottom row. Rotated 90 degrees

3 Layout

The conceptual picture (for Zebra 90XiII printer, or equivalent) should not be considered as specifications, but as an additional help for setting up the label.

3.1 Conceptual picture



Prepared (also subject responsible if other)

SEM/BGLDB, Monica Towman

Approved

SEM/BGLDB (Monica Towman)

Checked

Company Internal
MARKING DRAWING
No.

1202-5917 Uen

Date

2007-07-06

Rev

1.1

Reference

4

double underlined = major changes since last revision.

3.1 Label placement

To find the label follow these steps:

1. Remove the cover on the rear side of the product.
2. Remove the battery.
3. The label is located below the battery.

