

<i>Prepared</i>	<i>Date</i>	<i>Rev</i>	<i>Doc no.</i>
RT/SEM/CA/KA Mike Sink	2006-01-18	D	1/151 86-DPY 101 101 1498/230
<i>Approved</i>	<i>Checked</i>		<i>File</i>

1/151 86-DPY 101 1498/230 Marking Drawing For Katherine

Note: This marking drawing is applicable for all Katherine variants

Type TBD

Label

The Label used for marking is defined in the Manufacturing Specification 1301-SVF 930 1447.

Placing Labels

The labels shall be placed on the back of the telephone according to the Assembly Drawing (151 88 KRH 101 220) for the KRH.

Print Layout

Section 1

SAMPLE ONLY

Section 2

Line	
1	Sony Ericsson Z525a
2	Type AAC - 1052014 - BV AAA R5080Z
3	FCC ID: PY7AC052014 IC: 4170B - AC052014
4	
5	IMEI: 35719800 - 123456 - 0
6	
7	MSN: BDS012U6AO
8	23W23
9	UPC: 197553008932
	DPY 1464 RX Made in Malaysia
	28903

10,11

12

***Note:** representative samples, text in image may not match required information for this product defined in table below.

Line	Text
1.	Sony Ericsson Trademark, Model Number
2.	Type Number, GHY1 Fields, 7 Digit Repair Code
3.	Country Approval Mark 1, Country Approval Mark 2
4.	IMEI-Numbers as Barcode
5.	IMEI-Numbers as characters
6.	Serial number as barcode
7.	Serial number as characters
8.	Prod/Repair wk as characters & Prod wk as barcode
9.	UPC numbers as barcode & UPC number as characters
10.	Reduced DPY number & r-state
11.	Marking of Origin
12.	CE Marking

<i>Prepared</i>	<i>Date</i>	<i>Rev</i>	<i>Doc no.</i>
RT/SEM/CA/KA Mike Sink	2006-01-18	D	1/151 86-DPY 101 101 1498/230
<i>Approved</i>	<i>Checked</i>		<i>File</i>

Definitions

Sony Ericsson trademark	Sony Ericsson trademark shall be according to the corporate standard 190 89-EN/LZT 108 5347.
Model number	The model number is Z525a and shall be printed " Z525a "
Type number	The type number is AAC-1052014-BV and shall be printed "AAC-1052014-BV"
G-field	R-state identification of the CXC module according to the G-Field section of 1/151 86- KRH 101 454.
H-field	R-state identification of the KRH according to the H-Field section of 1/151 86- KRH 101 454.
Y ¹ -field	R-state identification of the ROA according to the Y-Field section of 1/151 86- KRH 101 454.
Country approval mark 1	Consist of text: FCC ID: PY7AC052014 Within a frame with height > 1,5 mm.
Country approval mark 2	Consist of text: IC ID: 4170B-AC052014 Within a frame with height > 1,5 mm.
IMEI number as barcode	See below for definition of IMEI-number. The bar code shall only contain the digits of the IMEI number (no -).
IMEI number as characters	See the 1/151 86-KRH 101 454 (latest revision). The text 'IMEI:' shall come before the IMEI number. Therefore the format shall be IMEI: 01AAAAAA-BBBBBB-C AAAAAA = TAC BBBBBB = assigned serial number C = A check digit, from 0-9, calculated according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
Serial number as barcode	According to Ericsson corporate standard 102 01 - 109.
Serial number as characters	According to Ericsson group standard 0012-101. Ericsson group factory number system according the Ericsson corporate standard 1120-101 The text 'MSN:' shall come before the Serial number.
UPC Code as Barcode	See below for definition of UPC-number. The UPC code shall only contain the digits of the UPC number
UPC Code as Characters	The text 'UPC:' shall come before the UPC number. Therefore the format shall be UPC: 095673 XXXXX, where XXXXX indicates the last five digits of the UPC number for the specific DPY.
Production week (Prod wk)	The production week shall be given as yyWww (yy = year, ww = week) according to the ISO 8601 standard.
Production week as barcode	According to Ericsson corporate standard 102 01 - 109.
Repair week	The field shall be left blank unless a repair centre repairs the unit. The repair week shall then be given as Rywwwxx (R = repair, y = year, ww = week, xx = Revision eg. 1A)
Reduced DPY	The reduced product number of the DPY leaves out the 3 digit number prefix (ex: DPY 101 1498/230 R2A would be printed DPY 1498/230 R2A).

<i>Prepared</i>	<i>Date</i>	<i>Rev</i>	<i>Doc no.</i>
RT/SEM/CA/KA Mike Sink	2006-01-18	D	1/151 86-DPY 101 101 1498/230
<i>Approved</i>	<i>Checked</i>		<i>File</i>

Marking of origin	"Made in" statement should reflect the country of origin of the KRC (i.e. Made in Malaysia).
CE Marking	1. N/A
	2. N/A

Print guidelines/ regulations

The printing shall be well readable and permanent.

Typeface	OCR-B
Type size	min 1.1 mm
Line spacing	min 1.5 mm
Trademark	min 1mm (required)
Approval Marks	min 5.0 mm

Product Listing

In the event that this marking drawing is to be used for the production of DPA units please use the following chart for cross-referencing the DPA number to the reduced DPY number that shall appear on the KRH label.

Product Number	Associated DPA	Customer
DPY 101 1498/230	N/A	N/A

Revision History

Revision	Reason	Originator
PA1	Initial Release	Mike Sink
PA2	Update for new KRH marking	Mike Sink
PA3	Exchanged "Katherine" for "Z520a"	Sandy Smith
D	Updated model number	Mike Sink
E	Included FCC and IC ID	Mike Sink