

## RF EXPOSURE REPORT

**REPORT NO.:** SA980324A01

MODEL NO.: BH-216

**VERSION:** HW: 1.2, SW: 1.0, ME: 1.2, Proto: B4.0

**ACCORDING:** FCC Guidelines for Human Exposure

**IEEE C95.1** 

**APPLICANT:** Nokia Corporation

ADDRESS: Elektroniikkatie 10 P.O. Box 50, Oulu, 90570 Finland

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.)

Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,

Taipei Hsien, 244 Taiwan

Report No: SA980324A01 1 Report Format Version 3.0.0



## Conclusion

No Evaluation Required if power is below this threshold:

F(GHz)		mW	
Low	2.402	24.58	
High	2.480	24.50	

Maximum measured transmitter power:

Pout (dBm	Pout (mW)	
Conducted Power	5.30	3.388
EIRP Power	3.78	2.388

<sup>\*</sup>Note: The antenna is IFA antenna with -1.52dBi gain

Threshold for no SAR evaluation is 24.58mW Transmitter power is 3.388mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold

---END---