

SAR Compliance Test Report

Test report no.:	Cph_SAR_0709_04	Date of report:	2007-02-27
Template version:	4.0	Number of pages:	57
Testing laboratory:	TCC Nokia Copenhagen Laboratory Frederikskaj 1790 COPENHAGEN V DENMARK Tel. +45 33 292929 Fax. +45 33 292934	Client:	Nokia Corporation P.O. Box 86 Joensuunkatu 7 FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 44277
Responsible test engineer:	Leif Funch Klysner	Product contact person:	Jarkko Luoma
Measurements made by:	Leif F Klysner & Mia-Maria Nielsen		
Tested device:	RA-6		
FCC ID:	PYARA-6	IC:	661V-RA6
Supplement reports:	Cph_SAR_0709_05		
Testing has been carried out in accordance with:	47CFR §2.1093 Radiofrequency Radiation Exposure Evaluation: Portable Devices FCC OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01) Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields RSS-102 Evaluation Procedure for Mobile and Portable Radio Transmitters with Respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields IEEE 1528 - 2003 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Technique		
Documentation:	The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test results:	The tested device complies with the requirements in respect of all parameters subject to the test. The test results and statements relate only to the items tested. The test report shall not be reproduced except in full, without written approval of the laboratory.		
Date and signatures:			
For the contents:			

CONTENTS

1. SUMMARY OF SAR TEST REPORT.....	3
1.1 TEST DETAILS.....	3
1.2 MAXIMUM RESULTS.....	3
1.2.1 Head Configuration.....	3
1.2.2 Body Worn Configuration	4
1.2.3 Maximum Drift	4
1.2.4 Measurement Uncertainty	4
2. DESCRIPTION OF THE DEVICE UNDER TEST.....	5
2.1 DESCRIPTION OF THE ANTENNA	5
3. TEST CONDITIONS	6
3.1 TEMPERATURE AND HUMIDITY	6
3.2 TEST SIGNAL, FREQUENCIES AND OUTPUT POWER	6
4. DESCRIPTION OF THE TEST EQUIPMENT	7
4.1 MEASUREMENT SYSTEM AND COMPONENTS	7
4.1.1 Isotropic E-field Probe Type ES3DV3	8
4.2 PHANTOMS	9
4.3 TISSUE SIMULANTS	9
4.3.1 Tissue Simulant Recipes	9
4.3.2 System Checking	10
4.3.3 Tissue Simulants used in the Measurements.....	11
5. DESCRIPTION OF THE TEST PROCEDURE	13
5.1 DEVICE HOLDER.....	13
5.2 TEST POSITIONS.....	13
5.2.1 Against Phantom Head.....	13
5.2.2 Body Worn Configuration	14
5.3 SCAN PROCEDURES	14
5.4 SAR AVERAGING METHODS.....	14
6. MEASUREMENT UNCERTAINTY	15
7. RESULTS	16
APPENDIX A: SYSTEM CHECKING SCANS	20
APPENDIX B: MEASUREMENT SCANS.....	29
APPENDIX C: RELEVANT PAGES FROM PROBE CALIBRATION REPORT(S)	56
APPENDIX D: RELEVANT PAGES FROM DIPOLE VALIDATION KIT REPORT(S)	57

1. SUMMARY OF SAR TEST REPORT

1.1 Test Details

Period of test	2006-12-19 to 2006-12-29
SN, HW and SW numbers of tested device	SN: 004400911738217, HW: 4100, SW: 06.46.00, DUT: 27943
Batteries used in testing	BP-4L, DUT: 27936, 27937, 27938, 27939
Headsets used in testing	HS-47, DUT: 27908
Other accessories used in testing	-
State of sample	Prototype unit
Notes	-

1.2 Maximum Results

The maximum measured SAR values for Head configuration and Body Worn configuration are given in section 1.2.1 and 1.2.2 respectively. The device conforms to the requirements of the standard(s) when the maximum measured SAR value is less than or equal to the limit.

1.2.1 Head Configuration

Mode	Ch / f (MHz)	Radiated power	Position	Measured SAR value (1g avg)	Scaled* SAR value (1g avg)	SAR limit (1g avg)	Result
2-slot GPRS 850	251 / 848.8	24.4 dBm ERP	Left, Cheek	0.078 W/kg	0.09 W/kg	1.6 W/kg	PASSED
2-slot GPRS 1900	661 / 1880.0	28.0 dBm EIRP	Left, Tilt	0.463 W/kg	0.52 W/kg	1.6 W/kg	PASSED
WLAN 2450	11 / 2462.0	20.0 dBm EIRP	Right, Cheek	0.123 W/kg	0.14 W/kg	1.6 W/kg	PASSED
2-slot GPRS 850 + WLAN 2450	-	-	Right, Cheek	0.172 W/kg	0.19 W/kg	1.6 W/kg	PASSED
2-slot GPRS 1900 + WLAN 2450	-	-	Left, Tilt	0.530 W/kg	0.59 W/kg	1.6 W/kg	PASSED

1.2.2 Body Worn Configuration

Mode	Ch / f (MHz)	Radiated power	Separation distance	Measured SAR value (1g avg)	Scaled* SAR value (1g avg)	SAR limit (1g avg)	Result
2-slot GPRS 850	251 / 848.8	24.4 dBm ERP	1.5 cm	0.447 W/kg	0.50 W/kg	1.6 W/kg	PASSED
2-slot GPRS 1900	810 / 1909.8	27.5 dBm EIRP	1.5 cm	0.566 W/kg	0.63 W/kg	1.6 W/kg	PASSED
WLAN 2450	7 / 2442.0	20.6 dBm EIRP	1.5 cm	0.084 W/kg	0.09 W/kg	1.6 W/kg	PASSED
2-slot GPRS 850 + WLAN 2450	-	-	1.5 cm	0.526 W/kg	0.59 W/kg	1.6 W/kg	PASSED
2-slot GPRS 1900 + WLAN 2450	-	-	1.5 cm	0.645 W/kg	0.72 W/kg	1.6 W/kg	PASSED

*SAR values are scaled up by 12% to cover measurement drift.

1.2.3 Maximum Drift

Maximum drift covered by 12% scaling up of the SAR values	Maximum drift during measurements
0.5dB	0.40dB

1.2.4 Measurement Uncertainty

Expanded Uncertainty (k=2) 95%	± 25.8%
--------------------------------	---------

2. DESCRIPTION OF THE DEVICE UNDER TEST

Device category	Portable
Exposure environment	General population / uncontrolled

Modes and Bands of Operation	GSM 850 / 1900	GPRS 850 / 1900	EGPRS 850 / 1900	BT	WLAN 2450
Modulation Mode	GMSK	GMSK	GMSK / 8PSK	GFSK	
Duty Cycle	1/8	1/8 to 3/8	1/8 to 3/8		1
Transmitter Frequency Range (MHz)	824 - 849 1850 - 1910	824 - 849 1850 - 1910	824 - 849 1850 - 1910	2402 – 2480	2412 – 2462

Outside of USA and Canada, the transmitter of the device is capable of operating also in 900 / 1800 / 2100 MHz bands, which are not part of this filing.

This device has Voice-over-IP/Dual Transfer Mode capability for use at the ear. Therefore, SAR for multi slot GPRS mode was evaluated against the head profile of the phantom.

2.1 Description of the Antenna

The device has an internal antenna.

3. TEST CONDITIONS

3.1 Temperature and Humidity

Ambient temperature (°C):	20.5 to 22.5
Ambient humidity (RH %):	35 to 55

3.2 Test Signal, Frequencies and Output Power

The device was put into operation by using a call tester. Communication between the device and the call tester was established by air link.

The device output power was set to maximum power level for all tests; a fully charged battery was used for every test sequence.

In all operating bands the measurements were performed on lowest, middle and highest channels.

The radiated output power of the device was measured by a separate test laboratory on the same unit(s) as used for SAR testing.

4. DESCRIPTION OF THE TEST EQUIPMENT

4.1 Measurement System and Components

The measurements were performed using an automated near-field scanning system, DASY4, manufactured by Schmid & Partner Engineering AG (SPEAG) in Switzerland. The SAR extrapolation algorithm used in all measurements was the 'advanced extrapolation' algorithm.

The following table lists calibration dates of SPEAG components:

Test Equipment	Serial Number	Calibration interval	Calibration expiry
DAE3	501	12 months	2007-02
DAE3	573	12 months	2007-09
DAE4	682	12 months	2007-08
DAE4	710	12 months	2007-09
E-field Probe ES3DV3	3116	12 months	2007-08
E-field Probe ES3DV3	3117	12 months	2007-08
E-field Probe ES3DV3	3118	12 months	2007-08
E-field Probe ES3DV3	3119	12 months	2007-08
Dipole Validation Kit, D835V2	4d042	24 months	2008-09
Dipole Validation Kit, D1900V2	5d026	24 months	2008-02
Dipole Validation Kit, D2450V2	750	24 months	2008-02
DASY4 software	Version 4.7	-	-

Additional test equipment used in testing:

Test Equipment	Model	Serial Number	Calibration interval	Calibration expiry
Signal Generator	SME06	848650/011	36 months	2008-07
Amplifier	ZHL-42W	E012903	-	-
Power Meter	NRP	100808	24 months	2007-03
Power Sensor	NRP-Z51	100412	12 months	2007-02
Call Tester	CMU200	105900	-	-
Call Tester	CMU200	110735	-	-
Call Tester	CMU200	831593	-	-
Call Tester	4400M	0411216	-	-
Call Tester	4400M	0211008	-	-
BT Tester	CBT	100263	-	-
Vector Network Analyzer	AT8753ES	MY40001091	12 months	2007-08
Dielectric Probe Kit	HP85070B	US33020403	-	-

4.1.1 Isotropic E-field Probe Type ES3DV3

Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., butyl diglycol)
Calibration	Calibration certificate in Appendix C
Frequency	10 MHz to 4 GHz (dosimetry); Linearity: ± 0.2 dB (30 MHz to 4 GHz)
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in HSL (rotation normal to probe axis)
Dynamic Range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 330 mm Tip length: 20 mm Body diameter: 12 mm Tip diameter: 3.9 mm
Application	Distance from probe tip to dipole centers: 2.0 mm General dosimetry up to 4 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms

4.2 Phantoms

The phantom used for all tests i.e. for both system checks and device testing, was the twin-headed "SAM Phantom", manufactured by SPEAG. The phantom conforms to the requirements of IEEE 1528 - 2003.

System checking was performed using the flat section, whilst Head SAR tests used the left and right head profile sections. Body SAR testing also used the flat section between the head profiles.

The SPEAG device holder (see Section 5.1) was used to position the device in all tests whilst a tripod was used to position the validation dipoles against the flat section of phantom.

4.3 Tissue Simulants

Recommended values for the dielectric parameters of the tissue simulants are given in IEEE 1528 - 2003 and FCC Supplement C to OET Bulletin 65. All tests were carried out using simulants whose dielectric parameters were within $\pm 5\%$ of the recommended values. All tests were carried out within 24 hours of measuring the dielectric parameters.

The depth of the tissue simulant was 15.0 ± 0.5 cm measured from the ear reference point during system checking and device measurements.

4.3.1 Tissue Simulant Recipes

The following recipe(s) were used for Head and Body tissue stimulant(s):

800MHz band

Ingredient	Head (% by weight)	Body (% by weight)
Deionised Water	39.74	55.97
HEC	0.25	1.21
Sugar	58.31	41.76
Preservative	0.15	0.27
Salt	1.55	0.79

1900MHz band

Ingredient	Head (% by weight)	Body (% by weight)
Deionised Water	54.88	69.02
Butyl Diglycol	44.91	30.76
Salt	0.21	0.22

2450MHz band

Ingredient	Head (% by weight)	Body (% by weight)
Deionised Water	56.0	70.2
Tween 20	44.0	29.62
Salt	-	0.18

4.3.2 System Checking

The manufacturer calibrates the probes annually. Dielectric parameters of the tissue simulants were measured every day using the dielectric probe kit and the network analyser. A system check measurement was made following the determination of the dielectric parameters of the simulant, using the dipole validation kit. A power level of 250 mW was supplied to the dipole antenna, which was placed under the flat section of the twin SAM phantom. The system checking results (dielectric parameters and SAR values) are given in the table below.

System checking, head tissue simulant

f [MHz]	Description	SAR [W/kg], 1g	Dielectric Parameters		Temp [°C]
			ϵ_r	σ [S/m]	
835	Reference result	2.33	42.2	0.90	
	± 10% window	2.10 - 2.56			
	2006-12-19	2.48	41.7	0.92	21.1
	2006-12-22	2.15	42.5	0.93	21.5
1900	Reference result	9.83	39.4	1.42	
	± 10% window	8.85 - 10.81			
	2006-12-27	10.7	40.4	1.48	21.9
2450	Reference result	13.7	38.5	1.79	
	± 10% window	12.3 - 15.1			
	2006-12-28	14.4	37.7	1.86	21.7

System checking, body tissue simulant

<i>f</i> [MHz]	Description	SAR [W/kg], 1g	Dielectric Parameters		Temp [°C]
			ϵ_r	σ [S/m]	
835	Reference result	2.45	53.8	0.98	
	± 10% window	2.20 - 2.70			
	2006-12-22	2.47	54.8	0.98	21.4
1900	Reference result	10.0	54.8	1.54	
	± 10% window	9.0 - 11.0			
	2006-12-27	10.5	53.3	1.50	21.6
	2006-12-28	10.2	53.4	1.49	22.1
2450	Reference result	13.5	53.8	1.97	
	± 10% window	12.1 - 14.9			
	2006-12-29	14.5	51.5	1.99	21.1

Plots of the system checking scans are given in Appendix A.

4.3.3 Tissue Simulants used in the Measurements

Head tissue simulant measurements

<i>f</i> [MHz]	Description	Dielectric Parameters		Temp [°C]
		ϵ_r	σ [S/m]	
836	Recommended value	41.5	0.90	
	± 5% window	39.4 – 43.6	0.86 – 0.95	
	2006-12-19	41.7	0.92	21.1
	2006-12-22	42.5	0.93	21.5
1880	Recommended value	40.0	1.40	
	± 5% window	38.0 – 42.0	1.33 – 1.47	
	2006-12-27	40.4	1.45	21.9
2442	Recommended value	39.2	1.79	
	± 5% window	37.3 – 41.2	1.70 – 1.88	
	2006-12-28	37.7	1.85	21.7

Body tissue simulant measurements

f [MHz]	Description	Dielectric Parameters		Temp [°C]
		ϵ_r	σ [S/m]	
836	Recommended value	55.2	0.97	
	$\pm 5\%$ window	52.4 – 58.0	0.92 – 1.02	
	2006-12-22	54.8	0.98	21.4
1880	Recommended value	53.3	1.52	
	$\pm 5\%$ window	50.6 – 56.0	1.44 – 1.60	
	2006-12-27	53.4	1.48	21.6
	2006-12-28	53.5	1.47	22.1
2442	Recommended value	52.7	1.94	
	$\pm 5\%$ window	50.1 – 55.3	1.85 – 2.04	
	2006-12-29	51.6	1.98	21.1

5. DESCRIPTION OF THE TEST PROCEDURE

5.1 Device Holder

The device was placed in the device holder (illustrated below) that is supplied by SPEAG as an integral part of the Dasy system.



Device holder supplied by SPEAG

A Nokia designed spacer (illustrated below) was used to position the device within the SPEAG holder. The spacer positions the device so that the holder has minimal effect on the test results but still holds the device securely. The spacer was removed before the tests.



Nokia spacer

5.2 Test Positions

5.2.1 Against Phantom Head

Measurements were made in “cheek” and “tilt” positions on both the left hand and right hand sides of the phantom.

The positions used in the measurements were according to IEEE 1528 - 2003 "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques".

5.2.2 Body Worn Configuration

The device was placed in the SPEAG holder using the Nokia spacer and placed below the flat section of the phantom. The distance between the device and the phantom was kept at the separation distance indicated in the photo given in Cph_SAR_0709_05 using a separate flat spacer that was removed before the start of the measurements. The device was oriented with its antenna facing the phantom since this orientation gives higher results.

5.3 Scan Procedures

First, area scans were used for determination of the field distribution. Next, a zoom scan, a minimum of 5x5x7 points covering a volume of at least 30x30x30mm, was performed around the highest E-field value to determine the averaged SAR value. Drift was determined by measuring the same point at the start of the area scan and again at the end of the zoom scan.

5.4 SAR Averaging Methods

The maximum SAR value was averaged over a cube of tissue using interpolation and extrapolation.

The interpolation, extrapolation and maximum search routines within Dasy4 are all based on the modified Quadratic Shepard's method (Robert J. Renka, "Multivariate Interpolation Of Large Sets Of Scattered Data", University of North Texas ACM Transactions on Mathematical Software, vol. 14, no. 2, June 1988, pp. 139-148).

The interpolation scheme combines a least-square fitted function method with a weighted average method. A trivariate 3-D / bivariate 2-D quadratic function is computed for each measurement point and fitted to neighbouring points by a least-square method. For the zoom scan, inverse distance weighting is incorporated to fit distant points more accurately. The interpolating function is finally calculated as a weighted average of the quadratics.

In the zoom scan, the interpolation function is used to extrapolate the Peak SAR from the deepest measurement points to the inner surface of the phantom.

6. MEASUREMENT UNCERTAINTY

Table 6.1 – Measurement uncertainty evaluation

Uncertainty Component	Section in IEEE 1528	Tol. (%)	Prob Dist	Div	G_i	$G_i \cdot u_i$ (%)	ν_i
Measurement System							
Probe Calibration	E2.1	±5.9	N	1	1	±5.9	∞
Axial Isotropy	E2.2	±4.7	R	√3	$(1-c_p)^{1/2}$	±1.9	∞
Hemispherical Isotropy	E2.2	±9.6	R	√3	$(c_p)^{1/2}$	±3.9	∞
Boundary Effect	E2.3	±1.0	R	√3	1	±0.6	∞
Linearity	E2.4	±4.7	R	√3	1	±2.7	∞
System Detection Limits	E2.5	±1.0	R	√3	1	±0.6	∞
Readout Electronics	E2.6	±1.0	N	1	1	±1.0	∞
Response Time	E2.7	±0.8	R	√3	1	±0.5	∞
Integration Time	E2.8	±2.6	R	√3	1	±1.5	∞
RF Ambient Conditions - Noise	E6.1	±3.0	R	√3	1	±1.7	∞
RF Ambient Conditions - Reflections	E6.1	±3.0	R	√3	1	±1.7	∞
Probe Positioner Mechanical Tolerance	E6.2	±0.4	R	√3	1	±0.2	∞
Probe Positioning with respect to Phantom Shell	E6.3	±2.9	R	√3	1	±1.7	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E5	±3.9	R	√3	1	±2.3	∞
Test sample Related							
Test Sample Positioning	E4.2	±6.0	N	1	1	±6.0	11
Device Holder Uncertainty	E4.1	±5.0	N	1	1	±5.0	7
Output Power Variation - SAR drift measurement	6.6.3	±0.0	R	√3	1	±0.0	∞
Phantom and Tissue Parameters							
Phantom Uncertainty (shape and thickness tolerances)	E3.1	±4.0	R	√3	1	±2.3	∞
Conductivity Target - tolerance	E3.2	±5.0	R	√3	0.64	±1.8	∞
Conductivity - measurement uncertainty	E3.3	±5.5	N	1	0.64	±3.5	5
Permittivity Target - tolerance	E3.2	±5.0	R	√3	0.6	±1.7	∞
Permittivity - measurement uncertainty	E3.3	±2.9	N	1	0.6	±1.7	5
Combined Standard Uncertainty			RSS			±12.9	116
Coverage Factor for 95%			k=2				
Expanded Uncertainty						±25.8	

7. RESULTS

The measured Head SAR values for the test device are tabulated below:

850MHz Head SAR results

Option used	Test configuration		SAR, averaged over 1g (W/kg)		
			Ch 128 824.2 MHz	Ch 190 836.6 MHz	Ch 251 848.8 MHz
GSM	Power		21.6 dBm	22.6 dBm	24.6 dBm
Closed	Left	Cheek	-	0.031	-
		Tilt	-	-	-
	Right	Cheek	-	-	-
		Tilt	-	-	-
2-slot GPRS	Power		21.4 dBm	22.3 dBm	24.4 dBm
Closed	Left	Cheek	0.040	0.058	0.078
		Tilt	-	0.052	-
	Right	Cheek	-	0.049	-
		Tilt	-	0.040	-
3-slot GPRS	Power		19.5 dBm	20.5 dBm	22.3 dBm
Closed	Left	Cheek	-	0.057	-
		Tilt	-	-	-
	Right	Cheek	-	-	-
		Tilt	-	-	-
2-slot 8PSK EGPRS	Power		16.9 dBm	17.7 dBm	19.6 dBm
Closed	Left	Cheek	-	-	0.017
2-slot GPRS	Left Cheek, BT active		-	-	0.076

1900MHz Head SAR results

Option used	Test configuration		SAR, averaged over 1g (W/kg)		
			Ch 512 1850.2 MHz	Ch 661 1880.0 MHz	Ch 810 1909.8 MHz
GSM	Power		26.3 dBm	28.0 dBm	27.4 dBm
Closed	Left	Cheek	-	0.211	-
		Tilt	-	-	-
	Right	Cheek	-	-	-
		Tilt	-	-	-
2-slot GPRS	Power		26.3 dBm	28.0 dBm	27.5 dBm
Closed	Left	Cheek	-	0.413	-
		Tilt	0.431	0.463	0.420
	Right	Cheek	-	0.297	-
		Tilt	-	0.451	-
3-slot GPRS	Power		23.9 dBm	25.4 dBm	24.6 dBm
Closed	Left	Cheek	-	0.375	-
		Tilt	-	-	-
	Right	Cheek	-	-	-
		Tilt	-	-	-
2-slot 8PSK EGPRS	Power		22.6 dBm	24.4 dBm	24.2 dBm
Closed	Left	Tilt	-	0.155	-
2-slot GPRS	Left Cheek, BT active		-	0.406	-

2450MHz Head SAR results

Option used	Test configuration		SAR, averaged over 1g (W/kg)		
			Ch 1 2412.0 MHz	Ch 7 2442.0 MHz	Ch 11 2462.0 MHz
WLAN	Power		20.2 dBm	20.6 dBm	20.0 dBm
Closed	Left	Cheek	-	0.078	-
		Tilt	-	0.067	-
	Right	Cheek	0.102	0.103	0.123
		Tilt	-	0.071	-

The measured Body SAR values for the test device are tabulated below:

850MHz Body SAR results

Option used	Test configuration	SAR, averaged over 1g (W/kg)		
		Ch 128 824.2 MHz	Ch 190 836.6 MHz	Ch 251 848.8 MHz
2-slot GPRS	Power	21.4 dBm	22.3 dBm	24.4 dBm
Closed	Without headset	0.350	0.397	0.441
	Headset HS-47	0.253	0.343	0.404
2-slot GPRS	Without headset, BT active	-	-	0.447

1900MHz Body SAR results

Option used	Test configuration	SAR, averaged over 1g (W/kg)		
		Ch 512 1850.2 MHz	Ch 661 1880.0 MHz	Ch 810 1909.8 MHz
2-slot GPRS	Power	26.3 dBm	28.0 dBm	27.5 dBm
Closed	Without headset	0.411	0.428	0.500
	Headset HS-47	0.420	0.424	0.498
2-slot GPRS	Without headset, BT active	-	-	0.566

2450MHz Body SAR results

	Test configuration	SAR, averaged over 1g (W/kg)		
		Ch 1 2412.0 MHz	Ch 7 2442.0 MHz	Ch 11 2462.0 MHz
WLAN	Power	20.2 dBm	20.6 dBm	20.0 dBm
Closed	Without headset	0.065	0.079	0.056
	Headset HS-47	0.069	0.084	0.058

Simultaneous transmissions: Combined SAR results

Test configuration	Max. 1g SAR results			Combined 1g SAR values	
	WLAN	850MHz	1900MHz	WLAN + 850MHz	WLAN + 1900MHz
Head: Left, Cheek	0.078	0.078	0.413	0.156	0.491
Head: Left, Tilt	0.067	0.052	0.463	0.119	0.530
Head: Right, Cheek	0.123	0.049	0.297	0.172	0.420
Head: Right, Tilt	0.071	0.040	0.451	0.111	0.522
Body: Without Headset	0.079	0.447	0.566	0.526	0.645
Body: Headset HS-47	0.084	0.404	0.498	0.488	0.582

Combining the maximum SAR values of WLAN2450 and the cellular bands tends to overestimate the SAR value since their maxima do not necessarily occur in the same location.

Plots of the Measurement scans are given in Appendix B.

APPENDIX A: SYSTEM CHECKING SCANS

See the following pages

Date/Time: 2006-12-19 09:18:06

Test Laboratory: TCC Copenhagen

Type: D835V2; Serial: 4d042

Communication System: Continuous Wave

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Head 850; Medium Notes: Medium Temperature: $t=21.1$ C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.92$ mho/m; $\epsilon_r = 41.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(5.78, 5.78, 5.78); Calibrated: 2006-08-18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2006-08-09
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

d=15mm, Pin=250mW/Area Scan (61x121x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 2.70 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 55.1 V/m


Peak SAR (extrapolated) = 3.66 W/kg

SAR(1 g) = 2.48 mW/g

SAR(10 g) = 1.62 mW/g

Power Drift = -0.050 dB

Maximum value of SAR (measured) = 2.68 mW/g



Date/Time: 2006-12-22 10:18:59

Test Laboratory: TCC Copenhagen

Type: D835V2; Serial: 4d042

Communication System: Continuous Wave

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Head 850; Medium Notes: Medium Temperature: t=21.5 C

Medium parameters used: f = 835 MHz; σ = 0.926 mho/m; ϵ_r = 42.5; ρ = 1000 kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(5.78, 5.78, 5.78); Calibrated: 2006-08-18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2006-08-09
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

d=15mm, Pin=250mW/Area Scan (61x121x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 2.33 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 50.7 V/m


Peak SAR (extrapolated) = 3.20 W/kg

SAR(1 g) = 2.15 mW/g

SAR(10 g) = 1.4 mW/g

Power Drift = -0.066 dB

Maximum value of SAR (measured) = 2.34 mW/g



Date/Time: 2006-12-27 12:06:52

Test Laboratory: TCC Copenhagen

Type: D1900V2; Serial: 5d026

Communication System: Continuous Wave

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: Head 1900; Medium Notes: Medium Temperature: t=21.9C

Medium parameters used: f = 1900 MHz; σ = 1.48 mho/m; ϵ_r = 40.4; ρ = 1000 kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(4.92, 4.92, 4.92); Calibrated: 2006-08-31
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2006-02-16
- Phantom: SAM 6; Type: SAM Twin Phantom; Serial: TP-1301
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

d=10mm, Pin=250mW/Area Scan (71x71x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 12.1 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 90.7 V/m


Peak SAR (extrapolated) = 20.2 W/kg

SAR(1 g) = 10.7 mW/g

SAR(10 g) = 5.5 mW/g

Power Drift = 0.021 dB

Maximum value of SAR (measured) = 12.1 mW/g



Date/Time: 2006-12-28 08:29:13

Test Laboratory: TCC Copenhagen

Type: D2450V2; Serial: 750

Communication System: Continuous Wave

Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: Head 2450; Medium Notes: Medium Temperature: t=21.7 C

Medium parameters used: f = 2450 MHz; σ = 1.86 mho/m; ϵ_r = 37.7; ρ = 1000 kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(4.37, 4.37, 4.37); Calibrated: 2006-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn710; Calibrated: 2006-09-13
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

d=10mm, Pin=250mW/Area Scan (71x71x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 16.7 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 87.1 V/m

Peak SAR (extrapolated) = 30.6 W/kg

SAR(1 g) = 14.4 mW/g

SAR(10 g) = 6.65 mW/g

Power Drift = 0.070 dB

Maximum value of SAR (measured) = 16.1 mW/g



Date/Time: 2006-12-22 13:02:56

Test Laboratory: TCC Copenhagen

Type: D835V2; Serial: 4d042

Communication System: Continuous Wave

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Body 835; Medium Notes: Medium Temperature: $t = 21.4^{\circ}\text{C}$

Medium parameters used: $f = 835\text{ MHz}$; $\sigma = 0.976\text{ mho/m}$; $\epsilon_r = 54.8$; $\rho = 1000\text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(5.7, 5.7, 5.7); Calibrated: 2006-08-18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2006-08-09
- Phantom: SAM 2; Type: Twin Phantom; Serial: TP-1037
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

d=15mm, Pin=250mW/Area Scan (61x121x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Maximum value of SAR (interpolated) = 2.68 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 53.3 V/m


Peak SAR (extrapolated) = 3.56 W/kg

SAR(1 g) = 2.47 mW/g

SAR(10 g) = 1.64 mW/g

Power Drift = -0.033 dB

Maximum value of SAR (measured) = 2.68 mW/g



SAR Report

Cph_SAR_0709_04

Applicant: Nokia Corporation

Type: RA-6

Copyright © 2007 TCC Nokia

Date/Time: 2006-12-27 08:59:02

Test Laboratory: TCC Copenhagen

Type: D1900V2; Serial: 5d026

Communication System: Continuous Wave

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: Body 1900; Medium Notes: Medium Temperature: t=21.6 C

Medium parameters used: f = 1900 MHz; σ = 1.5 mho/m; ϵ_r = 53.3; ρ = 1000 kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3119; Probe Notes:
- ConvF(4.68, 4.68, 4.68); Calibrated: 2006-08-31
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn573; Calibrated: 2006-09-08
- Phantom: SAM 8; Type: SAM Twin Phantom; Serial: TP-1408
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

d=10mm, Pin=250mW 2/Area Scan (71x71x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 12.2 mW/g

d=10mm, Pin=250mW 2/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 87.0 V/m


Peak SAR (extrapolated) = 18.6 W/kg

SAR(1 g) = 10.5 mW/g

SAR(10 g) = 5.58 mW/g

Power Drift = 0.034 dB

Maximum value of SAR (measured) = 11.9 mW/g



Date/Time: 2006-12-28 07:17:57

Test Laboratory: TCC Copenhagen

Type: D1900V2; Serial: 5d026

Communication System: Continuous Wave

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: Body 1900; Medium Notes: Medium Temperature: t=22.1 C

Medium parameters used: f = 1900 MHz; σ = 1.49 mho/m; ϵ_r = 53.4; ρ = 1000 kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3119; Probe Notes:
- ConvF(4.68, 4.68, 4.68); Calibrated: 2006-08-31
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn573; Calibrated: 2006-09-08
- Phantom: SAM 8; Type: SAM Twin Phantom; Serial: TP-1408
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

d=10mm, Pin=250mW/Area Scan (71x71x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 11.7 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 75.3 V/m


Peak SAR (extrapolated) = 18.0 W/kg

SAR(1 g) = 10.2 mW/g

SAR(10 g) = 5.38 mW/g

Power Drift = 0.047 dB

Maximum value of SAR (measured) = 11.5 mW/g



Date/Time: 2006-12-29 09:46:58

Test Laboratory: TCC Copenhagen

Type: D2450V2; Serial: 750

Communication System: Continuous Wave

Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: Body 2450; Medium Notes: Medium Temperature: t=21.1 C

Medium parameters used: f = 2450 MHz; σ = 1.99 mho/m; ϵ_r = 51.5; ρ = 1000 kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(4.2, 4.2, 4.2); Calibrated: 2006-08-18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2006-08-09
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

d=10mm, Pin=250mW/Area Scan (71x71x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 17.1 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 91.6 V/m


Peak SAR (extrapolated) = 30.1 W/kg

SAR(1 g) = 14.5 mW/g

SAR(10 g) = 6.68 mW/g

Power Drift = 0.052 dB

Maximum value of SAR (measured) = 16.7 mW/g



APPENDIX B: MEASUREMENT SCANS

See the following pages

Date/Time: 2006-12-19 10:36:33

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: GSM850
Frequency: 836.6 MHz; Duty Cycle: 1:8.3
Medium: Head 850; Medium Notes: Medium Temperature: $t=21.1$ C
Medium parameters used: $f = 837$ MHz; $\sigma = 0.923$ mho/m; $\epsilon_r = 41.7$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY4 Configuration:
- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(5.78, 5.78, 5.78); Calibrated: 2006-08-18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2006-08-09
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Cheek position - Middle/Area Scan (61x111x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (interpolated) = 0.033 mW/g

Cheek position - Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 4.90 V/m
Peak SAR (extrapolated) = 0.051 W/kg


SAR(1 g) = 0.031 mW/g

SAR(10 g) = 0.019 mW/g

Power Drift = 0.113 dB

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.033 mW/g



Date/Time: 2006-12-19 17:42:40

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: 2-slot GPRS850
Frequency: 848.8 MHz; Duty Cycle: 1:4.2
Medium: Head 850; Medium Notes: Medium Temperature: $t=21.1$ C
Medium parameters used: $f = 849$ MHz; $\sigma = 0.935$ mho/m; $\epsilon_r = 41.5$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(5.78, 5.78, 5.78); Calibrated: 2006-08-18
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2006-08-09
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Cheek position - High/Area Scan (101x161x1): Measurement grid: $dx=10$ mm, $dy=10$ mm
Maximum value of SAR (interpolated) = 0.085 mW/g

Cheek position - High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 7.94 V/m


Peak SAR (extrapolated) = 0.130 W/kg

SAR(1 g) = 0.078 mW/g

SAR(10 g) = 0.047 mW/g

Power Drift = -0.104 dB

Maximum value of SAR (measured) = 0.087 mW/g



Date/Time: 2006-12-19 12:45:20

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: 2-slot GPRS850
Frequency: 836.6 MHz; Duty Cycle: 1:4.2
Medium: Head 850; Medium Notes: Medium Temperature: $t=21.1$ C
Medium parameters used: $f = 837$ MHz; $\sigma = 0.923$ mho/m; $\epsilon_r = 41.7$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY4 Configuration:
- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(5.78, 5.78, 5.78); Calibrated: 2006-08-18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2006-08-09
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Tilt position - Middle/Area Scan (61x111x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (interpolated) = 0.057 mW/g

Tilt position - Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm


Reference Value = 5.76 V/m
Peak SAR (extrapolated) = 0.091 W/kg

SAR(1 g) = 0.052 mW/g

SAR(10 g) = 0.029 mW/g

Power Drift = 0.172 dB

Maximum value of SAR (measured) = 0.057 mW/g



Date/Time: 2006-12-19 13:01:44

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: 2-slot GPRS850
Frequency: 836.6 MHz; Duty Cycle: 1:4.2
Medium: Head 850; Medium Notes: Medium Temperature: $t=21.1$ C
Medium parameters used: $f = 837$ MHz; $\sigma = 0.923$ mho/m; $\epsilon_r = 41.7$; $\rho = 1000$ kg/m³
Phantom section: Right Section

DASY4 Configuration:
- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(5.78, 5.78, 5.78); Calibrated: 2006-08-18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2006-08-09
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Cheek position - Middle/Area Scan (61x111x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (interpolated) = 0.051 mW/g

Cheek position - Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm


Reference Value = 7.12 V/m
Peak SAR (extrapolated) = 0.070 W/kg

SAR(1 g) = 0.049 mW/g

SAR(10 g) = 0.036 mW/g

Power Drift = -0.072 dB

Maximum value of SAR (measured) = 0.050 mW/g



Date/Time: 2006-12-19 13:16:35

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: 2-slot GPRS850
Frequency: 836.6 MHz; Duty Cycle: 1:4.2
Medium: Head 850; Medium Notes: Medium Temperature: $t=21.1$ C
Medium parameters used: $f = 837$ MHz; $\sigma = 0.923$ mho/m; $\epsilon_r = 41.7$; $\rho = 1000$ kg/m³
Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(5.78, 5.78, 5.78); Calibrated: 2006-08-18
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2006-08-09
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Tilt position - Middle/Area Scan (61x111x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (interpolated) = 0.045 mW/g

Tilt position - Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 6.25 V/m


Peak SAR (extrapolated) = 0.068 W/kg

SAR(1 g) = 0.040 mW/g

SAR(10 g) = 0.024 mW/g

Power Drift = 0.102 dB

Maximum value of SAR (measured) = 0.043 mW/g



Date/Time: 2006-12-19 11:40:46

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: 3-slot GPRS850
Frequency: 836.6 MHz; Duty Cycle: 1:2.8
Medium: Head 850; Medium Notes: Medium Temperature: $t=21.1$ C
Medium parameters used: $f = 837$ MHz; $\sigma = 0.923$ mho/m; $\epsilon_r = 41.7$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY4 Configuration:
- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(5.78, 5.78, 5.78); Calibrated: 2006-08-18
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2006-08-09
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Cheek position - Middle/Area Scan (61x111x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (interpolated) = 0.062 mW/g

Cheek position - Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 6.69 V/m
Peak SAR (extrapolated) = 0.094 W/kg


SAR(1 g) = 0.057 mW/g

SAR(10 g) = 0.036 mW/g

Power Drift = 0.124 dB

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.062 mW/g



Date/Time: 2006-12-22 11:03:10

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: 2-slot 8PSK EGPRS850
Frequency: 848.8 MHz; Duty Cycle: 1:4.2
Medium: Head 850; Medium Notes: Medium Temperature: $t=21.5$ C
Medium parameters used: $f = 849$ MHz; $\sigma = 0.941$ mho/m; $\epsilon_r = 42.3$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY4 Configuration:
- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(5.78, 5.78, 5.78); Calibrated: 2006-08-18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2006-08-09
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Cheek position - Middle/Area Scan (61x111x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (interpolated) = 0.019 mW/g

Cheek position - Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 3.49 V/m
Peak SAR (extrapolated) = 0.029 W/kg


SAR(1 g) = 0.017 mW/g

SAR(10 g) = 0.011 mW/g

Power Drift = 0.063 dB

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.018 mW/g



Date/Time: 2006-12-27 12:47:18

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: GSM 1900
Frequency: 1880 MHz; Duty Cycle: 1:8.3
Medium: Head 1900; Medium Notes: Medium Temperature: $t=21.9^{\circ}\text{C}$
Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.45 \text{ mho/m}$; $\epsilon_r = 40.4$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

DASY4 Configuration:
- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(4.92, 4.92, 4.92); Calibrated: 2006-08-31
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2006-02-16
- Phantom: SAM 6; Type: SAM Twin Phantom; Serial: TP-1301
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Cheek position - Middle/Area Scan (61x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 0.220 mW/g

Cheek position - Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.1 V/m


Peak SAR (extrapolated) = 0.382 W/kg

SAR(1 g) = 0.211 mW/g

SAR(10 g) = 0.116 mW/g

Power Drift = -0.014 dB

Maximum value of SAR (measured) = 0.237 mW/g



Date/Time: 2006-12-27 13:06:46

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: 2-slot GPRS1900
Frequency: 1880 MHz; Duty Cycle: 1:4.2
Medium: Head 1900; Medium Notes: Medium Temperature: t=21.9C
Medium parameters used: f = 1880 MHz; σ = 1.45 mho/m; ϵ_r = 40.4; ρ = 1000 kg/m³
Phantom section: Left Section

DASY4 Configuration:
- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(4.92, 4.92, 4.92); Calibrated: 2006-08-31
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2006-02-16
- Phantom: SAM 6; Type: SAM Twin Phantom; Serial: TP-1301
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Cheek position - Middle/Area Scan (61x111x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.436 mW/g

Cheek position - Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm


Reference Value = 14.0 V/m
Peak SAR (extrapolated) = 0.747 W/kg

SAR(1 g) = 0.413 mW/g

SAR(10 g) = 0.228 mW/g

Power Drift = -0.182 dB

Maximum value of SAR (measured) = 0.455 mW/g



Date/Time: 2006-12-27 13:48:29

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: 2-slot GPRS1900
Frequency: 1880 MHz; Duty Cycle: 1:4.2
Medium: Head 1900; Medium Notes: Medium Temperature: $t=21.9^{\circ}\text{C}$
Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.45 \text{ mho/m}$; $\epsilon_r = 40.4$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(4.92, 4.92, 4.92); Calibrated: 2006-08-31
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2006-02-16
- Phantom: SAM 6; Type: SAM Twin Phantom; Serial: TP-1301
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Tilt position - Middle/Area Scan (61x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 0.530 mW/g

Tilt position - Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.6 V/m


Peak SAR (extrapolated) = 0.865 W/kg

SAR(1 g) = 0.463 mW/g

SAR(10 g) = 0.260 mW/g

Power Drift = -0.157 dB

Maximum value of SAR (measured) = 0.513 mW/g



Date/Time: 2006-12-27 14:02:23

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: 2-slot GPRS1900
Frequency: 1880 MHz; Duty Cycle: 1:4.2
Medium: Head 1900; Medium Notes: Medium Temperature: t=21.9C
Medium parameters used: f = 1880 MHz; σ = 1.45 mho/m; ϵ_r = 40.4; ρ = 1000 kg/m³
Phantom section: Right Section

DASY4 Configuration:
- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(4.92, 4.92, 4.92); Calibrated: 2006-08-31
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2006-02-16
- Phantom: SAM 6; Type: SAM Twin Phantom; Serial: TP-1301
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Cheek position - Middle/Area Scan (61x111x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.316 mW/g

Cheek position - Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 15.2 V/m


Peak SAR (extrapolated) = 0.489 W/kg

SAR(1 g) = 0.297 mW/g

SAR(10 g) = 0.181 mW/g

Power Drift = -0.109 dB

Maximum value of SAR (measured) = 0.325 mW/g



Date/Time: 2006-12-27 14:17:36

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: 2-slot GPRS1900
Frequency: 1880 MHz; Duty Cycle: 1:4.2
Medium: Head 1900; Medium Notes: Medium Temperature: t=21.9C
Medium parameters used: f = 1880 MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 40.4$; $\rho = 1000$ kg/m³
Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(4.92, 4.92, 4.92); Calibrated: 2006-08-31
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2006-02-16
- Phantom: SAM 6; Type: SAM Twin Phantom; Serial: TP-1301
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Tilt position - Middle/Area Scan (61x111x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.496 mW/g

Tilt position - Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 18.6 V/m


Peak SAR (extrapolated) = 0.749 W/kg

SAR(1 g) = 0.451 mW/g

SAR(10 g) = 0.262 mW/g

Power Drift = -0.019 dB

Maximum value of SAR (measured) = 0.496 mW/g



Date/Time: 2006-12-27 13:29:25

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: 3-slot GPRS1900
Frequency: 1880 MHz; Duty Cycle: 1:2.8
Medium: Head 1900; Medium Notes: Medium Temperature: $t=21.9^{\circ}\text{C}$
Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.45 \text{ mho/m}$; $\epsilon_r = 40.4$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

DASY4 Configuration:
- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(4.92, 4.92, 4.92); Calibrated: 2006-08-31
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2006-02-16
- Phantom: SAM 6; Type: SAM Twin Phantom; Serial: TP-1301
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Cheek position - Middle/Area Scan (61x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 0.396 mW/g

Cheek position - Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.2 V/m


Peak SAR (extrapolated) = 0.672 W/kg

SAR(1 g) = 0.375 mW/g

SAR(10 g) = 0.208 mW/g

Power Drift = -0.132 dB

Maximum value of SAR (measured) = 0.413 mW/g



Date/Time: 2006-12-27 15:20:55

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: 2-slot 8PSK EGPRS1900
Frequency: 1880 MHz; Duty Cycle: 1:4.2
Medium: Head 1900; Medium Notes: Medium Temperature: $t=21.9^{\circ}\text{C}$
Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.45 \text{ mho/m}$; $\epsilon_r = 40.4$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

DASY4 Configuration:
- Probe: ES3DV3 - SN3118; Probe Notes:
- ConvF(4.92, 4.92, 4.92); Calibrated: 2006-08-31
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn501; Calibrated: 2006-02-16
- Phantom: SAM 6; Type: SAM Twin Phantom; Serial: TP-1301
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Tilt position - Middle/Area Scan (61x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 0.169 mW/g

Tilt position - Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.1 V/m


Peak SAR (extrapolated) = 0.287 W/kg

SAR(1 g) = 0.155 mW/g

SAR(10 g) = 0.087 mW/g

Power Drift = -0.401 dB

Maximum value of SAR (measured) = 0.173 mW/g



Date/Time: 2006-12-28 09:53:05

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: WLAN2450
Frequency: 2442 MHz; Duty Cycle: 1:1
Medium: Head 2450; Medium Notes: Medium Temperature: $t=21.7\text{ C}$
Medium parameters used: $f = 2442\text{ MHz}$; $\sigma = 1.85\text{ mho/m}$; $\epsilon_r = 37.7$; $\rho = 1000\text{ kg/m}^3$
Phantom section: Left Section

DASY4 Configuration:
- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(4.37, 4.37, 4.37); Calibrated: 2006-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn710; Calibrated: 2006-09-13
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Cheek position - Middle/Area Scan (81x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 0.083 mW/g

Cheek position - Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$


Reference Value = 3.89 V/m
Peak SAR (extrapolated) = 0.155 W/kg

SAR(1 g) = 0.078 mW/g

SAR(10 g) = 0.040 mW/g

Power Drift = 0.387 dB

Maximum value of SAR (measured) = 0.085 mW/g



Date/Time: 2006-12-28 10:17:51

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: WLAN2450
Frequency: 2442 MHz; Duty Cycle: 1:1
Medium: Head 2450; Medium Notes: Medium Temperature: t=21.7 C
Medium parameters used: f = 2442 MHz; $\sigma = 1.85$ mho/m; $\epsilon_r = 37.7$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY4 Configuration:
- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(4.37, 4.37, 4.37); Calibrated: 2006-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn710; Calibrated: 2006-09-13
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Tilt position - Middle/Area Scan (81x111x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.082 mW/g

Tilt position - Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.94 V/m
Peak SAR (extrapolated) = 0.129 W/kg


SAR(1 g) = 0.067 mW/g

SAR(10 g) = 0.035 mW/g

Power Drift = 0.102 dB

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.075 mW/g



Date/Time: 2006-12-28 12:06:35

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: WLAN2450
Frequency: 2462 MHz; Duty Cycle: 1:1
Medium: Head 2450; Medium Notes: Medium Temperature: $t=21.7\text{ C}$
Medium parameters used: $f = 2462\text{ MHz}$; $\sigma = 1.87\text{ mho/m}$; $\epsilon_r = 37.6$; $\rho = 1000\text{ kg/m}^3$
Phantom section: Right Section

DASY4 Configuration:
- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(4.37, 4.37, 4.37); Calibrated: 2006-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn710; Calibrated: 2006-09-13
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Cheek position - High/Area Scan (81x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 0.142 mW/g

Cheek position - High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$


Reference Value = 4.88 V/m
Peak SAR (extrapolated) = 0.251 W/kg

SAR(1 g) = 0.123 mW/g

SAR(10 g) = 0.063 mW/g

Power Drift = 0.125 dB

Maximum value of SAR (measured) = 0.134 mW/g



Date/Time: 2006-12-28 11:03:54

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: WLAN2450
Frequency: 2442 MHz; Duty Cycle: 1:1
Medium: Head 2450; Medium Notes: Medium Temperature: $t=21.7\text{ C}$
Medium parameters used: $f = 2442\text{ MHz}$; $\sigma = 1.85\text{ mho/m}$; $\epsilon_r = 37.7$; $\rho = 1000\text{ kg/m}^3$
Phantom section: Right Section

DASY4 Configuration:
- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(4.37, 4.37, 4.37); Calibrated: 2006-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn710; Calibrated: 2006-09-13
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Tilt position - Middle/Area Scan (81x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 0.079 mW/g

Tilt position - Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$


Reference Value = 6.60 V/m
Peak SAR (extrapolated) = 0.138 W/kg

SAR(1 g) = 0.071 mW/g

SAR(10 g) = 0.035 mW/g

Power Drift = 0.042 dB

Maximum value of SAR (measured) = 0.078 mW/g



Date/Time: 2006-12-22 14:17:11

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: 2-slot GPRS850
Frequency: 848.8 MHz; Duty Cycle: 1:4.2
Medium: Body 835; Medium Notes: Medium Temperature: $t = 21.4^{\circ}\text{C}$
Medium parameters used: $f = 849\text{ MHz}$; $\sigma = 0.991\text{ mho/m}$; $\epsilon_r = 54.7$; $\rho = 1000\text{ kg/m}^3$
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(5.7, 5.7, 5.7); Calibrated: 2006-08-18
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2006-08-09
- Phantom: SAM 2; Type: Twin Phantom; Serial: TP-1037
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Body - High - No Accessory/Area Scan (61x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 0.471 mW/g

Body - High - No Accessory/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.1 V/m


Peak SAR (extrapolated) = 0.546 W/kg

SAR(1 g) = 0.441 mW/g

SAR(10 g) = 0.334 mW/g

Power Drift = 0.012 dB

Maximum value of SAR (measured) = 0.462 mW/g



Date/Time: 2006-12-22 14:53:41

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: 2-slot GPRS850
Frequency: 848.8 MHz; Duty Cycle: 1:4.2
Medium: Body 835; Medium Notes: Medium Temperature: $t = 21.4^{\circ}\text{C}$
Medium parameters used: $f = 849\text{ MHz}$; $\sigma = 0.991\text{ mho/m}$; $\epsilon_r = 54.7$; $\rho = 1000\text{ kg/m}^3$
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(5.7, 5.7, 5.7); Calibrated: 2006-08-18
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2006-08-09
- Phantom: SAM 2; Type: Twin Phantom; Serial: TP-1037
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Body - High - HS-47/Area Scan (61x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 0.428 mW/g

Body - High - HS-47/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.0 V/m


Peak SAR (extrapolated) = 0.533 W/kg

SAR(1 g) = 0.404 mW/g

SAR(10 g) = 0.302 mW/g

Power Drift = 0.001 dB

Maximum value of SAR (measured) = 0.426 mW/g



Date/Time: 2006-12-22 15:07:57

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: 2-slot GPRS850
Frequency: 848.8 MHz; Duty Cycle: 1:4.2
Medium: Body 835; Medium Notes: Medium Temperature: $t = 21.4^\circ\text{C}$
Medium parameters used: $f = 849\text{ MHz}$; $\sigma = 0.991\text{ mho/m}$; $\epsilon_r = 54.7$; $\rho = 1000\text{ kg/m}^3$
Phantom section: Flat Section

DASY4 Configuration:
- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(5.7, 5.7, 5.7); Calibrated: 2006-08-18
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2006-08-09
- Phantom: SAM 2; Type: Twin Phantom; Serial: TP-1037
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Body - High - No Accessory - BT active/Area Scan (61x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 0.477 mW/g

Body - High - No Accessory - BT active/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$


Reference Value = 22.3 V/m
Peak SAR (extrapolated) = 0.572 W/kg

SAR(1 g) = 0.447 mW/g

SAR(10 g) = 0.337 mW/g

Power Drift = -0.017 dB

Maximum value of SAR (measured) = 0.471 mW/g



Date/Time: 2006-12-28 08:21:25

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: 2-slot GPRS1900
Frequency: 1909.8 MHz; Duty Cycle: 1:4.2
Medium: Body 1900; Medium Notes: Medium Temperature: $t=22.1\text{ }^{\circ}\text{C}$
Medium parameters used: $f = 1910\text{ MHz}$; $\sigma = 1.51\text{ mho/m}$; $\epsilon_r = 53.4$; $\rho = 1000\text{ kg/m}^3$
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3119; Probe Notes:
- ConvF(4.68, 4.68, 4.68); Calibrated: 2006-08-31
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn573; Calibrated: 2006-09-08
- Phantom: SAM 8; Type: SAM Twin Phantom; Serial: TP-1408
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Body - High - No Accessory/Area Scan (61x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 0.563 mW/g

Body - High - No Accessory/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 9.31 V/m


Peak SAR (extrapolated) = 0.800 W/kg

SAR(1 g) = 0.500 mW/g

SAR(10 g) = 0.297 mW/g

Power Drift = -0.166 dB

Maximum value of SAR (measured) = 0.536 mW/g



Date/Time: 2006-12-28 08:33:41

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: 2-slot GPRS1900
Frequency: 1909.8 MHz; Duty Cycle: 1:4.2
Medium: Body 1900; Medium Notes: Medium Temperature: $t=22.1\text{ }^{\circ}\text{C}$
Medium parameters used: $f = 1910\text{ MHz}$; $\sigma = 1.51\text{ mho/m}$; $\epsilon_r = 53.4$; $\rho = 1000\text{ kg/m}^3$
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3119; Probe Notes:
- ConvF(4.68, 4.68, 4.68); Calibrated: 2006-08-31
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn573; Calibrated: 2006-09-08
- Phantom: SAM 8; Type: SAM Twin Phantom; Serial: TP-1408
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Body - High - HS-47/Area Scan (61x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 0.563 mW/g

Body - High - HS-47/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 9.10 V/m


Peak SAR (extrapolated) = 0.791 W/kg

SAR(1 g) = 0.498 mW/g

SAR(10 g) = 0.297 mW/g

Power Drift = 0.015 dB

Maximum value of SAR (measured) = 0.532 mW/g



Date/Time: 2006-12-28 08:50:21

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: 2-slot GPRS1900
Frequency: 1909.8 MHz; Duty Cycle: 1:4.2
Medium: Body 1900; Medium Notes: Medium Temperature: $t=22.1\text{ }^{\circ}\text{C}$
Medium parameters used: $f = 1910\text{ MHz}$; $\sigma = 1.51\text{ mho/m}$; $\epsilon_r = 53.4$; $\rho = 1000\text{ kg/m}^3$
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3119; Probe Notes:
- ConvF(4.68, 4.68, 4.68); Calibrated: 2006-08-31
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn573; Calibrated: 2006-09-08
- Phantom: SAM 8; Type: SAM Twin Phantom; Serial: TP-1408
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Body - High - No Accessory - BT Active/Area Scan (61x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 0.641 mW/g

Body - High - No Accessory - BT Active/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 9.84 V/m


Peak SAR (extrapolated) = 0.912 W/kg

SAR(1 g) = 0.566 mW/g

SAR(10 g) = 0.334 mW/g

Power Drift = -0.047 dB

Maximum value of SAR (measured) = 0.618 mW/g



Date/Time: 2006-12-29 11:57:52

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: WLAN2450
Frequency: 2442 MHz; Duty Cycle: 1:1
Medium: Body 2450; Medium Notes: Medium Temperature: $t=21.1\text{ C}$
Medium parameters used: $f = 2442\text{ MHz}$; $\sigma = 1.98\text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000\text{ kg/m}^3$
Phantom section: Flat Section

DASY4 Configuration:
- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(4.2, 4.2, 4.2); Calibrated: 2006-08-18
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2006-08-09
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Body - Middle - No Accessory/Area Scan (121x171x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$
Maximum value of SAR (interpolated) = 0.086 mW/g

Body - Middle - No Accessory/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$


Reference Value = 4.37 V/m
Peak SAR (extrapolated) = 0.145 W/kg

SAR(1 g) = 0.079 mW/g

SAR(10 g) = 0.046 mW/g

Power Drift = 0.090 dB

Maximum value of SAR (measured) = 0.085 mW/g



Date/Time: 2006-12-29 12:15:38

Test Laboratory: TCC Copenhagen
Type: RA-6; Serial: 004400911738217

Communication System: WLAN2450
Frequency: 2442 MHz; Duty Cycle: 1:1
Medium: Body 2450; Medium Notes: Medium Temperature: $t=21.1\text{ }^{\circ}\text{C}$
Medium parameters used: $f = 2442\text{ MHz}$; $\sigma = 1.98\text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000\text{ kg/m}^3$
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(4.2, 4.2, 4.2); Calibrated: 2006-08-18
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2006-08-09
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Body - Middle - HS-47/Area Scan (121x171x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$
Maximum value of SAR (interpolated) = 0.091 mW/g

Body - Middle - HS-47/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 4.30 V/m


Peak SAR (extrapolated) = 0.155 W/kg

SAR(1 g) = 0.084 mW/g

SAR(10 g) = 0.048 mW/g

Power Drift = 0.014 dB

Maximum value of SAR (measured) = 0.091 mW/g



APPENDIX C: RELEVANT PAGES FROM PROBE CALIBRATION REPORT(S)

See the following pages

APPENDIX D: RELEVANT PAGES FROM DIPOLE VALIDATION KIT REPORT(S)

See the following pages