



## **Test Setup photos for RM-718 SAR Compliance Test Report**

Test report no.: **Template version: Testing laboratory:**  SAR Photo RM-718 13 15.0

TCC Nokia Salo Laboratory

P.O.Box 86

Joensuunkatu 7H / Kiila 1B FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 45220

Date of report: **Number of pages:** 

Client:

2010-11-16

**Nokia Corporation** 

P.O. Box 86 Joensuunkatu 7

FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 44277

Responsible test

engineer:

Janne Hirsimäki

**Product contact** person:

Kari Koskela

IC: 661V-RM718

Measurements made by:

Alina Tähkäpää

**Tested device:** 

FCC ID:

RM-718

PYARM-718

**Supplement reports:** 

FCC\_RM-718\_12

Testing has been carried out in accordance with:

47CFR §2.1093

Radiofreguency Radiation Exposure Evaluation: Portable Devices

FCC OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01)

Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency

**Electromagnetic Fields** 

RSS-102

Evaluation Procedure for Mobile and Portable Radio Transmitters with Respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields

IEEE 1528 - 2003

IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices:

Measurement Technique

**Documentation:** 

The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.

**Test results:** 

The tested device complies with the requirements in respect of all parameters subject to the test. The test results and statements relate only to the items tested. The test report shall not be reproduced except in full, without written approval of the laboratory.

**Date and signatures:** 

For the contents:





# CONTENTS

1.	SUMI	MARY OF SAR TEST REPORT	3
	1.1	TEST DETAILS	=
	1.2	PICTURE OF THE DEVICE	3
2.	TEST	POSITIONS	6
	2.1	Against Phantom Head	4
		BODY WORN CONFIGURATION	





## 1. SUMMARY OF SAR TEST REPORT

## 1.1 Test Details

Period of test	2010-11-03
SN, HW and SW numbers of	SN: 353759/04/002344/6, HW: 0500 ES6.2, SW: 012.006, DUT: 15338
tested device	
Batteries used in testing	BL-5CT, DUT: 15335, 15336, 15337
Headsets used in testing	WH-102, DUT: 15334
Other accessories used in	-
testing	
State of sample	Prototype unit
Notes	-

### 1.2 Picture of the Device









#### 2. TEST POSITIONS

#### 2.1 Against Phantom Head

Measurements were made in "cheek" and "tilt" positions on both the left hand and right hand sides of the phantom.

The positions used in the measurements were according to IEEE 1528 - 2003 "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques".






Photo of the device in "cheek" position

Photo of the device in "tilt" position

#### 2.2 Body Worn Configuration

The device was placed in the SPEAG holder using the Nokia spacer and placed below the flat section of the phantom. The distance between the device and the phantom was kept at the separation distance indicated in the photo below using a separate flat spacer that was removed before the start of the measurements. The device was oriented with its back facing the phantom since this orientation gives higher results.



Photo of the device positioned for Body SAR measurement. The spacer was removed for the tests.