



UL Apex Co., Ltd.

Test report No. : 27DE0137-HO-C-1
Page : 1 of 46
Issued date : March 14, 2007
Revised date : March 22, 2007
FCC ID : PZWBHT400SLBWB

RADIO TEST REPORT

Test Report No. : 27DE0137-HO-C-1

Applicant : DENSO WAVE INCORPORATED
Type of Equipment : Barcode Handy Terminal
Model No. : BHT-470BWB-CE
FCC ID : PZWBHT400SLBWB
Test standard : FCC Part 15 Subpart C
Section 15.207, Section 15.247: 2006
Test Result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Apex Co., Ltd.
2. The results in this report apply only to the sample tested.
3. This equipment is in compliance with the above regulation.
4. The test results in this report are traceable to the national or international standards.

Date of test:


November 27, 2006 to February 9, 2007

Tested by:


Makoto Kosaka
EMC Services

Approved by :


Naoki Sakamoto
Assistant Manager of EMC Services



This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.

*As for the range of Accreditation in NVLAP, you may refer to the WEB address, <http://ulapex.jp/emc/nvlap.htm>

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Faxsimile : +81 596 24 8124

MF060b(14.06.06)

CONTENTS	PAGE
SECTION 1: Client information	3
SECTION 2: Equipment under test (E.U.T.).....	3
SECTION 3: Test specification, procedures & results.....	5
SECTION 4: Operation of E.U.T. during testing	8
SECTION 5: Conducted Emission.....	11
SECTION 6: Spurious Emission	12
SECTION 7: Bandwidth.....	13
SECTION 8: Maximum Peak Output Power	13
SECTION 9: Carrier Frequency Separation	13
SECTION 10: Number of Hopping Frequency	13
SECTION 11: Dwell time.....	13
APPENDIX 1: Photographs of test setup	14
Conducted Emission	14
Spurious Emission (Radiated)	15
Worst Case Position (Horizontal: Z-axis/ Vertical:Y-axis).....	16
APPENDIX 2: Data of EMI test.....	17
Carrier Frequency Separation	21
20dB Bandwidth.....	23
Number of Hopping Frequency	25
Dwell time	27
Maximum Peak Output Power	30
Radiated Spurious Emission (below 1GHz)	31
Conducted Spurious Emission.....	39
99% Occupied Bandwidth(BT)	44
APPENDIX 3:Test instruments	45

SECTION 1: Client information

Company Name : DENSO WAVE INCORPORATED
Address : 1-1 Showa-cho Kariya-shi Aichi, 448-8661 Japan

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment : Barcode Handy Terminal
Model No. : BHT-470BWB-CE
Serial No. : 5496310346600007
Rating : DC3.7V (Li-ion Battery)
Country of Manufacture : Japan
Receipt Date of Sample : November 16, 2006
Condition of EUT : Production prototype
(Not for Sale: This sample is equivalent to mass-produced items.)
Modification of EUT : No modification by the test lab.

2.2 Product Description

Model No: BHT-470BWB-CE is the Barcode Handy Terminal with IEEE802.11b/g Wireless LAN and Bluetooth. The Barcode Handy Terminal scans the barcode, sends and receives the data of barcode by radio. BHT-470BWB-CE has a variant model, BHT-420BWB-CE. The difference of BHT-470BWB-CE and BHT-420BWB-CE is number of keypads as follows, and the radio and electric parts of the both models are identical.

Model No.	Key type		Radio module type	
	50-key	31-key	IEEE802.11b/g Wireless LAN	Bluetooth
BHT-470BWB-CE	<input checked="" type="radio"/>	-	<input checked="" type="radio"/>	<input checked="" type="radio"/>
BHT-420BWB-CE	-	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>

The distance of IEEE802.11b/g Wireless LAN antenna and Bluetooth antenna is within 20cm. IEEE802.11b/g Wireless LAN and Bluetooth modules can transmit simultaneously.

Clock frequency in the system : [CPU] 32.768kHz, 13MHz (13MHz x 40 = 520MHz: Max Speed)
[Sub-CPU] 32.768kHz, 12.288MHz
[RTC] 32.768kHz
[IEEE802.11b/g Wireless LAN] 40MHz
[Bluetooth] 16MHz

Equipment Type : Transceiver

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(14.06.06)

		IEEE802.11b/g Wireless LAN
Frequency band	Lower limit	2412MHz
	Upper limit	2462MHz
Type of Modulation		DSSS, OFDM
Antenna Type		Multi-layer Mono Pole
Antenna Connector Type		Coaxial Connector
Antenna Gain		3.3dBi
ITU code		G1D(DSSS), D1D(OFDM)
Power Supply (Inner)		DC 3.3V

* For WLAN module test, please see UL Apex Test Report No. 27DE0137-HO-A.

		Bluetooth
Frequency band	Lower limit	2402MHz
	Upper limit	2480MHz
Bandwidth & Channel spacing		1MHz & 1MHz / CH
Type of Modulation		FHSS
Antenna Type		Multi-layer Mono Pole
Antenna Connector Type		Coaxial Connector
Antenna Gain		3.3dBi
ITU code		F1D
Power Supply (Inner)		DC 3.0V

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(14.06.06)

SECTION 3: Test specification, procedures & results

3.1 Test Specification

Test Specification : FCC Part15 Subpart C : 2006

Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators
Section 15.207 Conducted limits : 2006
Section 15.247 Operation within the bands 902-928MHz,
2400-2483.5MHz, and 5725-5850MHz : 2006

FCC 15.31 (e)

This EUT provides stable voltage(DC3.0V) constantly to RF Module regardless of input voltage. Therefore, this EUT complies with the requirement.

FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT. Therefore, the equipment complies with the antenna requirement of Section 15.203.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(14.06.06)

3.2 Procedures and results

No.	Item	Test Procedure	Specification	Remarks	Deviation	Worst Margin*0)	Results
1	Conducted emission	FCC: ANSI C63.4:2003 7. AC powerline conducted emission measurements	FCC: Section 15.207	-	N/A	24.5dB 4.60000MHz AV, L	Complied
		IC: RSS-Gen 7.2.2	IC: RSS-Gen 7.2.2				
2	Carrier Frequency Separation	FCC: ANSI C63.4:2003 13. Measurement of intentional radiators	FCC: Section15.247(a)(1)	Conducted	N/A	See data.	Complied
		IC: -	IC: RSS-210 A8.1 (2)				
3	20dB Bandwidth	FCC: ANSI C63.4:2003 13. Measurement of intentional radiators	FCC: Section15.247(a)(1)	Conducted	N/A	Complied	Complied
		IC: -	IC: RSS-210 A8.1 (1)				
4	Number of Hopping Frequency	FCC: ANSI C63.4:2003 13. Measurement of intentional radiators	FCC: Section15.247(a)(1)(iii)	Conducted	N/A	See data.	Complied
		IC: -	IC: RSS-210 A8.1 (4)				
5	Dwell time	FCC: ANSI C63.4:2003 13. Measurement of intentional radiators	FCC: Section15.247(a)(1)(iii)	Conducted	N/A	Complied	Complied
		IC: -	IC: RSS-210 A8.1 (4)				
6	Maximum Peak Output Power	FCC: ANSI C63.4:2003 13. Measurement of intentional radiators	FCC: Section15.247(b)(1)	Conducted	N/A	[Tx] 0.9dB 363.988MHz Horizontal [Rx] 1.0dB 363.778MHz Horizontal	Complied
		IC: RSS-Gen 4.6	IC: RSS-210 A8.4 (2)				
7	Band Edge Compliance	FCC: ANSI C63.4:2003 13. Measurement of intentional radiators	FCC: Section15.247(d)	Conducted	N/A	Complied	Complied
		IC: -	IC: RSS-210 A8.5				
8	Spurious Emission	FCC: ANSI C63.4:2003 13. Measurement of intentional radiators	FCC: Section15.247(d)	Conducted/ Radiated	N/A	[Tx] 0.9dB 363.988MHz Horizontal [Rx] 1.0dB 363.778MHz Horizontal	Complied
		IC: RSS-Gen 4.7 RSS-Gen 4.8	IC: RSS-210 A8.5 RSS-Gen 7.2.1 and 7.2.3				

Note: UL Apex's EMI Work Procedures No.QPM05 and QPM15.

*0) The result is rounded off to the second decimal place. Therefore, there may be 0.1 difference for the result.

*These tests were also referred to FCC Public Notice DA 00-705 "Guidance on Measurement for Frequency Hopping Spread Spectrum Systems".

*These tests were performed without any deviations from test procedure except for additions or exclusions.

3.3 Addition to standards

No.	Item	Test Procedure	Specification	Remarks	Deviation	Worst margin	Results
1	99% Occupied Band Width	RSS-Gen 4.4.1	-	Conducted	N/A	N/A	N/A

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(14.06.06)

3.4 Uncertainty

Conducted Emission

The measurement uncertainty (with a 95% confidence level) for this test is $\pm 2.66\text{dB}$.
 The data listed in this test report has enough margin, more than the site margin.

Spurious Emission (Radiated)

The measurement uncertainty (with a 95% confidence level) for this test using Biconical antenna is $\pm 4.59\text{dB}$ (3m).
 The measurement uncertainty (with a 95% confidence level) for this test using Logperiodic antenna is $\pm 4.62\text{dB}$ (3m).
 The measurement uncertainty (with a 95% confidence level) for this test using Horn antenna is $\pm 5.27\text{dB}$.
 The data listed in this report meets the limits unless the uncertainty is taken into consideration.

Other test except Conducted Emission and Spurious Emission (Radiated)

The measurement uncertainty (with a 95% confidence level) for this test is $\pm 3.0\text{dB}$.

3.5 Test Location

UL Apex Co., Ltd. Head Office EMC Lab. *NVLAP Lab. code: 200572-0

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116 Facsimile : +81 596 24 8124

	FCC Registration Number	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms
No.1 semi-anechoic chamber	313583	IC4247A	19.2 x 11.2 x 7.7m	7.0 x 6.0m	Preparation room
No.2 semi-anechoic chamber	655103	IC4247A-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 semi-anechoic chamber	148738	IC4247A-3	12.0 x 8.5 x 5.9m	6.8 x 5.75m	
No.3 shielded room	-	-	4.0 x 6.0 x 2.7m	N/A	-
No.4 semi-anechoic chamber	134570	IC4247A-4	12.0 x 8.5 x 5.9m	6.8 x 5.75m	-
No.4 shielded room	-	-	4.0 x 6.0 x 2.7m	N/A	-
No.5 semi-anechoic chamber	-	-	6.0 x 6.0 x 3.9m	N/A	-
No.6 shielded room	-	-	4.0 x 4.5 x 2.7m	2.0 x 2.0 m	-
No.6 measurement room	-	-	4.75 x 5.4 x 3.0m	4.75 x 5.4 m	-
No.7 shielded room	-	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.8 measurement room	-	-	3.1 x 5.0 x 2.7m	N/A	-

* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0m for No.1, No.2, No.3 and No.4 semi-anechoic chambers and No.7 shielded room.

3.6 Test set up, Test instruments and Data of EMI

Refer to APPENDIX 1 to 3.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(14.06.06)

SECTION 4: Operation of E.U.T. during testing

4.1 Operating Modes

The mode used for test : Transmitting mode(Packet size DH5, Data packet: PRBS9)

- Low Channel : 2402MHz
- Mid Channel : 2441MHz
- High Channel : 2480MHz

Inquiry mode

Receiving mode

- Mid Channel : 2441MHz

*As a result of preliminary test, the formal test was performed with the above modes, which had the max power rate.

[FHSS:Bluetooth]

Remarks: Test was not performed at AFH mode, because the decrease of number of channel (min: 20ch) at AFH mode does not influence on the output power and bandwidth of the EUT. However, the limit level 125mW of AFH mode was used for the test.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124


MF060b(14.06.06)

4.2 Configuration and peripherals

1) Used for Conducted emissions test



2) Used for Radiated emissions test



* Cabling and setup were taken into consideration and test data was taken under worse case conditions.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Faxsimile : +81 596 24 8124

MF060b(14.06.06)

Test report No. : 27DE0137-HO-C-1
 Page : 10 of 46
 Issued date : March 14, 2007
 Revised date : March 22, 2007
 FCC ID : PZWBHT400SLBWB

Description of EUT and Support equipment

No.	Item	Model number	Serial number	Manufacturer	Remark
A	Barcode Handy Terminal	BHT-470BWB-CE	5496310346600 007	DENSO WAVE INCORPORATED	EUT
B	Optical Communication Unit	CU-421	1	DENSO WAVE INCORPORATED	-
C	AC Adapter	AWW0515NE-001	0701	DENSO WAVE INCORPORATED	-
D	Note PC	Type 2366	97-99D4L	IBM	-
E	AC Adapter	02K6750	11S02K6750Z1 Z2uP29A0TJ	IBM	-
F	Access Point	A1R-A1131AG-J-K9	FHK0907C03L	Cisco System	-
G	AC Adapter	PSA18U-480C	I41001664A3	Cisco System	-
H	Note PC	PS460N-004YH0	31013015J	TOSHIBA	-
I	AC Adapter	PA3048U-1ACA	0150538P	TOSHIBA	-
J	Mouse	M-S8a	HCA43506420	Logitech	-
K	Barcode Handy Terminal	BHT-420-BB-CE	5496310346600 009	DENSO WAVE INCORPORATED	-

List of cables used

No.	Name	Length (m)	Shield		Remark
			Cable	Connector	
1	USB Cable	1.0	Shielded	Shielded	-
2	DC Power Cable	1.9	Unshielded	Unshielded	-
3	AC Power Cable	2.0	Unshielded	Unshielded	-
4	DC Cable	1.8	Unshielded	Unshielded	-
5	AC Cable	1.8	Unshielded	Unshielded	-
6	DC Cable	1.5	Unshielded	Unshielded	-
7	AC Cable	2.0	Unshielded	Unshielded	-
8	LAN Cable	2.0	Unshielded	Unshielded	-
9	DC Cable	1.8	Unshielded	Unshielded	-
10	AC Cable	2.0	Unshielded	Unshielded	-
11	Mouse Cable	1.4	Shielded	Shielded	-

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(14.06.06)

SECTION 5: Conducted Emission

Test Procedure and conditions

EUT was placed on a urethane platform of nominal size, 1.0m by 0.5m, raised 80cm above the conducting ground plane. The rear of tabletop was located 40cm to the vertical conducting plane. The rear of EUT, including peripherals aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80cm from any other grounded conducting surface. EUT was located 80cm from a Line Impedance Stabilization Network (LISN)/ Artificial mains Network (AMN) and excess AC cable was bundled in center.

For the tests on EUT itself (as a stand alone equipment)

Each EUT current-carrying power lead, except the ground (safety) lead, was individually connected through a LISN (AMN) to the input power source. All unused 50ohm connectors of the LISN(AMN) were resistivity terminated in 50ohm when not connected to the measuring equipment.

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT in a Semi Anechoic Chamber or a Measurement Room.

The EUT was connected to a LISN (AMN).

An overview sweep with peak detection has been performed.

Detector	: CISPR quasi-peak and average detector (IF BW 9 kHz)
Measurement range	: 0.15-30MHz
Test data	: APPENDIX 2
Test result	: Pass

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(14.06.06)

SECTION 6: Spurious Emission

[Conducted]

Test Procedure

The Out of Band Emission was measured with a spectrum analyzer connected to the antenna port.

Test data : APPENDIX 2

Test result : Pass

[Radiated]

Test Procedure

EUT was placed on a urethane platform of nominal size, 1.0m by 0.5m, raised 80cm above the conducting ground plane. The Radiated Electric Field Strength intensity has been measured in a Semi Anechoic Chamber with a ground plane and at a distance of 3m(Below 10GHz) and 1m(Upper 10GHz).

The height of the measuring varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer (in linear mode).

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.

20dBc was applied to the frequency over the limit of FCC 15.209 and outside the restricted band of FCC15.205.

Frequency	Below 1GHz	Above 1GHz
Instrument used	Test Receiver / Spectrum Analyzer	Spectrum Analyzer
Detector IF Bandwidth	QP: BW 120kHz(T/R) 20dBc : RBW: 100kHz VBW: 300kHz (S/A)	PK: RBW:1MHz/VBW: 1MHz AV: RBW:1MHz/VBW:10Hz 20dBc : RBW:100kHz/VBW:300kHz

The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

Test data : APPENDIX 2
Test result : Pass

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(14.06.06)

SECTION 7: Bandwidth

Test Procedure

The bandwidth was measured with a spectrum analyzer connected to the antenna port.

Test data : APPENDIX 2
Test result : Pass

SECTION 8: Maximum Peak Output Power

Test Procedure

The Maximum Peak Output Power was measured with a power meter (tested bandwidth: 50MHz) connected to the antenna port.

Test data : APPENDIX 2
Test result : Pass

SECTION 9: Carrier Frequency Separation

Test Procedure

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna port.

Test data : APPENDIX 2
Test result : Pass

SECTION 10: Number of Hopping Frequency

Test Procedure

The Number of Hopping Frequency was measured with a spectrum analyzer connected to the antenna port.

Test data : APPENDIX 2
Test result : Pass

SECTION 11: Dwell time

Test Procedure

The Dwell time was measured with a spectrum analyzer connected to the antenna port.

Test data : APPENDIX 2
Test result : Pass

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(14.06.06)