



## FCC PART 15B, CLASS B

### TEST REPORT

For

### Star Computer Group

2175 NORTHWEST 115<sup>TH</sup> AVE., DORAL, FL 33172, USA

**FCC ID: Q34-E350**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Smart Mobile Phone
<b>Test Engineer:</b> <u>Brown Lu</u>	
<b>Report Number:</b> <u>RSZ120906005-00A</u>	
<b>Report Date:</b> <u>2012-09-21</u>	
<b>Reviewed By:</b> <u>Sula Huang</u> <u>EMC Engineer</u>	
<b>Test Laboratory:</b> Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP\*, or any agency of the Federal Government.

\* This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk “★”

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>3</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
OBJECTIVE .....	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST FACILITY .....	3
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>5</b>
DESCRIPTION OF TEST CONFIGURATION .....	5
EUT EXERCISE SOFTWARE .....	5
EQUIPMENT MODIFICATIONS .....	5
SUPPORT EQUIPMENT LIST AND DETAILS .....	5
EXTERNAL I/O CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP .....	6
<b>SUMMARY OF TEST RESULTS.....</b>	<b>7</b>
<b>FCC §15.107 – AC LINE CONDUCTED EMISSIONS.....</b>	<b>8</b>
MEASUREMENT UNCERTAINTY .....	8
EUT SETUP .....	8
EMI TEST RECEIVER SETUP.....	9
TEST PROCEDURE .....	9
TEST EQUIPMENT LIST AND DETAILS.....	9
CORRECTED FACTOR & MARGIN CALCULATION .....	9
TEST RESULTS SUMMARY .....	9
TEST DATA .....	10
<b>FCC §15.109 - RADIATED SPURIOUS EMISSIONS .....</b>	<b>14</b>
MEASUREMENT UNCERTAINTY .....	14
EUT SETUP .....	14
EMI TEST RECEIVER SETUP.....	15
TEST PROCEDURE .....	15
TEST EQUIPMENT LIST AND DETAILS.....	15
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	15
TEST RESULTS SUMMARY .....	15
TEST DATA .....	16

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *Star Computer Group*'s product, model number: *E350 (FCC ID: Q34-E350)* or the "EUT" in this report was a *Smart mobile phone*, which was measured approximately: 11.3 cm (L) x 6.0 cm (W) x 1.0 cm (H), rated input voltage: DC 3.7 V Li-ion battery or DC 5V charging from adapter. The highest Operating Frequency is 104 MHz.

#### Adapter Information:

Model: E350

Input: 100-240V~50/60 Hz 0.15A

Output: 5V DC 0.5A

*\* All measurement and test data in this report was gathered from production sample serial number: E350120800001 (Assigned by applicant). The EUT supplied by the applicant was received on 2012-09-06.*

### Objective

This test report is prepared on behalf of *Star Computer Group* in accordance with Part 2-Subpart J, Part 15-Subparts A and B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine the compliance of the EUT with FCC Part 15B.

### Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS, FCC Part 15.247 DTS and Part 22H/24E PCE submissions with FCC ID: Q34-E350

### Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in a manufacturer testing fashion.

EUT operation mode 1: Charging& Multimedia playing

EUT operation mode 2: Downloading (data transmit with computer)

### EUT Exercise Software

“winthrax” exercise software was used.

### Equipment Modifications

No modification was made to the EUT tested.

### Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	PC	VOSTRO 220S	127BP2X
DELL	Keyboard	L100	CNORH656658907BL05DC
DELL	Mouse	MOC5UO	G1900NKD
DELL	LCD Monitor	E178WFPC	CN-OWY564-64180-7C4-2SQH
SAST	Modem	AEM-2100	0293
HP	Laser Jet5L	C3941A	JPTVOB2337

### External I/O Cable


Cable Description	Length (m)	From/Port	To
Shielded Detachable USB Cable	1.5	Host PC	Mouse
Shielded Detachable Serial Cable	1.2	Host PC	Modem
Shielded Detachable K/B Cable	1.5	Host PC	Keyboard
Shielded Detachable VGA Cable	1.5	Host PC	LCD Monitor
Shielded Detachable Printer Cable	1.2	Host PC	Printer
Shielded Detachable USB Cable with core	1.0	EUT	Host PC

**Block Diagram of Test Setup**

Charging&amp;multimedia playing



Downloading mode:



**SUMMARY OF TEST RESULTS**

---

FCC Rules	Description of Test	Results
§15.107	AC Line Conducted Emissions	Compliance
§15.109	Radiated Spurious Emissions	Compliance


## FCC §15.107 – AC LINE CONDUCTED EMISSIONS

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on CISPR 16-4-2, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is 2.4 dB( $k=2$ , 95% level of confidence), and the uncertainty will not be taken into consideration for all the test data recorded in the report.

### EUT Setup



**Note:** 1. Support units were connected to second LISN.  
2. Both of LISNs (AMIN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with per ANSI C63.4-2009. The related limit was specified in FCC Part 15.107 Class B.

The spacing between the peripherals was 10 cm.

For charging&multimedia mode, the adapter was connected to a 120 VAC/60 Hz power source. For downloading mode, the host PC was connected to a 120 VAC/60 Hz power source.

## EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

<u>Frequency Range</u>	<u>IF B/W</u>
150 kHz – 30 MHz	9 kHz

## Test Procedure

During the conducted emission test, the adapter or host PC was connected to the outlet of the first LISN, and the other relevant equipments were connected to the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2011-11-24	2012-11-23
Rohde & Schwarz	L.I.S.N.	ESH2-Z5	892107/021	2011-11-17	2012-11-16
Com-Power	L.I.S.N.	LI-200	12005	N/A	N/A
Com-Power	L.I.S.N.	LI-200	12208	N/A	N/A
Rohde & Schwarz	Pulse limiter	ESH3Z2	DE25985	2012-07-08	2013-07-07
BACL	CE Test software	BACL-CE	V1.0	-	-

\* **Statement of Traceability:** Bay Area Compliance Laboratory Corp (Shenzhen). attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

## Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Pulse Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Pulse Limiter Attenuation}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.107, with the worst margin reading of:

**6.00 dB at 8.745 MHz in the Neutral conducted mode**

## Test Data


### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Brown Lu on 2012-09-12.


EUT Operation Mode: Charging&multimedia playing

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dB $\mu$ V)	Correction Factor (dB)	Limit (dB $\mu$ V)	Margin (dB)	Detector (PK/Ave./QP)
21.970	42.39	12.49	60.00	17.61	QP
21.970	28.30	12.49	50.00	21.70	AV
3.420	39.48	10.25	56.00	16.52	QP
3.420	29.95	10.25	46.00	16.05	AV
2.045	35.97	10.20	56.00	20.03	QP
2.055	24.73	10.20	46.00	21.27	AV
1.840	37.66	10.20	56.00	18.34	QP
1.855	26.34	10.20	46.00	19.66	AV
0.310	40.04	10.26	61.43	21.39	QP
0.310	28.09	10.26	51.43	23.34	AV
1.350	36.92	10.18	56.00	19.08	QP
1.340	25.30	10.18	46.00	20.70	AV


## AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dB $\mu$ V)	Correction Factor (dB)	Limit (dB $\mu$ V)	Margin (dB)	Detector (PK/Ave./QP)
3.430	33.88	10.24	56.00	22.12	QP
3.450	25.30	10.24	46.00	20.70	AV
22.705	36.04	12.28	60.00	23.96	QP
22.705	23.24	12.28	50.00	26.76	AV
1.920	32.23	10.20	56.00	23.77	QP
1.925	22.41	10.20	46.00	23.59	AV
0.155	40.89	10.24	65.86	24.97	QP
0.155	23.58	10.24	55.86	32.28	AV
0.205	34.25	10.24	64.43	30.18	QP
0.205	24.56	10.24	54.43	29.87	AV
1.380	30.50	10.18	56.00	25.50	QP
1.385	21.03	10.18	46.00	24.97	AV


*EUT Operation Mode: Downloading (data transmits with Computer)*

**AC 120V/60 Hz, Line**



Frequency (MHz)	Corrected Amplitude (dB $\mu$ V)	Correction Factor (dB)	Limit (dB $\mu$ V)	Margin (dB)	Detector (PK/Ave./QP)
9.145	39.37	10.46	50.00	10.63	Ave.
1.105	35.16	10.17	46.00	10.84	Ave.
1.610	34.47	10.19	46.00	11.53	Ave.
8.240	37.57	10.42	50.00	12.43	Ave.
0.200	41.37	10.27	54.57	13.20	Ave.
4.925	32.35	10.30	46.00	13.65	Ave.
9.145	40.27	10.46	60.00	19.73	QP
1.105	35.39	10.17	56.00	20.61	QP
1.610	34.81	10.19	56.00	21.19	QP
0.200	42.77	10.27	64.57	21.80	QP
8.240	38.18	10.42	60.00	21.82	QP
4.925	32.90	10.30	56.00	23.10	QP

## AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dB $\mu$ V)	Correction Factor (dB)	Limit (dB $\mu$ V)	Margin (dB)	Detector (PK/Ave./QP)
8.745	44.00	10.44	50.00	6.00	Ave.
1.105	35.77	10.17	46.00	10.23	Ave.
1.610	33.89	10.19	46.00	12.11	Ave.
4.925	33.37	10.29	46.00	12.63	Ave.
7.640	35.82	10.40	50.00	14.18	Ave.
5.835	35.12	10.32	50.00	14.88	Ave.
8.745	44.24	10.44	60.00	15.76	QP
7.640	40.68	10.40	60.00	19.32	QP
1.105	35.96	10.17	56.00	20.04	QP
1.610	35.82	10.19	56.00	20.18	QP
5.845	39.40	10.32	60.00	20.60	QP
4.925	34.90	10.29	56.00	21.10	QP


## FCC §15.109 - RADIATED SPURIOUS EMISSIONS

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2, the Treatment of Uncertainty in EMC Measurements, the estimation of the uncertainty of radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is 4.0 dB( $k=2$ , 95% level of confidence), and the uncertainty will not be taken into consideration for all the test data recorded in the report.

### EUT Setup



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC Part 15.109 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

For charging&multimedia mode, the adapter was connected to a 120 VAC/60 Hz power source.

For downloading mode, the host PC was connected to a 120 VAC/60 Hz power source.

## EMI Test Receiver Setup

The system was investigated from 30 MHz to 1000 MHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

<b>Frequency</b>	<b>RB/W</b>	<b>VB/W</b>	<b>IF B/W</b>	<b>Detection</b>
30 MHz-1 GHz	100 kHz	300 kHz	120 kHz	Quasi-peak

## Test Procedure

For the radiated emissions test, the adapter or host PC and relevant equipments were connected to AC floor outlet for downloading mode.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All the data was recorded in the Quasi-peak detection mode from 30 MHz to 1 GHz.

## Test Equipment List and Details

<b>Manufacturer</b>	<b>Description</b>	<b>Model</b>	<b>Serial Number</b>	<b>Calibration Date</b>	<b>Calibration Due Date</b>
HP	Amplifier	HP8447E	1937A01046	2011-11-24	2012-11-23
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2011-11-17	2012-11-16
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2012-11-27
R&S	Auto test Software	EMC32	V6.30	-	-

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.109, Class B, with the worst margin reading of:

**3.4 dB at 38.9 MHz in the Vertical polarization**

**Test Data****Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	100.0 kPa

The testing was performed by Brown Lu on 2012-09-12.

EUT Operation Mode: Charging&multimedia playing

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna			Cable Loss (dB)	Amp. Gain (dB)	Cord. Amp. (dB $\mu$ V/m)	FCC Part 15B	
	Reading (dB $\mu$ V/m)	Detector (PK/QP/Ave)		Height (m)	Polar (H/V)	Factor (dB)				Limit (dB $\mu$ V/m)	Margin (dB)
38.9	48.04	QP	9.0	1.1	V	14.8	0.26	26.50	36.6	40.0	3.4*
51.9	48.74	QP	73.0	1.1	V	7.3	0.26	26.50	29.8	40.0	10.2
31.3	30.84	QP	229.0	1.1	V	19.8	0.26	26.50	24.4	40.0	15.6
317.2	41.61	QP	29.0	1.5	H	13.6	0.39	26.50	29.1	46.0	16.9
64.9	40.44	QP	1.0	1.2	V	7.3	0.26	26.50	21.5	40.0	18.5
168.3	32.32	QP	342.0	2.3	H	11.8	0.28	26.50	17.9	43.5	25.6

EUT Operation Mode: Downloading (data transmits with Computer)

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna			Cable Loss (dB)	Amp. Gain (dB)	Cord. Amp. (dB $\mu$ V/m)	FCC Part 15B	
	Reading (dB $\mu$ V/m)	Detector (PK/QP/Ave)		Height (m)	Polar (H/V)	Factor (dB)				Limit (dB $\mu$ V/m)	Margin (dB)
240.1	48.60	QP	189.0	1.5	V	11.3	0.30	26.50	33.7	46.0	12.3
465.6	42.13	QP	178.0	3.8	H	17.0	0.47	26.50	33.1	46.0	12.9
500.9	41.39	QP	216.0	1.2	V	17.5	0.51	26.50	32.9	46.0	13.1
837.0	35.70	QP	244.0	2.1	H	21.4	0.70	26.50	31.3	46.0	14.7
30.1	29.54	QP	64.0	1.3	V	21.5	0.26	26.50	24.8	40.0	15.2
597.2	38.53	QP	145.0	1.1	H	17.9	0.57	26.50	30.5	46.0	15.5

\*\*\*\*\* END OF REPORT \*\*\*\*\*