

Model Difference Letter_18826_Rev1

We, the undersigned,

Company: Radwin Ltd.

Address: 32 Habarzel str. Tel Aviv, 69710

Country: ISRAEL

Telephone number: +972 3 7662900

Fax number: +972 3 7662922

Declare that model RADWIN 2000 differs from model RADWIN 1000 in the number of software activated antenna ports. The PCB layout is the same in both models.

RADWIN 2000 can activate both transmission channels under the maximum output power (+26.95 dBm per pole or +29.95 dBm in total for both RF chains) and feeds this power into different poles, horizontal and vertical, of the dual pole transmitting antenna.

RADWIN 1000 activates only one transmission channel under the maximum output power (+26.5 dBm) and feeds this power into one of two poles either horizontal or vertical of the dual pole transmitting antenna.

The RADWIN 1000 external antenna configuration, being a single pole model, has a single pole enclosure option.

The RADWIN 1000 integrated antenna configuration has the same enclosure as the RADWIN 2000.

The antennas used for both models are the same.

The maximum allowed power level in the single pole RADWIN 1000 model will not exceed the maximum allowed power level at the corresponding pole of the RADWIN 2000 model. (See table)

Model	Max power
RADWIN 2000	29.95 dBm
RADWIN 1000 Ant1	26.95 dBm
RADWIN 1000 Ant2	26.95 dBm

Drawn up in: ...Radwin..Ltd.....

on12.1.09.....

(date)

RADWIN LTD.

(company stamp)



(signature)

.....Itai Rubinstein / Engineering Dep. Manager.....

(name and function)