


A.1.3. Power Spectral Density



power density

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2408.249 MHz : -6.295 dBm	Limit: 4.990 dBm Margin: -11.28 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 281 of 440



power density

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2408.225 MHz : -6.482 dBm	Limit: 4.990 dBm Margin: -11.47 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 282 of 440



power density

Variant: 802.11n HT-20, Channel: 2437.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2443.897 MHz : -5.805 dBm	Limit: 4.990 dBm Margin: -10.79 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 283 of 440



power density

Variant: 802.11n HT-20, Channel: 2437.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2438.554 MHz : -5.964 dBm	Limit: 4.990 dBm Margin: -10.95 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 284 of 440



power density

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2457.310 MHz : -6.082 dBm	Limit: 4.990 dBm Margin: -11.07 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 285 of 440



power density

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2459.191 MHz : -6.855 dBm	Limit: 4.990 dBm Margin: -11.84 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 286 of 440



power density

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2405.746 MHz : -8.972 dBm	Limit: 4.990 dBm Margin: -13.96 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 287 of 440



power density

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2430.432 MHz : -8.848 dBm	Limit: 4.990 dBm Margin: -13.84 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

power density

Variant: 802.11n HT-40, Channel: 2437.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2452.596 MHz : -8.038 dBm	Limit: 4.990 dBm Margin: -13.03 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 289 of 440



power density

Variant: 802.11n HT-40, Channel: 2437.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2426.959 MHz : -8.720 dBm	Limit: 4.990 dBm Margin: -13.71 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 290 of 440



power density

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2466.688 MHz : -9.010 dBm	Limit: 4.990 dBm Margin: -14.00 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 291 of 440



power density

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2441.392 MHz : -9.204 dBm	Limit: 4.990 dBm Margin: -14.19 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 292 of 440



power density

Variant: 802.11b, Channel: 2412.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2412.773 MHz : -1.142 dBm	Limit: 4.990 dBm Margin: -6.13 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 293 of 440



power density

Variant: 802.11b, Channel: 2412.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2412.777 MHz : -0.890 dBm	Limit: 4.990 dBm Margin: -5.88 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 294 of 440



power density

Variant: 802.11b, Channel: 2437.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2435.626 MHz : -0.664 dBm	Limit: 4.990 dBm Margin: -5.65 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 295 of 440



power density

Variant: 802.11b, Channel: 2437.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2436.767 MHz : -1.103 dBm	Limit: 4.990 dBm Margin: -6.09 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 296 of 440



power density

Variant: 802.11b, Channel: 2462.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2463.937 MHz : -0.568 dBm	Limit: 4.990 dBm Margin: -5.56 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 297 of 440



power density

Variant: 802.11b, Channel: 2462.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2460.628 MHz : 0.046 dBm	Limit: 4.990 dBm Margin: -4.94 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 298 of 440



power density

Variant: 802.11g, Channel: 2412.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2417.001 MHz : -4.609 dBm	Limit: 4.990 dBm Margin: -9.60 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 299 of 440



power density

Variant: 802.11g, Channel: 2412.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2418.252 MHz : -4.971 dBm	Limit: 4.990 dBm Margin: -9.96 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

power density

Variant: 802.11g, Channel: 2437.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2436.753 MHz : -6.787 dBm	Limit: 4.990 dBm Margin: -11.78 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 301 of 440



power density

Variant: 802.11g, Channel: 2437.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2435.125 MHz : -4.583 dBm	Limit: 4.990 dBm Margin: -9.57 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 302 of 440



power density

Variant: 802.11g, Channel: 2462.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2468.252 MHz : -5.024 dBm	Limit: 4.990 dBm Margin: -10.01 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 303 of 440



power density

Variant: 802.11g, Channel: 2462.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2457.879 MHz : -5.128 dBm	Limit: 4.990 dBm Margin: -10.12 dB

[Back to the Matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

3x3 802.11b



power density

Variant: 802.11b, Channel: 2412.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2412.598 MHz : -4.680 dBm	Limit: 3.229 dBm Margin: -7.91 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 305 of 440



power density

Variant: 802.11b, Channel: 2412.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2412.598 MHz : -5.872 dBm	Limit: 3.229 dBm Margin: -9.10 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 306 of 440



power density

Variant: 802.11b, Channel: 2412.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2412.598 MHz : -5.234 dBm	Limit: 3.229 dBm Margin: -8.46 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 307 of 440



power density

Variant: 802.11b, Channel: 2437.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2437.598 MHz : -4.800 dBm	Limit: 3.229 dBm Margin: -8.03 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 308 of 440



power density

Variant: 802.11b, Channel: 2437.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2437.598 MHz : -5.762 dBm	Limit: 3.229 dBm Margin: -8.99 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 309 of 440



power density

Variant: 802.11b, Channel: 2437.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2437.598 MHz : -5.325 dBm	Limit: 3.229 dBm Margin: -8.55 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 310 of 440



power density

Variant: 802.11b, Channel: 2462.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2462.598 MHz : -4.965 dBm	Limit: 3.229 dBm Margin: -8.19 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 311 of 440



power density

Variant: 802.11b, Channel: 2462.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2462.598 MHz : -5.537 dBm	Limit: 3.229 dBm Margin: -8.77 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 312 of 440



power density

Variant: 802.11b, Channel: 2462.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2460.508 MHz : -5.087 dBm	Limit: 3.229 dBm Margin: -8.32 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 313 of 440

3x3 802.11g



power density

Variant: 802.11g, Channel: 2412.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2416.055 MHz : -8.205 dBm	Limit: 3.229 dBm Margin: -11.43 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 314 of 440



power density

Variant: 802.11g, Channel: 2412.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2407.971 MHz : -10.330 dBm	Limit: 3.229 dBm Margin: -13.56 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 315 of 440



power density

Variant: 802.11g, Channel: 2412.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2419.462 MHz : -9.195 dBm	Limit: 3.229 dBm Margin: -12.42 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 316 of 440



power density

Variant: 802.11g, Channel: 2437.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2432.973 MHz : -9.478 dBm	Limit: 3.229 dBm Margin: -12.71 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 317 of 440



power density

Variant: 802.11g, Channel: 2437.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2433.869 MHz : -10.131 dBm	Limit: 3.229 dBm Margin: -13.36 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 318 of 440



power density

Variant: 802.11g, Channel: 2437.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2440.775 MHz : -9.464 dBm	Limit: 3.229 dBm Margin: -12.69 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 319 of 440



power density

Variant: 802.11g, Channel: 2462.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2464.486 MHz : -8.386 dBm	Limit: 3.229 dBm Margin: -11.61 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 320 of 440



power density

Variant: 802.11g, Channel: 2462.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2469.494 MHz : -9.527 dBm	Limit: 3.229 dBm Margin: -12.76 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 321 of 440



power density

Variant: 802.11g, Channel: 2462.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2457.973 MHz : -9.649 dBm	Limit: 3.229 dBm Margin: -12.88 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 322 of 440

3x3 802.11n HT-20



power density

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2415.787 MHz : -8.357 dBm	Limit: 3.229 dBm Margin: -11.59 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 323 of 440



power density

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2417.328 MHz : -11.729 dBm	Limit: 3.229 dBm Margin: -14.96 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

power density

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2415.795 MHz : -6.987 dBm	Limit: 3.229 dBm Margin: -10.22 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

power density

Variant: 802.11n HT-20, Channel: 2437.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2433.286 MHz : -8.882 dBm	Limit: 3.229 dBm Margin: -12.11 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 326 of 440



power density

Variant: 802.11n HT-20, Channel: 2437.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2442.672 MHz : -11.648 dBm	Limit: 3.229 dBm Margin: -14.88 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 327 of 440



power density

Variant: 802.11n HT-20, Channel: 2437.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2442.300 MHz : -9.444 dBm	Limit: 3.229 dBm Margin: -12.67 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 328 of 440



power density

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2467.610 MHz : -9.553 dBm	Limit: 3.229 dBm Margin: -12.78 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 329 of 440



power density

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2467.672 MHz : -11.349 dBm	Limit: 3.229 dBm Margin: -14.58 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

power density

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2455.753 MHz : -8.303 dBm	Limit: 3.229 dBm Margin: -11.53 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 331 of 440

3x3 802.11n HT-40



power density

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2429.538 MHz : -12.159 dBm	Limit: 3.229 dBm Margin: -15.39 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 332 of 440



power density

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2436.987 MHz : -10.017 dBm	Limit: 3.229 dBm Margin: -13.25 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

power density

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2415.458 MHz : -13.678 dBm	Limit: 3.229 dBm Margin: -16.91 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 334 of 440



power density

Variant: 802.11n HT-40, Channel: 2437.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2451.997 MHz : -11.233 dBm	Limit: 3.229 dBm Margin: -14.46 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 335 of 440



power density

Variant: 802.11n HT-40, Channel: 2437.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2452.943 MHz : -14.821 dBm	Limit: 3.229 dBm Margin: -18.05 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

power density

Variant: 802.11n HT-40, Channel: 2437.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2452.300 MHz : -10.890 dBm	Limit: 3.229 dBm Margin: -14.12 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 337 of 440



power density

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2441.652 MHz : -14.331 dBm	Limit: 3.229 dBm Margin: -17.56 dB


[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



power density

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2468.169 MHz : -12.730 dBm	Limit: 3.229 dBm Margin: -15.96 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 339 of 440



power density

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2444.466 MHz : -10.564 dBm	Limit: 3.229 dBm Margin: -13.79 dB


[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

A.1.4. Conducted Spurious Emissions

bandedge

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -22.367 dBm M2 : 2402.232 MHz : -14.329 dBm M3 : 2418.248 MHz : 7.037 dBm	Limit: -12.96 Margin: -9

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -23.858 dBm M2 : 2402.377 MHz : -13.738 dBm M3 : 2406.994 MHz : 6.964 dBm	Limit: -13.04 Margin: -11

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2455.607 MHz : 7.078 dBm M2 : 2471.768 MHz : -14.525 dBm M3 : 2483.500 MHz : -36.335 dBm	Limit: -12.92 Margin: -23

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge


Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2456.906 MHz : 7.350 dBm M2 : 2471.479 MHz : -13.059 dBm M3 : 2483.500 MHz : -36.500 dBm	Limit: -12.65 Margin: -24

[Back to the Matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2371.984 MHz : 6.915 dBm M2 : 1591.323 MHz : -40.677 dBm	Limit: -13.09 Margin: -28

[Back to the Matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2371.984 MHz : 6.085 dBm M2 : 1591.323 MHz : -42.237 dBm	Limit: -13.92 Margin: -28

[Back to the Matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 6.195 dBm M2 : 1591.323 MHz : -39.650 dBm	Limit: -13.81 Margin: -26

[Back to the Matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 6.069 dBm M2 : 1591.323 MHz : -39.803 dBm	Limit: -13.93 Margin: -26

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 5.784 dBm M2 : 1643.367 MHz : -40.164 dBm	Limit: -14.22 Margin: -26

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 5.558 dBm M2 : 1643.367 MHz : -40.378 dBm	Limit: -14.44 Margin: -26

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 350 of 440



bandedge

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -22.318 dBm M2 : 2402.922 MHz : -14.964 dBm M3 : 2438.393 MHz : 5.083 dBm	Limit: -14.92 Margin: -7

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -24.195 dBm M2 : 2402.621 MHz : -17.397 dBm M3 : 2439.595 MHz : 5.373 dBm	Limit: -14.63 Margin: -10

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2468.072 MHz : 4.416 dBm M2 : 2471.379 MHz : -16.648 dBm M3 : 2483.500 MHz : -34.289 dBm	Limit: -15.58 Margin: -19

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge


Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2469.275 MHz : 4.242 dBm M2 : 2471.078 MHz : -16.736 dBm M3 : 2483.500 MHz : -34.269 dBm	Limit: -15.76 Margin: -19

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 4.076 dBm M2 : 1591.323 MHz : -40.494 dBm	Limit: -15.92 Margin: -25

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


con tx spr emissions
 Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2371.984 MHz : 3.140 dBm M2 : 1591.323 MHz : -40.356 dBm	Limit: -16.86 Margin: -23

[Back to the Matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 3.848 dBm M2 : 1591.323 MHz : -40.203 dBm	Limit: -16.15 Margin: -24

[Back to the Matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 2.404 dBm M2 : 6899.820 MHz : -42.518 dBm	Limit: -17.60 Margin: -25

[Back to the Matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 3.224 dBm M2 : 1591.323 MHz : -40.660 dBm	Limit: -16.78 Margin: -24

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 2.021 dBm M2 : 3256.733 MHz : -42.414 dBm	Limit: -17.98 Margin: -24

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 360 of 440



bandedge

Variant: 802.11b, Channel: 2412.000 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -34.354 dBm M2 : 2404.108 MHz : -8.688 dBm M3 : 2412.621 MHz : 11.898 dBm	Limit: -8.10 Margin: -26

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11b, Channel: 2412.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -33.774 dBm M2 : 2403.964 MHz : -10.161 dBm M3 : 2412.621 MHz : 11.409 dBm	Limit: -8.59 Margin: -25

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11b, Channel: 2462.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2462.533 MHz : 11.635 dBm M2 : 2470.036 MHz : -9.910 dBm M3 : 2483.500 MHz : -44.205 dBm	Limit: -8.37 Margin: -36

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11b, Channel: 2462.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2462.677 MHz : 11.419 dBm M2 : 2470.036 MHz : -9.481 dBm M3 : 2483.500 MHz : -44.842 dBm	Limit: -8.58 Margin: -36

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11b, Channel: 2412.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2371.984 MHz : 9.803 dBm M2 : 6951.864 MHz : -42.206 dBm	Limit: -10.20 Margin: -32

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11b, Channel: 2412.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2371.984 MHz : 9.644 dBm M2 : 3204.689 MHz : -42.780 dBm	Limit: -10.36 Margin: -32

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11b, Channel: 2437.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 9.244 dBm M2 : 3204.689 MHz : -41.279 dBm	Limit: -10.76 Margin: -31


[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



con tx spr emissions

Variant: 802.11b, Channel: 2437.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 10.321 dBm M2 : 3204.689 MHz : -40.213 dBm	Limit: -9.68 Margin: -31

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions


Variant: 802.11b, Channel: 2462.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 10.437 dBm M2 : 3256.733 MHz : -42.005 dBm	Limit: -9.56 Margin: -32

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 9.697 dBm M2 : 3256.733 MHz : -41.574 dBm	Limit: -10.30 Margin: -31

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: AP0127450, AP0127460
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: RDWN14-U1 Rev A
Issue Date: 12th December 2012
Page: 370 of 440



bandedge

Variant: 802.11g, Channel: 2412.000 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -23.595 dBm M2 : 2402.521 MHz : -14.710 dBm M3 : 2417.238 MHz : 5.325 dBm	Limit: -14.68 Margin: -9

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11g, Channel: 2412.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -23.616 dBm M2 : 2402.810 MHz : -14.952 dBm M3 : 2417.094 MHz : 5.522 dBm	Limit: -14.48 Margin: -9

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11g, Channel: 2462.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2466.140 MHz : 4.863 dBm M2 : 2471.623 MHz : -16.154 dBm M3 : 2483.500 MHz : -37.419 dBm	Limit: -15.14 Margin: -22

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11g, Channel: 2462.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2466.285 MHz : 5.347 dBm M2 : 2471.335 MHz : -15.141 dBm M3 : 2483.500 MHz : -37.486 dBm	Limit: -14.65 Margin: -23

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11g, Channel: 2412.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2371.984 MHz : 4.489 dBm M2 : 1591.323 MHz : -40.121 dBm	Limit: -15.51 Margin: -25

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spurious emissions

Variant: 802.11g, Channel: 2412.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2371.984 MHz : 4.226 dBm M2 : 3204.689 MHz : -41.552 dBm	Limit: -15.77 Margin: -26

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11g, Channel: 2437.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 3.814 dBm M2 : 3204.689 MHz : -40.321 dBm	Limit: -16.19 Margin: -24

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11g, Channel: 2437.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 4.468 dBm M2 : 3204.689 MHz : -39.927 dBm	Limit: -15.53 Margin: -24


[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



con tx spr emissions

Variant: 802.11g, Channel: 2462.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 3.360 dBm M2 : 3256.733 MHz : -41.128 dBm	Limit: -16.64 Margin: -24


[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



con tx spr emissions

Variant: 802.11g, Channel: 2462.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 3.559 dBm M2 : 3256.733 MHz : -40.632 dBm	Limit: -16.44 Margin: -24

[Back to the Matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

3x3 802.11b



bandedge

Variant: 802.11b, Channel: 2412.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -37.063 dBm M2 : 2404.253 MHz : -10.467 dBm M3 : 2412.621 MHz : 9.988 dBm	Limit: -10.01 dBm Margin: -27.05 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11b, Channel: 2412.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -36.308 dBm M2 : 2404.108 MHz : -11.605 dBm M3 : 2411.900 MHz : 8.410 dBm	Limit: -11.59 dBm Margin: -24.72 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11b, Channel: 2412.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -36.501 dBm M2 : 2404.253 MHz : -11.187 dBm M3 : 2412.621 MHz : 9.225 dBm	Limit: -10.78 dBm Margin: -25.72 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11b, Channel: 2462.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2462.533 MHz : 9.697 dBm M2 : 2469.892 MHz : -12.269 dBm M3 : 2483.500 MHz : -43.768 dBm	Limit: -10.30 dBm Margin: -33.47 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11b, Channel: 2462.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2462.533 MHz : 9.087 dBm M2 : 2469.892 MHz : -12.605 dBm M3 : 2483.500 MHz : -45.332 dBm	Limit: -10.91 dBm Margin: -34.42 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11b, Channel: 2462.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2462.533 MHz : 9.671 dBm M2 : 2469.892 MHz : -11.525 dBm M3 : 2483.500 MHz : -45.431 dBm	Limit: -10.33 dBm Margin: -35.10 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11b, Channel: 2412.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2371.984 MHz : 9.372 dBm M2 : 3204.689 MHz : -41.986 dBm	Limit: -10.63 dBm Margin: -31.36 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11b, Channel: 2412.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2371.984 MHz : 8.651 dBm M2 : 3204.689 MHz : -42.680 dBm	Limit: -11.35 dBm Margin: -31.33 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11b, Channel: 2412.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2371.984 MHz : 8.446 dBm M2 : 6431.423 MHz : -42.017 dBm	Limit: -11.55 dBm Margin: -30.47 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11b, Channel: 2437.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 8.922 dBm M2 : 1591.323 MHz : -40.656 dBm	Limit: -11.08 dBm Margin: -29.58 dB


[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



con tx spr emissions


Variant: 802.11b, Channel: 2437.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 8.794 dBm M2 : 3204.689 MHz : -40.321 dBm	Limit: -11.21 dBm Margin: -29.11 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 7.979 dBm M2 : 3204.689 MHz : -43.514 dBm	Limit: -12.02 dBm Margin: -31.49 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11b, Channel: 2462.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 8.076 dBm M2 : 3256.733 MHz : -41.777 dBm	Limit: -11.92 dBm Margin: -29.86 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11b, Channel: 2462.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 7.409 dBm M2 : 3256.733 MHz : -41.550 dBm	Limit: -12.59 dBm Margin: -28.96 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11b, Channel: 2462.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 8.772 dBm M2 : 6899.820 MHz : -41.490 dBm	Limit: -11.23 dBm Margin: -30.26 dB

[Back to the Matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

3x3 802.11g



bandedge

Variant: 802.11g, Channel: 2412.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -25.149 dBm M2 : 2402.810 MHz : -16.028 dBm M3 : 2417.094 MHz : 5.164 dBm	Limit: -14.84 dBm Margin: -10.31 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11g, Channel: 2412.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -27.102 dBm M2 : 2402.954 MHz : -17.191 dBm M3 : 2417.094 MHz : 4.482 dBm	Limit: -15.52 dBm Margin: -11.58 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11g, Channel: 2412.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -26.719 dBm M2 : 2402.954 MHz : -16.473 dBm M3 : 2417.094 MHz : 5.357 dBm	Limit: -14.64 dBm Margin: -12.08 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11g, Channel: 2462.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2467.006 MHz : 4.564 dBm M2 : 2471.190 MHz : -15.885 dBm M3 : 2483.500 MHz : -41.289 dBm	Limit: -15.44 dBm Margin: -25.85 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11g, Channel: 2462.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2467.006 MHz : 4.470 dBm M2 : 2471.190 MHz : -16.850 dBm M3 : 2483.500 MHz : -40.620 dBm	Limit: -15.53 dBm Margin: -25.09 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11g, Channel: 2462.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2467.006 MHz : 5.429 dBm M2 : 2471.046 MHz : -14.691 dBm M3 : 2483.500 MHz : -41.022 dBm	Limit: -14.57 dBm Margin: -26.45 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11g, Channel: 2412.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2371.984 MHz : 4.110 dBm M2 : 3204.689 MHz : -40.907 dBm	Limit: -15.89 dBm Margin: -25.02 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11g, Channel: 2412.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2371.984 MHz : 3.433 dBm M2 : 3204.689 MHz : -41.792 dBm	Limit: -16.57 dBm Margin: -25.22 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spurious emissions

Variant: 802.11g, Channel: 2412.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2371.984 MHz : 5.237 dBm M2 : 6951.864 MHz : -41.012 dBm	Limit: -14.76 dBm Margin: -26.25 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spurious emissions

Variant: 802.11g, Channel: 2437.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 4.515 dBm M2 : 3204.689 MHz : -41.342 dBm	Limit: -15.49 dBm Margin: -25.85 dB


[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



con tx spr emissions

Variant: 802.11g, Channel: 2437.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 2.996 dBm M2 : 3204.689 MHz : -40.213 dBm	Limit: -17.00 dBm Margin: -23.21 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11g, Channel: 2437.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 4.751 dBm M2 : 3204.689 MHz : -43.371 dBm	Limit: -15.25 dBm Margin: -28.12 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11g, Channel: 2462.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 2.880 dBm M2 : 3256.733 MHz : -41.073 dBm	Limit: -17.12 dBm Margin: -23.95 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11g, Channel: 2462.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 2.607 dBm M2 : 3256.733 MHz : -40.449 dBm	Limit: -17.39 dBm Margin: -23.06 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11g, Channel: 2462.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 5.333 dBm M2 : 3256.733 MHz : -40.924 dBm	Limit: -14.67 dBm Margin: -26.25 dB

[Back to the Matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

3x3 802.11n HT-20



bandedge

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -24.510 dBm M2 : 2402.377 MHz : -15.304 dBm M3 : 2417.094 MHz : 5.640 dBm	Limit: -14.36 dBm Margin: -10.15 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -26.325 dBm M2 : 2402.521 MHz : -16.392 dBm M3 : 2417.094 MHz : 4.859 dBm	Limit: -15.14 dBm Margin: -11.18 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -24.061 dBm M2 : 2402.521 MHz : -15.668 dBm M3 : 2417.094 MHz : 5.855 dBm	Limit: -14.15 dBm Margin: -9.91 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2467.006 MHz : 5.343 dBm M2 : 2471.479 MHz : -14.679 dBm M3 : 2483.500 MHz : -39.013 dBm	Limit: -14.66 dBm Margin: -24.35 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2467.006 MHz : 5.253 dBm M2 : 2471.768 MHz : -15.456 dBm M3 : 2483.500 MHz : -40.044 dBm	Limit: -14.75 dBm Margin: -25.29 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2467.006 MHz : 6.181 dBm M2 : 2471.479 MHz : -14.888 dBm M3 : 2483.500 MHz : -38.958 dBm	Limit: -13.82 dBm Margin: -25.14 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2371.984 MHz : 5.402 dBm M2 : 3204.689 MHz : -42.157 dBm	Limit: -14.60 dBm Margin: -27.56 dB


[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



con tx spr emissions

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2371.984 MHz : 4.405 dBm M2 : 3204.689 MHz : -42.147 dBm	Limit: -15.60 dBm Margin: -26.55 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2371.984 MHz : 6.059 dBm M2 : 3204.689 MHz : -41.445 dBm	Limit: -13.94 dBm Margin: -27.51 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11n HT-20, Channel: 2437.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 5.443 dBm M2 : 3204.689 MHz : -40.544 dBm	Limit: -14.56 dBm Margin: -25.98 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11n HT-20, Channel: 2437.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 4.948 dBm M2 : 3204.689 MHz : -40.764 dBm	Limit: -15.05 dBm Margin: -25.71 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11n HT-20, Channel: 2437.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 5.040 dBm M2 : 3204.689 MHz : -43.119 dBm	Limit: -14.96 dBm Margin: -28.16 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 4.908 dBm M2 : 3256.733 MHz : -41.437 dBm	Limit: -15.09 dBm Margin: -26.35 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 4.582 dBm M2 : 3256.733 MHz : -40.396 dBm	Limit: -15.42 dBm Margin: -24.98 dB


[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



con tx spr emissions

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 5.667 dBm M2 : 3256.733 MHz : -41.453 dBm	Limit: -14.33 dBm Margin: -27.12 dB

[Back to the Matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

3x3 802.11n HT-40



bandedge

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -24.645 dBm M2 : 2402.922 MHz : -18.157 dBm M3 : 2437.190 MHz : 2.630 dBm	Limit: -17.37 dBm Margin: -7.27 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -27.197 dBm M2 : 2402.922 MHz : -18.247 dBm M3 : 2437.190 MHz : 2.361 dBm	Limit: -17.64 dBm Margin: -9.56 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -26.652 dBm M2 : 2403.222 MHz : -17.596 dBm M3 : 2437.190 MHz : 3.305 dBm	Limit: -16.70 dBm Margin: -9.95 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2466.870 MHz : 2.646 dBm M2 : 2471.078 MHz : -17.860 dBm M3 : 2483.500 MHz : -36.040 dBm	Limit: -17.35 dBm Margin: -18.69 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2466.870 MHz : 2.325 dBm M2 : 2471.078 MHz : -18.519 dBm M3 : 2483.500 MHz : -35.054 dBm	Limit: -17.68 dBm Margin: -17.37 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

bandedge

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2466.870 MHz : 3.149 dBm M2 : 2471.379 MHz : -18.521 dBm M3 : 2483.500 MHz : -34.768 dBm	Limit: -16.85 dBm Margin: -17.92 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 2.453 dBm M2 : 3204.689 MHz : -41.083 dBm	Limit: -17.55 dBm Margin: -23.53 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 2.379 dBm M2 : 3204.689 MHz : -40.882 dBm	Limit: -17.62 dBm Margin: -23.26 dB


[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



con tx spr emissions

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 3.132 dBm M2 : 3204.689 MHz : -43.367 dBm	Limit: -16.87 dBm Margin: -26.50 dB


[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



con tx spurious emissions

Variant: 802.11n HT-40, Channel: 2437.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 2.107 dBm M2 : 3204.689 MHz : -40.443 dBm	Limit: -17.89 dBm Margin: -22.55 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11n HT-40, Channel: 2437.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 2.072 dBm M2 : 3204.689 MHz : -39.994 dBm	Limit: -17.93 dBm Margin: -22.06 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11n HT-40, Channel: 2437.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 2.858 dBm M2 : 3204.689 MHz : -43.227 dBm	Limit: -17.14 dBm Margin: -26.09 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain A, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 2.225 dBm M2 : 3256.733 MHz : -41.669 dBm	Limit: -17.78 dBm Margin: -23.89 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain B, Temp: Ambient, Voltage: 48.00 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 1.580 dBm M2 : 3256.733 MHz : -41.088 dBm	Limit: -18.42 dBm Margin: -22.67 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

con tx spr emissions

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain C, Temp: Ambient, Voltage: 48.00 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 2.840 dBm M2 : 3256.733 MHz : -41.537 dBm	Limit: -17.16 dBm Margin: -24.38 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



440 Boulder Court, Suite 200
Pleasanton, CA 94566, USA

Tel: 1.925.462.0304

Fax: 1.925.462.0306

www.micomlabs.com