



ANSI/IEEE Std. C95.1-1992

**In accordance with the requirements of
FCC Report and Order: ET Docket 93-62, and OET Bulletin 65 Supplement C**

FCC SAR TEST REPORT

For

Wireless IP Phone

Model: PWG-500

Trade Name: G-Tek

Issued to

**G-Tek electronics corporation
16 F, 106, Sec. 1, Hsin-Tai 5th Road., Hsichih,
Taipei Country, Taiwan, R.O.C.**

Issued by

**Compliance Certification Services Inc.
No. 11, Wu-Kung 6 Rd, Wu-Ku Hsiang,
Wu-Ku Industrial District, Taipei Hsien, (248) Taiwan.
<http://www.ccsemc.com.tw>
service@tw.ccsemc.com**



***Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.*



TABLE OF CONTENTS

1. CERTIFICATE OF COMPLIANCE (SAR EVALUATION).....	3
2. EUT DESCRIPTION	4
3. REQUIREMENTS FOR COMPLIANCE TESTING DEFINED BY THE FCC	5
4. DOSIMETRIC ASSESSMENT SETUP	5
4.1 MEASUREMENT SYSTEM DIAGRAM.....	6
4.2 SYSTEM COMPONENTS	7
5. EVALUATION PROCEDURES.....	9
6. MEASUREMENT UNCERTAINTY.....	13
7. EXPOSURE LIMIT	14
8. EUT ARRANGEMENT	15
8.1 ANTHROPOMORPHIC HEAD PHANTOM	15
8.2 DEFINITION OF THE “CHEEK/TOUCH” POSITION	16
8.3 DEFINITION OF THE “TILTED” POSITION.....	17
9. MEASUREMENT RESULTS	18
9.1 SYSTEM PERFORMANCE CHECK	18
9.2 TEST LIQUIDS CONFIRMATION.....	20
9.3 EUT TUNE-UP PROCEDURES	22
9.4 SAR MEASUREMENT RESULTS	24
10. EUT PHOTOS	35
11. EQUIPMENT LIST & CALIBRATION STATUS.....	37
12. FACILITIES	38
13. REFERENCES	38
14. ATTACHMENTS.....	39



1. CERTIFICATE OF COMPLIANCE (SAR EVALUATION)

Applicant G-Tek electronics corporation
16 F, 106, Sec.1, Hsin-Tai 5th Road., Hsichih,
Taipei Country, Taiwan, R.O.C.

Equipment Under Test: Wireless IP Phone

Trade Name: G-Tek

Model Number: PWG-500

Date of Test: January 10 ~ March 11, 2006

Device Category: PORTABLE DEVICES

Exposure Category: GENERAL POPULATION/UNCONTROLLED EXPOSURE

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC OET 65 Supplement C	No non-compliance noted
Deviation from Applicable Standard	
None	

The device was tested by Compliance Certification Services Inc. in accordance with the measurement methods and procedures specified in OET Bulletin 65 Supplement C(Edition 01-01). The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:

Gavin Lim
Section Manager
Compliance Certification Services Inc.

Reviewed by:

Chris Hsieh
Section Manager
Compliance Certification Services Inc.

**2. EUT DESCRIPTION**

Product	Tri-band mobile phone
Trade Name / Model Number	G-Tek / PWG-500
Model Discrepancy	N/A
Frequency Range	GSM850: 824 MHz to 849 MHz GPRS850: 824 MHz to 849 MHz GSM 1900: 1850.2 MHz to 1909.8 MHz GPRS1900: 1850.2 MHz to 1909.8 MHz
Transmit Power	GSM 850: 30.49 dBm GPRS850: 34.50 dBm GSM 1900: 27.95 dBm GPRS1900: 30.01 dBm 2450MHz Head: 11.60 dBm 2450MHz Body: 11.59 dBm Bluetooth: -5.19 dBm
Max. SAR (1g):	GSM 850: Head: 0.668 W/kg (Right head Tilted position) Body: 0.463 W/kg (Body position) GPRS: 0.803 W/kg (Body position) GSM 1900: Head: 0.818 W/kg (Right head Tilted position) Body: 0.256 W/kg (Body position) GPRS: 0.441 W/kg (Body position) 2450MHz: Head: 0.00151 W/kg (Right head Cheek position) Body: 0.009676 W/kg (Body position)
Modulation Technique	TDMA
Antenna Specification	Antenna. Type: GSM antenna: Helical antenna WiFi antenna: Chip antenna Bluetooth antenna: Chip antenna



3. REQUIREMENTS FOR COMPLIANCE TESTING DEFINED BY THE FCC

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992. According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.


4. DOSIMETRIC ASSESSMENT SETUP

These measurements were performed with the automated near-field scanning system DASY4 from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9 m), which positions the probes with a positional repeatability of better than ± 0.02 mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The SAR measurements were conducted with the dosimetric probe EX3DV4-SN:3552 and EX3DV4-SN:3554 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure described in [7] with accuracy of better than $\pm 10\%$. The spherical isotropy was evaluated with the procedure described in [8] and found to be better than ± 0.25 dB. The phantom used was the SAM Twin Phantom as described in FCC supplement C, IEE P1528 and CENELEC EN50361.

The Tissue simulation liquid used for each test is in according with the FCC OET65 supplement C as listed below.

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

4.1 MEASUREMENT SYSTEM DIAGRAM



The DAS4 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 2000 or Windows XP.
- DAS4 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing validating the proper functioning of the system.]

4.2 SYSTEM COMPONENTS

DASY4 Measurement Server



The DASY4 measurement server is based on a PC/104 CPU board with a 166MHz low-power Pentium, 32MB chip disk and 64MB RAM. The necessary circuits for communication with either the DAE3 electronic box as well as the 16-bit AD-converter system for optical detection and digital I/O interface are contained on the DASY4 I/O-board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.

The PC-operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with two expansion slots which are reserved for future applications. Please note that the expansion slots do not have a standardized pinout and therefore only the expansion cards provided by SPEAG can be inserted. Expansion cards from any other supplier could seriously damage the measurement server. Calibration: No calibration required.

Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE3) consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE3 box is 200MΩ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



EX3DV4 Isotropic E-Field Probe for Dosimetric Measurements

Construction:	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration:	Basic Broad Band Calibration in air: 10-3000 MHz. Conversion Factors (CF) for HSL 900 and HSL 1800 CF-Calibration for other liquids and frequencies upon request.
Frequency:	10 MHz to > 6 GHz; Linearity: ± 0.2 dB (30 MHz to 3 GHz)
Directivity:	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in HSL (rotation normal to probe axis)
Dynamic Range:	10 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions:	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Distance from probe tip to dipole centers: 1 mm
Application:	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.



Interior of probe



E-Field probe EX3DV4

SAM Phantom (V4.0)

Construction: The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-200X, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.

Shell Thickness: 2 ± 0.2 mm

Filling Volume: Approx. 25 liters

Dimensions: Height: 810mm; Length: 1000mm; Width: 500mm



Device Holder for SAM Twin Phantom

Construction: In combination with the Twin SAM Phantom V4.0 or Twin SAM, the Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, and flat phantom).



System Validation Kits

Construction: Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.

Frequency: 450, 900, 1800, 2450, 5800 MHz

Return loss: > 20 dB at specified validation position

Power capability: > 100 W ($f < 1\text{GHz}$); > 40 W ($f > 1\text{GHz}$)

Dimensions:
 450V2: dipole length: 270 mm; overall height: 330 mm
 D900V2: dipole length: 149 mm; overall height: 330 mm
 D1800V2: dipole length: 72 mm; overall height: 300 mm
 D2450V2: dipole length: 51.5 mm; overall height: 300 mm
 D5GHzV2: dipole length: 25.5 mm; overall height: 290 mm



5. EVALUATION PROCEDURES

DATA EVALUATION

The DASY4 post processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	$Norm_i, a_{i0}, a_{i1}, a_{i2}$
	- Conversion factor	$ConvF_i$
	- Diode compression point	dcp_i
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with	V_i	= Compensated signal of channel i	(i = x, y, z)
	U_i	= Input signal of channel i	(i = x, y, z)
	cf	= Crest factor of exciting field	(DASY parameter)
	dcp_i	= Diode compression point	(DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$\text{E-field probes: } E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

$$\text{H-field probes: } H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

with	V_i	= Compensated signal of channel i	(i = x, y, z)
	$Norm_i$	= Sensor sensitivity of channel i	(i = x, y, z)
		$\mu V/(V/m)^2$ for E0field Probes	
	$ConvF$	= Sensitivity enhancement in solution	
	a_{ij}	= Sensor sensitivity factors for H-field probes	
	f	= Carrier frequency (GHz)	
	E_i	= Electric field strength of channel i in V/m	
	H_i	= Magnetic field strength of channel i in A/m	

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.



$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with SAR = local specific absorption rate in mW/g
 E_{tot} = total field strength in V/m
 σ = conductivity in [mho/m] or [Siemens/m]
 ρ = equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{3770} \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

with P_{pwe} = Equivalent power density of a plane wave in mW/cm²
 E_{tot} = total electric field strength in V/m
 H_{tot} = total magnetic field strength in A/m



SAR EVALUATION PROCEDURES

The procedure for assessing the peak spatial-average SAR value consists of the following steps:

- **Power Reference Measurement**

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

- **Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in DASY4 software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the area scan's property sheet is brought-up, grid was at to 15 mm by 15 mm and can be edited by a user.

- **Zoom Scan**

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures 5 x 5 x 7 points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more than one maximum, the number of Zoom Scans has to be enlarged accordingly (The default number inserted is 1).

- **Power Drift measurement**

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have DASY4 software stop the measurements if this limit is exceeded.

SPATIAL PEAK SAR EVALUATION

The procedure for spatial peak SAR evaluation has been implemented according to the IEEE1529 standard. It can be conducted for 1 g and 10 g.

The DASY4 system allows evaluations that combine measured data and robot positions, such as:

- maximum search
- extrapolation
- boundary correction
- peak search for averaged SAR

During a maximum search, global and local maximum searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

Extrapolation

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation.

Extrapolation routines require at least 10 measurement points in 3-D space. They are used in the Cube Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard's method for extrapolation. For a grid using 5x5x7 measurement points with 5mm resolution amounting to 343 measurement points, the uncertainty of the extrapolation routines is less than 1% for 1 g and 10 g cubes.

Boundary effect

For measurements in the immediate vicinity of a phantom surface, the field coupling effects between the probe and the boundary influence the probe characteristics. Boundary effect errors of different dosimetric probe types have been analyzed by measurements and using a numerical probe model. As expected, both methods showed an enhanced sensitivity in the immediate vicinity of the boundary. The effect strongly depends on the probe dimensions and disappears with increasing distance from the boundary. The sensitivity can be approximately given as:

$$S \approx S_o + S_b \exp\left(-\frac{z}{a}\right) \cos\left(\pi \frac{z}{\lambda}\right)$$

Since the decay of the boundary effect dominates for small probes ($a \ll \lambda$), the cos-term can be omitted. Factors S_b (parameter Alpha in the DASY4 software) and a (parameter Delta in the DASY4 software) are assessed during probe calibration and used for numerical compensation of the boundary effect. Several simulations and measurements have confirmed that the compensation is valid for different field and boundary configurations.

This simple compensation procedure can largely reduce the probe uncertainty near boundaries. It works well as long as:

- the boundary curvature is small
- the probe axis is angled less than 30° to the boundary normal
- the distance between probe and boundary is larger than 25% of the probe diameter
- the probe is symmetric (all sensors have the same offset from the probe tip)

Since all of these requirements are fulfilled in a DASY4 system, the correction of the probe boundary effect in the vicinity of the phantom surface is performed in a fully automated manner via the measurement data extraction during postprocessing.

6. MEASUREMENT UNCERTAINTY

UNCERTAINTY BUDGE ACCORDING TO IEEE P1528						
Error Description	Uncertainty Value $\pm\%$	Probability distribution	Divisor	C_1 1g	Standard unc.(1g/10g) $\pm\%$	V_1 or V_{eff}
Measurement System						
Probe calibration	± 4.8	normal	1	1	± 4.8	∞
Axial isotropy of probe	± 4.6	rectangular	$\sqrt{3}$	$(1-C_p)^{1/2}$	± 1.9	∞
Sph. Isotropy of probe	± 9.7	rectangular	$\sqrt{3}$	$(C_p)^{1/2}$	± 3.9	∞
Probe linearity	± 4.5	rectangular	$\sqrt{3}$	1	± 2.7	∞
Detection Limit	± 0.9	rectangular	$\sqrt{3}$	1	± 0.6	∞
Boundary effects	± 8.5	rectangular	$\sqrt{3}$	1	± 4.8	∞
Readoutelectronics	± 1.0	normal	1	1	± 1.0	∞
Response time	± 0.9	rectangular	$\sqrt{3}$	1	± 0.5	∞
Integration time	± 1.2	rectangular	$\sqrt{3}$	1	± 0.8	∞
Mech Constrains of robot	± 0.5	rectangular	$\sqrt{3}$	1	± 0.2	∞
Probe positioning	± 2.7	rectangular	$\sqrt{3}$	1	± 1.7	∞
Extrap. And integration	± 4.0	rectangular	$\sqrt{3}$	1	± 2.3	∞
RF ambient conditiona	± 0.54	rectangular	$\sqrt{3}$	1	± 0.43	∞
Test Sample Related						
Device positioning	± 2.2	normal	1	1	± 2.23	11
Device holder uncertainty	± 5	normal	1	1	± 5.0	7
Power drift	± 5	rectangular	$\sqrt{3}$	1	± 2.9	∞
Phantom and Set up						
Phantom uncertainty	± 4	rectangular	$\sqrt{3}$	1	± 2.3	∞
Liquid conductivity	± 5	rectangular	$\sqrt{3}$	0.6	± 1.7	∞
Liquid conductivity	± 5	rectangular	$\sqrt{3}$	0.6	$\pm 3.5/1.7$	∞
Liquid permittivity	± 5	rectangular	$\sqrt{3}$	0.6	± 1.7	∞
Liquid permittivity	± 5	rectangular	$\sqrt{3}$	0.6	± 1.7	∞
Combined Standard Uncertainty					$\pm 12.14/11.76$	
Coverage Factor for 95%		$k_p=2$				
Expanded Standard Uncertainty					$\pm 24.29/23.51$	

Table: Worst-case uncertainty for DASY4 assessed according to IEEE P1528.

The budge is valid for the frequency range 300 MHz to 6G Hz and represents a worst-case analysis.



7. EXPOSURE LIMIT

(A).Limits for Occupational/Controlled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
0.4	8.0	2.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Population/Uncontrolled Environments:

are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Occupational/Controlled Environments:

are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE
GENERAL POPULATION/UNCONTROLLED EXPOSURE
PARTIAL BODY LIMIT
1.6 W/kg

8. EUT ARRANGEMENT

Please refer to IEEE P1528 illustration below.

8.1 ANTHROPOMORPHIC HEAD PHANTOM

Figure 7-1a shows the front, back and side views of SAM. The point “M” is the reference point for the center of mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERPs are 15 mm posterior to the entrance to ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 7-1b. The plane passing through the two ear reference points and M is defined as the Reference Plane. The line N-F (Neck-Front) perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Figure 7-1c). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines should be marked on the external phantom shell to facilitate handset positioning. Posterior to the N-F line, the thickness of the phantom shell with the shape of an ear is a flat surface 6 mm thick at the ERPs. Anterior to the N-F line, the ear is truncated as illustrated in Figure 7-1b. The ear truncation is introduced to avoid the handset from touching the ear lobe, which can cause unstable handset positioning at the cheek.

Figure 7-1a
Front, back and side view of SAM (model for the phantom shell)




Figure 7-1b
Close up side view of phantom showing the ear region




Figure 7-1b
Close up side view of phantom showing the ear region

Figure 7-1c
Side view of the phantom showing relevant markings and the 7 cross sectional plane locations




Figure 7-1c
Side view of the phantom showing relevant markings and the 7 cross sectional plane locations

8.2 DEFINITION OF THE “CHEEK/TOUCH” POSITION

The “cheek” or “touch” position is defined as follows:

- a. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece, open the cover. (If the handset can also be used with the cover closed both configurations must be tested.)
- b. Define two imaginary lines on the handset: the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A on Figures 7-2a and 7-2b), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 7-2a). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output. However, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 7-2b), especially for clamshell handsets, handsets with flip pieces, and other irregularly-shaped handsets.
- c. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 7-2c), such that the plane defined by the vertical center line and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
- d. Translate the handset towards the phantom along the line passing through RE and LE until the handset touches the pinna.
- e. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to MB-NF including the line MB (called the reference plane).
- f. Rotate the handset around the vertical centerline until the handset (horizontal line) is symmetrical with respect to the line NF.
- g. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE and maintaining the handset contact with the pinna, rotate the handset about the line NF until any point on the handset is in contact with a phantom point below the pinna (cheek). See Figure 7-2c. The physical angles of rotation should be noted.




Figure 7.2c

Phone “cheek” or “touch” position. The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for handset positioning, are indicated.




Figure 7.2a

Figure 7.2b

8.3 DEFINITION OF THE “TILTED” POSITION

The “tilted” position is defined as follows:

- Repeat steps (a) – (g) of 7.2 to place the device in the “cheek position.”
- While maintaining the orientation of the handset move the handset away from the pinna along the line passing through RE and LE in order to enable a rotation of the handset by 15 degrees.
- Rotate the handset around the horizontal line by 15 degrees.
- While maintaining the orientation of the handset, move the handset towards the phantom on a line passing through RE and LE until any part of the handset touches the ear. The tilted position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna (e.g., the antenna with the back of the phantom head), the angle of the handset should be reduced. In this case, the tilted position is obtained if any part of the handset is in contact with the pinna as well as a second part of the handset is contact with the phantom (e.g., the antenna with the back of the head).




Figure 7-3

Phone “tilted” position. The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for handset positioning, are indicated.

9. MEASUREMENT RESULTS

9.1 SYSTEM PERFORMANCE CHECK

The system performance check is performed prior to any usage of the system in order to guarantee reproducible results. The system performance check verifies that the system operates within its specifications of $\pm 10\%$. The system performance check results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

IEEE P1528 Recommended Reference Value

Frequency (MHz)	1 g SAR	10 g SAR	Local SAR at surface (Above feed point)	Local SAR at surface (y=2cm offset from feed point)
300	3.0	2.0	4.4	2.1
450	4.9	3.3	7.2	3.2
835	9.5	6.2	14.1	4.9
900	10.8	6.9	16.4	5.4
1450	29.0	16.0	50.2	6.5
1800	38.1	19.8	69.5	6.8
1900	38.8	20.4	67.6	6.6
2000	41.1	21.1	74.6	6.5
2450	52.4	24.0	104.2	7.7
3000	63.8	25.7	140.2	9.5

SYSTEM PERFORMANCE CHECK MEASUREMENT CONDITIONS

- The measurements were performed in the flat section of the SAM twin phantom filled with Head and Body simulating liquid of the following parameters.
- The DASY4 system with an E-field probe EX3DV4 SN: 3552 and an E-field probe EX3DV4 SN: 3554 was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 15 mm (below 1 GHz) and 10 mm (above 1 GHz) from dipole center to the simulating liquid surface.
- The dipole input power (forward power) was 250 mW.
- The 1g and 10 g spatial average SAR values normalized to 1 W dipole input power give reference data for comparisons.

SYSTEM PERFORMANCE CHECK RESULTS

Dipole: D835V2 SN: 4d015

Date: March 11, 2006

Ambient condition: Temperature 24.5°C; Relative humidity: 57%

Head Simulating Liquid			Parameters	Target	Measured	Deviation[%]	Limited[%]
Frequency	Temp. [°C]	Depth [cm]					
835MHz	23.50	15.00	Permittivity:	41.50	40.50	-2.41	± 5
			Conductivity:	0.90	0.894	-0.67	± 5
			1g SAR:	8.72	8.84	1.38	± 5

**Dipole:** D1900V2 SN: 5d056**Date:** January 10, 2006**Ambient condition:** Temperature 24.5°C; Relative humidity: 57%

Head Simulating Liquid			Parameters	Target	Measured	Deviation[%]	Limited[%]
Frequency	Temp. [°C]	Depth [cm]					
1900.00	23.50	15.00	Permittivity:	40.00	38.60	-3.50	±5
			Conductivity:	1.40	1.46	4.29	± 5
			1 g SAR:	38.84	37.56	-3.30	± 5

Dipole: D835V2 SN: 4d015**Date:** March 11, 2006**Ambient condition:** Temperature 24.5°C; Relative humidity: 57%

Body Simulating Liquid			Parameters	Target	Measured	Deviation[%]	Limited[%]
Frequency	Temp. [°C]	Depth [cm]					
835MHz	23.50	15.00	Permittivity:	55.20	54.10	-1.99	±5
			Conductivity:	0.97	0.939	-3.20	± 5
			1 g SAR:	9.60	9.40	-2.08	± 5

Dipole: D1900V2 SN: 5d056**Date:** January 11, 2006**Ambient condition:** Temperature 24.6°C; Relative humidity: 58%

Body Simulating Liquid			Parameters	Target	Measured	Deviation[%]	Limited[%]
Frequency	Temp. [°C]	Depth [cm]					
1900.00	23.40	15.00	Permittivity:	53.30	51.70	-3.00	±5
			Conductivity:	1.52	1.49	-1.97	± 5
			1 g SAR:	40.40	39.24	-2.87	± 5

Dipole: D2450V2 SN: 728**Date:** March 11, 2006**Ambient condition:** Temperature 24.5°C; Relative humidity: 57%

Head Simulating Liquid			Parameters	Target	Measured	Deviation[%]	Limited[%]
f(MHz)	Temp. [°C]	Depth [cm]					
2450.00	23.50	15.00	Permittivity:	39.20	39.80	1.53	± 5
			Conductivity:	1.80	1.84	2.22	± 5
			1 g SAR:	58.40	57.60	-1.37	± 5

Dipole: D2450V2 SN: 728**Date:** March 11, 2006**Ambient condition:** Temperature 24.5°C; Relative humidity: 57%

Body Simulating Liquid			Parameters	Target	Measured	Deviation[%]	Limited[%]
f(MHz)	Temp. [°C]	Depth [cm]					
2450.00	23.50	15.00	Permittivity:	52.70	51.80	-1.71	± 5
			Conductivity:	1.95	1.97	1.03	± 5
			1 g SAR:	53.60	54.40	1.49	± 5

9.2 TEST LIQUIDS CONFIRMATION

SIMULATING LIQUIDS PARAMETER CHECK

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values

The relative permittivity and conductivity of the tissue material should be within $\pm 5\%$ of the values given in the table below. 5% may not be easily achieved at certain frequencies. Under such circumstances, 10% tolerance may be used until more precise tissue recipes are available

IEEE SCC-34/SC-2 P1528 RECOMMENDED TISSUE DIELECTRIC PARAMETERS

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in P1528

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800-2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	45.3	5.27	48.2	6.00

(ϵ_r = relative permittivity, σ = conductivity and $\rho = 1000 \text{ kg/m}^3$)

LIQUID MEASUREMENT RESULTS

Date: March 11, 2006

Ambient condition: Temperature 24.5°C; Relative humidity: 57%

Head Simulating Liquid			Parameters	Target	Measured	Deviation[%]	Limited[%]
Frequency	Temp. [°C]	Depth (cm)					
835MHz	23.50	15.00	Permittivity:	41.50	40.50	-2.41	± 5
			Conductivity:	0.90	0.894	-0.67	± 5

Date: January10, 2006

Ambient condition: Temperature 24.5°C; Relative humidity: 57%

Head Simulating Liquid			Parameters	Target	Measured	Deviation[%]	Limited[%]
Frequency	Temp. [°C]	Depth (cm)					
1900 MHz	23.10	15.00	Permittivity:	40.00	38.60	-3.50	± 5
			Conductivity:	1.40	1.46	4.29	± 5

Dipole: D835V2 SN: 4d015
Date: March 11, 2006

Ambient condition: Temperature 24.5°C; Relative humidity: 57%

Body Simulating Liquid			Parameters	Target	Measured	Deviation[%]	Limited[%]
Frequency	Temp. [°C]	Depth (cm)					
835MHz	23.50	15.00	Permittivity:	55.20	54.10	-1.99	± 5
			Conductivity:	0.97	0.939	-3.20	± 5

Date: January11, 2006

Ambient condition: Temperature 24.6°C; Relative humidity: 58%

Body Simulating Liquid			Parameters	Target	Measured	Deviation[%]	Limited[%]
Frequency	Temp. [°C]	Depth (cm)					
1900 MHz	23.40	15.00	Permittivity:	53.30	51.70	-3.00	± 5
			Conductivity:	1.52	1.49	-1.97	± 5

Date: March 11, 2006

Ambient condition: Temperature 24.5°C; Relative humidity: 57%

Head Simulating Liquid			Parameters	Target	Measured	Deviation[%]	Limited[%]
f(MHz)	Temp. [°C]	Depth [cm]					
2450.00	23.50	15.00	Permittivity:	39.20	39.80	1.53	± 5
			Conductivity:	1.80	1.84	2.22	± 5

Date: March 11, 2006

Ambient condition: Temperature 24.5°C; Relative humidity: 57%

Body Simulating Liquid			Parameters	Target	Measured	Deviation[%]	Limited[%]
f(MHz)	Temp. [°C]	Depth [cm]					
2450.00	23.50	15.00	Permittivity:	52.70	51.80	-1.71	± 5
			Conductivity:	1.95	1.97	1.03	± 5



9.3 EUT TUNE-UP PROCEDURES

The following procedures had been used to prepare the EUT for the SAR test.

- To setup the desire channel frequency and the maximum output power. A Radio Communication Tester “R&S CMU200” was used to program the EUT.

GSM850

Network Support: *GSM only*

Main Service: *Circuit Switched*

Power Setting: *PCL: 5 (33dBm)*

Class: B

GSM1900

Network Support: *GSM only*

Main Service: *Circuit Switched*

Power Setting: *PCL: 0 (30dBm)*

Class: B

GPRS850

Network Support: *GSM + GPRS*

Main Service: *Packet data*

Power Setting: *PCL: 5 (33dBm)*

Class: 10 (2 Up / 3 Down)

GPRS1900

Network Support: *GSM + GPRS*

Main Service: *Packet data*

Power Setting: *PCL: 0 (30dBm)*

Class: 10 (2 Up / 3 Down)

- Maximum conducted power was measured by replacing the antenna with an adapter for conductive measurements, before and after the SAR measurements was done.


IEEE802.11b: Power (Avg)

Frequency	Power
1(2412 MHz)	11.60 dBm
6(2437 MHz)	10.67 dBm
11(2462 MHz)	9.96 dBm


Bluetooth: Power (Avg)

Frequency	Power
Ch 0(2402 MHz)	-5.52 dBm
Ch 39(2441 MHz)	-5.19 dBm
Ch 78(2480 MHz)	-5.58 dBm

GPRS Setup photo:




Distance between Phantom bottom and EUT :



9.4 SAR MEASUREMENT RESULTS


Left head position

								
Cheek position				Tilted position				
Test mode: GSM850 , Duty Cycle: 12.5%, Crest Factor: 8						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_°C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Left Cheek	Fixed	128	824.20	29.85	29.80	23.5	0.313	1.6
		190	836.60	30.48	30.43	23.5	0.418	
		251	848.80	30.45	30.39	23.5	0.416	
Test mode: GSM850 , Duty Cycle: 12.5%, Crest Factor: 8						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_°C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Left Tilted	Fixed	128	824.20	29.84	29.80	23.5	0.369	1.6
		190	836.60	30.48	30.43	23.5	0.447	
		251	848.80	30.45	30.40	23.5	0.445	
Notes: 1. *: Average power								
2. Please refer to attachment for the result presentation in plot format.								

Right head position

								
Cheek position				Tilted position				
Test mode: GSM850 , Duty Cycle: 12.5%, Crest Factor: 8						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_ °C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Right Cheek	Fixed	128	824.20	29.85	29.81	23.5	0.456	1.6
		190	836.60	30.49	30.44	23.5	0.574	
		251	848.80	30.46	30.40	23.5	0.564	
Test mode: GSM850 , Duty Cycle: 12.5%, Crest Factor: 8						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_ °C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Right Tilted	Fixed	128	824.20	29.84	29.79	23.5	0.552	1.6
		190	836.60	30.48	30.43	23.5	0.668	
		251	848.80	30.45	30.39	23.5	0.645	
Co-location: GSM850+WiFi+ Bt , Duty Cycle: 12.5%, Crest Factor: 8						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_ °C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Right Tilted	Fixed	190	836.60	30.48	30.42	23.5	0.606	1.6
Notes: 1. *: Average power 2. Please refer to attachment for the result presentation in plot format.								

Left head position

								
Cheek position				Tilted position				
Test mode: GSM1900 , Duty Cycle: 12.5%, Crest Factor: 8						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_ °C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Left Cheek	Fixed	512	1850.2	27.94	27.90	23.5	0.197	1.6
		661	1880.0	27.27	27.23	23.5	0.224	
		810	1909.8	27.17	27.12	23.5	0.361	
Test mode: GSM1900 , Duty Cycle: 12.5%, Crest Factor: 8						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_ °C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Left Tilted	Fixed	512	1850.2	27.95	27.91	23.5	0.271	1.6
		661	1880.0	27.28	27.23	23.5	0.298	
		810	1909.8	27.18	27.13	23.5	0.488	
Notes: 1. *: Average power								
2. Please refer to attachment for the result presentation in plot format.								

Right head position

								
Cheek position				Tilted position				
Test mode: GSM1900 , Duty Cycle: 12.5%, Crest Factor: 8						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_ °C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Right Cheek	Fixed	512	1850.2	27.94	27.90	23.5	0.216	1.6
		661	1880.0	27.28	27.24	23.5	0.275	
		810	1909.8	27.17	27.13	23.5	0.478	
Test mode: GSM1900 , Duty Cycle: 12.5%, Crest Factor: 8						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_ °C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Right Tilted	Fixed	512	1850.2	27.94	27.91	23.5	0.283	1.6
		661	1880.0	27.28	27.23	23.5	0.360	
		810	1909.8	27.19	27.14	23.5	0.620	
Co-location: GSM1900+ WiFi+ Bt , Duty Cycle: 12.5%, Crest Factor: 8						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_ °C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Right Tilted	Fixed	810	1909.8	27.19	27.13	23.5	0.818	1.6
Notes: 1. *: Average power 2. Please refer to attachment for the result presentation in plot format.								

Body Front position


								
GSM Body position				GPRS Body position				
Test mode: GSM850, Duty Cycle: 12.5%, Crest Factor: 8						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_ °C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Body Front	Fixed	128	824.20	29.84	29.80	23.5	0.262	1.6
		190	836.60	30.47	30.43	23.5	0.317	
		251	848.80	30.43	30.39	23.5	0.309	
Test mode: GPRS850, Duty Cycle: 25%, Crest Factor: 4						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_ °C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Body Front	Fixed	128	824.20	33.28	33.24	23.5	0.430	1.6
		190	836.60	32.85	32.79	23.5	0.532	
		251	848.80	34.49	34.44	23.5	0.546	
Notes: 1. *: Average power 2. Please refer to attachment for the result presentation in plot format. 3. The distance between EUT and phantom is 22.5 mm.								

Body Back position


								
GSM Body position				GPRS Body position				
Test mode: GSM850, Duty Cycle: 12.5%, Crest Factor: 8						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_°C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Body	Fixed	128	824.20	29.85	29.81	23.5	0.394	1.6
		190	836.60	30.48	30.44	23.5	0.463	
		251	848.80	30.44	30.40	23.5	0.442	
Co-location: GSM850+ WiFi+ Bt, Duty Cycle: 12.5%, Crest Factor: 8						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_°C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Body	Fixed	190	836.60	30.47	30.43	23.5	0.384	1.6
Test mode: GPRS850, Duty Cycle: 25%, Crest Factor: 4						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_°C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Body	Fixed	128	824.20	33.29	33.24	23.5	0.657	1.6
		190	836.60	32.87	32.80	23.5	0.803	
		251	848.80	34.50	34.44	23.5	0.794	
Co-location: GPRS850+WiFi+Bt, Duty Cycle: 25%, Crest Factor: 4						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_°C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Body	Fixed	190	836.60	32.85	32.80	23.5	0.776	1.6

Notes: 1. *: Average power
2. Please refer to attachment for the result presentation in plot format.
3. The distance between EUT and phantom is 22.5 mm.


Body Front position

								
GSM Body position				GPRS Body position				
Test mode: GSM1900 , Duty Cycle: 12.5%, Crest Factor: 8						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_°C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Body	Fixed	512	1850.2	27.94	27.91	23.4	0.065	1.6
		661	1880.0	27.24	27.21	23.4	0.086	
		810	1909.8	27.16	27.12	23.4	0.139	
Test mode: GPRS1900 , Duty Cycle: 25%, Crest Factor: 4						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_°C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Body	Fixed	512	1850.2	31.04	31.01	23.4	0.135	1.6
		661	1880.0	29.99	29.95	23.4	0.173	
		810	1909.8	29.99	29.94	23.4	0.273	
Notes: 1. *: Average power 2. Please refer to attachment for the result presentation in plot format. 3. The distance between EUT and phantom is 22.5 mm.								

Body Back position

								
GSM Body position				GPRS Body position				
Test mode: GSM1900, Duty Cycle: 12.5%, Crest Factor: 8						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_°C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Body	Fixed	512	1850.2	27.95	27.91	23.4	0.088	1.6
		661	1880.0	27.25	27.22	23.4	0.114	
		810	1909.8	27.16	27.12	23.4	0.182	
Co-location: GSM1900+ WiFi+ Bt, Duty Cycle: 12.5%, Crest Factor: 8 Depth of liquid: 15.0 cm								
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_°C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Body	Fixed	810	1909.8	27.17	27.13	23.4	0.256	1.6
Test mode: GPRS1900, Duty Cycle: 25%, Crest Factor: 4						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_°C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Body	Fixed	512	1850.2	31.04	31.01	23.4	0.176	1.6
		661	1880.0	30.00	29.96	23.4	0.224	
		810	1909.8	30.00	29.95	23.4	0.355	
Co-location: GPRS1900+WiFi+Bt, Duty Cycle: 25%, Crest Factor: 4 Depth of liquid: 15.0 cm								
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_°C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Body	Fixed	810	1909.8	30.01	29.96	23.4	0.441	1.6
Notes: 1. *: Average power 2. Please refer to attachment for the result presentation in plot format. 3. The distance between EUT and phantom is 22.5 mm.								


Left head position

								
Cheek position				Tilted position				
Test mode: 802.11b , Duty Cycle: 100%, Crest Factor: 1						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_ °C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Left Cheek	Fixed	1	2412	11.59	11.56	23.5	0.000279	1.6
Test mode: 802.11b , Duty Cycle: 100%, Crest Factor: 1						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_ °C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Left Tilted	Fixed	1	2412	11.59	11.55	23.5	0.00079	1.6
Notes: 1. *: Average power								
2. Please refer to attachment for the result presentation in plot format.								

Right head position



								
Cheek position				Tilted position				
Test mode: 802.11b , Duty Cycle: 100%, Crest Factor: 1						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_°C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Right Cheek	Fixed	1	2412	11.60	11.57	23.5	0.00151	1.6
Test mode: 802.11b 0 , Duty Cycle: 100%, Crest Factor: 1						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_°C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Right Tilted	Fixed	1	2412	11.58	11.55	23.5	0.000868	1.6
Notes: 1. *: Average power								
2. Please refer to attachment for the result presentation in plot format.								

Body position

								
Body Front position				Body Back position				
Test mode: 802.11b , Duty Cycle: 100%, Crest Factor: 1						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_°C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Body	Fixed	1	2412	11.59	11.56	23.5	0.000967	1.6
Test mode: 802.11b , Duty Cycle: 100%, Crest Factor: 1						Depth of liquid: 15.0 cm		
EUT Position	Antenna	Frequency		*Conducted Power dBm		Liquid Temp_°C	SAR (1g) (W/kg)	Limit (W/kg)
		Channel	MHz	Before	After			
Body	Fixed	1	2412	11.58	11.55	23.5	0.000631	1.6
Notes: 1. *: Average power								
2. Please refer to attachment for the result presentation in plot format.								

10.EUT PHOTOS





**11.EQUIPMENT LIST & CALIBRATION STATUS**

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Cycle(days)	Calibration Due
S-Parameter Network Analyzer	Agilent	E8358A	US40260243	365	08/15/06
Electronic Probe kit	Hewlett Packard	85070D	N/A	N/A	N/A
Power Meter	Agilent	E4416A	GB41291611	365	05/24/06
Power Sensor	Agilent	E9327A	US40441097	365	05/24/06
Thermometer	Amarell	4046	25058	3650	10/02/14
Wireless Communication Test Set	Agilent	E5515C	GB44051665	365	09/01/06
Universal Radio Communication Tester	Rohde & Schwarz	CMU 200	1100.0008.02	N/A	09/20/06
Signal Generator	Agilent	E8257C	US42340383	365	06/07/06
Amplifier	Mini-Circuit	ZVE-8G	N/A	N/A	N/A
Amplifier	Mini-Circuit	ZHL-1724HLN	N/A	N/A	N/A
DC Power generator	ABM	8301HD	N/A	N/A	N/A
Data Acquisition Electronics (DAE)	SPEAG	DAE3	427	365	09/21/06
Dosimetric E-Field Probe	SPEAG	EX3DV4	3552	365	03/19/06
Dosimetric E-Field Probe	SPEAG	EX3DV4	3554	365	02/21/07
835 MHz System Validation Dipole	SPEAG	D835V2	4d015	730	12/08/06
900 MHz System Validation Dipole	SPEAG	D900V2	179	730	05/12/06
1800 MHz System Validation Dipole	SPEAG	D1800V2	2d062	730	03/17/06
1900 MHz System Validation Dipole	SPEAG	D1900V2	5d056	730	12/08/06
2450 MHz System Validation Dipole	SPEAG	D2450V2	728	730	03/22/06
5GHz System Validation Dipole	SPEAG	D5GHz	1004	730	02/09/08
Probe Alignment Unit	SPEAG	LB (V2)	348	N/A	N/A
Robot	Staubli	RX90B L	F02/5T69A1/A/01	N/A	N/A
SAM Twin Phantom V4.0	SPEAG	N/A	N/A	N/A	N/A
Devices Holder	SPEAG	N/A	N/A	N/A	N/A
Head/ Muscle 835 MHz	CCS	H/M 835A	N/A	N/A	N/A
Head/ Muscle 900 MHz	CCS	H/M 900A	N/A	N/A	N/A
Head/ Muscle 1800 MHz	CCS	H/M 1800A	N/A	N/A	N/A
Head/ Muscle 1900 MHz	CCS	H/M 1900A	N/A	N/A	N/A
Head/ Muscle 2450 MHz	CCS	H/M 2450A	N/A	N/A	N/A
Head/ Muscle 5800 MHz	CCS	H/M 5800A	N/A	N/A	N/A



12.FACILITIES

All measurement facilities used to collect the measurement data are located at

- ☐ No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang, Taoyuan Hsien, Taiwan, R.O.C.
- ☒ No. 11, Wu-Kung 6 Rd, Wu-Ku Hsiang, Wu-Ku Industrial District, Taipei Hsien, (248) Taiwan.
- ☐ No. 199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

13.REFERENCES

- [1] Federal Communications Commission, \Report and order: Guidelines for evaluating the environ-mental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.
- [2] David L. Means Kwok Chan, Robert F. Cleveland, \Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commision, O_cce of Engineering & Technology, Washington, DC, 1997.
- [3] Thomas Schmid, Oliver Egger, and Niels Kuster, \Automated E-_eld scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105{113, Jan. 1996.
- [4] Niels Kuster, Ralph K.astle, and Thomas Schmid, \Dosimetric evaluation of mobile communications equipment with known precision", IEICE Transactions on Communications, vol. E80-B, no. 5, pp. 645{652, May 1997.
- [5] CENELEC, \Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz - 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.
- [6] ANSI, ANSI/IEEE C95.1-1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.
- [7] Katja Pokovic, Thomas Schmid, and Niels Kuster, \Robust setup for precise calibration of E-_eld probes in tissue simulating liquids at mobile communications frequencies", in ICECOM _97, Dubrovnik, October 15{17, 1997, pp. 120{124.
- [8] Katja Pokovic, Thomas Schmid, and Niels Kuster, \E-_eld probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23 {25 June, 1996, pp. 172{175.
- [9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard K. uhn, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions onMicrowave Theory and Techniques, vol. 44, no. 10, pp. 1865{1873, Oct. 1996.
- [10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.
- [11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recepies in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992..Dosimetric Evaluation of Sample device, month 1998 9
- [13] NIS81 NAMAS, \The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.
- [14] Barry N. Taylor and Christ E. Kuyatt, \Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10



14.ATTACHMENTS

Exhibit	Content
1	System Performance Check Plots
2	SAR Test Plots

END OF REPORT