



RF EXPOSURE REPORT

REPORT NO.: SA971225L02

MODEL NO.: 8062

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: CipherLab Co., Ltd.

ADDRESS: 12F, 333 Dunhua S. Rd., Sec.2 Taipei, Taiwan

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,
Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

No evaluation required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.580
High	2.480	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	1.470	1.403
EIRP Power	4.470	2.799

***Note:** The antenna is PCB printing wire antenna with 3dBi gain

Threshold for no SAR evaluation is 24.580mW
Transmitter power is 2.799mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold