



PCTEST Engineering Laboratory, Inc.

6660-B Dobbin Road · Columbia, MD 21045 · U.S.A.
 TEL (410) 290-6652 · FAX (410) 290-6654
<http://www.pctestlab.com>



CERTIFICATE OF COMPLIANCE FCC Part 22 Certification

FLEXTRONICS Sales & Marketing (A-P), Ltd.
 Suite 402 St. James Court St. Dennis Street
 Port Louis, Mauritius
 Attn: Loh Boon Liang, Project Manager

Dates of Tests: April 15-16, 2003
 Test Report S/N: 22.230414187.Q3O
 Test Site: PCTEST Lab, Columbia MD USA

FCC ID

Q3OKWC-K112

APPLICANT

FLEXTRONICS Sales & Marketing (A-P), Ltd.

Classification:

Non-Broadcast Transmitter held to ear (TNE)

FCC Rule Part(s):

§22(H), §22.901(d), §2

EUT Type:

Dual-Mode Cellular Phone (AMPS/CDMA)

Model:

K112

Tx Frequency Range:

824.04MHz – 848.97MHz (AMPS) / 824.70 – 848.31MHz (CDMA)

Rx Frequency Range:

869.04MHz – 893.97MHz (AMPS) / 869.70 – 893.31MHz (CDMA)

Max. RF Output Power:

0.419 W ERP AMPS (26.219 dBm) / 0.284 W ERP CDMA (24.533 dBm)

Max. SAR Measurement:

1.170 W/kg AMPS Head SAR; 1.290 W/kg AMPS Body SAR;

0.771 W/kg CDMA Head SAR; 0.911 W/kg CDMA Body SAR

Emission Designator(s):

40K0F8W / 40K0F1D (AMPS), 1M25F9W (CDMA)

Test Device Serial No.

Identical Prototype [S/N: PB100300254]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Grant conditions: Output is ERP. SAR compliance for body-worn operating configurations is limited to the specific configuration tested for this filing. Body-worn operations are restricted to belt-clips, holsters or similar accessories that provide at least 1.1 cm. separation between the device, and the user's body. End-users must be informed of the body-worn operating requirements for satisfying RF exposure compliance.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862




 Alfred Cirwilhian
 Vice President Engineering

2 3 0 4 1 4 1 8 7 . Q 3 0

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O	Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112		Page 1 of 24

TABLE OF CONTENTS

ATTACHMENT A: COVER LETTER(S)

ATTACHMENT B: ATTESTATION STATEMENT(S)

ATTACHMENT C: TEST REPORT

1.1 SCOPE	3
2.1 INTRODUCTION	4
3.1 INSERTS	5
4.1 DESCRIPTION OF TESTS	6-8
5.1 EFFECTIVE RADIATED POWER OUTPUT	9-10
6.1 RADIATED MEASUREMENTS	11-16
7.1 FREQUENCY STABILITY	17-20
8.1 PLOTS OF EMISSIONS	21
9.1 LIST OF TEST EQUIPMENT	22
10.1 SAMPLE CALCULATIONS	23
11.1 CONCLUSION	24

ATTACHMENT D: TEST PLOTS

ATTACHMENT E: FCC ID LABEL / LOCATION

ATTACHMENT F: TEST SETUP PHOTOGRAPHS

ATTACHMENT G: EXTERNAL PHOTOGRAPHS

ATTACHMENT H: INTERNAL PHOTOGRAPHS

ATTACHMENT I: BLOCK DIAGRAM(S)

ATTACHMENT J: SCHEMATIC DIAGRAM(S)

ATTACHMENT K: OPERATIONAL / CIRCUIT DESCRIPTION


ATTACHMENT L: PARTS LIST/TUNE UP PROCEDURE

ATTACHMENT M: USER'S MANUAL

ATTACHMENT N: SAR MEASUREMENT REPORT

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O		Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112	Page 2 of 24

MEASUREMENT REPORT



1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

§2.1033 General Information

Applicant Name:	FLEXTRONICS Sales & Marketing (A-P), Ltd.
Address:	Suite 402 St. James Court St. Dennis Street
	Port Louis, Mauritius
Attention:	Loh Boon Liang, Project Manager

- FCC ID: **Q3OKWC-K112**
- Quantity: Quantity production is planned
- Emission Designators: 40K0F8W / 40K0F1D (AMPS), 1M25F9W (CDMA)
- Tx Freq. Range: 824.04 – 848.97 MHz (AMPS)
824.70 – 848.31 MHz (CDMA)
- Rx Freq. Range: 869.04 – 893.97 MHz (AMPS)
869.70 – 893.31 MHz (CDMA)
- Max. Power Rating: 0.419 W ERP AMPS (26.219 dBm)
0.284 W ERP CDMA (24.533 dBm)
- FCC Classification(s): Non-Broadcast Transmitter held to ear (TNE)
- Equipment (EUT) Type: Dual-Mode Cellular Phone (AMPS/CDMA)
- Modulation(s): AMPS / CDMA
- Frequency Tolerance: $\pm 0.00025\%$ (2.5 ppm)
- FCC Rule Part(s): §22(H), §22.901(d), §2
- Dates of Tests: April 15-16, 2003
- Place of Tests: PCTEST Lab, Columbia, MD U.S.A.
- Test Report S/N: 22.230414187.Q3O

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O		Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112	Page 3 of 24

2.1 INTRODUCTION




Figure 1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.




Figure 2. Diagram of 3-meter outdoor test range

These measurement tests were conducted at **PCTEST Engineering Laboratory, Inc.** facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 1992.

Measurement Procedure

The radiated and spurious measurements were made outdoors at a 3-meter test range (see Figure 2). The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O		Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112	Page 4 of 24

3.1 INSERTS

Function of Active Devices (Confidential)

The Function of active devices are shown in Attachment K.

Block & Schematic Diagrams (Confidential)

The block diagrams are shown in Attachment I, and the schematic diagrams are shown in Attachment J.

Operating Instructions

The instruction manual is shown in Attachment M.

Parts List & Tune-Up Procedure (Confidential)

The parts list & tune-up procedure is shown in Attachment L.

Description of Freq. Stabilization Circuit (Confidential)

The description of frequency stabilization circuit is shown in Attachment K.

Description for Suppression of Spurious Radiation, for Limiting Modulation, and Harmonic Supresion Circuits (Confidential)

The description of suppression stabilization circuits is shown in Attachment K.

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O		Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112	Page 5 of 24

4.1 DESCRIPTION OF TESTS

4.2 Transmitter Audio Frequency Response

The frequency response of the audio modulating circuit over the frequency range 100 – 5000 Hz is measured. The audio signal generator is connected to the audio input circuit/microphone of the EUT. The audio signal input is adjusted to obtain 50% modulation at 1kHz and this point is taken as the 0dB reference. With the input held constant and below the limit at all frequencies, the audio signal generator is varied from 100 to 50 kHz.

4.3 Audio Low Pass Filter Frequency Response

The response in dB relative to 1kHz is measured using the HP8901 a Modulation Analyzer. For the frequency response of the audio low-pass filter, the audio input is connected at the input to the modulation limiter and the modulated stage. The audio output is connected at the output of the modulated stage. The corresponding plots are shown herein.

4.4 Modulation Limiting

The audio signal generator is connected to the audio input circuit/microphone of the EUT. The modulation response is measured for each of the three modulating frequencies (300Hz, 1000 Hz, and 3000Hz), and the input voltage is varied from 30% modulation ($\pm 3.6\text{kHz}$ deviation) to at least 20dB higher than the saturation point. Measurements of modulation and the plots are attached herein. Measurements were performed for ST, SAT, and wide-band data modulations. The corresponding results are shown herein.

Note: ST, SAT, & Wide-Band data were internally generated by the EUT.




Fig. 3. Transmitter Audio Frequency & Tone Modulation Test Setup.

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O		Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112	Page 6 of 24

4.1 DESCRIPTION OF TESTS (CONTINUED)

4.5 Occupied Bandwidth

The audio signal generator is adjusted to 1kHz. The output level is set to ± 6 kHz deviation. With the level constant, the frequency is set to 2500Hz. Then the audio signal level is increased by 16dB. The occupied bandwidth data is obtained for the SAT (Supervisory Audio Tone), ST (Signaling Tone), WBD (Wideband data), and DTMF (Dual Tone Multi Frequencies). The results are shown on the attached graphs.

Specified Limits:

- On any frequency removed from the assigned carrier frequency by more than 20 kHz, up to and including 45kHz, the sideband is at least 26dB below the carrier.
- On any frequency removed from the assigned carrier frequency by more than 45 kHz, up to and including 90kHz, the sideband is at least 45dB below the carrier.
- On any frequency removed from the assigned carrier frequency by more than 90 kHz, up to the first multiple of the carrier frequency, the sideband is at least 60dB below the carrier or $40 + \log_{10}$ (mean power output in Watts) dB, whichever is the smaller attenuation.

4.6 Spurious and Harmonic Emissions at Antenna Terminal

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to 10 GHz. The transmitter is modulated with a 2500Hz tone at a level of 16dB greater than that required to provided 50% modulation.

At the input terminals of the spectrum analyzer, an isolator (RF circulator with on port terminated with 50 ohms) and an 870 MHz to 890 MHz bandpass filter is connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The rejection of the bandpass filter to signals in the 825 – 845 MHz range is adequate to limit the transmit energy from the test transceiver which appears to a level which will allow the analyzer to measure signals less than -90dBm. Calibration of the test receiver is performed in the 870 – 890 MHz range to insure accuracy to allow variation in the bandpass filter insertion loss to be calibrated.

4.7 Frequencies

At the input terminals of the spectrum analyzer, an isolator (RF pad) and an high-pass filter are connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The high-pass filter (signals below 1.6 GHz) is to limit the fundamental frequency from interfering with the measurement of low-level spurious and harmonic emissions and to ensure that the preamplifier is not saturated.

4.8 Radiation Spurious and Harmonic Emissions

Radiation and harmonic emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N:	Test Dates:	Phone Type:	FCC ID:		
22.230414187.Q3O	April 15-16, 2003	Dual-Mode (AMPS/CDMA)	Q3OKWC-K112	Page 7 of 24	

5.0 Frequency Stability/Temperature Variation.

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +60°C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025 (±2.5 ppm) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (25°C to 27°C to provide a reference).
2. The equipment is subjected to an overnight "soak" at -30°C without any power applied.
3. After the overnight "soak" at 30°C (usually 14-16 hours), the equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying power to the transmitter.
4. Frequency measurements are made at 10°C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency were made at 10 intervals starting at 30°C up to +50°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after re-applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

NOTE: The EUT is tested down to the battery endpoint.

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O		Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112	Page 8 of 24

5.1 Test Data

5.2 Effective Radiated Power Output

A. POWER: Low (Analog Mode)

Freq. Tuned (MHz)	REF. LEVEL (dBm)	POL (H/V)	ERP (W)	ERP (dBm)
824.04	-35.550	V	0.004	5.723
836.49	-35.210	V	0.004	6.219
848.97	-35.850	V	0.004	5.735

B. POWER: High (Analog Mode)

Freq. Tuned (MHz)	REF. LEVEL (dBm)	POL (H/V)	ERP (W)	ERP (dBm)	BATTERY
824.04	-15.550	V	0.37353	25.723	Standard
836.49	-15.210	V	0.41869	26.219	Standard
848.97	-15.850	V	0.37453	25.735	Standard

Note: Standard batteries are the only options for this phone

NOTES:

Effective Radiated Power Output Measurements by Substitution Method
according to ANSI/TIA/FIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O	Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112		Page 9 of 24

5.1 Test Data

5.3 Effective Radiated Power Output

A. POWER: High (CDMA Mode)

Freq. Tuned (MHz)	REF. LEVEL (dBm)	POL (H/V)	ERP (W)	ERP (dBm)	BATTERY
824.70	-16.850	V	0.27687	24.423	Standard
835.89	-16.900	V	0.28397	24.533	Standard
848.31	-17.350	V	0.26502	24.233	Standard

Note: Standard batteries are the only options for this phone

NOTES:

Effective Radiated Power Output Measurements by Substitution Method
according to ANSI/TIA/FIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O		Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112	Page 10 of 24

6.1 Test Data

6.2 AMPS Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.04 MHz
 CHANNEL: 0991 (Low)
 MEASURED OUTPUT POWER: 26.219 dBm = 0.419 W
 MODULATION SIGNAL: FM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 39.22 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1648.08	-70.78	6.10	-64.68	V	90.9
2472.12	-75.78	6.70	-69.08	V	95.3
3296.16	-80.08	6.80	-73.28	V	99.5

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O	Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112		Page 11 of 24

6.1 Test Data (Continued)

6.3 AMPS Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.52 MHz
 CHANNEL: 0384 (Mid)
 MEASURED OUTPUT POWER: 26.219 dBm = 0.419 W
 MODULATION SIGNAL: FM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 39.22 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1673.04	-69.78	6.10	-63.68	V	89.9
2509.56	-73.28	6.70	-66.58	V	92.8
3346.08	-81.38	6.80	-74.58	V	100.8

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O	Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112		Page 12 of 24

6.1 Test Data (Continued)

6.4 AMPS Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.97 MHz
 CHANNEL: 0799 (High)
 MEASURED OUTPUT POWER: 26.219 dBm = 0.419 W
 MODULATION SIGNAL: FM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 39.22 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1697.94	-73.28	6.10	-67.18	V	93.4
2546.91	-76.78	6.70	-70.08	V	96.3
3395.88	-80.98	6.80	-74.18	V	100.4

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O	Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112		Page 13 of 24

6.1 Test Data (Continued)

6.5 CELLULAR CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.70 MHz
 CHANNEL: 1013 (Low)
 MEASURED OUTPUT POWER: 24.533 dBm = 0.284 W
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 37.53 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1649.40	-74.28	6.10	-68.18	V	92.7
2474.10	-79.38	6.70	-72.68	V	97.2
3298.80	-82.58	6.80	-75.78	V	100.3

NOTES:

Radiated Spurious Emission Measurements by Substitution Method

according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O	Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112		Page 14 of 24

6.1 Test Data (Continued)

6.6 CELLULAR CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.52 MHz
 CHANNEL: 0384 (Mid)
 MEASURED OUTPUT POWER: 24.533 dBm = 0.284 W
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 37.53 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1673.04	-72.08	6.10	-65.98	V	90.5
2509.56	-77.28	6.70	-70.58	V	95.1
3346.08	-81.48	6.80	-74.68	V	99.2
#REF!	-83.78	7.00	-76.78	V	101.3

NOTES:

Radiated Spurious Emission Measurements by Substitution Method

according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O	Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112		Page 15 of 24

6.1 Test Data (Continued)

6.7 CELLULAR CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.31 MHz
 CHANNEL: 0777 (High)
 MEASURED OUTPUT POWER: 24.533 dBm = 0.284 W
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 37.53 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1696.62	-74.28	6.10	-68.18	V	92.7
2544.93	-77.58	6.70	-70.88	V	95.4
3393.24	-83.08	6.80	-76.28	V	100.8

NOTES:

Radiated Spurious Emission Measurements by Substitution Method

according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O	Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112		Page 16 of 24

7.1 Test Data

7.2 FREQUENCY STABILITY (AMPS)

OPERATING FREQUENCY: 836,520,002 Hz

CHANNEL: 384

REFERENCE VOLTAGE: 3.7 VDC


DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQ. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	836,520,002	0.000000
100 %		- 30	836,519,826	0.000021
100 %		- 20	836,519,768	0.000028
100 %		- 10	836,519,785	0.000026
100 %		0	836,519,843	0.000019
100 %		+ 10	836,519,868	0.000016
100 %		+ 20	836,520,002	0.000000
100 %		+ 25	836,519,927	0.000009
100 %		+ 30	836,519,851	0.000018
100 %		+ 40	836,519,785	0.000026
100 %		+ 50	836,519,692	0.000037
100 %		+ 60	836,519,617	0.000046
85 %	3.15	+ 20	836,520,002	0.000000
115 %	4.26	+ 20	836,520,002	0.000000
BATT. ENDPOINT	2.91	+ 20	836,520,002	0.000000

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O	Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112	Page 17 of 24	

7.1 Test Data (Continued)

7.3 FREQUENCY STABILITY (AMPS)



PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By:
Test Report S/N: 22.230414187.Q3O		Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112	Quality Manager
					Page 18 of 24

7.1 Test Data

7.4 FREQUENCY STABILITY (CDMA)

OPERATING FREQUENCY: 836,520,002 Hz

CHANNEL: 384

REFERENCE VOLTAGE: 3.7 VDC


DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQ. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	836,520,002	0.000000
100 %		- 30	836,519,851	0.000018
100 %		- 20	836,519,810	0.000023
100 %		- 10	836,519,868	0.000016
100 %		0	836,519,851	0.000018
100 %		+ 10	836,519,935	0.000008
100 %		+ 20	836,520,002	0.000000
100 %		+ 25	836,519,910	0.000011
100 %		+ 30	836,519,877	0.000015
100 %		+ 40	836,519,709	0.000035
100 %		+ 50	836,519,701	0.000036
100 %		+ 60	836,519,651	0.000042
85 %	3.15	+ 20	836,520,002	0.000000
115 %	4.26	+ 20	836,520,002	0.000000
BATT. ENDPOINT	2.92	+ 20	836,520,002	0.000000

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O	Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112	Page 19 of 24	

7.1 Test Data (Continued)

7.5 FREQUENCY STABILITY (AMPS)



PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By:
Test Report S/N: 22.230414187.Q3O		Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112	Quality Manager
					Page 20 of 24

8.1 PLOT(S) OF EMISSIONS

(SEE ATTACHMENT D)

PCTEST [®] PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O		Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112	Page 21 of 24

9.1 TEST EQUIPMENT

Type	Model	Cal. Due Date	S/N
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	08/15/03	3638A08713
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	04/17/04	2542A11898
Spectrum Analyzer/Tracking Gen.	HP 8591A (100Hz-1.8GHz)	08/10/03	3144A02458
Signal Generator*	HP 8640B (500Hz-1GHz)	06/03/03	2232A19558
Signal Generator*	HP 8640B (500Hz-1GHz)	06/03/03	1851A09816
Signal Generator*	Rohde & Schwarz (0.1-1000MHz)	09/11/03	894215/012
Alltech/Eaton Receiver	NM 37/57A-SL (30-1000MHz)	04/12/04	0792-03271
Alltech/Eaton Receiver	NM 37/57A (30-1000MHz)	03/11/04	0805-03334
Alltech/Eaton Receiver	NM17/27A (0.1-32MHz)	09/17/03	0608-03241
Quasi-Peak Adapter	HP 85650A	08/15/03	2043A00301
Alltech/Eaton Adapter	CCA-7 CISPR/ANSI QP Adapter	03/11/04	0194-04082
Gigatronics Universal Power Meter	8657A		1835256
Gigatronics Power Sensor	80701A (0.05-18GHz)		1833460
Signal Generator	HP 8648D (9kHz-4GHz)		3613A00315
Amplifier Research	5SIG4 (5W, 800MHz-4.2GHz)		22322
Network Analyzer	HP 8753E (30kHz-3GHz)		JP38020182
Audio Analyzer	HP 8903B		3011A09025
Modulation Analyzer	HP 8901A		2432A03467
Power Meter	HP 437B		3125U24437
Power Sensor	HP 8482H (30μW-3W)		2237A02084
Harmonic/Flicker Test System	HP 6841A (IEC 555-2/3)		3531A00115
Broadband Amplifier (2)	HP 8447D		1145A00470, 1937A03348
Broadband Amplifier	HP 8447F		2443A03784
Horn Antenna	EMCO Model 3115 (1-18GHz)		9704-5182
Horn Antenna	EMCO Model 3115 (1-18GHz)		9205-3874
Horn Antenna	EMCO Model 3116 (18-40GHz)		9203-2178
Biconical Antenna (4)	Eaton 94455/Eaton 94455-1/Singer 94455-1/Compliance Design 1295, 1332, 0355		
Log-Spiral Antenna (3)	Alltech/Eaton 93490-1		0608, 1103, 1104
Roberts Dipoles	Compliance Design (1set)		
Alltech Dipoles	DM-105A (1set)		33448-111
EMCO LISN (6)	3816/2		1079
Microwave Preamplifier 40dB Gain	HP 83017A (0.5-26.5GHz)		3123A00181
Microwave Cables	MicroCoax (1.0-26.5GHz)		
Alltech/Eaton Receiver	NM37/57A-SL		0792-03271
Spectrum Analyzer	HP 8591A		3051A00187
Spectrum Analyzer (2)	HP 8591A		3034A01395, 3108A02053
Microwave Survey Meter	Holaday Model 1501 (2.450GHz)		80931
Digital Thermometer	Extech Instruments 421305		426966
Attenuator	HP 8495A (0-70dB) DC-4GHz		
Bi-Directional Coax Coupler	Narda 3020A (50-1000MHz)		
Shielded Screen Room	RF Lindgren Model 26-2/2-0		6710 (PCT270)
Shielded Semi-Anechoic Chamber	Ray Proof Model S81		R2437 (PCT278)
Environmental Chamber	Associated Systems Model 1025 (Temperature/Humidity)		PCT285

* Calibration traceable to the National Institute of Standards and Technology (NIST).

PCTEST® PT. 22 REPORT	FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q30	Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112	Page 22 of 24

10.1 SAMPLE CALCULATIONS

A. Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

(Measured at the 99.75% power bandwidth)

Emission Designator = 40K0F8W

Calculation: Voice + SAT

Modulation: Voice is 2.5 kHz and SAT is 6 kHz – Maximum modulation is M = 6 kHz

Deviation: Voice is 12 kHz and SAT is 2 kHz – Maximum deviation is D = 12 + 2 = 14 kHz

Bn = 2xM + 2xDK with K = 1

Bn = 40 kHz

Calculation: Signaling Tone (ST) + SAT

Modulation: ST is 10 kHz and SAT is 6 kHz – Maximum modulation is M = 10 kHz

Deviation: ST is 8 kHz and SAT is 2 kHz – Maximum deviation is D = 8 + 2 = 10 kHz

Bn = 2xM + 2xDK with K = 1

Bn = 40 kHz

Emission Designator = 40K0F1D

Calculation: Voice + SAT

Modulation: Wideband Data is 10 kHz and SAT is 6 kHz – Maximum modulation is M = 10 kHz

Deviation: Wideband Data is 8 kHz and SAT is 2 kHz – Maximum deviation is D = 8 + 2 = 10 kHz

Bn = 2xM + 2xDK with K = 1

Bn = 40 kHz

PCTEST® PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O		Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112	Page 23 of 24

11.1 CONCLUSION

The data collected shows that the **FLEXTRONICS Sales & Marketing (A-P), Ltd. Dual-Mode Cellular Phone (AMPS/CDMA) FCC ID: Q3OKWC-K112** complies with all the requirements of Parts 2 and 22 of the FCC rules.

PCTEST [®] PT. 22 REPORT		FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22.230414187.Q3O		Test Dates: April 15-16, 2003	Phone Type: Dual-Mode (AMPS/CDMA)	FCC ID: Q3OKWC-K112	Page 24 of 24