



TEST REPORT

Report No. : AD009207-1

Date : 2003 July 23

Applicant : Early Light Industrial Co., Ltd.
Early Light International Centre,
No. 9, Ka Fu Close, Sheung Shui,
N. T., Hong Kong.

Attn. : Simon Lam / Jacky Yu

Sample Description : One(1) submitted sample stated to be 1/64 Scale RC Car of Model No. A0335.
Rating : 2 x 1.5 V AA size batteries
No. of sample(s) : Three(3) pieces ***

Date Received : 2003 May 22.

Test Period : 2003 May 22 – 2003 July 15.

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – May 2002
ANSI C63.4 – 1992

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC
Part 15 Subpart C.

For and on behalf of
CMA Testing and Certification Laboratories

Authorized Signature :

Danny Chui
EMC Engineer - EL. Division

FCC ID : Q4RA0335

Page 1 of 11



TEST REPORT

Report No. : AD009207-1

Date : 2003 July 23

Table of Contents

1	General Information	3
1.1	General Description.....	3
1.2	Related Submittal Grants	3
1.3	Location of the test site.....	4
1.4	List of measuring equipment	5
2	Description of the radiated emission test	6
2.1	Test Procedure	6
2.2	Test Result.....	6
2.3	Radiated Emission Measurement Data.....	7
3	Description of the Line-conducted Test	8
3.1	Test Procedure	8
3.2	Test Result.....	8
3.3	Graph and Table of Conducted Emission Measurement Data	8
4	Photograph	9
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	9
4.2	Photographs of the External and Internal Configurations of the EUT	9
5	Supplementary document	10
5.1	Bandwidth	10
6	Appendices.....	11



TEST REPORT

Report No. : AD009207-1

Date : 2003 July 23

1 General Information

1.1 General Description

The equipment under test (EUT) is a transmitter for 1/64 scale RC car operating at 27.145 MHz which is controlled by a crystal. The EUT is powered by 3 V battery. There are four buttons in the center of the EUT. When the Forward / Backward button is pressed once, it will transmit a radio frequency for receiver going Forward / Backward. When the Left / Right button is pressed, it will transmit a radio frequency for receiver going Left / Right.

The brief circuit description is listed as follows :

- X1 and associated circuit act as oscillator
- IC101 and associated circuit act as encoding, modulation and transmission

1.2 Related Submittal Grants

This is a single application for certification of a transmitter.

The receiver for this transmitter is exempted from the Part 15 technical rules per 15.101(b).

FCC ID : Q4RA0335

Page 3 of 11



TEST REPORT

Report No. : AD009207-1

Date : 2003 July 23

1.3 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 1992. An Open Area Testing Site is set up for investigation and located at :

Top of the Roof, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 1992. A double shielded room is located at :

Roof Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

FCC ID : Q4RA0335

Page 4 of 11



TEST REPORT

Report No. : AD009207-1

Date : 2003 July 23

1.4 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S21141
Broadband Antenna	Schaffner	CBL6113B	2718	AC1753
Signal Generator	IFR	2023B	202302/938	Nil
LISN	R&S	ESH3-Z5	100038	S21142
Pulse Limiter	R&S	ESH3-Z2	100001	20-73194
Biconical Antenna	R&S	HK116	837414/004	4000.7752.02

FCC ID : Q4RA0335

Page 5 of 11



TEST REPORT

Report No. : AD009207-1

Date : 2003 July 23

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 1992.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

2.2 Test Result

Peak Detector data was measured unless otherwise stated.

* Emissions appearing within the restricted bands shall follow the requirement of section 15.205.

It was found that the EUT meet the FCC requirement.

FCC ID : Q4RA0335

Page 6 of 11



TEST REPORT

Report No. : AD009207-1

Date : 2003 July 23

2.3 Radiated Emission Measurement Data

Radiated emission
pursuant to
the requirement of FCC Part 15 subpart C

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Averaging Factor (-dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
27.145	V	59.6	16.4	6.9	69.1	80.0	-10.9
54.290	H	13.4	8.9	--	22.3	40.0	-17.7
81.436	H	16.2	8.0	--	24.2	40.0	-15.8
*108.581	H	12.8	12.0	--	24.8	43.5	-18.7
*135.726	H	12.1	13.1	--	25.2	43.5	-18.3
*162.871	H	13.0	11.0	--	24.0	43.5	-19.5
190.016	H	15.4	10.5	--	25.9	43.5	-17.6
217.161	H	13.9	10.7	--	24.6	46.0	-21.4
*244.310	H	20.9	10.7	--	31.6	46.0	-14.4
*271.456	H	15.3	13.9	--	29.2	46.0	-16.8

FCC ID : Q4RA0335

Page 7 of 11



TEST REPORT

Report No. : AD009207-1

Date : 2003 July 23

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 1992. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable

FCC ID : Q4RA0335

Page 8 of 11



TEST REPORT

Report No. : AD009207-1

Date : 2003 July 23

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExtPho1.jpg to ExtPho2.jpg and IntPho1.jpg to IntPho2.jpg.

FCC ID : Q4RA0335

Page 9 of 11



TEST REPORT

Report No. : AD009207-1

Date : 2003 July 23

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmpl.pdf
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

The plot on saved in TestRpt2.pdf shows the fundamental emission is confined in the specified band. It also shows that the band edge met the 15.229 requirement at 26.9599 and 27.2801 MHz.

5.2 The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 31.4 ms.

Effective period of the cycle = $(0.4 \times 18) \text{ ms.} + (0.88 \times 8) \text{ ms.}$
= 14.24 ms.

Duty Cycle = $14.24 / 31.4 \text{ ms.}$
= 0.453 ms.

Therefore, the averaging factor is found by $20 \log_{10} 0.453 = -6.9 \text{ dB}$

FCC ID : Q4RA0335

Page 10 of 11



TEST REPORT

Report No. : AD009207-1

Date : 2003 July 23

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1 page
A2.	Photos of External Configurations	1 page
A3.	Photos of Internal Configurations	1 page
A4.	ID Label/Location	1 page
A5.	Bandwidth Plot	1 page
A6.	Average Factor	2 pages
A7.	Block Diagram	1 page
A8.	Schematics	1 page
A9.	User Manual	2 pages
A10.	Operation Description	1 page

***** End of Report *****

FCC ID : Q4RA0335

Page 11 of 11